*********** INFORMATION FOR CERTIFICATION (1) *********

APPLICANT:

Name : <u>Sharp Corporation, Reliability Control Group</u>

Address <u>22-22 Nagaike-Cho, Abeno-Ku</u>

Osaka 545-8522, Japan

Grantee Code: : <u>APY</u>
Applicant Rep. : <u>H. Nishira</u>

CONTACT PERSON:

Name : <u>Sharp Electronics Corporation</u>

Address : <u>Sharp Plaza, Mahwah, New Jersey 07430</u> Applicant Rep. : <u>Steve Petruska, Product Safety Dept.</u>

Telephone No. : <u>201-529-9689</u>

MEASUREMENT SITE:

Name : <u>Japan Quality Assurance Organization</u>

Chubu Testing Center, Shikatsu Branch

Address : 53-1, Yamaura, Yakushiji, Shikatsu-cho, Nishikasugai-gun

Aichi 481-0005, Japan

MANUFACTURER:

Name : <u>Sharp Appliances (Thailand) Ltd.</u>

Address : 64 Moo 5, Tambol Bangsamuk Amphur Bangpakong

Chachoengsao Province, Thailand

FCC IDENTIFICATION : APYDMR0151

EQUIPMENT

Model Name : Microwave Oven Model R-55TS#

(#: May be followed by additional suffix letters or numbers)

Brand : <u>Sharp Electronics Corp.</u> Importer : <u>Sharp Electronics Corp.</u>

.....

******* INFORMATION FOR CERTIFICATION (2) ********

(1) Type(s) of emission: Not Applicable

(2) Frequency range: 2450 MHz

(3) Range of operating power and description of means provided for variation of operating power:

RF output power 650 W (Average power output is controlled by ON/OFF switching cycles.)

(4) Max. power rating as described in the applicable rules:

650 W

(5) The voltage and current to magnetron:

Magnetron Cat. No. 2M213 : 3.0kV peak, 270 mA

(6) Function of each electro tube, semiconductor or other active circuit device:

Fixed Magnetron, Type 2M213 as power generator

(7) Complete circuit diagram: Attached

(8) Instruction book: Attached

(9) Tune up procedure over the power range or at specific operating power levels: Not adjustable

(10) A description of all circuitry and devices provided for determining and stabilizing frequency:

Fixed by magnetron and oven design

(11) A description of any circuit or devices employed for suppression of spurious radiation, for limiting modulation, and for limiting the operating power:

Suppression obtained by shielding design

(12) Identification plate or label: <u>Illustration attached</u>
Location of identification plate or label: Photo. Attached

*********** INFORMATION FOR CERTIFICATION (3) *********

DESCRIPTION OF THE MICROWAVE OVEN

Unit Body Dimensions : 450 mm wide, 291 mm high, 390 mm deep

(include feet)

Door Dimensions : <u>364 mm wide, 268 mm high</u>

(Viewing Area: 240 mm wide, 129 mm high)

Oven Cavity Dimensions : 302 mm wide, 170 mm high, 287 mm deep

(without tray)

Feed Type and Location : Supplied by waveguide located side of oven

Door Seal Type : <u>Choke and Capacitive Seals</u>

Magnetron Type : 2M213 mfd by LG Electronics