

Safety Human Exposure

1.1 Radio Frequency Exposure Compliance

1.1.1 Electromagnetic Fields

RESULT:

Pass

Test item	: Treadmill
Identification / Type No.	: TRX5500(XTERRA FITNESS), GT90D(DYACO)
FCC ID	: FCC ID: 2AHVL-GT90DNT041
IC	: IC: 22282-GT90DNT041
HVIN	: TRX5500, GT90D
Test standard	: CFR47 FCC Part 2: Section 2.1091 CFR47 FCC Part 1: Section 1.1310 FCC KDB Publication 447498 v06 RSS-102 Issue 5 February 2021

➤ Product Classification

This device defined as a transmitting device designed to be used in fixed locations and to generally be used in such a way that the RF source's radiating structure(s) is/are over 20 centimeters of the body of the user.

Max 2.00 dB

➤ Radio Frequency Exposure Limit

a. For FCC:

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

Table 1 – Limits for Maximum Permissible Exposure(MPE)

Frequency range [MHz]	Electric field strength [v/m]	Magnetic field strength [A/m]	Power density [mw/cm ²]	Averaging time [minutes]
(A) Limits for Occupational/Controlled Exposure				
0.3 - 3.0	614	1.63	*(100)	≤6
3.0 - 30	1842/f	4.89/f	*(900/f ²)	≤6
30 - 300	61.4	0.163	1.0	≤6
300 – 1,500			f/300	≤6
1,500 – 100,000			5	≤6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*(100)	≤30
1.34 – 30	824/f	2.19/f	*(180/f ²)	≤30
30 – 300	27.5	0.073	0.2	≤30
300 – 1,500			f/1500	≤30
1,500 – 100,000			1.0	≤30

f = frequency in MHz.

* = Plane-wave equivalent power density.

b. For IC:

For the purpose of this standard, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public
(Uncontrolled Environment)

Frequency Range [MHz]	Electric Field [V/m rms]	Magnetic Field [A/m rms]	Power Density [W/m ²]	Reference Period [minutes]
0.003 - 10 ²¹	83	90	-	Instantaneous*
0.1 - 10	-	0.73/f	-	6**
1.1 - 10	87/f ^{0.5}	-	-	6**
10 - 20	27.46	0.0728	2	6
20 - 48	58.07/f ^{0.25}	0.1540/f ^{0.25}	8.944/f ^{0.5}	6
48 - 300	22.06	0.05852	1.291	6
300 - 6000	3.142f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000 - 15000	61.4	0.163	10	6
15000 - 150000	61.4	0.163	10	616000/f ^{1.2}
150000 - 300000	0.158f ^{0.5}	4.21*10 ⁻⁴ f ^{0.5}	6.67*10 ⁻⁵ f	616000/f ^{1.2}
Note: F is frequency in MHz *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR)				

➤ **Radio Frequency Exposure Calculation Formula**

a. Power Density

$$S = \frac{PG}{4\pi R^2}$$

where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or:

$$S = \frac{EIRP}{4\pi R^2}$$

where:

EIRP = equivalent (or effective) isotropically radiated power

➤ **EUT RF Exposure Evaluation**

a. Evaluation for Standalone Transmission Operation

Mode	Frequency [MHz]	Measured RF Output Power [dBm]	Antenna Gain [dBi]	E.I.R.P [dBm]	Distance [cm]	Power Density [mW/cm ²]	FCC Limit [mW/cm ²]	IC Limit [mW/cm ²]
Bluetooth (EW-BLED-26)	2480	2.842	2	4.842	20	0.000607	1	5.47
Bluetooth (AP6236)	2480	8.140	2	10.140	20	0.002055	1	5.47
Wi-Fi (AP6236)	2462	23.72	2	25.72	20	0.074256	1	5.44

Note:

1. Bluetooth(EW-BLED-26) RF Output Power refer to, CN213MUT 001
2. Bluetooth(AP6236) RF Output Power refer to, CN213MUT 002
3. Wi-Fi(AP6236) RF Output Power refer to, CN213MUT 003

b. Evaluation for Simultaneous Transmission Operation

Simultaneous Transmission Scenarios

No.	Simultaneous Transmission
1	Bluetooth(EW-BLED-26)+Bluetooth(AP6236)
2	Bluetooth(EW-BLED-26)+Wi-Fi(AP6236)

Mode	Sum Power Density [mW/cm ²]	Distance [cm]	Max Allowed Power (1g SAR) [mW]	Max Allowed Power (10g SAR) [mW]
Bluetooth(EW-BLED-26)+Bluetooth(AP6236)	0.002662	20	1	5.47
Bluetooth(EW-BLED-26)+Wi-Fi(AP6236)	0.074863	20	1	5.44

➤ **Conclusion**

The maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.