

Toshiba Corporation  
FCC ID: CJ6UPA3231WL  
Request for limited modular approval

Transmitter Module Characteristics

Item	Requirements	EUT
<b>1</b>	Have its own RF shielding	<b>Device is equipped with Metal shielding to cover RF section. Refer external photos</b>
<b>2</b>	Have buffered modulation/data inputs (if such inputs are provided),	<b>All inputs to the modules are buffered through logic or microprocessor inputs.</b>
<b>3</b>	Have it own power supply regulation	<b>Internal 1.8V power regulator. Refer to Block diagram</b>
<b>4</b>	Meet the antenna requirements of Section 15.203	<b>Device is equipped with unique antenna ( u.FL(v)-LP-040) connector. Refer to external photos</b>
<b>5</b>	Be labeled with its own FCC ID number, <b>and</b> if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	<b>Proposed FCC ID label format is included in the filing. Refer to FCC ID label format and location file.</b>
<b>7</b>	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	<b>Refer to “User’s Guide” Exhibit</b>
<b>8</b>	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	<b>The max. output power measured is 0.092W . Antenna will be installed on the top edge of LCD panel which  provide at least 20cm separation distance to the body.</b>