

FCC - TEST REPORTReport Number : **60.792.18.013.01R01** Date of Issue : August 27, 2018Model : **HG04641A-US-TX, HG04641B-US-TX**Product Type : **TEMPERATURE STATION LCD**Applicant : Lidl US Trading, LLCAddress : 3500 S. Clark Street, Arlington, Virginia, United StatesProduction Facility : PUTIAN DIOR INDUSTRIAL CO., LTD.Address : Linan Industrial Area, Xianyou County, Putian, Fujian, ChinaTest Result : ☒ **Positive** ☐ **Negative**Total pages
including
Appendices : 19

TÜV SÜD HONG KONG LTD. is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025. TÜV SÜD HONG KONG LTD. reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD HONG KONG LTD. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD HONG KONG LTD. issued reports. This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1 Table of Contents.....	2
2 Description of Equipment Under Test	3
3 Summary of Test Standards	4
4 Details about the Test Laboratory	5
4.1 Test Equipment Site List	6
4.2 Measurement System Uncertainty	7
5 Summary of Test Results.....	8
6 General Remarks	9
7 Emission Test Results	10
7.1 Spurious Radiated Emission	10
7.2 20dB Bandwidth.....	14
7.3 Transmission Time.....	15
8 Appendix A - General Product Information	17

2 Description of Equipment Under Test

Description of the Equipment Under Test

Product:	TEMPERATURE STATION LCD
Model no.:	HG04641A-US-TX
FCC ID:	2AJ9O-HG4641TX
Rating:	3 VDC (2 x AA battery)
Frequency:	433.92MHz
Antenna gain:	0 dBi
Number of operated channel:	1
Modulation:	FSK

3 Summary of Test Standards

Test Standards
FCC Part 15 Subpart C 10-1-17 Edition Federal Communications Commission, PART 15 — Radio Frequency Devices, Subpart C — Unintentional Radiators

4 Details about the Test Laboratory

Site 1

Company name: TÜV SÜD Hong Kong Ltd.
3/F, West Wing, Lakeside 2,
10 Science Park West Avenue,
Science Park, Shatin, Hong Kong

Site 2

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13 Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2,
Shenzhen 518052, P.R.China
FCC Registration Number: 514049

Emission Tests	
Test Item	Test Site
FCC Part 15 Subpart C	
FCC Title 47 Part 15.205, 15.209 & 15.231(e) Radiated Emission	Site 2
FCC Title 47 Part 15.207 Conduct Emission	NIL
FCC Title 47 Part 15.231(c) 20dB Bandwidth	Site 2
FCC Title 47 Part 15.247(e) Transmission Time	Site 2

4.1 Test Equipment Site List

Radiated emission Test – Site 2

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2019-7-6
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2019-6-28
Horn Antenna	Rohde & Schwarz	HF907	102294	2019-6-28
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2019-7-6
Signal Generator	Rohde & Schwarz	SMY01	839369/005	2019-7-6
Attenuator	Agilent	8491A	MY39264334	2019-7-6
3m Semi-anechoic chamber	TDK	9X6X6	----	2020-7-7
Test software	Rohde & Schwarz	EMC32	Version 9.15.00	N/A

20dB Bandwidth, Transmission Time – Site 2

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	101030	2019-7-6

4.2 Measurement System Uncertainty

Measurement System Uncertainty Emissions

System Measurement Uncertainty	
Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 9kHz-30MHz	4.54dB
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.83dB; Vertical: 4.91dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-25000MHz	Horizontal: 4.89dB; Vertical: 4.88dB;
Uncertainty for Conducted RF test	2.04dB

5 Summary of Test Results

Emission Tests				
FCC Part 15 Subpart C				
Test Condition	Pages	Test Result		
		Pass	Fail	N/A
FCC Title 47 Part 15.205, 15.209 & 15.231(e) Radiated Emission	10-13	☒	☐	☐
FCC Title 47 Part 15.207 Conduct Emission (1)	NIL	☐	☐	☒
FCC Title 47 Part 15.231(c) 20dB Bandwidth	14	☒	☐	☐
FCC Title 47 Part 15.247(e) Transmission Time	15	☒	☐	☐

Remark:

- 1) These requirements do not apply for equipment which employ battery power for operation and which do not operate from the AC power lines.

6 General Remarks

Remarks

Client informs that the HG04641B-US-TX have the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction, with TEMPERATURE STATION LCD, HG04641A-US-TX. The difference lies only on different color of the different models. (Client's conformation letter shown at appendix C)

EMC Tests were performed on model: HG04641A-US-TX

SUMMARY:

- All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

- The Equipment Under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.


Sample Received Date: August 1, 2018

Testing Start Date: August 7, 2018

Testing End Date: August 15, 2018

- TÜV SÜD HONG KONG LTD. -

Reviewed by:



Hosea CHAN
EMC Project Engineer

Prepared by:



Eric LI
EMC Senior Project Engineer

7 Emission Test Results

7.1 Spurious Radiated Emission

EUT: HG04641A-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.205, 15.209 & 15.231(e) Antenna: Horizontal
 Comment: 3 VDC
 Remark: 9kHz to 5GHz

Test Result	
☒	Passed
☐	Not Passed

Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector
59.9622	16.65	40	-23.35	Peak
182.1822	12.25	43.5	-31.25	Peak
433.9258	64.42	92.87	-28.45	Peak
867.8516	41.37	72.87	-31.50	Peak
1301.7774	52.54	74	-21.46	Peak
1735.7032	47.10	74	-26.90	Peak
2169.6290	57.41	74	-16.59	Peak
2603.5548	56.39	74	-17.61	Peak
3037.4806	52.69	74	-21.31	Peak
3471.4064	52.54	74	-21.46	Peak

Duty cycle factor=-10.78
 Average value = Peak value + Duty cycle factor

Frequency MHz	PK Result @3m dBμV/m	Duty Cycle Factor dB	AV Result @3m dBμV/m	Limit dBμV/m	Margin dB
59.9622	16.65	/	/	40	-23.35
182.1822	12.25	/	/	43.5	-31.25
433.9258	64.42	-10.78	53.64	72.87	-19.23
867.8516	41.37	-10.78	30.59	52.87	-22.28
1301.7774	52.54	-10.78	41.76	54	-12.24
1735.7032	47.10	-10.78	36.32	54	-17.68
2169.6290	57.41	-10.78	46.63	54	-7.37
2603.5548	56.39	-10.78	45.61	54	-8.39
3037.4806	52.69	-10.78	41.91	54	-12.09
3471.4064	42.51	-10.78	31.73	54	-22.27

Spurious Radiated Emission

EUT: HG04641A-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.205, 15.209 & 15.231(e) Antenna: Vertical
 Comment: 3 VDC
 Remark: 9kHz to 5GHz

Test Result	
☒	Passed
☐	Not Passed

Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector
63.3033	17.97	40	-22.03	Peak
113.9050	10.09	43.5	-33.41	Peak
433.9258	73.67	92.87	-19.20	Peak
867.8516	54.87	72.87	-18.00	Peak
1301.7774	44.23	74	-29.77	Peak
1735.7032	44.69	74	-29.31	Peak
2169.629	56.40	74	-17.60	Peak
2603.5548	51.67	74	-22.33	Peak
3037.4806	56.77	74	-17.23	Peak


Duty cycle factor=-10.78
 Average value = Peak value + Duty cycle factor

Frequency MHz	PK Result @3m dBμV/m	Duty Cycle Factor dB	AV Result @3m dBμV/m	Limit dBμV/m	Margin dB
63.3033	17.97	/	/	40	-22.03
113.9050	10.09	/	/	43.5	-33.41
433.9258	73.67	-10.78	62.89	72.87	-9.98
867.8516	54.87	-10.78	44.09	52.87	-8.78
1301.7774	44.23	-10.78	33.45	54	-20.55
1735.7032	44.69	-10.78	33.91	54	-20.09
2169.629	56.40	-10.78	45.62	54	-8.38
2603.5548	51.67	-10.78	40.89	54	-13.11
3037.4806	56.77	-10.78	45.99	54	-8.01

EUT:	HG04641A-US-TX
Op Condition:	Operated, TX Mode (433.92MHz)
Test Specification:	FCC15.205, 15.209 & 15.231(e) Antenna: Vertical
Comment:	3 VDC
Remark:	9kHz to 5GHz

Test Result	
☒	Passed
☐	Not Passed

a. Transmission period




Spurious Radiated Emission


EUT: HG04641A-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.205, 15.209 & 15.231(e) Antenna: Vertical
 Comment: 3 VDC
 Remark: 9kHz to 5GHz

Test Result	
☒	Passed
☐	Not Passed

c. Pulse number in 100ms



d. Pulse width=535 μs




Calculation:
 Max. allowed $T_p=100\text{ms}$
 Number of pulses in 100ms=54
 Pulse width=535 μs
 $T_{on} = \text{Pulse width} \times \text{Number of pulses in 100ms} = 28.89\text{ms}$
 $\text{Duty cycle factor} = 20 \times \log(T_{on}/T_p) = -10.78$

7.2 20dB Bandwidth

EUT: HG04641A-US-TX
 Op Condition: Operated, TX Mode (433.92MHz)
 Test Specification: FCC15.231(c) 20dB Bandwidth
 Comment: 3 VDC

Test Result
☒ Passed
☐ Not Passed



Bandwidth	Measured Value	Limit
20dB bandwidth	7.530 kHz	> 1084.8 kHz
Limit=0.25%*Center Frequency=0.25%*433.92MHz=1084.8kHz		

7.3 Transmission Time

EUT: HG04641A-US-TX
Op Condition: Operated, TX Mode (433.92MHz)
Test Specification: FCC15.231(e)
Comment: 3 VDC

Test Result	
☒	Passed
☐	Not Passed

Frequency	Duration of each transmission	Limit	Silent period	Limit
433.92MHz	960ms	< 1s	32s	28.8s


Note: Silent period limit is 30 times the duration of the transmission but in no case less than 10 seconds

Transmission Time


EUT: HG04641A-US-TX
Op Condition: Operated, TX Mode (433.92MHz)
Test Specification: FCC15.231(e)
Comment: 3 VDC

Test Result
☒ Passed
☐ Not Passed

Duration of each transmission



Silent period



8 Appendix A - General Product Information

To: TÜV SÜD HKG Ltd.

Attention: Edmond Fung
From: Mr. Maxwell Hand
Fax No:

Date: September 6, 2018
Total Page (Cover Included): 1

Declaration Letter

Subject:

We:

Officially notify TÜV SÜD HKG Ltd. that the <<Additional Model>> have the same technical construction including circuit diagram, PCB Layout, components and component layout, all electrical construction and mechanical construction, with <<PRODUCT>>, <<Main Test Model>>. The difference lies only on the different on the non-metallic outlook case color of the different models.

<<Additional Model >>: HG04641B-US-TX , HG04641B-US-RX

<<Main Test Model >>: HG04641A-US-TX , HG04641A-US-RX

<<Product>>: TEMPERATURE STATION LCD

Applicant: Lidl US, LCC

9/6/18
(Date)



(Applicant's authorized signature and company Chop)
Mr. Maxwell Hand
Senior Quality Assurance Manager

9 Appendix C - General Product Information

Radiofrequency radiation exposure evaluation

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances ≤ 50 mm, the Numeric threshold is determined as:

Step a)

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]

· $[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

>> The fundamental frequency of the EUT is 433.92MHz, the test separation distance is $\leq 5\text{mm}$ & $\leq 20\text{mm}$

(Manufacturer specified the separation distance is:20mm)

Step a.1)

>> Numeric threshold, mW / **5 mm** * $\sqrt{0.43392\text{GHz}} \leq 3.0$

Numeric threshold $\leq$ **22.771mW**

Step a.2)

>> Numeric threshold, mW / **20 mm** * $\sqrt{0.43392\text{GHz}} \leq 3.0$

Numeric threshold $\leq$ **91.084mW**

>> The power of EUT measured is: -1.69dBm = 0.68mW

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.

Appendix C - Conducted power

EUT: HG04641A-US-TX
Op Condition: Operated, TX Mode
Comment: 3 VDC
Remark: NA

Test Result	
☒	Passed
☐	Not Passed

