

TEST REPORT

Reference No..... : WTX24X12283259W001
FCC ID..... : A4X-WPC12-3TFNA
Applicant..... : CE LINK LIMITED
Address..... : 22 Dongkang Road, Dalingshan Town, Dongguan City, Guangdong
Province, China.
Manufacturer..... : DONGGUAN CE LINK LIMITED
Address..... : 22 Dongkang Road, Dalingshan Town, Dongguan City, Guangdong
Province, China.
Product Name..... : Wireless Charger
Model No..... : WPC12-3TFNA
Standards..... : **47 CFR FCC Part 18**
Date of Receipt sample..... : 2024-12-02
Date of Test..... : 2024-12-02 to 2024-12-18
Date of Issue..... : 2024-12-18
Test Report Form No..... : WTX_FCC Part 18_001
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:


Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,

Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Gala Wang

Approved by:



Jason Su

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND OPERATION MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	12
3. CONDUCTED EMISSIONS	13
3.1 STANDARD APPLICABLE	13
3.2 TEST PROCEDURE	13
3.3 BASIC TEST SETUP BLOCK DIAGRAM	13
3.4 ENVIRONMENTAL CONDITIONS	13
3.5 TEST RECEIVER SETUP	14
3.6 SUMMARY OF TEST RESULTS/PLOTS	14
4. RADIATED EMISSIONS	21
4.1 TEST PROCEDURE	21
4.2 TEST RECEIVER SETUP	22
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	22
4.4 ENVIRONMENTAL CONDITIONS	23
4.5 SUMMARY OF TEST RESULTS/PLOTS	23
APPENDIX PHOTOGRAPHS	32

Report version

Version No.	Date of issue	Description
Rev.00	2024-12-18	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Factory#1: SuiChuan CE LINK LIMITED
 Address of factory: SuiChuan county industrial park east zone, Ji'an city, Jiangxi province, China.

Factory#2: CE LINK VIET NAM COMPANY LIMITED.
 Address of factory: Part of lots CNSG-04, CNSG-06 Van Trung Industrial Zone, Van Trung Ward, Viet Yen Town, Bac Giang Province, Vietnam

General Description of EUT	
Product Name:	Wireless Charger
Trade Name:	CE-LINK
Model No.:	WPC12-3TFNA
Adding Model(s):	B0874YN8B9
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model WPC12-3TFNA, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	110-205kHz
Modulation Type:	ASK
Antenna Type:	Coil Antenna
Rated Voltage:	Input: Type C 5V, 9V, 12V
Rated Current:	Input: Type C 2A, 2A, 1.5A
Rate Power:	Input: Type C 18W Output: 5W, 7.5W, 10W, 12W
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

47 CFR FCC Part 18: Industrial, Scientific, and medical medical equipment.

MP5-1986: FCC METHODS OF MESUREMENTS OF RADIO NOISE EMISSIONS FROM INDUSTRIAL, SCIENTIFIC, AND MEDICAL EQUIPMENT.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014 and FCC MP-5:1986, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101)

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark	Power Supply Mode
TM1	Wireless Charging	AC230V/50Hz for adapter	Input: DC9V2A; Wireless charging 1: output 12W
TM2	Wireless Charging	AC230V/50Hz for adapter	Input: DC9V2A; Wireless charging 2: output 12W
TM3	Wireless Charging	AC230V/50Hz for adapter	Input: DC9V2A; Wireless charging 3: output 12W

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Adapter	Iottie	CHCRIO160	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Type-C Cable	1.0	Unshielded	Without Ferrite

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Radiated Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-18GHz ±3.92dB

1.7 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1004A 1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2024-02-27	2025-02-26
WTXE1103A 1003	Attenuator	Pasternack	PE4007-4	/	2024-02-24	2025-02-23
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2024-07-03	2025-01-03
☒ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
WTXE1007A 1001	Amplifier	HP	8447F	2805A034 75	2024-02-24	2025-02-23
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2024-02-24	2025-02-23
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2024-03-15	2025-03-14
☒ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2024-02-24	2025-02-23
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	2002	2024-02-27	2025-02-26
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2024-02-26	2025-02-25
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
WTXE1104A	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14

1033-2						
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2024-03-15	2025-03-14
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2024-02-24	2025-02-23
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2024-02-24	2025-02-23
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2024-07-03	2025-07-02
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
☐ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2024-02-24	2025-02-23
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2024-07-03	2025-07-02
☐ Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2024-02-27	2025-02-26
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003A	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28

1001						
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-02
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2024-07-03	2025-07-02
☒ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2024-12-08	2025-12-07
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2024-02-24	2025-02-23
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2024-02-24	2025-02-23
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2024-07-03	2025-07-02
☐ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2024-02-24	2025-02-23
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2024-07-03	2025-07-02

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission A)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission B)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission C)	Farad	EZ-EMC	RA-03A1-2 (1.1.4.2)
EMI Test Software (Conducted Emission Room 1#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3
EMI Test Software (Conducted Emission Room 2#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3

*Remark: indicates software version used in the compliance certification testing

2. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§18.307 (b)	Conducted Emission	Compliant
§18.305 (b)	Radiated Emission	Compliant

N/A: Not applicable.

3. Conducted Emissions

3.1 Standard Applicable

According to FCC 18.307(b), the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies shall not exceed the limits in the following tables:


Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

3.2 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 18.307 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

3.3 Basic Test Setup Block Diagram



3.4 Environmental Conditions

Temperature:	23.5° C
Relative Humidity:	54%
ATM Pressure:	1016 mbar


3.5 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth.....	9 kHz
Quasi-Peak Adapter Mode.....	Normal


3.6 Summary of Test Results/Plots

Test mode:	TM1	Polarity:	Line
------------	-----	-----------	------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1940	41.23	9.59	50.82	63.86	-13.04	QP
2	0.2060	25.92	9.57	35.49	53.36	-17.87	AVG
3	0.3100	36.27	9.64	45.91	59.97	-14.06	QP
4	0.3780	25.01	9.68	34.69	48.32	-13.63	AVG
5	0.7180	34.54	9.69	44.23	56.00	-11.77	QP
6	0.8820	27.49	9.68	37.17	46.00	-8.83	AVG
7	1.1298	36.02	9.66	45.68	56.00	-10.32	QP
8	1.6339	32.08	9.64	41.72	46.00	-4.28	AVG
9	3.3900	35.71	9.63	45.34	56.00	-10.66	QP
10	3.3900	26.95	9.63	36.58	46.00	-9.42	AVG
11	18.1500	26.08	10.14	36.22	50.00	-13.78	AVG
12	25.2099	35.22	10.13	45.35	60.00	-14.65	QP

Test mode:	TM1	Polarity:	Neutral
------------	-----	-----------	---------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2060	42.19	9.57	51.76	63.36	-11.60	QP
2	0.2060	25.37	9.57	34.94	53.36	-18.42	AVG
3	0.3020	22.09	9.64	31.73	50.19	-18.46	AVG
4	0.3133	35.66	9.65	45.31	59.88	-14.57	QP
5	0.6300	32.00	9.70	41.70	56.00	-14.30	QP
6	0.8780	24.11	9.68	33.79	46.00	-12.21	AVG
7	1.3820	35.38	9.65	45.03	56.00	-10.97	QP
8	1.3820	29.64	9.65	39.29	46.00	-6.71	AVG
9	1.6339	35.74	9.64	45.38	56.00	-10.62	QP
10	1.6339	32.26	9.64	41.90	46.00	-4.10	AVG
11	20.6060	25.15	10.23	35.38	50.00	-14.62	AVG
12	24.3380	34.79	10.14	44.93	60.00	-15.07	QP

Test mode:	TM2	Polarity:	Line
------------	-----	-----------	------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1620	44.59	9.71	54.30	65.36	-11.06	QP
2	0.1700	28.99	9.68	38.67	54.96	-16.29	AVG
3	0.2500	24.61	9.60	34.21	51.75	-17.54	AVG
4	0.2540	38.43	9.61	48.04	61.62	-13.58	QP
5	0.3500	24.97	9.66	34.63	48.96	-14.33	AVG
6	0.5780	34.52	9.72	44.24	56.00	-11.76	QP
7	0.8100	28.67	9.69	38.36	46.00	-7.64	AVG
8	1.0420	35.69	9.67	45.36	56.00	-10.64	QP
9	1.2740	39.09	9.66	48.75	56.00	-7.25	QP
10	1.2740	32.49	9.66	42.15	46.00	-3.85	AVG
11	1.5060	37.49	9.64	47.13	56.00	-8.87	QP
12	1.5060	32.53	9.64	42.17	46.00	-3.83	AVG

Test mode:	TM2	Polarity:	Neutral
------------	-----	-----------	---------




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1660	44.07	9.70	53.77	65.15	-11.38	QP
2	0.1700	26.96	9.68	36.64	54.96	-18.32	AVG
3	0.2500	24.83	9.60	34.43	51.75	-17.32	AVG
4	0.2620	37.90	9.61	47.51	61.36	-13.85	QP
5	0.5820	31.58	9.72	41.30	56.00	-14.70	QP
6	0.5820	23.35	9.72	33.07	46.00	-12.93	AVG
7	1.0500	26.51	9.67	36.18	46.00	-9.82	AVG
8	1.2820	35.14	9.66	44.80	56.00	-11.20	QP
9	1.5140	36.27	9.64	45.91	56.00	-10.09	QP
10	1.5140	31.31	9.64	40.95	46.00	-5.05	AVG
11	19.8100	25.99	10.23	36.22	50.00	-13.78	AVG
12	27.9660	35.11	10.07	45.18	60.00	-14.82	QP

Test mode:	TM3	Polarity:	Line
------------	-----	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2060	47.44	9.57	57.01	63.36	-6.35	QP
2	0.2060	34.75	9.57	44.32	53.36	-9.04	AVG
3	0.2980	45.99	9.64	55.63	60.30	-4.67	QP
4	0.2980	30.72	9.64	40.36	50.30	-9.94	AVG
5	0.6139	38.55	9.71	48.26	56.00	-7.74	QP
6	0.6139	31.20	9.71	40.91	46.00	-5.09	AVG
7	0.8579	32.61	9.68	42.29	46.00	-3.71	AVG
8	1.1019	38.39	9.66	48.05	56.00	-7.95	QP
9	1.5900	38.02	9.64	47.66	56.00	-8.34	QP
10	1.5900	33.31	9.64	42.95	46.00	-3.05	AVG
11	2.0859	37.90	9.62	47.52	56.00	-8.48	QP
12	2.0859	30.91	9.62	40.53	46.00	-5.47	AVG

Test mode:	TM3	Polarity:	Neutral
------------	-----	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2060	48.85	9.57	58.42	63.36	-4.94	QP
2	0.2060	34.29	9.57	43.86	53.36	-9.50	AVG
3	0.2980	43.28	9.64	52.92	60.30	-7.38	QP
4	0.3700	26.41	9.68	36.09	48.50	-12.41	AVG
5	0.8620	29.86	9.68	39.54	46.00	-6.46	AVG
6	1.3500	32.22	9.65	41.87	46.00	-4.13	AVG
7	1.3540	37.08	9.65	46.73	56.00	-9.27	QP
8	1.6019	35.26	9.64	44.90	56.00	-11.10	QP
9	1.6019	31.80	9.64	41.44	46.00	-4.56	AVG
10	1.8420	35.84	9.63	45.47	56.00	-10.53	QP
11	2.0939	37.22	9.62	46.84	56.00	-9.16	QP
12	2.0939	32.78	9.62	42.40	46.00	-3.60	AVG


4. Radiated Emissions

4.1 Test Procedure


The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 18.305 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

The test setup for emission measurement below 30MHz..



The test setup for emission measurement from 30 MHz to 1 GHz..



4.2 Test Receiver Setup

Frequency :9kHz-30MHz

RBW=10kHz

VBW =30kHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120kHz,

VBW=300kHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Any non-ISM frequency device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 18.305 Limit}$$


4.4 Environmental Conditions

Temperature:	22.5 °C
Relative Humidity:	54 %
ATM Pressure:	1011 mbar

4.5 Summary of Test Results/Plots


Plot of Radiated Emissions Test Data (Below 30MHz)

Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	0.0091	72.84	-6.22	66.62	103.50	-36.88	-	-	peak
2	0.0338	60.89	-6.88	54.01	103.50	-49.49	-	-	peak
3	0.1490	81.60	-8.00	73.60	103.50	-29.90	-	-	peak
4	1.6046	33.96	-7.89	26.07	103.50	-77.43	-	-	peak
5	3.3843	34.41	-7.65	26.76	103.50	-76.74	-	-	peak
6	19.8360	32.49	-7.73	24.76	103.50	-78.74	-	-	peak

Test mode:	TM2	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	0.0158	58.37	-6.52	51.85	103.50	-51.65	-	-	peak
2	0.0332	62.57	-6.86	55.71	103.50	-47.79	-	-	peak
3	0.1267	72.97	-7.95	65.02	103.50	-38.48	-	-	peak
4	3.3029	34.66	-7.67	26.99	103.50	-76.51	-	-	peak
5	4.4954	34.28	-7.60	26.68	103.50	-76.82	-	-	peak
6	9.4048	32.70	-7.87	24.83	103.50	-78.67	-	-	peak

Test mode:	TM3	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	0.0160	68.36	-6.52	61.84	103.50	-41.66	-	-	peak
2	0.0340	61.93	-6.88	55.05	103.50	-48.45	-	-	peak
3	0.1277	80.68	-7.95	72.73	103.50	-30.77	-	-	peak
4	1.2682	34.64	-7.92	26.72	103.50	-76.78	-	-	peak
5	4.7580	33.03	-7.62	25.41	103.50	-78.09	-	-	peak
6	20.4902	30.91	-7.64	23.27	103.50	-80.23	-	-	peak

Plot of Radiated Emissions Test Data (Above 30MHz)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	30.8551	33.96	-9.53	24.43	63.50	-39.07	-	-	QP
2	48.0392	31.56	-7.73	23.83	63.50	-39.67	-	-	QP
3	165.4713	34.98	-8.19	26.79	63.50	-36.71	-	-	QP
4	288.2839	45.32	-8.23	37.09	63.50	-26.41	-	-	QP
5	360.9773	35.18	-6.86	28.32	63.50	-35.18	-	-	QP
6	862.8015	37.08	1.68	38.76	63.50	-24.74	-	-	QP

Test mode:	TM1	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	48.3778	37.32	-7.71	29.61	63.50	-33.89	-	-	QP
2	71.7052	39.41	-10.62	28.79	63.50	-34.71	-	-	QP
3	106.2810	37.50	-11.41	26.09	63.50	-37.41	-	-	QP
4	288.2839	44.28	-8.23	36.05	63.50	-27.45	-	-	QP
5	646.8215	36.32	-1.59	34.73	63.50	-28.77	-	-	QP
6	862.8015	35.42	1.68	37.10	63.50	-26.40	-	-	QP

Test mode:	TM2	Polarity:	Horizontal
------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	32.1839	32.96	-9.37	23.59	63.50	-39.91	-	-	QP
2	71.7052	36.15	-10.62	25.53	63.50	-37.97	-	-	QP
3	185.1622	36.93	-10.30	26.63	63.50	-36.87	-	-	QP
4	286.2651	45.02	-8.30	36.72	63.50	-26.78	-	-	QP
5	527.5706	34.19	-4.23	29.96	63.50	-33.54	-	-	QP
6	787.4746	34.86	0.80	35.66	63.50	-27.84	-	-	QP

Test mode:	TM2	Polarity:	Vertical
------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	52.6343	38.17	-7.87	30.30	63.50	-33.20	-	-	QP
2	71.7052	41.65	-10.62	31.03	63.50	-32.47	-	-	QP
3	189.1074	43.72	-10.73	32.99	63.50	-30.51	-	-	QP
4	286.2651	42.18	-8.30	33.88	63.50	-29.62	-	-	QP
5	718.7246	34.72	-0.62	34.10	63.50	-29.40	-	-	QP
6	881.1837	31.57	1.88	33.45	63.50	-30.05	-	-	QP

Test mode:	TM3	Polarity:	Horizontal
------------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	49.0626	33.60	-7.66	25.94	63.50	-37.56	-	-	QP
2	139.7906	32.28	-8.90	23.38	63.50	-40.12	-	-	QP
3	202.8745	36.35	-11.44	24.91	63.50	-38.59	-	-	QP
4	286.2651	41.92	-8.30	33.62	63.50	-29.88	-	-	QP
5	358.4497	37.19	-6.90	30.29	63.50	-33.21	-	-	QP
6	862.8015	34.90	1.68	36.58	63.50	-26.92	-	-	QP

Test mode:	TM3	Polarity:	Vertical
------------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.0172	39.39	-7.95	31.44	63.50	-32.06	-	-	QP
2	71.7052	44.15	-10.62	33.53	63.50	-29.97	-	-	QP
3	128.4858	37.66	-9.43	28.23	63.50	-35.27	-	-	QP
4	286.2651	41.25	-8.30	32.95	63.50	-30.55	-	-	QP
5	646.8215	36.48	-1.59	34.89	63.50	-28.61	-	-	QP
6	787.4746	34.34	0.80	35.14	63.50	-28.36	-	-	QP

Remark: '-' Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****