

FCC PART 15.249
EMI MEASUREMENT AND TEST REPORT
For
SHENZHEN DIT SECURITY&SURVEILLANCE TECHNOLOGY
CO.,LTD
3-4F,Building 5 th,Wandaiheng High-Tech park,Guangming,Shenzhen,china

FCC ID: 2ADESDIT

October 18, 2014

This Report Concerns: Original Report	Equipment Type: Wireless Kit Camera
Test Engineer:	Lisa Chen <i>Lisa Chen</i>
Report No.:	BSL141018Y-1EE-4
Receive EUT Date/Test Date:	October 08, 2014 / October 08-18, 2014
Reviewed By:	Mike moo <i>Mike moo</i>
Prepared By:	BSL Testing Co.,LTD. NO. 24, ZH Park, Nantou, Shenzhen, 518000 China Tel: 86- 755-26508703 Fax: 86- 755-26508703

TABLE OF CONTENTS

1.	GENERAL INFORMATION	3
1.1.	Report information	3
1.2.	Measurement Uncertainty	3
2.	PRODUCT DESCRIPTION	4
2.1.	EUT Description	4
2.2.	Block Diagram of EUT Configuration.....	6
2.3.	Support Equipment List	6
2.4.	Test Conditions	6
3.	TEST RESULTS SUMMARY	7
	Modifications	7
4.	TEST EQUIPMENT USED	8
5.	ANTENNA REQUIREMENT	9
5.1.	Standard Applicable.....	9
5.2.	Antenna Connected Construction	9
5.3.	Result	9
6.	CONDUCTED POWER LINE TEST	10
6.1.	Test Equipment	10
6.2.	Test Procedure	10
6.3.	Test Setup.....	10
6.4.	Conducted Power line Emission Limits.....	10
6.5.	Conducted Power Line Test Result.....	11
7.	RADIATED EMISSION TEST	13
7.1.	Test Equipment	13
7.2.	Test Procedure	13
7.3.	Radiated Test Setup	13
7.4.	Radiated Emission Limit.....	15
7.5.	Radiated Emission Test Result	16
8.	BAND EDGE	21
8.1.	Test Equipment	21
8.2.	Test Procedure	21
8.3.	Band Edge FCC 15.249(d) Limit.....	21
8.4.	Band Edge Test Result.....	22
9.	20-DB BANDWIDTH	23
9.1.	Test Equipment	23
9.2.	Test Procedure	23
9.3.	Limit.....	23
9.4.	Test Result /Plots	23

1. GENERAL INFORMATION

1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BSL approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BSL in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BSL therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BSL, unless the applicant has authorized BSL in writing to do so.

Test Facility -

The test site used to collect the radiated data is located on the address of BSL Testing Co.,LTD.

(FCC Registered Test Site Number: 191509) on

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

The Test Site is constructed and calibrated to meet the FCC requirements.

1.2. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	+/-1.25dB
2	RF Power, Conducted	+/-0.20dB
3	Spurious emissions, conducted	+/-0.33dB
4	All emissions, radiated (<1G)	+/-3.47dB
5	All emissions, radiated (>1G)	+/-3.82dB
6	Temperature	+/-0.5°CdB
7	Humidity	+/-2%

2. PRODUCT DESCRIPTION

2.1. EUT Description

Description	: Wireless Kit Camera
Trade	: N/A
Applicant	: SHENZHEN DIT SECURITY&SURVEILLANCE TECHNOLOGY CO.,LTD 3-4F,Building 5 th,Wandaiheng High-Tech park,Guangming,Shenzhen,china
Manufacturer	: SHENZHEN DIT SECURITY&SURVEILLANCE TECHNOLOGY CO.,LTD 3-4F,Building 5 th,Wandaiheng High-Tech park,Guangming,Shenzhen,china
Model Number	: L0712DW+C5664VD*4,L0712DW+C5664VD*1,L0712DW+C 5664VD*2
Modulation type	: GFSK
Antenna gain	: 2dBi
Antenna type	: Integral Antenna
Frequency	: 2408-2473MHz
Number of Channels	: 22 Channels
Power Supply	: DC 5V By Adaptor

The product model(s):

L0712DW+C5664VD*1,L0712DW+C5664VD*2 are identical in the same PCB layout, interior structure and electrical circuits with the model L0712DW+C5664VD*4 which tested in Shenzhen BSL Technology Co., Ltd. the only differences are the model name and appearance color for commercial purpose.

Channel List			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2408	12	2442
2	2412	13	2445
3	2415	14	2448
4	2418	15	2451
5	2421	16	2454
6	2424	17	2457
7	2427	18	2460
8	2430	19	2463
9	2433	20	2466
10	2436	21	2469
11	2439	22	2473

2.2. Block Diagram of EUT Configuration

Radiated emissions and Conducted Emission test




Figure 1 EUT Setup

2.3. Support Equipment List

Name	Model No	S/N	Manufacturer	Used “Yes/No”
Adaptor	JF005WR-0500100 VH	--	DIT	Yes

2.4. Test Conditions

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-25
Humidity (%RH)	25-75	50-63
Barometric pressure (mbar)	860-1060	950-1000

3. TEST RESULTS SUMMARY

FCC 15 Subpart C, Paragraph 15.249:2013

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	Compliant
Section 15.249(a)	The fundamental field strength and the harmonics	Compliant
Section 15.209 Section 15.249(d)	Radiated Emission	Compliant
Section 15.249(d)	Band Edge	Compliant
Section 15.203	Antenna Requirement	Compliant
Section 15.249	20dB Bandwidth	Compliant

Remark: "N/A" means "Not applicable".

Statement: All testing was performed using the test procedures found in ANSI C63.4-2003.

Modifications

No modification was made.

4. TEST EQUIPMENT USED

EQUIPMENT/FACILITIES	MANUFACTURER	MODEL	SERIAL NO.	DATE OF CAL.	CAL. INTERVAL
3m Semi-Anechoic Chamber	Chengyu Electron	9 (L)*6 (W)* 6 (H)	BSL086	Aug. 23 2014	1 Year
EMI Test Receiver	Rohde & Schwarz	ESCI3	BSL001	Sep. 28 2014	1 Year
BiConiLog Antenna	Rohde & Schwarz	HL562	BSL009	Sep. 28 2014	1 Year
Double -ridged waveguide horn	Rohde & Schwarz	9120D	BSL008	Aug. 27 2014	1 Year
Horn Antenna	ETS-LINDGREN	3160	BSL072	Dec. 28 2013	1 Year
Cable	Rohde & Schwarz	BSL045	BSL045	Aug. 27 2014	1 Year
Cable	Rohde & Schwarz	BSL046	BSL046	Aug. 27 2014	1 Year
Cable	Rohde & Schwarz	BSL047	BSL047	Aug. 27 2014	1 Year
Amplifier(100kHz-40G Hz)	R&S	SMR40	BSL007	Sep. 28 2014	1 Year
Band filter	Amindeon	82346	BSL049	Aug. 27 2014	1 Year
Active Loop Antenna	EMTES	EM15	BSL011	Sep. 28 2014	1 Year
Coaxial Switch	YUANFANG	TA218B	BSL004	Aug. 27 2014	1 Year
Spectrum analyzer	Rohde & Schwarz	FSP40	BSL049	Sep. 28 2014	1 Year
Shielding Room	zhongyu Electron	7.0(L)x3.0(W)x3.0(H)	BSL085	Sep. 28 2014	1 Year
EMI Test Receiver	R&S	ESPI	BSL002	Sep. 28 2014	1 Year
10dB Pulse Limita	R&S	BSL003	BSL003	Sep. 28 2014	1 Year
Coaxial Switch	YUANFANG	TA218B	BSL004	Aug. 27 2014	1 Year
LISN	Rohde & Schwarz	ESH3-Y5	BSL005	Sep. 28 2014	1 Year
Coaxial Cable	YUANFANG	BSL048	BSL048	Aug. 27 2014	1 Year
EMI TEST SOFTWARE	AUDIX	E3	N/A	N/A	N/A

5. ANTENNA REQUIREMENT

5.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.2. Antenna Connected Construction

According to § 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The antenna used in this product is integrated Antenna. The antenna is permanently attached. Refer to the product photo.

5.3. Result

Compliance

6. CONDUCTED POWER LINE TEST


6.1. Test Equipment

Please refer to section 4 this report.

6.2. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.).This provides a 50ohm/50uh coupling inpedance for the measuring equipment.The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uh coupling inpedance with 50ohm termination. Both sides of A.C. Line are check for maximum conducted interference.In order to find the maximum emission,the relative positions of equipment and all of the interface cables must be changed according to ASIN C63.4:2003 on conducted measurement .Conducted emissions were invested over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

6.3. Test Setup



For the actual test configuration,Please refer to the related items-Photos of testing

6.4. Conducted Power line Emission Limits


FCC Part 15 Paragraph 15.207 (dBuV)		
Frequency Range (MHZ)	Class A QP/AV	Class B QP/AV
0.15-0.5	79/66	65-56/56-46
0.5-5.0	73/60	56-46
5.0-3.0	73/60	60-50

Note: In the above table, the tighter limit applies at the band edges.

6.5. Conducted Power Line Test Result

PASS

Link Mode



Condition:


: RBW:9.000KHz VBW:30.000KHz

	Freq	Level	Limit	Over		
	MHz	dBuV	Line	Limit	Remark	Pol/Phase
			dBuV	dB		
1	0.358	27.8	48.8	-21.0	Average	LINE
2	0.654	21.0	46.0	-25.0	Average	LINE
3	1.184	21.1	46.0	-24.9	Average	LINE
4	3.310	20.6	46.0	-25.4	Average	LINE
5	6.914	23.0	50.0	-27.0	Average	LINE
6	9.654	24.9	50.0	-25.1	Average	LINE
7	10.342	15.4	50.0	-34.6	Average	LINE
8	24.529	6.8	50.0	-43.2	Average	LINE

Condition:

: RBW:9.000KHz VBW:30.000KHz

	Freq	Level	Limit	Over		
	MHz	dBuV	Line	Limit	Remark	Pol/Phase
			dBuV	dB		
1	0.150	53.7	66.0	-12.3	QP	LINE
2	0.360	39.3	58.7	-19.4	QP	LINE
3	0.630	32.3	56.0	-23.7	QP	LINE
4	1.141	32.3	56.0	-23.7	QP	LINE
5	4.430	35.3	56.0	-20.7	QP	LINE
6	6.914	44.5	60.0	-15.5	QP	LINE
7	9.654	48.0	60.0	-12.0	QP	LINE
8	15.885	22.9	60.0	-37.1	QP	LINE



Condition:

: RBW:9.000KHz VBW:30.000KHz

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	Line	Limit	dB	
1	0.150	27.6	56.0	-28.4	Average	NEUTRAL
2	0.360	25.4	48.7	-23.3	Average	NEUTRAL
3	1.117	23.1	46.0	-22.9	Average	NEUTRAL
4	1.449	21.7	46.0	-24.3	Average	NEUTRAL
5	2.869	17.9	46.0	-28.1	Average	NEUTRAL
6	9.156	26.4	50.0	-23.6	Average	NEUTRAL
7	19.845	26.5	50.0	-23.5	Average	NEUTRAL
8	27.127	7.1	50.0	-42.9	Average	NEUTRAL

Condition:

: RBW:9.000KHz VBW:30.000KHz

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	Line	Limit	dB	
1	0.354	39.8	58.9	-19.1	QP	NEUTRAL
2	1.117	41.5	56.0	-14.5	QP	NEUTRAL
3	1.396	39.5	56.0	-16.5	QP	NEUTRAL
4	7.137	36.5	60.0	-23.5	QP	NEUTRAL
5	9.156	46.6	60.0	-13.4	QP	NEUTRAL
6	11.438	38.5	60.0	-21.5	QP	NEUTRAL
7	19.845	44.4	60.0	-15.6	QP	NEUTRAL
8	23.888	19.5	60.0	-40.5	QP	NEUTRAL

7. RADIATED EMISSION TEST

7.1. Test Equipment

Please refer to section 4 this report.

7.2. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level.

Calibrated Loop antenna is used as receiving antenna for frequencies below 30MHz, Calibrated Bilog antenna is used as receiving antenna for frequencies between 30 MHz and 1 GHz, Calibrated Horn antenna is used as receiving antenna for frequencies above 1000MHz. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.


The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Peak detector and Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.


Through three orthogonal axes to determine which attitude and equipment arrangement produces the highest emission relative to the limit. And Y direction is worst mode

7.3. Radiated Test Setup


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.4. Radiated Emission Limit

All emission from a digital device,including any network of conductors and apparatus connected thereto,shall not exceed the level of field strength specified below :

A. Fundamental and Harmonics Radiated Emissions 15.249(a) Limit

Fundamental Frequency (MHZ)	Field as trength of Fundamental(3m)			Field as trength of Harmonics(3m)		
	mV/m	dBuV/m		uV/m	dBuV/m	
902-928	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)
2400-2483.5	50	94(AV)	114(Peak)	500	54(AV)	74(Peak)

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

(3) The emission limit in this paragraph os based on measurement instrumentation employing an average detector.Measurement using instrumentation with a peak detector function,corresponding to 20dB above the maximum permitted average limit.

B. Spurious Radiated Emissions.

Frequency (MHz)	Limit			
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dBμV/m)	Measurement distance (m)	The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
0.009 - 0.490	2400/F(kHz)	/	300	
0.490 - 1.705	24000/F(kHz)	/	30	
1.705-30	30	29.5	30	
30 - 88	100	40	3	
88 - 216	150	43.5	3	
216 - 960	200	46	3	
Above 960	500	54	3	

Note: (1) RF Voltage (dBuV)=20 log Voltage(uV)

(2) In the Above Table,the tighter limit applies at the band edges.

(3) Distaqnce refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

7.5. Radiated Emission Test Result

Pass

A. Fundamental Radiated Emissions Data

CH Low

Freq. (MHz)	Read Level (dBuV) AV/PK	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission (dBuV/m) AV/PK	HORIZ/ VERT	Limits (dBuV/m) AV/PK	Margin (dB)
2408	61.79/76.68	27.47	5.42	30.17	64.51/79.95	VERT	94/114	-29.49/-34.05
2408	73.94/86.16	27.47	5.42	30.17	76.66/89.43	HORIZ	94/114	-17.34/-24.57

CH Middle

Freq. (MHz)	Read Level (dBuV) AV/PK	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission (dBuV/m) AV/PK	HORIZ/ VERT	Limits (dBuV/m) AV/PK	Margin (dB)
2442	61.69/77.43	27.40	5.40	30.15	64.34/80.08	VERT	94/114	-24.66/-28.92
2442	73.52/88.74	27.40	5.40	30.15	76.17/91.39	HORIZ	94/114	-17.83/-22.61

CH High

Freq. (MHz)	Read Level (dBuV) AV/PK	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Emission (dBuV/m) AV/PK	HORIZ/ VERT	Limits (dBuV/m) AV/PK	Margin (dB)
2473	68.38/82.15	27.50	5.46	29.98	71.36/85.13	VERT	94/114	-22.64/-28.87
2473	72.53/86.96	27.50	5.46	29.98	75.51/89.94	HORIZ	94/114	-18.57/-24.06

Remark:

Final Emission = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

B. General Radiated Emissions Data

For below 9kHz-30MHz Spurious

Freq. (MHz)	Emission(dBuV/m) AV/PK	Limits(dBuV/m) AV/PK	Margin (dB)
-	-	-	-
-	-	-	-


Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.

For 30M-1000MHz Spurious


2442MHz Transmitting(*Worst case mode*)

Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain



Condition : FCC CLASS-B 3m HORIZONTAL
: RBW:120.000KHz VBW:300.000KHz SWT:Auto

	Freq	Limit	Level	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	40.135	40.0	33.8	-6.2	QP	HORIZONTAL
2	167.824	43.5	30.6	-12.9	QP	HORIZONTAL
3	216.024	46.0	34.5	-11.5	QP	HORIZONTAL
4	312.179	46.0	38.1	-7.9	QP	HORIZONTAL
5	408.946	46.0	36.1	-9.9	QP	HORIZONTAL
6 max	576.644	46.0	44.1	-1.9	QP	HORIZONTAL
7	649.660	46.0	41.8	-4.2	QP	HORIZONTAL
8	952.094	46.0	39.2	-6.8	QP	HORIZONTAL



Condition : FCC CLASS-B 3m VERTICAL
 : RBW:120.000KHz VBW:300.000KHz SWT:Auto

	Limit	Over			
Freq	Line	Level	Limit	Remark	Pol/Phase
MHz	dBuV/m	dBuV/m	dB		
1	40.135	40.0	33.4	-6.6 QP	VERTICAL
2	47.994	40.0	32.8	-7.2 QP	VERTICAL
3	239.987	46.0	30.7	-15.3 QP	VERTICAL
4	408.946	46.0	35.7	-10.3 QP	VERTICAL
5 max	601.427	46.0	40.2	-5.8 QP	VERTICAL
6	696.857	46.0	38.2	-7.8 QP	VERTICAL
7	744.866	46.0	34.5	-11.5 QP	VERTICAL
8	952.094	46.0	39.9	-6.1 QP	VERTICAL

For 1000MHz-25000MHz Spurious**CH Low**

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4816.0	42.74/59.56	VERT	54.0/74.0	-11.26/-14.44
7224.0	42.22/60.11		54.0/74.0	-11.78/-13.89
9632.0	44.95/61.15		54.0/74.0	-9.05/-12.85
4816.0	44/61.03	HORIZ	54.0/74.0	-10/-12.97
7224.0	43.61/61.35		54.0/74.0	-10.39/-12.65
9632.0	45.05/62.23		54.0/74.0	-8.95/-11.77

CH Middle

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4884.0	42.83/59.92	VERT	54.0/74.0	-11.17/-14.08
7326.0	42.8/60.25		54.0/74.0	-11.2/-13.75
9768.0	44.61/61.41		54.0/74.0	-9.39/-12.59
4884.0	43.8/61.17	HORIZ	54.0/74.0	-10.2/-12.83
7326.0	43.61/61.95		54.0/74.0	-10.39/-12.05
9768.0	44.89/62.55		54.0/74.0	-9.11/-11.45

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
4946.0	43.2/61.02	VERT	54.0/74.0	-10.8/-12.98
7419.0	42.3/60.17		54.0/74.0	-11.7/-13.83
9892.0	43.55/61.46		54.0/74.0	-10.45/-12.54
4946.0	44.3/62.13	HORIZ	54.0/74.0	-9.7/-11.87
7419.0	43.7/61.66		54.0/74.0	-10.3/-12.34
9892.0	44.71/62.69		54.0/74.0	-9.29/-11.31

Note:

1. The average measurement was not performed when the peak measured data under the limit of average detection.
2. Emissions attenuated more than 20 dB below the permissible value are not reported.

8. BAND EDGE

8.1. Test Equipment

Please refer to Section 4 this report.

8.2. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated measurement. The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz respectively.

8.3. Band Edge FCC 15.249(d) Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

8.4. Band Edge Test Result

Pass

ALL of the restriction bands were tested, and only the data of worst case was exhibited.

CH Low

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2390	29.04/38.76	VERT	54.0/74.0	-24.96/-35.24
2400	39.33/55.3		54.0/74.0	-14.67/-18.7
2390	27.43/35.82	HORIZ	54.0/74.0	-26.57/-38.18
2400	38.59/54.87		54.0/74.0	-15.41/-19.13

CH High

Freq. (MHz)	Emission(dBuV/m) AV/PK	HORIZ/ VERT	Limits(dBuV/m) AV/PK	Margin (dB)
2483.5	38.52/47.18	VERT	54.0/74.0	-15.48/-26.82
2500.00	34.07/46.52		54.0/74.0	-19.93/-27.48
2483.5	37.53/46.66	HORIZ	54.0/74.0	-16.47/-27.34
2500.00	33.34/44.98		54.0/74.0	-20.66/-29.02

Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.

9. 20-DB BANDWIDTH

9.1. Test Equipment

Please refer to Section 4 this report.

9.2. Test Procedure


1. The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on measurement.
2. Set center frequency of spectrum analyzer = operating frequency.
3. The spectrum analyzer as RBW=30 KHz, VBW=100 KHz, Sweep=auto
4. Mark the peak frequency and -20dB (upper and lower) frequency.


9.3. Limit

Please refer section15.249

9.4. Test Result /Plots

Limit	Channel Frequency (MHz)	20dB Bandwidth (MHz)
/	2408	4.06
/	2442	4.088
/	2473	4.116

1 PK
VIEW

1 PK
VIEW

1 PK
VIEW