

			Title: JCI LABEL DRAWING	ECM 23319
	Name	Date	Product Name: LABEL IQ LOCKDOWN PG PRODUCT	
Created	ALBERT F.	13.03.2024	Document No: 4018129	
Updated			Document Rev: 00	
Approved	SHAY A.	13.03.2024	Sheet 1 of 1	

Model: IQ LOCKDOWN PG (915-3:085) MPN: HL1-CNT-001-LDG P/N: 90-210279 Installation Instr.: D-309014 S/N: WWYYXXXXXX	DO NOT PAINT OR REMOVE THIS LABEL Ratings: 5VDC/0.5A Lithium Battery rated 3.7V/5200mAh FCC ID: F5323IQLOCKDOWNPG IC:160A-IQLOCKDOWNPG UL294 Access Control Single Point Locking Device 20 Minute - 45 Minute Rating Test Standard: UL 10C, NFPA 252, CAN/ULC S104 Guardian Fire Testing Laboratories inc	ID: 505-DDDD  S-210280 REV.00 www.firetesting.com ISO 17020,17025,17065 Johnson Controls	  <small>This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</small> CAN ICES-3(B)/NMB-3(B) Tyco Safety Products Canada Ltd.
Made in CN Date:03/13/24			

SIZE: 102*38mm



NOTES:

- Model: IQ LOCKDOWN--- Constant (Description from SAP).
- MPN: HL1-CNT-001-LDG --- Constant (Description from Qolsys System).
- 90-210279 – Constant (product Cat. Number from SAP)

Short ID:

- 505** – Constant (Product Power G type)
- DDDD** – Variable (short Panel ID, cannot be 0000)

S/N - Barcode S/N– Data Matrix:

- WW – Week
- YY- Year
- XXXXXX- Numerator, increment by 1. Became equal to 000001 every new week

Other fields- Fixed