



**FCC Part 1 Subpart I
FCC Part 2 Subpart J**

RF EXPOSURE REPORT

FOR

Left Shifter with AIREA and BLE Radios

MODEL NUMBER: 00020

**FCC ID: C90-LSBB2
IC: 10161A-LSBB2**

REPORT NUMBER: 13079833-E3V2

ISSUE DATE: September 25, 2020

Prepared for
SRAM LLC
1000 W Fulton Market 4th Floor
Chicago, IL 60607 U.S.A

Prepared by
UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	3/30/2020	Initial Issue	--
V2	9/25/2020	Updated Max Power	Steven Tran

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. REFERENCES	5
4. FACILITIES AND ACCREDITATION	5
5. DEVICE UNDER TEST	5
6. MAXIMUM OUTPUT POWER	5
7. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS	6
7.1. FCC	6

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SRAM LLC
1000 W Fulton Market 4th Floor
Chicago, IL 60607 U.S.A

EUT DESCRIPTION: Left Shifter with AIREA and BLE Radios

MODEL: 00020

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies

UL Verification Services Inc. calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Approved & Released For
UL Verification Services Inc. By:



Dan Corona
OPERATIONS LEADER
UL Verification Services Inc.

Prepared By:



Steven Tran
TEST ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

All calculations were made in accordance with FCC KDB 447498.

3. REFERENCES

All measurements were made as documented in test report UL Verification Services Inc. Document 13079833-E1 and 13079833-E2 for operation in the 2.4 GHz band and UL Verification Services Inc.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports or client declarations.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://nist.gov/standards/scopes/2000650.htm>.

5. DEVICE UNDER TEST

The EUT is a Right Shifter with radios AIREA operating in the frequency range of 2405 to 2475 MHz and BLE operating in the frequency range of 2402 to 2480MHz. The user to antenna separation distance is 0mm.

6. MAXIMUM OUTPUT POWER

The maximum output power of the device is declared as the following:

BLE = 4dBm; Antenna Gain: 2.2dBi

AIREA = 4dBm; Antenna Gain: 2.2dBi

7. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

7.1. FCC

SAR test exclusion in accordance with KDB 447498 D01 v06.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [f(\text{GHz})] \leq 3.0$, for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

This test exclusion is applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

SAR Exclusion Calculation Table for Portable Devices (Separation distance < 50 mm)

Tx	Frequency (MHz)	Max Output power		Duty Cycle	Max Output Power with Duty factor correction (mW)	Separation distances (mm)	Calculated Threshold Value
		dBm	mW				
BLE	2480	4.0	3	100%	3	5	0.9

Tx	Frequency (MHz)	Max Output power		Duty Cycle	Max Output Power with Duty factor correction (mW)	Separation distances (mm)	Calculated Threshold Value
		dBm	mW				
AIREA	2475	4.0	3	100%	3	5	0.9

Conclusion:

The device operates with a maximum Duty Cycle of 100%. The Calculated Threshold with duty cycle applied is ≤ 3 for 1-g SAR and ≤ 7 for 10-g extremity SAR; therefore, this device qualifies for Standalone SAR test exclusion.

END OF REPORT