



REPORT No.: SZ23080275W05

TEST REPORT

APPLICANT : BLU Products, Inc.

PRODUCT NAME : Smart Phone

MODEL NAME : G73L

BRAND NAME : BLU

FCC ID : YHLBLUG73L

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2023-10-18

TEST DATE : 2023-10-19 to 2023-12-01

ISSUE DATE : 2023-12-13



Edited by:

Peng Mi

Peng Mi (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	10
2.4. Test Configuration of EUT	11
2.5. Test Conditions	11
2.6. Test Setup Layout Diagram	12
3. Test Results	15
3.1. Antenna Requirement	15
3.2. Duty Cycle of Test Signal	16
3.3. Maximum Peak and Average Conducted Output Power	17
3.4. 6 dB Bandwidth	18
3.5. Conducted Spurious Emissions and Band Edge	19
3.6. Power Spectral Density	20
3.7. Conducted Emission	21
3.8. Restricted Frequency Bands	22
3.9. Radiated Emission	23
Annex A Test Data and Result	25



REPORT No.: SZ23080275W05

Change History		
Version	Date	Reason for change
1.0	2023-12-13	First edition

1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle of Test Signal	Nov. 22, 2023	Zhong Yanshan	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Nov. 24, 2023	Zhong Yanshan	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Nov. 24, 2023	Zhong Yanshan	PASS	No deviation
5	15.247(a)	Bandwidth	Nov. 22, 2023	Zhong Yanshan	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Nov. 22, 2023	Zhong Yanshan	PASS	No deviation
7	15.247(e)	Power Spectral Density	Nov. 22, 2023	Zhong Yanshan	PASS	No deviation
8	15.207	Conducted Emission	Oct. 24, 2023	Wang Deyong	PASS	No deviation
9	15.247(d)	Restricted Frequency Bands	Nov. 25, 2023	Su Zhan	PASS	No deviation
10	15.209, 15.247(d)	Radiated Emission	Dec. 01, 2023	Su Zhan	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB 558074 D01 v05r02.

Note 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2023.02.27	2024.02.26
Power Sensor	MY54180008	U2021XA	Agilent	2023.10.17	2024.10.16
Attenuator	MTJ6004-20	VAT-10+	MTJ Cooperation	N/A	N/A
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2023.02.09	2024.02.08
LISN	8127449	NSLK 8127	Schwarzbeck	2023.02.21	2024.02.20
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2023.06.27	2024.06.26
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	N/A	N/A

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
Morlab EMCR	Morlab	V1.2
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**1.2.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2023.06.21	2024.06.20
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2023.07.01	2024.06.30
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2023.06.26	2024.06.25
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2023.07.01	2024.06.30
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2023.07.01	2024.06.30
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2023.06.27	2024.06.26
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2023.06.27	2024.06.26
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2023.07.04	2024.07.03
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2023.07.04	2024.07.03
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2023.07.04	2024.07.03
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-N N-5	Qualwave	2023.07.04	2024.07.03
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone	+86 755 36698555
Facsimile	+86 755 36698525
FCC Designation Number	CN1192
FCC Test Firm Registration Number	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant	BLU Products, Inc.
Applicant Address	8600 NW 36th Street, Suite #200 Doral, FL 33166, USA
Manufacturer	BLU Products, Inc.
Manufacturer Address	8600 NW 36th Street, Suite #200 Doral, FL 33166, USA

2.2. Information of EUT

Product Name:	Smart Phone	
Sample No.:	1#; 13#	
Hardware Version:	SC6303_MB_V1.1.0	
Software Version:	BLU_G0930_V13.0.G.01.00_GENERIC 24-09-2023	
Modulation Technology:	DSSS, OFDM	
Modulation Type:	Refer to section1.3	
Operating Frequency Range:	802.11b/g/n (HT20): 2412MHz–2462MHz	
Antenna Type:	PIFA Antenna	
Antenna Gain:	2.10dBi	
Accessory Information:	Battery	
	Brand Name:	BLU
	Model No.:	C806051500P
	Serial No.:	N/A
	Capacity:	5000mAh
	Rated Voltage:	3.87V
	Charge Limit:	4.45V
	Manufacturer:	Shenzhen Jiuliyuan Electronic Technology Co., Ltd.



Accessory Information:	Adaptor	
	Brand Name:	BLU
	Model No.:	US-HY-2000
	Serial No.:	N/A
	Rated Output:	5V $\pm$ 2000mA
	Rated Input:	100-240V $\sim$ 50/60Hz, 0.3A
	Manufacturer:	Shenzhen Zhongfu core Technology Co., LTD

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3.Channel List of EUT

Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
802.11b/g/n (HT20)	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432		
	6	2437		
	7	2442		

Note 1: The black bold channels were selected for test.



2.4. Test Configuration of EUT

2.4.1. Modulation Type and Data Rate of EUT

Modulation technology	Modulation Type	Data Rate (Mbps) Note1
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/ 11
OFDM (802.11g)	BPSK	6 / 9
	QPSK	12 / 18
	16QAM	24 / 36
	64QAM	48 / 54
OFDM (802.11n (HT20))	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65

Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.

Note2: The RF signal transmission of EUT is controlled by the build-in engineering mode which is provided by the manufacturer. The recorded power setting value is the maximum that the engineering mode has configuration during testing.

2.5. Test Conditions

Temperature (°C)	15-35
Relative Humidity (%)	30-60
Atmospheric Pressure (kPa)	86-106


2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement

Power item



Other items



2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Inside of the EUT has a PIFA antenna coupled with the metal shrapnel. Please refer to the EUT internal photos.



3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak and Average Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 and A.3 in this report.



3.4.6 dB Bandwidth

3.4.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.4.1.Test Procedures

KDB 558074 Section 8.2 was used in order to prove compliance.

3.4.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.3.Test Result

Refer to Annex A.4 in this report.



3.5. Conducted Spurious Emissions and Band Edge

3.5.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.5.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.5.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.6. Power Spectral Density

3.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 30kHz
- d) Set VBW to 100kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level and recorded as PD
- j) Use below formula to calculate the Conducted PSD value that at specified RBW:

Conducted PSD = PD - 10lg(30k/3k)

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.7 in this report.

3.7. Conducted Emission

3.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.7.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.7.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.7.4. Test Result

Refer to Annex A.8 in this report.



3.8.Restricted Frequency Bands

3.8.1.Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.8.2.Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.8.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.8.4.Test Result

Refer to Annex A.9 in this report.

3.9. Radiated Emission

3.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.9.2. Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4. Test Result

Refer to Annex A.10 in this report.




Annex A Test Data and Result

A.1. Duty Cycle of Test Signal


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	Ant1	99.71	0.01	0.08
NVNT	b	2437	Ant1	99.69	0.01	0.08
NVNT	b	2462	Ant1	99.69	0.01	0.08
NVNT	g	2412	Ant1	97.09	0.13	0.48
NVNT	g	2437	Ant1	98.02	0.09	0.48
NVNT	g	2462	Ant1	97.55	0.11	0.48
NVNT	n20	2412	Ant1	98.27	0.08	0.52
NVNT	n20	2437	Ant1	97.87	0.09	0.52
NVNT	n20	2462	Ant1	97.87	0.09	0.52

Test Graphs

Duty Cycle NVNT b 2412MHz Ant1




Duty Cycle NVNT b 2437MHz Ant1






Duty Cycle NVNT b 2462MHz Ant1




Duty Cycle NVNT g 2412MHz Ant1






Duty Cycle NVNT g 2437MHz Ant1




Duty Cycle NVNT g 2462MHz Ant1






Duty Cycle NVNT n20 2412MHz Ant1




Duty Cycle NVNT n20 2437MHz Ant1





Duty Cycle NVNT n20 2462MHz Ant1




**A.2. Maximum Peak Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	b	2412	Ant1	18.82	0	18.82	0.07621	30	Pass
NVNT	b	2437	Ant1	17.83	0	17.83	0.06067	30	Pass
NVNT	b	2462	Ant1	18.73	0	18.73	0.07464	30	Pass
NVNT	g	2412	Ant1	20.59	0	20.59	0.11455	30	Pass
NVNT	g	2437	Ant1	20.87	0	20.87	0.12218	30	Pass
NVNT	g	2462	Ant1	20.85	0	20.85	0.12162	30	Pass
NVNT	n20	2412	Ant1	20.93	0	20.93	0.12388	30	Pass
NVNT	n20	2437	Ant1	21.24	0	21.24	0.13305	30	Pass
NVNT	n20	2462	Ant1	20.08	0	20.08	0.10186	30	Pass

Test Graphs


Peak Power NVNT b 2412MHz Ant1




Peak Power NVNT b 2437MHz Ant1




Peak Power NVNT b 2462MHz Ant1




Peak Power NVNT g 2412MHz Ant1




Peak Power NVNT g 2437MHz Ant1




Peak Power NVNT g 2462MHz Ant1




Peak Power NVNT n20 2412MHz Ant1



Peak Power NVNT n20 2437MHz Ant1



Peak Power NVNT n20 2462MHz Ant1




**A.3. Maximum Average Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	b	2412	Ant1	16.05	0.01	16.06	0.04036	30	Pass
NVNT	b	2437	Ant1	15.62	0.01	15.63	0.03656	30	Pass
NVNT	b	2462	Ant1	15.56	0.01	15.57	0.03606	30	Pass
NVNT	g	2412	Ant1	13.34	0.13	13.47	0.02223	30	Pass
NVNT	g	2437	Ant1	13.64	0.09	13.73	0.0236	30	Pass
NVNT	g	2462	Ant1	13.59	0.11	13.7	0.02344	30	Pass
NVNT	n20	2412	Ant1	13.38	0.08	13.46	0.02218	30	Pass
NVNT	n20	2437	Ant1	13.65	0.09	13.74	0.02366	30	Pass
NVNT	n20	2462	Ant1	12.57	0.09	12.66	0.01845	30	Pass

Test Graphs


Average Power NVNT b 2412MHz Ant1




Average Power NVNT b 2437MHz Ant1




Average Power NVNT b 2462MHz Ant1



Average Power NVNT g 2412MHz Ant1




Average Power NVNT g 2437MHz Ant1




Average Power NVNT g 2462MHz Ant1



Average Power NVNT n20 2412MHz Ant1




Average Power NVNT n20 2437MHz Ant1





Average Power NVNT n20 2462MHz Ant1



**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	8.577	0.5	Pass
NVNT	b	2437	Ant1	8.567	0.5	Pass
NVNT	b	2462	Ant1	8.542	0.5	Pass
NVNT	g	2412	Ant1	16.361	0.5	Pass
NVNT	g	2437	Ant1	16.424	0.5	Pass
NVNT	g	2462	Ant1	16.353	0.5	Pass
NVNT	n20	2412	Ant1	17.318	0.5	Pass
NVNT	n20	2437	Ant1	17.574	0.5	Pass
NVNT	n20	2462	Ant1	17.543	0.5	Pass



Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1



-6dB Bandwidth NVNT b 2437MHz Ant1




-6dB Bandwidth NVNT b 2462MHz Ant1




-6dB Bandwidth NVNT g 2412MHz Ant1




-6dB Bandwidth NVNT g 2437MHz Ant1



-6dB Bandwidth NVNT g 2462MHz Ant1




-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1





**A.5. Conducted Spurious Emissions**


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-35.27	-20	Pass
NVNT	b	2437	Ant1	-34.32	-20	Pass
NVNT	b	2462	Ant1	-34.89	-20	Pass
NVNT	g	2412	Ant1	-30.36	-20	Pass
NVNT	g	2437	Ant1	-30.25	-20	Pass
NVNT	g	2462	Ant1	-31.23	-20	Pass
NVNT	n20	2412	Ant1	-30.18	-20	Pass
NVNT	n20	2437	Ant1	-31.01	-20	Pass
NVNT	n20	2462	Ant1	-31.25	-20	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ant1 Ref




Tx. Spurious NVNT b 2412MHz Ant1 Emission



Tx. Spurious NVNT b 2437MHz Ant1 Ref




Tx. Spurious NVNT b 2437MHz Ant1 Emission




Tx. Spurious NVNT b 2462MHz Ant1 Ref




Tx. Spurious NVNT b 2462MHz Ant1 Emission



Tx. Spurious NVNT g 2412MHz Ant1 Ref




Tx. Spurious NVNT g 2412MHz Ant1 Emission



Tx. Spurious NVNT g 2437MHz Ant1 Ref




Tx. Spurious NVNT g 2437MHz Ant1 Emission



Tx. Spurious NVNT g 2462MHz Ant1 Ref




Tx. Spurious NVNT g 2462MHz Ant1 Emission




Tx. Spurious NVNT n20 2412MHz Ant1 Ref




Tx. Spurious NVNT n20 2412MHz Ant1 Emission



Tx. Spurious NVNT n20 2437MHz Ant1 Ref




Tx. Spurious NVNT n20 2437MHz Ant1 Emission



Tx. Spurious NVNT n20 2462MHz Ant1 Ref



Tx. Spurious NVNT n20 2462MHz Ant1 Emission





REPORT No.: SZ23080275W05

A.6. Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-43.18	-20	Pass
NVNT	b	2462	Ant1	-53.07	-20	Pass
NVNT	g	2412	Ant1	-31.3	-20	Pass
NVNT	g	2462	Ant1	-43.28	-20	Pass
NVNT	n20	2412	Ant1	-36.09	-20	Pass
NVNT	n20	2462	Ant1	-40.79	-20	Pass




Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref




Band Edge NVNT b 2412MHz Ant1 Emission



Band Edge NVNT b 2462MHz Ant1 Ref




Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref




Band Edge NVNT g 2412MHz Ant1 Emission



Band Edge NVNT g 2462MHz Ant1 Ref




Band Edge NVNT g 2462MHz Ant1 Emission



Band Edge NVNT n20 2412MHz Ant1 Ref



Band Edge NVNT n20 2412MHz Ant1 Emission



Band Edge NVNT n20 2462MHz Ant1 Ref



Band Edge NVNT n20 2462MHz Ant1 Emission




**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	Ant1	-4.78	0	-4.78	8	Pass
NVNT	b	2437	Ant1	-9.04	0	-9.04	8	Pass
NVNT	b	2462	Ant1	-4.31	0	-4.31	8	Pass
NVNT	g	2412	Ant1	-11.99	0	-11.99	8	Pass
NVNT	g	2437	Ant1	-12.36	0	-12.36	8	Pass
NVNT	g	2462	Ant1	-12.15	0	-12.15	8	Pass
NVNT	n20	2412	Ant1	-12.95	0	-12.95	8	Pass
NVNT	n20	2437	Ant1	-12.99	0	-12.99	8	Pass
NVNT	n20	2462	Ant1	-11.95	0	-11.95	8	Pass

Test Graphs

PSD NVNT b 2412MHz Ant1




PSD NVNT b 2437MHz Ant1



PSD NVNT b 2462MHz Ant1




PSD NVNT g 2412MHz Ant1





PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1





PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1





PSD NVNT n20 2462MHz Ant1





A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT + Adapter + USB Cable + Earphone +WIFI TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.5411	36.51	35.11	56.00	46.00	Line	PASS
2	0.6001	36.87	35.78	56.00	46.00		PASS
3	0.7166	36.16	33.63	56.00	46.00		PASS
4	1.0806	35.78	32.10	56.00	46.00		PASS
5	1.2042	35.86	31.88	56.00	46.00		PASS
6	2.4537	34.64	26.88	56.00	46.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.5411	34.03	28.81	56.00	46.00	Neutral	PASS
2	1.2655	31.90	24.27	56.00	46.00		PASS
3	2.3942	31.66	20.64	56.00	46.00		PASS
4	3.4942	32.38	21.02	56.00	46.00		PASS
5	13.2864	39.90	20.06	60.00	50.00		PASS
6	16.1757	38.33	21.00	60.00	50.00		PASS



A.9. Restricted Frequency Bands

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading


G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m


Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

802.11b Mode

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2387.70	PK	22.15	6.74	27.20	56.09	74	PASS
1	2387.25	AV	10.64	6.74	27.20	44.58	54	PASS
11	2491.79	PK	21.82	6.74	27.20	55.76	74	PASS
11	2483.50	AV	10.40	6.74	27.20	44.34	54	PASS



(PEAK, Channel 1, 802.11b)



(AVERAGE, Channel 1, 802.11b)



(PEAK, Channel 11, 802.11b)




(AVERAGE, Channel 11, 802.11b)




802.11g Mode

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2389.71	PK	27.55	6.74	27.20	61.49	74	PASS
1	2390.00	AV	12.52	6.74	27.20	46.46	54	PASS
11	2484.19	PK	28.27	6.74	27.20	62.21	74	PASS
11	2483.50	AV	14.61	6.74	27.20	48.55	54	PASS




(PEAK, Channel 1, 802.11g)



(AVERAGE, Channel 1, 802.11g)



(PEAK, Channel 11, 802.11g)




(AVERAGE, Channel 11, 802.11g)




802.11n (HT20) Mode

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBμV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2390.00	PK	30.42	6.74	27.20	64.36	74	PASS
1	2390.00	AV	13.24	6.74	27.20	47.18	54	PASS
11	2483.89	PK	31.30	6.74	27.20	65.24	74	PASS
11	2483.50	AV	16.53	6.74	27.20	50.47	54	PASS




(PEAK, Channel 1, 802.11n (HT20))



(AVERAGE, Channel 1, 802.11n (HT20))



(PEAK, Channel 11, 802.11n (HT20))



(AVERAGE, Channel 11, 802.11n (HT20))



A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


**802.11b Mode**

Plot for Channel 1




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	31.26	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
45.5355	26.97	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
65.9259	18.89	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
90.2002	18.25	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
196.0360	20.12	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.1301	26.51	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2625.2709	36.73	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3912.5760	39.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5557.7131	44.36	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7235.3529	41.70	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10649.3874	45.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14657.2214	47.76	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	32.88	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
47.4775	28.29	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
63.9840	20.95	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
180.5005	22.30	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
360.1301	30.36	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
891.2513	23.59	N/A	N/A	N/A	46.00	N/A	Vertical	PASS


(Antenna Vertical, 30MHz to 1GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2924.3207	37.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4213.8512	41.18	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5846.4872	44.31	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7247.8540	41.76	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11360.6967	46.04	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13605.8838	48.01	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 1GHz to 18GHz)

Plot for Channel 6




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	29.02	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
45.5355	25.73	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
64.9550	18.06	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
90.2002	17.49	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
195.0651	21.22	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.1301	25.78	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2358.5598	34.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3771.3143	39.61	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5552.7127	43.87	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8442.9536	42.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10665.6388	45.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13608.3840	47.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	33.78	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
47.4775	29.80	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
64.9550	21.80	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
197.9780	20.96	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
360.1301	30.05	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
691.2312	20.68	N/A	N/A	N/A	46.00	N/A	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2896.6494	37.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3787.5656	40.63	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5688.9741	44.62	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7244.1037	40.84	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10260.6051	44.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14643.4703	48.53	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)




Plot for Channel 11




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	30.32	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
47.4775	26.35	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
63.9840	17.78	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
90.2002	17.13	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
194.0941	20.88	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.1301	25.91	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2904.3174	37.25	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3783.8153	40.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5917.7431	44.55	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7244.1037	42.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10544.3787	45.27	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14673.4728	48.15	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	33.83	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
47.4775	29.14	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
63.9840	21.11	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
197.9780	20.22	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
360.1301	30.57	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
850.4705	22.33	N/A	N/A	N/A	46.00	N/A	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2911.6519	37.35	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3818.8182	40.38	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5558.9632	45.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7242.8536	41.64	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11358.1965	47.05	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13618.3849	48.24	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)

**802.11g Mode****Plot for Channel 1**


Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	31.95	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
47.4775	26.79	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
63.9840	18.04	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
90.2002	17.31	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
196.0360	22.37	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.1301	26.10	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2931.9887	37.91	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3828.8191	39.96	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5556.4630	44.48	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7202.8502	41.57	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11355.6963	45.98	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13598.3832	48.70	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	32.95	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
47.4775	29.10	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
64.9550	22.54	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
107.6777	15.76	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
179.5295	21.85	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
360.1301	30.64	N/A	N/A	N/A	46.00	N/A	Vertical	PASS


(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2726.2877	37.79	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4380.1150	41.88	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5515.2096	44.66	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
9021.7518	43.86	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11349.4458	46.88	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14632.2194	48.09	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)


Plot for Channel 6



(Antenna Horizontal, 30MHz to 1GHz)




(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	32.77	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
47.4775	28.67	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
61.0711	21.77	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
80.4905	17.57	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
197.9780	20.12	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
360.1301	30.33	N/A	N/A	N/A	46.00	N/A	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
3098.7582	38.21	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4553.8795	43.11	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5583.9653	44.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7245.3538	41.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11363.1969	47.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13405.8672	48.04	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)




Plot for Channel 11




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	31.42	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
45.5355	27.34	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
65.9259	18.69	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
90.2002	17.08	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
191.1812	20.16	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
360.1301	26.37	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
3221.2684	37.94	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4548.8791	42.43	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5550.2125	44.83	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8526.7106	41.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11360.6967	47.31	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13734.6446	48.00	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	30.88	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
47.4775	28.95	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
63.9840	21.46	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
179.5295	20.76	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
360.1301	30.34	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
439.7498	23.21	N/A	N/A	N/A	46.00	N/A	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2895.6493	37.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3731.3109	39.46	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5550.2125	44.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8995.4996	42.95	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12244.5204	46.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14617.2181	48.41	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)


**802.11n (HT20) Mode**

Plot for Channel 1




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	29.22	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
54.2743	17.43	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
90.2002	16.87	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
194.0941	25.90	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
267.8879	23.10	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
360.1301	24.86	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2893.3156	37.18	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3813.8178	40.37	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5567.7140	44.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7544.1287	40.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11358.1965	45.94	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14622.2185	47.69	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	30.80	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
62.0420	22.13	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
194.0941	21.78	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
266.9169	23.17	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
360.1301	30.75	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
760.1702	24.45	N/A	N/A	N/A	46.00	N/A	Vertical	PASS


(Antenna Vertical, 30MHz to 1GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
3807.5673	40.07	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4650.1375	41.90	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5566.4639	44.52	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8025.4188	42.07	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10626.8856	45.64	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14643.4703	48.08	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 1GHz to 18GHz)

Plot for Channel 6




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	28.73	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
54.2743	16.19	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
93.1131	17.25	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
191.1812	30.85	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
273.7137	22.53	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
360.1301	25.19	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2862.6438	37.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4658.8882	42.00	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5556.4630	44.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8982.9986	43.81	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11365.6971	46.38	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13598.3832	48.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	31.58	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
123.2132	20.71	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
195.0651	21.58	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
279.5395	23.28	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
360.1301	31.33	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
760.1702	24.63	N/A	N/A	N/A	46.00	N/A	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2730.6218	36.93	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3848.8207	39.74	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5545.2121	44.59	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8052.9211	41.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10570.6309	45.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
15072.2560	48.26	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)




Plot for Channel 11




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	29.63	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
90.2002	17.43	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
194.0941	26.97	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
268.8589	23.50	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
360.1301	24.92	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
679.5796	22.69	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1624.1040	33.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3070.0058	37.82	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5200.1833	44.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8912.9927	43.44	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10578.1315	45.41	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
15134.7612	48.46	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	30.93	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
62.0420	21.30	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
130.0100	22.44	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
197.0070	21.72	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
360.1301	30.92	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
760.1702	24.22	N/A	N/A	N/A	46.00	N/A	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
2319.5533	34.72	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4397.6165	40.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5541.4618	45.04	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7246.6039	41.73	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
11435.7030	46.74	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14649.7208	48.51	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)

END OF REPORT