

FCC TEST REPORT

for

PART 15, SUBPART B CLASS B

EQUIPMENT : TABLET

MODEL NO. : NewSketch 1212 HRIII

F C C I D : FSUGNWHR

FILING TYPE : Original Grant

APPLICANT : **KYE SYSTEMS CORP.**

No. 492, Sec. 5, Chung Hsin Rd., San Chung,
Taipei Hsien, 241, Taiwan, R.O.C.

- The test result refers exclusively to the test presented test model / sample.
- Without the written authorization of the test lab., the Test Report may not be copied.

SPORTON INTERNATIONAL INC.

6F, No. 106, Hsin Tai Wu Rd., Sec. 1, Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

TABLE OF CONTENT

SECTION TITLE	PAGE
CERTIFICATE OF COMPLIANCE	3
1. GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST.....	4
1.1. APPLICANT	4
1.2. MANUFACTURER	4
1.3. BASIC DESCRIPTION OF EQUIPMENT UNDER TEST.....	4
1.4. FEATURE OF EQUIPMENT UNDER TEST.....	4
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	5
2.1. TEST MANNER	5
2.2. DESCRIPTION OF TEST SYSTEM.....	5
2.3. CONNECTION DIAGRAM OF TEST SYSTEM.....	7
3. TEST SOFTWARE.....	8
4. GENERAL INFORMATION OF TEST	9
4.1. TEST FACILITY	9
4.2. STANDARD FOR METHODS OF MEASUREMENT	9
4.3. TEST IN COMPLIANCE WITH.....	9
4.4. FREQUENCY RANGE INVESTIGATED.....	9
4.5. TEST DISTANCE	9
5. TEST OF CONDUCTED POWERLINE.....	10
5.1. MAJOR MEASURING INSTRUMENTS.....	10
5.2. TEST PROCEDURES.....	11
5.3. TYPICAL TEST SETUP LAYOUT OF CONDUCTED POWERLINE.....	12
5.4. TEST RESULT OF AC POWERLINE CONDUCTED EMISSION	13
5.5. PHOTOGRAPHS OF CONDUCTED EMISSION TEST CONFIGURATION.....	15
6. TEST OF RADIATED EMISSION	15
6.1. MAJOR MEASURING INSTRUMENTS.....	19
6.2. TEST PROCEDURES.....	20
6.3. TYPICAL TEST SETUP LAYOUT OF RADIATED EMISSION	21
6.4. TEST RESULT OF RADIATED EMISSION.....	22
6.5. PHOTOGRAPHS OF RADIATED EMISSION TEST CONFIGURATION	24
7. ANTENNA FACTOR AND CABLE LOSS	26
8. LIST OF MEASURING EQUIPMENT USED.....	27

CERTIFICATE OF COMPLIANCE

for

FCC PART 15, SUBPART B CLASS B

EQUIPMENT : TABLET

MODEL NO. : NewSketch 1212 HRIII

F C C I D : FSUGNWHHR

APPLICANT : **KYE SYSTEMS CORP.**

No. 492, Sec. 5, Chung Hsin Rd., San Chung,
Taipei Hsien, 241, Taiwan, R.O.C.

I HEREBY CERTIFY THAT :

The measurement shown in this report were made in accordance with the procedures given in **ANSI C63.4 -1992** and the energy emitted by this equipment was ***passed*** both radiated and conducted emissions **Class B** limits.

Testing was carried out on **July 10, 1998** at **SPORTON International Inc.**

W. L. Huang
General Manager

SPORTON INTERNATIONAL INC.

6F, No. 106, Hsin Tai Wu Rd., Sec. 1, Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1. GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST

1.1. APPLICANT

KYE SYSTEMS CORP.

No. 492, Sec. 5, Chung Hsin Rd., San Chung,
Taipei Hsien, 241, Taiwan, R.O.C.

1.2. MANUFACTURER

Same as 1.1

1.3. BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

EQUIPMENT : TABLET

MODEL NO. : NewSketch 1212 HRIII

TRADE NAME : GENIUS

FCC ID. : FSUGNWHR

RS232 DATA CABLE : Shielded

S09, S11, P04, P05, P06, P07 DATA CABLE : Non-shielded

POWER SUPPLY TYPE : Linear

POWER CORD : N/A

1.4. FEATURE OF EQUIPMENT UNDER TEST

Genius Tablet is a graphics tablet used to create or reproduce diagrams, drawings, building layouts, maps, etc. You can then save these graphics into your computer for other uses.

Using this tablet, you can :

- Trace anything; pictures, drawings, photos, maps, etc.
- Draw freehand; achieve precision and accuracy.
- Move the puck (or stylus) to select commands on the template, or move objects on the screen.
- Create a symbol library for your most often used symbols using AutoCAD.

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST

2.1. TEST MANNER

- a. The EUT has been associated with personal computer and peripherals pursuant to ANSI C63.4-1992 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. The DELL keyboard, HP printer, ACEEX modem, SONY monitor, GENIUS USB mouse and EUT were connected to the FIC P.C. for EMI test.
- c. The following three models EUT are used and tested.
- | | | |
|---|----------------------|-------|
| ① | PUCK | (P04) |
| ② | STYLUS | (S11) |
| ③ | PUCK (P06) + EMITEST | |
- d. According to the above tests, we listed the following modes as the worst cases:
- | | | |
|---|--------|-------|
| ① | PUCK | (P04) |
| ② | STYLUS | (S11) |
- These modes test results are included in this test report.
- e. Frequency range investigated: Conduction 450 KHz to 30 MHz, Radiation 30 MHz to 1000MHz.

2.2. DESCRIPTION OF TEST SYSTEM

Support Device 1. --- MONITOR (SONY)

FCC ID	: AK8GDM17SE2T
Model No.	: GDM-17SE2T
Serial No.	: SP1006
Data Cable	: Shielded, 1.7m
Power Supply Type	: Switching
Power Cord	: Non-shielded

Support Device 2. --- KEYBOARD (DELL)

FCC ID	: GYUM92SK
Model No.	: AT101 (DE8M)
Serial No.	: SP1009
Data Cable	: Shielded, 1.9m

Support Device 3. -- USB MOUSE (GENIUS)

FCC ID : FSUGMZFG
Model No. : NICHE USB
Serial No. : SP1017
Data Cable : Shielded, 1.8m

Support Device 4. --- PRINTER (HP)

FCC ID : B94C2642X
Model No. : DESKJET 400
Serial No. : SP0037
Data Cable : Shielded, 1.35m
Power Supply Type : Linear


Support Device 5. -- MODEM (ACEEX)

FCC ID : IFAXDM1414
Model No. : DM1414
Power Supply Type : Linear, AC Adapter
Power Cord : Non-shielded
Serial No. : SP1019
Data Cable : Shielded, 1.15m

Support Device 6. --- P.C. (FIC)

FCC ID : N/A
Model No. : P2L97
Serial No. : SP1003
Data Cable : Shielded
Power Cord : Non-shielded
Power Supply Type : Switching

(Remark : This support device was tested to comply with FCC standards and
authorized under a declaration of conformity.)

2.3. CONNECTION DIAGRAM OF TEST SYSTEM

1. The I/O cable is connected from the PC to the support device 1.
2. The I/O cable is connected from the PC to the support device 2.
3. The I/O cable is connected from the PC to the support device 3.
4. The I/O cable is connected from the PC to the support device 4.
5. The I/O cable is connected from the PC to the support device 5.
6. The I/O cable is connected from the EUT to the support device 6.

3. TEST SOFTWARE

An executive program, EMITEST.EXE under WIN 98, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The PC reads the test program from the floppy disk drive and runs it.
- c. The PC sends " H " messages to the monitor, and the monitor displays " H " patterns on the screen.
- d. The PC sends " H " messages to the printer, then the printer prints them on the paper.
- e. The PC sends " H " messages to the modem.
- f. The PC sends " H " messages to the internal Hard Disk, and the Hard Disk reads and writes the message.
- g. Repeat the steps from b to f.

4. GENERAL INFORMATION OF TEST

4.1. TEST FACILITY

This test was carried out by SPORTON INTERNATIONAL INC.

Openarea Test Site Location : No. 30-1, Lin 6, Diing-Fwu Tsuen, Lin-Kou-Hsiang,
Taipei Hsien, Taiwan, R.O.C.

TEL : 886-2-2601-1640

FAX : 886-2-2601-1695

4.2. STANDARD FOR METHODS OF MEASUREMENT

ANSI C63.4-1992

4.3 .TEST IN COMPLIANCE WITH

FCC PART 15, SUBPART B CLASS B

4.4. FREQUENCY RANGE INVESTIGATED

- a. Conduction : from 450 KHz to 30 MHz
- b. Radiation : from 30 MHz to 1000 MHz.

4.5. TEST DISTANCE

The test distance of radiated emission from antenna to EUT is 3M.

5. TEST OF CONDUCTED POWERLINE


Conducted Emissions were measured from 450 KHz to 30 MHz with a bandwidth of 9 KHz on the 115 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-1992 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in Figure 5-3. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

5.1. MAJOR MEASURING INSTRUMENTS

- Test Receiver
 - Attenuation 0 dB
 - Start Frequency 0.45 MHz
 - Stop Frequency 30 MHz
 - Step MHz 0.007 MHz
 - IF Bandwidth 9 KHz

5.2. TEST PROCEDURES

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room and was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connect to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm , 50 microhenry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 450 KHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- i. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported otherwise the emissions which do not have 6 dB margin will be retested on by one using the quasi-peak method and reported.



5.4. TEST RESULT OF AC POWERLINE CONDUCTED EMISSION

- Frequency Range of Test : from 0.45 MHz to 30 MHz
- All emissions not reported here are more than 10 dB below the prescribed limit.
- Temperature : 30•
- Relative Humidity : 42% RH
- Test Mode : P04 (PUCK)
- Test Date : July 10, 1998

The Conducted Emission test was passed at Line 0.77 MHz / 27.40 dBuV.

Frequency (MHz)	Line / Neutral	Meter Reading		Limits		Margin
		(dBuV)	(uV)	(dBuV)	(uV)	(dB)
0.77	L	27.40	23.44	48.00	251.19	-20.60
20.52	L	24.50	16.79	48.00	251.19	-23.50
0.78	N	26.70	21.63	48.00	251.19	-21.30
9.28	N	24.50	16.79	48.00	251.19	-23.50
15.21	N	25.80	19.50	48.00	251.19	-22.20
21.27	N	23.40	14.79	48.00	251.19	-24.60

Test Engineer :

Kenny Chuang

5.4.1. TEST RESULT OF AC POWERLINE CONDUCTED EMISSION

- Frequency Range of Test : from 0.45 MHz to 30 MHz
- All emissions not reported here are more than 10 dB below the prescribed limit.
- Temperature : 30•
- Relative Humidity : 42% RH
- Test Mode : S11 (STYLUS)
- Test Date : July 10, 1998

The Conducted Emission test was passed at Line 0.45 MHz / 44.10 dBuV.

Frequency (MHz)	Line / Neutral	Meter Reading		Limits		Margin
		(dBuV)	(uV)	(dBuV)	(uV)	(dB)
0.45	L	44.10	160.32	48.00	251.19	-3.90
0.98	L	39.80	97.72	48.00	251.19	-8.20
1.67	L	28.50	26.61	48.00	251.19	-19.50
0.45	N	40.30	103.51	48.00	251.19	-7.70
0.91	N	39.20	91.20	48.00	251.19	-8.80
1.74	N	36.80	69.18	48.00	251.19	-11.20

Test Engineer :


Kenny Chuang

5.5. PHOTOGRAPHS OF CONDUCTED EMISSION TEST CONFIGURATION

FRONT VIEW
(P04)



REAR VIEW
(P04)



SIDE VIEW
(P04)



FRONT VIEW
(S11)



REAR VIEW
(S11)



SIDE VIEW
(S11)



6. TEST OF RADIATED EMISSION

Radiated emissions from 30 MHz to 1000 MHz were measured with a bandwidth of 120 KHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in Figure 6-3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

6.1. MAJOR MEASURING INSTRUMENTS

- Pre-Amplifier
 - RF Gain 25 dB
 - Signal Input Input (for 0.1 MHz to 1.3 GHz)


- Spectrum Analyzer (HP 8560E)
 - Attenuation 0 dB
 - Start Frequency 30 MHz
 - Stop Frequency 1000 MHz
 - Resolution Bandwidth 1 MHz
 - Video Bandwidth 1 MHz
 - Signal Input Input 1 (for 30MHz to 2.9GHz)

- Quasi-Peak Adapter
 - Resolution Bandwidth 120 KHz
 - Frequency Band 30 MHz to 1 GHz
 - Quasi-Peak Detector ON for Quasi-Peak Mode
 - OFF for Peak Mode

6.2. TEST PROCEDURES

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported otherwise the emissions which do not have 6 dB margin will be repeated one by one using the quasi-peak method and reported.

6.3. TYPICAL TEST SETUP LAYOUT OF RADIATED EMISSION



6.4. TEST RESULT OF RADIATED EMISSION

- Equipment meets the technical specifications of 15.109
- Frequency Range of Test : from 30 MHz to 1000 MHz
- Test Distance : 3 M
- Temperature : 32•
- Relative Humidity : 60 % RH
- Test Mode : P04 (PUCK)
- Test Date : July 08, 1998
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Sample Calculation at 135.70 MHz
Corrected Reading = 11.13 + 1.86 + 20.67 = 33.66 (dBuV/m)

The Radiated Emission test was passed at

466.01 MHz / 41.45 dBuV (Vertical)

Antenna Height 2.0 Meter , Turntable Degree 205°.

Frequency	Antenna	Cable	Reading	Limits	Emission	Level	Margin		
Polarity	Factor	Loss							
(MHz)	(dB/m)	(dB)	(dBuV)	(dBuV/m)	(uV/m)	(dBuV/m)	(uV/m)	(dB)	
135.70	H	11.13	1.86	20.67	43.50	150	33.66	48.19	-9.84
167.71	H	12.23	2.16	19.28	43.50	150	33.67	48.25	-9.83
54.64	V	3.09	1.10	30.51	40.00	100	34.70	54.33	-5.30
168.05	V	12.23	2.17	20.38	43.50	150	34.78	54.83	-8.72
178.95	V	12.94	2.29	20.43	43.50	150	35.66	60.67	-7.84
466.01	V	22.37	3.90	15.18	46.00	200	41.45	118.17	-4.55

Test Engineer :

Jack Deng

6.4.1. TEST RESULT OF RADIATED EMISSION

- Equipment meets the technical specifications of 15.109
 - Frequency Range of Test : from 30 MHz to 1000 MHz
 - Test Distance : 3 M
 - Temperature : 32•
 - Relative Humidity : 60 % RH
 - Test Mode : S11 (STYLUS)
 - Test Date : July 08, 1998
-
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
 - Sample Calculation at 85.36 MHz
Corrected Reading = 7.58 + 1.40 + 26.42 = 35.40 (dBuV/m)

The Radiated Emission test was passed at

85.36 MHz / 35.40 dBuV (Horizontal)

Antenna Height 3.0 Meter , Turntable Degree 165°.

Frequency	Antenna	Cable	Reading	Limits	Emission	Level	Margin
Polarity	Factor	Loss					
(MHz)	(dB/m)	(dB)	(dBuV)	(dBuV/m)	(uV/m)	(dBuV/m)	(uV/m)
85.36	H	7.58	1.40	26.42	40.00	100	35.40
215.75	H	14.25	2.40	18.79	43.50	150	35.44
206.19	V	14.13	2.40	17.88	43.50	150	34.41
160.62	V	12.25	2.02	18.48	43.50	150	32.75
167.61	V	12.23	2.16	19.36	43.50	150	33.75
192.10	V	13.62	2.32	18.29	43.50	150	34.23

Test Engineer :

Jack Deng

6.5. PHOTOGRAPHS OF RADIATED EMISSION TEST CONFIGURATION

**FRONT VIEW
(P04)**



**REAR VIEW
(P04)**



FRONT VIEW
(S11)



REAR VIEW
(S11)



7. ANTENNA FACTOR AND CABLE LOSS

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)
30	-1.91	0.90
35	-0.50	0.92
40	0.61	1.04
45	1.40	1.28
50	2.39	1.10
55	3.54	1.11
60	4.40	1.30
65	4.84	1.40
70	5.59	1.37
75	6.21	1.24
80	7.60	1.51
85	7.73	1.60
90	8.22	1.60
95	8.90	1.70
100	9.36	1.70
110	10.01	1.70
120	10.41	1.90
130	10.84	1.90
140	11.42	1.91
150	11.91	2.01
160	12.25	2.11
170	12.72	2.21
180	13.02	2.30
190	13.50	2.30
200	14.05	2.40
220	15.11	2.50
240	16.81	2.60
260	17.51	2.71
280	17.70	2.90
300	17.89	2.91
320	18.00	3.10
340	18.33	3.20
360	19.44	3.30
380	20.31	3.40
400	21.19	3.50
450	21.10	3.70
500	22.21	4.10
550	23.42	4.30
600	24.01	4.50
650	25.11	4.70
700	26.00	4.90
750	26.41	5.11
800	27.10	5.50
850	27.51	5.60
900	27.90	5.80
950	28.01	5.90

8. LIST OF MEASURING EQUIPMENT USED

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration	Remark
EMC Receiver (site 2)	HP	8591EM	3710A01187	9 KHz - 18 GHz	Sep. 29, 1997	Conduction
LISN (EUT) (site 2)	Telemeter	NNB-2/16Z	98009	50 ohm / 50 uH	Jan. 29, 1998	Conduction
LISN (Support Unit) (site 2)	EMCO	3810/2NM	9703-1839	50 ohm / 50 uH	July 06, 1998	Conduction
Spectrum Analyzer (Site 4)	HP	8560E	3728A03186	30MHz - 2.9GHz	Sep. 24, 1997	Radiation
Amplifier (Site 4)	HP	8447D	2944A09072	0.1MHz -1.3GHz	Sep. 17, 1997	Radiation
Test Receiver (Site 4)	R&S	ESVP	893610/003	20MHz - 1.3GHz	April 13, 1998	Radiation
Bilog Antenna (Site 4)	CHASE	CBL6112A	2288	30MHz -2GHz	Jul. 24, 1997	Radiation
Half-wave dipole antenna (Site 4)	EMCO	3121C	9705-1285	28 M - 1GHz	May 19, 1998	Radiation
Turn Table (site 4)	EMCO	2080	9711-1090	0 ~ 360 degree	N/A	Radiation
Antenna Mast (site 4)	EMCO	2075	9711-2114	1 m- 4 m	N/A	Radiation