

TEST REPORT

Report Number. : R15541444-E1

Applicant : HID Global Corporation 611 Center Ridge Dr Austin, TX USA

- **Model : 30**
- FCC ID : JQ6-SIGNO30
 - IC : 2236B-SIGNO30
- EUT Description : Signo Décor Reader
- Test Standard(s) : FCC 47 CFR PART 15 SUBPART C ISED RSS-247 ISSUE 3 ISED RSS-GEN ISSUE 5 + A1 + A2

Date Of Issue: 2025-03-13

Prepared by:

UL LLC 12 Laboratory Dr. Research Triangle Park, NC 27709 U.S.A. TEL: (919) 549-1400



REPORT REVISION HISTORY

Rev.	lssue Date	Revisions	Revised By
V1	2025-01-22	Initial Issue	Noah Bennett
V2	2025-03-13	Misc. editorial updates	Mike Antola

Page 2 of 59

TABLE OF CONTENTS

RE	POR		2
TA	BLE	OF CONTENTS	3
1.	AT	TESTATION OF TEST RESULTS	5
2.	TES	ST RESULTS SUMMARY	6
3.	TES	ST METHODOLOGY	.6
4.	FAG	CILITIES AND ACCREDITATION	.7
5.	DE	CISION RULES AND MEASUREMENT UNCERTAINTY	.7
,	5.1.	METROLOGICAL TRACEABILITY	.7
	5.2.	DECISION RULES	7
,	5.3.	MEASUREMENT UNCERTAINTY	7
	5.4.	SAMPLE CALCULATION	8
6.	EQ	UIPMENT UNDER TEST	9
	6.1.	EUT DESCRIPTION	9
	6.2.	MAXIMUM OUTPUT POWER	9
	6.3.	DESCRIPTION OF AVAILABLE ANTENNAS	9
	6.4.	SOFTWARE AND FIRMWARE	9
	6.5.	WORST-CASE CONFIGURATION AND MODE 1	10
	6.6.	DESCRIPTION OF TEST SETUP	10
7.	ME	ASUREMENT METHOD	1
8.	TES	ST AND MEASUREMENT EQUIPMENT1	2
9.	AN [.]	TENNA PORT TEST RESULTS1	4
	9.1.	ON TIME AND DUTY CYCLE	14
	9.2.	99% BANDWIDTH	16
	9.2. 9.2	.1. BLE (1Mbps)	6 7
	9.3.	6 dB BANDWIDTH	18
	9.3.	.1. BLE (1Mbps)	8
	9.3.		9
	<i>9.4.</i> 9.4.	22.1. BLE (1Mbps)	20 21
	9.4.	.2. BLE (2Mbps)	21
	9.4. 9.4.	.3. DLE (TWDPS)	:2 22

Page 3 of 59

9.5. POWER SPECTRAL DENSITY	
9.5.1. BLE (1Mbps)	23
9.5.2. BLE (2Mbps)	24
	05
9.6. CONDUCTED SPURIOUS EMISSIONS	
9.6.1. BLE (1MDps)	
9.6.2. BLE (2Mbps)	
	20
10. RADIATED TEST RESULTS	
10.1. LIMITS AND PROCEDURE	
10.2 TRANSMITTER ABOVE 1 GHz	30
10.21 BLE (1Mbps)	
10.2.2 BLE (2Mbps)	40
	10
10.3. WORST CASE BELOW 30MHZ	
10.4. WORST CASE BELOW 1 GHZ	
	E A
10.1. WORST CASE SPURIOUS 16-20 GHZ	
11 AC POWER LINE CONDUCTED EMISSIONS	56
11.1.1. AC Power Line	57
	59

Page 4 of 59

1. ATTESTATION OF TEST RESULTS

COMPANY NAME:	HID Global Corporation 611 Center Ridge Dr Austin, TX USA	
EUT DESCRIPTION:	Signo Décor Reader	
MODEL:	30	
SERIAL NUMBER:	Non-Serialized	
SAMPLE RECEIPT DATE:	2024-11-19	
DATE TESTED:	2024-11-19 THRU 2024-11-21	
	APPLICABLE STANDARDS	
S	TANDARD	TEST RESULTS
CFR 47	Part 15 Subpart C	Complies
ISED F	RSS-247 Issue 3	Complies

ISED RSS-GEN Issue 5 + A1 + A2

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document.

Approved & Released For UL LLC By:

31.×

Brian Kiewra **Project Engineer** Consumer, Medical and IT Segment **UL LLC**

Prepared By:

hunder

TEL:(919) 549-1400

Complies

Noah Bennett **Engineer Project Associate** Consumer, Medical and IT Segment **UL LLC**

Page 5 of 59

2. TEST RESULTS SUMMARY

This report contains data provided by the customer which can impact the validity of results. UL LLC is only responsible for correctly integrating customer-provided data with measurements performed by UL LLC. Below is a list of the data provided by the customer:

- 1) Antenna gain and type (section 6.3)
- 2) Cable loss (section 9)
- 3) Supported Data-Rates and Power Settings. Orientation of Operation (Section 6.5)
- 4) Software, Firmware and Hardware Versions of EUT (section 6.4)

FCC Clause	ISED Clause	Requirement	Result	Comment
See Comment		Reporting ANSI C63.10 Sectio	ANSI C63.10 Section	
See Comment			purposes only	11.6.
	RSS-GEN 6.7	00% OBW/	Reporting	ANSI C63.10 Section
-		9978 OBW	purposes only	6.9.3.
15.247 (a) (2)	RSS-247 5.2 (a)	6dB BW	Compliant	None.
15.247 (b) (3)	RSS-247 5.4 (d)	Output Power	Compliant	None.
See Comment		Average power	Reporting	Per ANSI C63.10,
			purposes only	Section 11.9.2.3.2.
15.247 (e)	RSS-247 5.2 (b)	PSD		None.
15.247 (d)	RSS-247 5.5	Conducted Spurious Emissions		None.
15.209, 15.205	RSS-GEN 8.9, 8.10	Radiated Emissions	Compliant	None.
15.207	RSS-Gen 8.8	AC Mains Conducted Emissions]	None.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with:

- FCC CFR 47 Part 2,
- FCC CFR 47 Part 15,
- ANSI C63.10-2020,
- KDB 558074 D01 15.247 Meas Guidance v05r02,
- KDB 414788 D01 Radiated Test Site v01r01,
- RSS-GEN Issue 5 + A1 + A2,
- RSS-247 Issue 3

Page 6 of 59

4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, Certificate Number 0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
\boxtimes	Building 2800 Suite Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A	US0067	27265	825374

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radio Frequency (Spectrum Analyzer)	141.2 Hz
Occupied Channel Bandwidth	1.22%
PE output nower, conducted	1.3 dB (PK)
RF output power, conducted	0.45 dB (AV)
Power Spectral Density, conducted	2.47 dB
Unwanted Emissions, conducted	1.94 dB
All emissions, radiated	6.01 dB
Conducted Emissions (0.150-30MHz) - LISN	3.40 dB
Temperature	0.57°C
Humidity	3.39%
DC Supply voltages	1.70%
Time	3.39%

Uncertainty figures are valid to a confidence level of 95%.

5.4. SAMPLE CALCULATION

RADIATED EMISSIONS

Where relevant, the following sample calculation is provided: Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB) 36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

MAINS CONDUCTED EMISSIONS

Where relevant, the following sample calculation is provided: Final Voltage (dBuV) = Measured Voltage (dBuV) + Cable Loss (dB) + Limiter Factor (dB) + LISN Insertion Loss.

36.5 dBuV + 0 dB +10.1 dB+ 0 dB = 46.6 dBuV

6. EQUIPMENT UNDER TEST

6.1. **EUT DESCRIPTION**

The EUT is a reader module that can be used for flush-mounted or inset reader designed to meet the security needs of an organization, while providing a sleek new design for various architectural and style requirements.

The EUT supports the following technologies:

Wireless technologies	Frequency Band(s)	Operating mode(s)		
NFC	13.56MHz	Type A 106, 212, 424 & 848 Kbps		
Bluetooth	2.4 GHz	LE 1 & 2 Mbps		
Notes: 1) The EUT operated in a 1x1 SISO mode.				

2) The EUT only supports 1 type of NFC tag.

This report covers the full testing of the BLE radio.

6.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	BLE	0.395	1.095

6.3. **DESCRIPTION OF AVAILABLE ANTENNAS**

Chain	Designation in	Frequency Range	Maximum Gain
	Documentation	(MHz)	(dBi)
0	CC2674R10	2402 – 2482	-3.15

6.4. SOFTWARE AND FIRMWARE

EUT FW Version: R10.0.0.22

EUT HW Version: **B**.1

EUT Control SW Version: V1.3

Page 9 of 59

WORST-CASE CONFIGURATION AND MODE 6.5.

Radiated emissions below 1GHz, above 18GHz, and power line conducted emission were performed with the EUT set to transmit at the mode and channel with highest output power as worst-case scenario.

The EUT is meant to be powered via an auxiliary device that does not come with the product. Therefore, for AC Lines, the scan was run using a DC power supply as representative.

Band edge and radiated emissions between 1GHz and 18GHz were performed with the EUT set to transmit at the highest power on low, middle and high channels.

The EUT is only meant to be installed in one orientation, during normal operation. Therefore, radiated tested was done in this orientation only.

Technology	Test Type	Mode/Data-Rate	Channel	Power Setting
BLE	Antenna Port & Radiated Data	1Mbps & 2Mbps	0 (2402MHz) 19 (2440MHz) 39 (2480MHz)	Pset 0 (Default)

6.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List						
Description	Description Manufacturer Model Serial Number FCC ID					
Laptop	Lenovo	Yoga 7 16IAP7	PF49WDF9	-		

I/O CABLES

	I/O Cable List					
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC	1	Barrel	Unshielded	<3m	Used to connect EUT to DC Power Supply.
2	UART	1	Serial-USB	Unshielded	<5m	Program EUT

TEST SETUP

The EUT is connected to a test laptop during the tests. Test software exercised the radio card. The laptop was removed from the chamber for testing.

SETUP DIAGRAMS

Please refer to R15541444-EP1 for setup diagrams

Page 10 of 59

TEL:(919) 549-1400

7. MEASUREMENT METHOD

<u>6 dB BW:</u> ANSI C63.10 Subclause -11.8.2 RBW ≤ DTS BW

Occupied BW (99%): ANSI C63.10 Section 6.9.3

Output Power: ANSI C63.10 Subclause -11.9.1.3 Method PKPM1 Peak-reading power meter Output Power: ANSI C63.10 Subclause -11.9.2.3.2 Method AVGPM-G (Measurement using a gated RF average-reading power meter)

PSD: ANSI C63.10 Subclause -11.10.2 Method PKPSD (peak PSD)

Conducted emissions non-restricted frequency bands: ANSI C63.10 Subclause -11.11 and 6.10.4

Radiated emissions restricted & unrestricted frequency bands: ANSI C63.10 Subclause -11.12.1 and 6.10.5, 6.3 to 6.6.

AC Power-line conducted emissions: ANSI C63.10, Section 6.2.

8. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment Used	 Radiated Disturbance Emilia 	issions Test Equipment	(Morrisville – Chamber 2)

Equip. ID	Description	Manufacturer/Brand	Model Number	Last Cal.	Next Cal.
	0.009-30MHz				
135144	Active Loop Antenna	ETS-Lindgren	6502	2024-10-02	2025-10-02
	30-1000 MHz				
159203	Hybrid Broadband Antenna	Sunol Sciences Corp.	JB3	2024-03-05	2026-03-05
	1-18 GHz				
86408	Double-Ridged Waveguide Horn Antenna, 1 to 18 GHz	ETS Lindgren	3117	2023-06-19	2025-06-19
	18-40 GHz				
204704	Horn Antenna, 18-26.5GHz	Com-Power	AH-826	2023-07-20	2025-07-20
	Gain-Loss Chains				
91975	Gain-loss string: 0.009-30MHz	Various	Various	2024-05-10	2025-05-10
91978	Gain-loss string: 25-1000MHz	Various	Various	2024-05-10	2025-05-10
91977	Gain-loss string: 1-18GHz	Various	Various	2024-07-17	2025-07-17
136042	Gain-loss string: 18-40GHz	Various	Various	2024-05-10	2025-05-10
	Receiver & Software				
206496	Spectrum Analyzer	Rohde & Schwarz	ESW44	2024-08-29	2025-08-29
81018	Spectrum Analyzer	Agilent	E4446A	2024-07-31	2025-07-31
SOFTEMI	EMI Software	UL	Version 9	9.5 (18 Oct 20	21)
	Additional Equipment used				
200540	Environmental Meter	Fisher Scientific	15-077-963	2023-07-19	2025-07-19
76021	DC Power Supply	Circuit Specialist	CSI3005X5	-	-

Test Equipment Used - Wireless Conducted Measurement Equipment

Equipment ID	Description	Manufacturer	Model Number	Last Cal.	Next Cal.
	Common Equipment				
	Conducted Room 1				
90411	Spectrum Analyzer	Keysight Technologies	N9030A	2024-08-01	2025-08-01
211057	Real-Time Peak Power Sensor 50MHz to 8GHz	Boonton	RTP5000	2024-08-01	2025-08-01
179892	Environmental Meter	Fisher Scientific	15-077-963	2024-08-12	2025-08-12
91212	True RMS Multimeter	Agilent	U1232A	2024-08-01	2025-08-01
76022	DC Regulated Power Supply	CircuitSpecialists.Com	CSI3005X5	NA	NA
SOFTEMI	Antenna Port Software	UL	Version 2022.8.16	NA	NA
Power Software	Boonton Power Analyzer	Boonton	Version 3.0.13.0	NA	NA

Test Equipment Used - Line-Conducted Emissions – Voltage (Morrisville – Conducted 1)

Equipment ID	Description	Manufacturer	Model Number	Last Cal.	Next Cal.
70374	EMI Test Receiver	ROHDE & SCHWARZ	ESCI7	2024-07-30	2025-07-30
CBL087	Coax cable, RG223, N- male to BNC-male, 20-ft.	Pasternack	PE3W06143-240	2024-04-04	2025-04-04
179892	Environmental Meter	Fisher Scientific	15-077-963	2024-08-12	2025-08-12
80391	LISN, 50-ohm/50-uH, 250uH 2-conductor, 25A	Fischer Custom Com.	FCC-LISN-50/250- 25-2-01	2024-08-01	2025-08-01
PS216	AC Power Source	Elgar	CW2501M	NA	NA
SOFTEMI	EMI Software	UL	Version 9.	5 (18 Oct 202	1)

9. ANTENNA PORT TEST RESULTS

9.1. **ON TIME AND DUTY CYCLE**

LIMITS

None; for reporting purposes only.

PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time	Period	Duty Cycle	Duty	Duty Cycle	1/B
	В		x	Cycle	Correction Factor	Minimum VBW
	(msec)	(msec)	(linear)	(%)	(dB)	(kHz)
2.4GHz Band						
BLE - 1Mbps	100.000	100.000	1.000	100.00%	0.00	0.010
BLE - 2Mbps	100.000	100.000	1.000	100.00	0.00	0.010

DUTY CYCLE PLOTS



Page 14 of 59

TEL:(919) 549-1400

Keysight Spectrum Analyzer - AP2024.2.23,8	35502,MOR-CON2				
μ L RF 50 Ω DC	DNO: Fast and Trig: F	SENSE:INT #Avg	ALIGN AUTO Type: RMS Hold: 1/1	12:27:09 PM Nov 19, 2024 TRACE 1 2 3 4 5 6 TYPE A WWWWW	Frequency
10 dB/div Ref 20.00 dBm	IFGain:Low #Atten	: 30 dB	Δ	DET P NNNN Mkr3 100.0 ms -0.018 dB	Auto Tune
10.0 2 0.00				3∆2	Center Freq 2.440000000 GHz
-20.0					Start Freq 2.440000000 GHz
-50.0					Stop Freq 2.440000000 GHz
Center 2.440000000 GHz Res BW 8 MHz	#VBW 50 MH		Sweep 10	Span 0 Hz 10.0 ms (1001 pts) Function value	CF Step 8.000000 MHz <u>Auto</u> Mar
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	100.0 ms (Δ) -0.01 0.000 s -0.575 100.0 ms (Δ) -0.01	18 dB dBm 18 dB		E	Freq Offset 0 Hz
8 9 10 11 *	m		STATUS	•	
	עדוום		2Mhns		

9.2. 99% **BANDWIDTH**

LIMITS

None; for reporting purposes only.

RESULTS

9.2.1. BLE (1Mbps)

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0661
Middle	2440	1.0659
High	2480	1.0774



Page 16 of 59

9.2.2. BLE (2Mbps)

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	2.0760
Middle	2440	2.0806
High	2480	2.0861





UL LLC 12 Laboratory Drive; RTP NC 27606, USA This report shall not be reproduced except in full, without the written approval of UL LLC

9.3. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2) RSS-247 5.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS

9.3.1. BLE (1Mbps)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.7050	0.5
Middle	2440	0.7080	0.5
High	2480	0.7050	0.5



9.3.2. BLE (2Mbps)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	1.2180	0.5
Middle	2440	1.2840	0.5
High	2480	1.2180	0.5





9.4. PEAK & AVERAGE POWER

LIMITS

Peak Power: FCC §15.247 (b) (3) RSS-247 5.4 (d)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

Avg Power is for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter for Peak and Gated Average power measurements. .

The EUT cable assembly insertion loss of 1.22 dB was entered as an offset in the power meter.

The power output was measured on the EUT antenna port using SMA cable with 10dB attenuator connected to a power meter via wideband average power sensor. Gated output power was read directly from power meter.

PEAK POWER RESULTS

9.4.1. BLE (1Mbps)

Tested By:	85502
Date:	11/19/2024

Channel	Frequency	Frequency Peak Power Reading		Margin	
	(MHz)	(dBm)	(dBm)	(dB)	
Low	2402	0.278	30	-29.722	
Middle	2440	0.358	30	-29.642	
High	2480	0.357	30	-29.643	

9.4.2. BLE (2Mbps)

Tested By:	85502
Date:	11/19/2024

Channel	Frequency	Peak Power Reading (dBm)	Limit	Margin	
		(автт)	(abm)	(ab)	
Low	2402	0.306	30	-29.694	
Middle	2440	0.395	30	-29.605	
High	2480	0.357	30	-29.643	

AVG POWER RESULTS

9.4.3. BLE (1Mbps)

Tested By:	85502
Date:	11/19/2024

Channel	Frequency	AV power		
	(MHz)	(dBm)		
Low	2402	0.055		
Middle	2440	0.141		
High	2480	0.118		

9.4.4. BLE (2Mbps)

Tested By:	85502
Date:	11/19/2024

Channel	Frequency	AV power		
	(MHz)	(dBm)		
Low	2402	0.064		
Middle	2440	0.145		
High	2480	0.12		

9.5. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e) RSS-247 (5.2) (b)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

9.5.1. BLE (1Mbps)

Channel	Frequency	PSD	Limit	Margin
	(MHz)	(dBm/3kHz)	(dBm/3kHz)	(dB)
Low	2402	-13.11	8	-21.11
Middle	2440	-13.06	8	-21.06
High	2480	-12.32	8	-20.32



Page 23 of 59

9.5.2. BLE (2Mbps)

Channel	Frequency	PSD	Limit	Margin		
	(MHz) (dBm/3kHz) (dB		(MHz) (dBm/3kH		(dBm/3kHz)	(dB)
Low	2402	-14.97	8	-22.97		
Middle	2440	-14.99	8	-22.99		
High	2480	-15.54	8	-23.54		





9.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d) RSS-247 5.5

Output power was measured based on the use of peak measurements, so the required attenuation is -20 dBc.

RESULTS

Page 25 of 59

9.6.1. BLE (1Mbps)



Page 26 of 59

9.6.2. BLE (2Mbps)



Page 27 of 59

10. RADIATED TEST RESULTS

10.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
0.009-0.490	2400/F(kHz) @ 300 m	-
0.490-1.705	24000/F(kHz) @ 30 m	-
1.705 - 30	30 @ 30m	-
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

RSS-GEN, Section 8.9 and 8.10.

Frequency Range (kHz)	Field Strength Limit (uA/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
0.009-0.490	6.37/F(kHz) @ 300 m	-
0.490-1.705	63.7/F(kHz) @ 30 m	-
1.705 - 30	0.08 @ 30m	-
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements in the 30-1000MHz range, 9kHz for peak and/or quasi-peak detection measurements in the 0.15-30MHz range and 200Hz for peak and/or quasi-peak detection measurements in the 9 to 150kHz range. Peak detection is used unless otherwise noted as quasi-peak or average (9-90kHz and 110-490kHz).

For pre-scans above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3MHz for peak measurements. For final measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements and as applicable for average measurements. Linear voltage averaging was used.

The spectrum from 1 GHz to 18 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band. Below 1GHz and above 18GHz emissions, the channel with the highest output power was tested.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

3D antenna use - For below 30MHz testing, investigation was done on three antenna orientations (parallel, perpendicular, and ground-parallel).

Based on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

KDB 414788 Open Field Site(OFS) and Chamber Correlation Justification

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

Page 29 of 59

10.2. TRANSMITTER ABOVE 1 GHz

10.2.1. BLE (1Mbps)

<u>Antenna 1</u>

BANDEDGE (LOW CHANNEL)

HORIZONTAL RESULT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	AVG Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 2.38996	33.68	Pk	32.3	-23.6	42.38	-	-	74	-31.62	22	101	Н
2	* ** 2.37311	35.14	Pk	32.2	-23.6	43.74	-	-	74	-30.26	22	101	Н
3	* ** 2.38996	21.42	ADV	32.3	-23.6	30.12	54	-23.88	-	-	22	101	Н
4	* ** 2.37027	22.68	ADV	32.2	-23.6	31.28	54	-22.72	-	-	22	101	Н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band

- Pk Peak detector
- ADV Linear Voltage Average

REPORT NO: R15541444-E1 FCC ID: JQ6-SIGNO30

Margin(dB

VERTICAL RESULT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	AVG Margin (dB))	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 2.38996	32.29	Pk	32.3	-23.6	40.99	-	-	74	-33.01	228	144	V
2	* ** 2.38985	35.12	Pk	32.3	-23.5	43.92	-	-	74	-30.08	228	144	V
3	* ** 2.38996	20.9	ADV	32.3	-23.6	29.6	54	-24.4	-	-	228	144	V
4	* ** 2.37011	22.94	ADV	32.2	-23.6	31.54	54	-22.46	-	-	228	144	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Pk - Peak detector

BANDEDGE (HIGH CHANNEL)





Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	AVG Margin (dB))	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 2.48354	34.24	Pk	32.5	-24.1	42.64	-	-	74	-31.36	9	136	Н
2	** 2.54204	35.33	Pk	32.5	-24.6	43.23	-	-	74	-30.77	9	136	Н
3	* ** 2.48354	22.58	ADV	32.5	-24.1	30.98	54	-23.02	-	-	9	136	V
4	* ** 2.48441	23.24	ADV	32.5	-24.2	31.54	54	-22.46	-	-	9	136	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

** - indicates frequency in Taiwan NCC LP0002 Restricted Band Pk - Peak detector

VERTICAL RESULT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	AVG Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 2.48354	33.15	Pk	32.5	-24.1	41.55	-	-	74	-32.45	243	132	V
2	** 2.56285	34.96	Pk	32.5	-24.6	42.86	-	-	74	-31.14	243	132	V
3	* ** 2.48354	21.92	ADV	32.5	-24.1	30.32	54	-23.68	-	-	243	132	V
4	* ** 2.48374	22.45	ADV	32.5	-24.1	30.85	54	-23.15	-	-	243	132	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Pk - Peak detector

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL RESULTS





Page 34 of 59

RTP NC 27606, USA TEL:(919) 549-1400 This report shall not be reproduced except in full, without the written approval of UL LLC

RADIATED EMISSIONS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	AVG Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 3.94313	53.17	Pk	33.4	-45	41.57	54	-12.43	74	-32.43	0-360	101	Н
3	* ** 8.14969	49.51	Pk	35.8	-40.7	44.61	54	-9.39	74	-29.39	0-360	199	Н
4	* ** 9.45	49.3	Pk	36.3	-40.4	45.2	54	-8.8	74	-28.8	0-360	101	Н
5	* ** 4.17	54.66	Pk	33.4	-45.2	42.86	54	-11.14	74	-31.14	0-360	101	V
7	* ** 8.30906	49.37	Pk	35.8	-40.6	44.57	54	-9.43	74	-29.43	0-360	101	V
8	* ** 9.39094	48.51	Pk	36.2	-39.7	45.01	54	-8.99	74	-28.99	0-360	101	V
6	7.20563	52.83	Pk	35.6	-41.7	46.73	-	-	-	-	0-360	101	V
2	7.20656	52.98	Pk	35.6	-41.7	46.88	-	-	-	-	0-360	199	Н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band Pk - Peak detector

Page 35 of 59

MID CHANNEL RESULTS





Page 36 of 59

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	AVG Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 4.87875	51.28	Pk	34.1	-43.7	41.68	54	-12.32	74	-32.32	0-360	101	Н
2	* ** 7.31906	52.57	Pk	35.6	-41.8	46.37	54	-7.63	74	-27.63	0-360	200	Н
4	* ** 5.02875	51.56	Pk	34.1	-43.3	42.36	54	-11.64	74	-31.64	0-360	200	V
5	* ** 7.32094	51.36	Pk	35.6	-41.8	45.16	54	-8.84	74	-28.84	0-360	101	V
6	* ** 9.12375	49.22	Pk	35.9	-39.5	45.62	54	-8.38	74	-28.38	0-360	101	V
3	9.51281	48.67	Pk	36.4	-40.5	44.57	54	-9.43	74	-29.43	0-360	101	Н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Pk - Peak detector

Page 37 of 59

HIGH CHANNEL RESULTS





Page 38 of 59

RADIATED EMISSIONS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	AVG Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
4	* ** 2.806	34.64	Pk	32.5	-25.7	41.44	54	-12.56	74	-32.56	0-360	101	V
1	* ** 7.43906	50.42	Pk	35.6	-41.1	44.92	54	-9.08	74	-29.08	0-360	101	Н
2	* ** 4.01438	52.7	Pk	33.4	-44.3	41.8	54	-12.2	74	-32.2	0-360	101	Н
3	* ** 9.41063	48.33	Pk	36.2	-40.1	44.43	54	-9.57	74	-29.57	0-360	101	Н
5	* ** 7.43906	51.31	Pk	35.6	-41.1	45.81	54	-8.19	74	-28.19	0-360	101	V
6	* ** 9.06656	47.55	Pk	35.9	-39.8	43.65	54	-10.35	74	-30.35	0-360	200	V
7	* ** 9.465	48.88	Pk	36.3	-40.1	45.08	54	-8.92	74	-28.92	0-360	101	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Pk - Peak detector

Page 39 of 59

10.2.2. BLE (2Mbps)

<u>Antenna 1</u>

BANDEDGE (LOW CHANNEL)

HORIZONTAL RESULT



Marke	r Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	AVG Margin (dB))	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 2.38996	33.73	Pk	32.3	-23.6	42.43	-	-	74	-31.57	25	122	Н
2	* ** 2.36723	35.34	Pk	32.2	-23.6	43.94	-	-	74	-30.06	25	122	Н
3	* ** 2.38996	21.68	ADV	32.3	-23.6	30.38	54	-23.62	_	-	25	121	Н
4	* ** 2.38655	22.31	ADV	32.2	-23.4	31.11	54	-22.89	-	-	25	121	Н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

- ** indicates frequency in Taiwan NCC LP0002 Restricted Band
- Pk Peak detector

VERTICAL RESULT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	AVG Margin (dB))	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 2.38996	33.73	Pk	32.3	-23.6	42.43	-	-	74	-31.57	237	146	V
2	* ** 2.38555	35.51	Pk	32.2	-23.4	44.31	-	-	74	-29.69	237	146	V
3	* ** 2.38996	22.2	ADV	32.3	-23.6	30.9	54	-23.1	-	-	237	146	V
4	* ** 2.37001	22.86	ADV	32.2	-23.6	31.46	54	-22.54	-	-	237	146	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Pk - Peak detector

BANDEDGE (HIGH CHANNEL)



HORIZONTAL RESULT

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	AVG Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 2.48354	36.9	Pk	32.5	-24.1	45.3	-	-	74	-28.7	17	155	Н
2	* ** 2.48359	37.8	Pk	32.5	-24.1	46.2	-	-	74	-27.8	17	155	Н
3	* ** 2.48354	25.88	ADV	32.5	-24.1	34.28	54	-19.72	-	-	17	155	Н
4	* ** 2.48374	25.42	ADV	32.5	-24.1	33.82	54	-20.18	-	-	17	155	Н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Pk - Peak detector

VERTICAL RESULT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	AVG Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 2.48354	34.72	Pk	32.5	-24.1	43.12	-	-	74	-30.88	191	150	V
2	* ** 2.48601	35.17	Pk	32.5	-24.2	43.47	-	-	74	-30.53	191	150	V
3	* ** 2.48354	23.06	ADV	32.5	-24.1	31.46	54	-22.54	-	-	191	150	V
4	* ** 2.48395	23.18	ADV	32.5	-24.2	31.48	54	-22.52	-	-	191	150	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Pk - Peak detector

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL RESULTS





Page 44 of 59

RADIATED EMISSIONS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	AVG Margin (dB))	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 2.82	35.76	Pk	32.5	-25.7	42.56	54	-11.44	74	-31.44	0-360	199	Н
5	* ** 2.8495	36.13	Pk	32.6	-25.6	43.13	54	-10.87	74	-30.87	0-360	199	V
3	* ** 7.6275	49.48	Pk	35.7	-41.1	44.08	54	-9.92	74	-29.92	0-360	101	Н
4	* ** 9.13781	48.5	Pk	35.9	-39.7	44.7	54	-9.3	74	-29.3	0-360	101	Н
6	* ** 4.87875	52.46	Pk	34.1	-43.7	42.86	54	-11.14	74	-31.14	0-360	200	V
8	* ** 9.48656	49.56	Pk	36.4	-40.1	45.86	54	-8.14	74	-28.14	0-360	101	V
7	7.20469	52.65	Pk	35.6	-41.7	46.55	-	-	-	-	0-360	101	V
2	7.20656	53.12	Pk	35.6	-41.7	47.02	-	-	-	-	0-360	200	Н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band Pk - Peak detector

Page 45 of 59

MID CHANNEL RESULTS





Page 46 of 59

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	AVG Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
4	* ** 2.852	35.29	Pk	32.6	-25.6	42.29	54	-11.71	74	-31.71	0-360	200	V
1	* ** 7.31906	50.8	Pk	35.6	-41.8	44.6	54	-9.4	74	-29.4	0-360	101	Н
2	* ** 9.045	48.05	Pk	35.9	-40	43.95	54	-10.05	74	-30.05	0-360	199	Н
3	* ** 9.3975	48.5	Pk	36.2	-39.6	45.1	54	-8.9	74	-28.9	0-360	199	Н
5	* ** 8.10469	49.77	Pk	35.8	-40.6	44.97	54	-9.03	74	-29.03	0-360	101	V
6	* ** 9.46688	48.1	Pk	36.3	-40.1	44.3	54	-9.7	74	-29.7	0-360	101	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Pk - Peak detector

HIGH CHANNEL RESULTS





Page 48 of 59

RADIATED EMISSIONS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	86408 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	AVG Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 5.07563	51.76	Pk	34.1	-43.6	42.26	54	-11.74	74	-31.74	0-360	200	Н
3	* ** 9.42563	47.86	Pk	36.3	-40	44.16	54	-9.84	74	-29.84	0-360	101	Н
4	* ** 4.76156	51.36	Pk	34.2	-44.1	41.46	54	-12.54	74	-32.54	0-360	199	V
6	* ** 7.44094	50.81	Pk	35.6	-41.1	45.31	54	-8.69	74	-28.69	0-360	101	V
7	* ** 9.13031	48.32	Pk	35.9	-39.5	44.72	54	-9.28	74	-29.28	0-360	199	V
2	6.15281	52.13	Pk	35.5	-41.2	46.43	54	-7.57	74	-27.57	0-360	200	Н
5	6.15844	51.45	Pk	35.5	-41.1	45.85	54	-8.15	74	-28.15	0-360	199	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Pk - Peak detector

Page 49 of 59

10.3. WORST CASE BELOW 30MHZ

SPURIOUS EMISSIONS BELOW 30 MHz (WORST-CASE CONFIGURATION)

Note: All measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz – 30 MHz) to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were 40*Log (test distance / specification distance).



Below 30MHz Data

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	135144 (dB/m)	Gain/Loss (dB)	Dist. Corr. Factor (dB)	Corrected Reading dB(uVolts/meter)	QP/AV Limit (dBuV/m)	PK Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Loop Angle
4	.01312	43.87	Pk	16.9	.1	-80	-19.13	45.25	65.25	-84.38	0-360	90 degs
7	.01589	43.17	Pk	15.7	.1	-80	-21.03	43.58	63.58	-84.61	0-360	Flat
1	.01631	43.98	Pk	15.5	.1	-80	-20.42	43.35	63.35	-83.77	0-360	0 degs
2	.15663	45.98	Pk	11	.1	-80	-22.92	23.71	43.71	-66.63	0-360	0 degs
8	.18009	45.19	Pk	11	.1	-80	-23.71	22.49	42.49	-66.2	0-360	Flat
5	.48864	38.94	Pk	11	.1	-80	-29.96	13.82	33.82	-63.78	0-360	90 degs
9	.50265	36.14	Pk	11	.1	-40	7.24	33.58	-	-26.34	0-360	Flat
6	.54902	35.04	Pk	11	.1	-40	6.14	32.81	-	-26.67	0-360	90 degs
3	.56167	34.9	Pk	11	.1	-40	6	32.61	-	-26.61	0-360	0 degs

Pk - Peak detector

Page 50 of 59



Below 30MHz Data H-FIELD

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	135144 (dB/m)	Gain/Loss (dB)	Dist. Corr. Factor (dB)	Corrected Reading dB(uAmps/meter)	QP/AV Limit (dBuA/m)	PK Limit (dBuA/m)	Margin (dB)	Azimuth (Degs)	Loop Angle
4	.01312	43.87	Pk	-34.6	.1	-80	-70.63	-6.25	13.75	-84.38	0-360	90 degs
7	.01589	43.17	Pk	-35.8	.1	-80	-72.53	-7.92	12.08	-84.61	0-360	Flat
1	.01631	43.98	Pk	-36	.1	-80	-71.92	-8.15	11.85	-83.77	0-360	0 degs
2	.15663	45.98	Pk	-40.5	.1	-80	-74.42	-27.79	-7.79	-66.63	0-360	0 degs
8	.18009	45.19	Pk	-40.5	.1	-80	-75.21	-29.01	-9.01	-66.2	0-360	Flat
5	.48864	38.94	Pk	-40.5	.1	-80	-81.46	-37.68	-17.68	-63.78	0-360	90 degs
9	.50265	36.14	Pk	-40.5	.1	-40	-44.26	-17.92	-	-26.34	0-360	Flat
6	.54902	35.04	Pk	-40.5	.1	-40	-45.36	-18.69	-	-26.67	0-360	90 degs
3	.56167	34.9	Pk	-40.5	.1	-40	-45.5	-18.89	-	-26.61	0-360	0 degs

10.4. WORST CASE BELOW 1 GHZ

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)





Page 52 of 59

Below 1GHz Data

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	159203 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 37.954	28.31	Pk	21.8	-31.6	18.51	40	-21.49	0-360	299	Н
2	* ** 129.522	28.73	Pk	20.2	-30.6	18.33	43.52	-25.19	0-360	199	Н
3	* ** 268.329	28.66	Pk	19.6	-29.5	18.76	46.02	-27.26	0-360	100	Н
4	* ** 74.038	35.94	Pk	14.5	-31.2	19.24	40	-20.76	0-360	101	V
5	* ** 123.023	28.64	Pk	20.3	-30.6	18.34	43.52	-25.18	0-360	101	V
6	* ** 612	26.66	Pk	25.5	-28.1	24.06	46.02	-21.96	0-360	299	V

Pk - Peak detector

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

** - indicates frequency in Taiwan NCC LP0002 Restricted Band

Page 53 of 59

10.1. WORST CASE SPURIOUS 18-26 GHZ





Page 54 of 59

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	204704 (dB/m)	Gain/Loss (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* ** 19.09724	48.1	Pk	33.7	-38	43.8	54	-10.2	74	-30.2	0-360	249	Н
2	* ** 22.24193	47.18	Pk	34.3	-37.4	44.08	54	-9.92	74	-29.92	0-360	249	Н
3	* ** 23.95025	46.83	Pk	34.5	-37.2	44.13	54	-9.87	74	-29.87	0-360	300	Н
5	* ** 20.98405	47.61	Pk	33.6	-38	43.21	54	-10.79	74	-30.79	0-360	150	V
6	* ** 22.10679	47.18	Pk	34.3	-37.8	43.68	54	-10.32	74	-30.32	0-360	101	V
7	* ** 23.91031	46.98	Pk	34.4	-37.1	44.28	54	-9.72	74	-29.72	0-360	250	V
8	25.89401	48.79	Pk	35.3	-35.9	48.19	-	-	-	-	0-360	150	V
4	26.11669	48.48	Pk	35.2	-36.2	47.48	-	-	-	-	0-360	300	Н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band ** - indicates frequency in Taiwan NCC LP0002 Restricted Band Pk - Peak detector

11. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a) RSS-Gen 8.8

Frequency of Emission (MHz)	Conducted Limit (dBuV)				
	Quasi-peak	Average			
0.15-0.5	66 to 56 °	56 to 46 "			
0.5-5	56	46			
5-30	60	50			

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasipeak or average.

Line conducted data is recorded for both lines.

RESULTS

11.1.1. AC Power Line



LINE 1 RESULTS

Range 1	Range 1: Line-L1 .15 - 30MHz													
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN VDF (dB)	Cbl/Limiter (dB)	Corrected Reading dBuV	QP Limit (dBuV)	Margin (dB)	Average Limit (dBuV)	Margin (dB)				
1	.171	45.56	Pk	.2	9.8	55.56	64.91	-9.35	-	-				
2	.171	11.32	Av	.2	9.8	21.32	-	-	54.91	-33.59				
3	.237	36.94	Pk	.1	9.8	46.84	62.2	-15.36	-	-				
4	.237	3.52	Av	.1	9.8	13.42	-	-	52.2	-38.78				
6	.684	6.39	Av	0	9.8	16.19	-	-	46	-29.81				
5	.711	27.59	Pk	0	9.8	37.39	56	-18.61	-	-				
7	9.924	11.58	Pk	.1	10	21.68	60	-38.32	-	-				
8	9.924	5.52	Av	.1	10	15.62	-	-	50	-34.38				
10*	13.56	13.69	Av	.1	10	23.79	-	-	50	-26.21				
9*	13.563	24.91	Pk	.1	10	35.01	60	-24.99	-	-				
12	27.288	.15	Av	.4	10.2	10.75	-	-	50	-39.25				
11	27.318	21.43	Pk	.4	10.2	32.03	60	-27.97	-	-				

Pk - Peak detector

Av - Average detection

*Emissions from unrelated laboratory equipment.

LINE 2 RESULTS



Range 2	Range 2: Line-L2 .15 - 30MHz													
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN VDF (dB)	Cbl/Limiter (dB)	Corrected Reading dBuV	QP Limit (dBuV)	Margin (dB)	Average Limit (dBuV)	Margin (dB)				
13	.171	45.36	Pk	.2	9.8	55.36	64.91	-9.55	-	-				
14	.171	11.24	Av	.2	9.8	21.24	-	-	54.91	-33.67				
15	.24	36.66	Pk	.1	9.8	46.56	62.1	-15.54	-	-				
16	.24	3.76	Av	.1	9.8	13.66	-	-	52.1	-38.44				
17	.711	27.47	Pk	0	9.8	37.27	56	-18.73	-	-				
18	.711	6.7	Av	0	9.8	16.5	-	-	46	-29.5				
19	9.924	10.69	Pk	.1	10	20.79	60	-39.21	-	-				
20	9.924	4.48	Av	.1	10	14.58	-	-	50	-35.42				
22*	13.56	10.45	Av	.1	10	20.55	-	-	50	-29.45				
21*	13.563	20.38	Pk	.1	10	30.48	60	-29.52	-	-				
24	25.803	10.56	Av	.4	10.2	21.16	-	-	50	-28.84				
23	25.806	16.69	Pk	.4	10.2	27.29	60	-32.71	-	-				

Pk - Peak detector

Av - Average detection

*Emissions from unrelated laboratory equipment.

12. SETUP PHOTOS

Please refer to R15541444-EP1 for setup photos

END OF TEST REPORT