

RF Exposure Report

Report No.: SA180108C15A

FCC ID: TOR-W118

Test Model: W-118

Received Date: Jan. 08, 2018

Test Date: Feb. 22 ~ Mar. 20, 2018

Issued Date: Apr. 17, 2018

Applicant: Mojo Networks, Inc.

Address: 339 N. Bernardo Avenue, Suite #200, Mountain View, California United

States 94043

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,

R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA180108C15A Page No. 1 / 7 Report Format Version: 6.1.1 Reference No.: 180108C16



Table of Contents

Relea	se Control Record	. 3
1	Certificate of Conformity	. 4
2	RF Exposure	. 5
2.2	Limits for Maximum Permissible Exposure (MPE)	. 5
3	Calculation Result of Maximum Conducted Power	. 6



Release Control Record

Issue No.	Description	Date Issued
	222,022	
SA180108C15A	Original release.	Apr. 17, 2018

Page No. 3 / 7 Report Format Version: 6.1.1

Report No.: SA180108C15A Reference No.: 180108C16



1 Certificate of Conformity

Product: Wall Jack Access Point

Brand: Mojo

Test Model: W-118

Sample Status: Engineering sample

Applicant: Mojo Networks, Inc.

Test Date: Feb. 22 ~ Mar. 20, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : _______, Date: ______, Apr. 17, 2018

Pettie Chen / Senior Specialist

Approved by: Apr. 17, 2018

Bruce Chen / Project Engineer

Page No. 4 / 7



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Magnetic Field I Strength (V/m) Strength (A/m)		Power Density (mW/cm²)	Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 23cm away from the body of the user. So, this device is classified as Mobile Device.

Report No.: SA180108C15A Reference No.: 180108C16



3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
	Radio 1				
WLAN 2412~2462 (CDD mode)	26.09	7.32	23	0.330	1
WLAN 2412~2462 (Beamforming mode)	21.70	7.32	23	0.120	1
		Radio	2		
WLAN 5180~5240 (CDD mode)	23.44	9	23	0.264	1
WLAN 5260~5320 (CDD mode)	22.83	9	23	0.229	1
WLAN 5500~5700 (CDD mode)	23.76	9	23	0.284	1
WLAN 5745~5825 (CDD mode)	26.63	9	23	0.550	1
WLAN 5180~5240 (Beamforming mode)	21.43	9	23	0.166	1
WLAN 5260~5320 (Beamforming mode)	19.82	9	23	0.115	1
WLAN 5500~5700 (Beamforming mode)	20.75	9	23	0.142	1
WLAN 5745~5825 (Beamforming mode)	23.62	9	23	0.275	1
Radio 3					
WLAN 2412~2462 (CDD mode)	18.80	7.84	23	0.069	1
WLAN 5180~5240 (CDD mode)	17.29	7.32	23	0.043	1
WLAN 5260~5320 (CDD mode)	17.31	7.32	23	0.044	1
WLAN 5500~5700 (CDD mode)	17.43	7.32	23	0.045	1
WLAN 5745~5825 (CDD mode)	17.09	7.32	23	0.042	1
BT LE/Zigbee					
BT LE 2402~2480	2.38	2.76	23	0.0005	1
Zigbee	2.36	2.76	23	0.0005	1

Note: 2.4GHz:

Radio 1: Directional gain = 4.31dBi +10log(2) = 7.32dBi Radio 3: Directional gain = 4.83dBi +10log(2) = 7.84dBi

5.0GHz:

Radio 2: Directional gain = 5.99dBi+10log(2) = 9dBi Radio 3: Directional gain = 4.80dBi+10log(2) = 7.81dBi

		Max. Power (dBm)		Total Power	(dBm)
Frequency Band	Radio 1	Radio 3 (WLAN 2.4GHz)	BTLE	Zigbee	(dBm)	
2.4GHz	26.09	18.80	2.38	ı	26.85	30
2.4GHz	26.09	18.80	-	2.36	26.85	30



Conclusion:

The formula of calculated the MPE is: CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

The simultaneous operation mode was determined by client.

No	Mode
1	Radio 1 + Radio 2 + Radio 3(2.4GHz) + BT LE
2	Radio 1 + Radio 3(5GHz) + BT LE
3	Radio 1 + Radio 2 + Radio 3(2.4GHz)+ Zigbee
4	Radio 1 + Radio 3(5GHz) + Zigbee

^{*}The Radio 2 and Radio 3(5GHz) cannot transmit simultaneously.

Radio 1 + Radio 2 + Radio 3(2.4GHz) + BT LE = 0.330 + 0.550 + 0.069 + 0.0005 = 0.95

Radio 1 + Radio 3(5GHz) + BT LE = 0.330 + 0.045 + 0.0005 = 0.376

Radio 1 + Radio 2 + Radio 3(2.4GHz) + Zigbee = 0.330 + 0.550 + 0.069 + 0.0005 = 0.95

Radio 1 + Radio 3(5GHz) + Zigbee = 0.330 + 0.045 + 0.0005 = 0.376

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---