

FCC PART 15 SUBPART C MEASUREMENT AND TEST REPORT

For

Acrox Technologies Co., Ltd.

4F., No.89, Minshan St., Neihu Dist., Taipei City 114, Taiwan, R.O.C

E.U.T.: 2.4GHz Dongle

Model Name: MQ6

Brand Name: Blackweb

FCC ID: PRDRX0B

Report Number: NTC1506035F

Test Date(s): June 10, 2015 to June 25, 2015

Report Date(s): June 25, 2015

Prepared by

Dongguan Nore Testing Center Co., Ltd.

**Building D, Gaosheng Science and Technology Park, Hongtu Road,
Nancheng District, Dongguan City, Guangdong, China**

Tel: +86-769-22022444

Fax: +86-769-22022799

Prepared By

Approved & Authorized Signer



Rose Hu / Engineer



Sunm Lv / Q.A. Director

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Dongguan NTC Co., Ltd. The test results referenced from this report are relevant only to the sample tested.

Table of Contents

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	3
1.2 RELATED SUBMITTAL(S) / GRANT (S).....	5
1.3 TEST METHODOLOGY	5
1.4 EQUIPMENT MODIFICATIONS	5
1.5 SUPPORT DEVICE	5
1.6 TEST FACILITY AND LOCATION.....	6
1.7 SUMMARY OF TEST RESULTS	7
2. SYSTEM TEST CONFIGURATION.....	8
2.1 EUT CONFIGURATION	8
2.2 SPECIAL ACCESSORIES.....	8
2.3 DESCRIPTION OF TEST MODES	8
2.4 EUT EXERCISE	8
3. CONDUCTED EMISSIONS TEST	9
3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	9
3.2 TEST CONDITION	9
3.3 MEASUREMENT RESULTS.....	9
4. RADIATED EMISSION TEST	12
4.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	12
4.2 MEASUREMENT PROCEDURE	13
4.3 LIMIT	14
4.4 MEASUREMENT RESULTS	15
5. 20DB BANDWIDTH.....	19
5.1 MEASUREMENT PROCEDURE	19
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	19
5.3 MEASUREMENT RESULTS.....	19
6. BAND EDGE	22
6.1 MEASUREMENT PROCEDURE	22
6.2 LIMIT.....	22
6.3 MEASUREMENT RESULTS.....	22
7. ANTENNA REQUIREMENT	23
7.1 MEASUREMENT PROCEDURE	23
7.2 MEASUREMENT RESULTS.....	23
8. TEST EQUIPMENT LIST.....	24

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

This device is a 2.4GHz Dongle, it's powered by PC USB Port. For more details features, please refer to User's Manual.

Manufacturer	: Acrox Technologies Co., Ltd.
Address	: Hsinmin Industrial, Changan Town, Dongguan City, Guangdong, China
Frequency range:	: 2408-2474MHz
Modulation	: GFSK
Number of Channel	: 34
Antenna Type	: PCB
Antenna Gain	: -1dBi (declaration by manufacturer)
Power Supply	: AC 120V 60Hz(PC Input)
Model name	: MQ6
Model Difference Description	: N/A
Note:	: N/A

Channel List:

Channel	Frequency (KHz)	Channel	Frequency (KHz)	Channel	Frequency (KHz)
0	2408	12	2432	24	2456
1	2410	13	2434	25	2458
2	2412	14	2436	26	2460
3	2414	15	2438	27	2462
4	2416	16	2440	28	2464
5	2418	17	2442	29	2466
6	2420	18	2444	30	2468
7	2422	19	2446	31	2470
8	2424	20	2448	32	2472
9	2426	21	2450	33	2474
10	2428	22	2452		
11	2430	23	2454		

Note: The Lowest, middle, and the Highest frequency of channel were selected to perform the test. The frequency selected see below:

The Lowest frequency: 2408MHz
The middle frequency: 2440MHz
The Highest frequency: 2474MHz

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: PRDRX0B filing to comply with Section 15.249 of the FCC Part 15 (2014), Subpart C Rule.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

Notebook PC	: Manufacturer: IBM Corporation M/N: R50e S/N: L3-HZNGO P/N: 1834KDC
Adapter	: Manufacturer: IBM Corporation M/N: 08K8210 Input: AC100-240V 50/60Hz 0.5-1.0A Output: DC 16V 4.5A

1.6 Test Facility and Location

Listed by FCC, August 02, 2011
The Certificate Registration Number is 665078.
Listed by Industry Canada, July 01, 2011
The Certificate Registration Number is 9743A-1.


Dongguan NTC Co., Ltd.
(Full Name: Dongguan Nore Testing Center Co., Ltd.)

Building D, Gaosheng Science and Technology Park, Hongtu Road,
Nancheng District, Dongguan City, Guangdong, China
(Full Name: Building D, Gaosheng Science & Technology Park,
Zhouxi Longxi Road, Nancheng District, Dongguan, Guangdong, China.

1.7 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.249(a)/ 15.209	Radiated Emissions	Compliant
§15.249(d)/ 15.205	Band Edge	Compliant
§15.215(c)	20dB Bandwidth	Compliant
§15.203	Antenna Requirement	Compliant
§15.207	Conduction Emissions	Compliant

Note: The EUT operate multiple positions, so the EUT shall be performed 3 planes. The worst plane is X.



2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Special Accessories

Not available for this EUT intended for grant.

2.3 Description of test modes


The EUT has been tested under operating condition. The Lowest, middle and highest frequencies were chosen for testing.

2.4 EUT Exercise

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

3. Conducted Emissions Test

3.1 Test SET-UP (Block Diagram of Configuration)



3.2 Test Condition

Test Requirement: FCC Part 15.207

Frequency Range: 150KHz ~ 30MHz

Detector: RBW 9KHz, VBW 30KHz

Operation Mode: TX

3.3 Measurement Results


Please refer to following plots.



Dongguan NTC Co., Ltd.
Tel: +86-769-22022444 Fax: +86-769-22022799
Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Site: Conduction

Test Time: 2015-6-9 14:44:42



Report No.: MQ6

Test Standard: FCC PART 15_Class B_QP

Test item: Conducted Emission

Phase: L1

Applicant: Acrox

Temp.()/Hum.(%): 24(C) / 58 %

Product: 2.4GHz Dongle

Power Rating: DC 5V PC Input

Model No.: MQ6

Test Engineer: Gavin

Test Mode: TX

Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1539	10.80	34.70	45.50	65.78	-20.28	QP	P	
2	0.1539	10.80	31.40	42.20	55.78	-13.58	AVG	P	
3	0.5380	10.80	17.00	27.80	56.00	-28.20	QP	P	
4	0.5380	10.80	14.60	25.40	46.00	-20.60	AVG	P	
5	0.7700	10.80	16.30	27.10	56.00	-28.90	QP	P	
6	0.7700	10.80	13.70	24.50	46.00	-21.50	AVG	P	
7	2.3820	10.80	16.00	26.80	56.00	-29.20	QP	P	
8	2.3820	10.80	12.00	22.80	46.00	-23.20	AVG	P	
9	3.6100	10.80	15.00	25.80	56.00	-30.20	QP	P	
10	3.6100	10.80	8.70	19.50	46.00	-26.50	AVG	P	
11	8.6859	10.80	21.90	32.70	60.00	-27.30	QP	P	
12	8.6859	10.80	16.30	27.10	50.00	-22.90	AVG	P	

Note: Level=Reading+Factor.


Margin=Limit-Level.



Dongguan NTC Co., Ltd.
Tel: +86-769-22022444 Fax: +86-769-22022799
Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Site: Conduction

Test Time: 2015-6-9 14:40:53



Report No.: MQ6

Test Standard: FCC PART 15_Class B_QP

Test item: Conducted Emission

Phase: N

Applicant: Acrox

Temp.()/Hum.(%): 24(C) / 58 %

Product: 2.4GHz Dongle

Power Rating: DC 5V PC Input

Model No.: MQ6

Test Engineer: Gavin

Test Mode: TX

Remark:

No.	Frequency (MHz)	Factor (dBuV)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1539	10.80	31.40	42.20	65.78	-23.58	QP	P	
2	0.1539	10.80	26.40	37.20	55.78	-18.58	AVG	P	
3	0.5380	10.80	18.30	29.10	56.00	-26.90	QP	P	
4	0.5380	10.80	15.40	26.20	46.00	-19.80	AVG	P	
5	0.7700	10.80	17.00	27.80	56.00	-28.20	QP	P	
6	0.7700	10.80	14.80	25.60	46.00	-20.40	AVG	P	
7	2.1538	10.80	16.90	27.70	56.00	-28.30	QP	P	
8	2.1538	10.80	13.50	24.30	46.00	-21.70	AVG	P	
9	4.8418	10.80	17.00	27.80	56.00	-28.20	QP	P	
10	4.8418	10.80	11.60	22.40	46.00	-23.60	AVG	P	
11	9.0739	10.80	22.50	33.30	60.00	-26.70	QP	P	
12	9.0739	10.80	17.40	28.20	50.00	-21.80	AVG	P	


Note: Level=Reading+Factor.

Margin=Limit-Level.


4. Radiated Emission Test

4.1 Test SET-UP (Block Diagram of Configuration)

4.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz



4.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



4.2 Measurement Procedure

- Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room. Above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi- anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

For 30MHz to 1GHz:

Set the spectrum analyzer as: RBW=120kHz, VBW=300kHz, Detector=Quasi-Peak

For Above 1GHz:

Set the spectrum analyzer as: RBW=1MHz, VBW=3MHz, Detector=Peak.

Set the spectrum analyzer as: RBW=1MHz, VBW=10Hz, Detector=Peak.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Level	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

4.3 Limit

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)	
		$\mu\text{V/m}$	
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	
88 ~ 216	3	150	
216 ~ 960	3	200	
Above 960	3	500	
Frequency range MHz	Distance Meters	Field Strengths Limit (15.249)	
		mV/m (Field strength of fundamental)	$\mu\text{V/m}$ (Field strength of Harmonics)
902 ~ 928	3	50	500
2400 ~ 2483.5	3	50	500
5725 ~ 5875	3	50	500
24000 ~ 2425000	3	250	2500

- Remark :
- (1) Emission level (dB) μV = 20 log Emission level $\mu\text{V/m}$
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 - (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

4.4 Measurement Results


Please refer to following the test plots and data tables of the worst case: **X Plane**.



Dongguan NTC Co., Ltd.
Tel: +86-769-22022444 Fax: +86-769-22022799
Web: <http://www.ntc-c.com>

Site: Radiation

Test Time: 2015-6-9 15:14:30



Report No.: MQ6

Test Standard: FCC Part 15B_Class B_3M

Test item: Radiation Emission

Applicant: Acrox

Product: 2.4GHz Dongle

Model No.: MQ6

Test Distance:

Ant. Polarization: Horizontal

Temp.(C)/Hum.(%): 21(C) / 55 %

Power Rating: DC 5V PC Input

Test Engineer: Lecdon

Test Mode: TX

Remark:

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	54.2500	-17.64	25.74	8.10	40.00	-31.90	QP			P	
2	112.4500	-12.57	26.87	14.30	43.50	-29.20	QP			P	
3	163.8600	-15.02	31.72	16.70	43.50	-26.80	QP			P	
4	195.8700	-13.42	30.52	17.10	43.50	-26.40	QP			P	
5	298.6900	-10.50	30.80	20.30	46.00	-25.70	QP			P	
6	590.6599	-5.26	27.56	22.30	46.00	-23.70	QP			P	

Note: Level=Reading+Factor.

Margin=Limit-Level.


Other emissions are lower than 10dB below the allowable limit.



Dongguan NTC Co., Ltd.
Tel: +86-769-22022444 Fax: +86-769-22022799
Web: <http://www.ntc-c.com>

Site: Radiation

Test Time: 2015-6-9 15:09:09



Report No.: MQ6

Test Standard: FCC Part 15B_Class B_3M

Test item: Radiation Emission

Applicant: Acrox

Product: 2.4GHz Dongle

Model No.: MQ6

Test Distance:

Ant. Polarization: Vertical

Temp.(C)/Hum.(%): 21(C) / 55 %

Power Rating: DC 5V PC Input

Test Engineer: Lecdon

Test Mode: TX

Remark:

No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	58.1300	-14.11	26.91	12.80	40.00	-27.20	QP			P	
2	106.6300	-16.02	26.22	10.20	43.50	-33.30	QP			P	
3	195.8700	-16.42	30.52	14.10	43.50	-29.40	QP			P	
4	298.6900	-12.50	30.60	18.10	46.00	-27.90	QP			P	
5	461.6500	-9.68	28.38	18.70	46.00	-27.30	QP			P	
6	584.8400	-7.43	29.23	21.80	46.00	-24.20	QP			P	

Note: Level=Reading+Factor.

Margin=Limit-Level.

Other emissions are lower than 10dB below the allowable limit.

The worst case: X Plane

Frequency Range: 1-25GHz Test Date : June 10, 2015
Test Result: PASS Temperature : 21 °C
Measured Distance: 3m Humidity : 55 %
Test By: Sance

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode (Low)							
2408	V	90.26	87.70	114.00	94.00	-23.74	-6.30
4816	V	58.17	45.56	74.00	54.00	-15.83	-8.44
7224	V	64.93	50.73	74.00	54.00	-9.07	-3.27

2408	H	84.52	81.12	114.00	94.00	-29.48	-12.88
4816	H	57.36	50.16	74.00	54.00	-16.64	-3.84
7224	H	62.22	50.68	74.00	54.00	-11.78	-3.32

Operation Mode: TX Mode (Mid)							
2440	V	85.96	80.95	114.00	94.00	-28.04	-13.05
4880	V	57.92	45.73	74.00	54.00	-16.08	-8.27
7320	V	65.07	50.90	74.00	54.00	-8.93	-3.10

2440	H	92.30	88.47	114.00	94.00	-21.70	-5.53
4880	H	57.87	45.77	74.00	54.00	-16.13	-8.23
7320	H	66.22	50.98	74.00	54.00	-7.78	-3.02

Operation Mode: TX Mode (High)							
2474	V	92.33	88.95	114.00	94.00	-21.67	-5.05
4948	V	40.00	44.45	74.00	54.00	-34.00	-9.55
7422	V	56.42	47.71	74.00	54.00	-17.58	-6.29

2474	H	86.73	83.36	114.00	94.00	-27.27	-10.64
4948	H	55.99	42.91	74.00	54.00	-18.01	-11.09
7422	H	66.12	49.28	74.00	54.00	-7.88	-4.72

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level + Factor
 - (3) Factor= Antenna Gain + Cable Loss – Amplifier Gain
 - (4) Data of measurement within this frequency range shown “ ---” in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
 - (5) Measurement uncertainty : ± 3.7 dB.
 - (6) Horn antenna used for the emission over 1000MHz.


5. 20dB Bandwidth

5.1 Measurement Procedure

The 20dB bandwidth of the emission was contained within the frequency band designated which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered, FCC Rule 15.215(c):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

5.2 Test SET-UP (Block Diagram of Configuration)




5.3 Measurement Results

Refer to attached data chart.

RBW:	100KHz	VBW:	300KHz
Spectrum Detector:	PK	Temperature :	23 °C
Test By:	Sance	Humidity :	54 %
Test Result:	PASS	Test Date :	June 10, 2015


Channel frequency (MHz)	20dB Down BW(kHz)
2408	1692
2440	1705
2474	1692

Lowest Channel



Date: 10.JUN.2015 07:10:31


Middle Channel



Date: 10.JUN.2015 07:11:57



Highest Channel



Date: 10.JUN.2015 07:13:59

6. Band Edge

6.1 Measurement Procedure

Same as Radiated Emission Test.

6.2 Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

6.3 Measurement Results

Operation Mode:	TX Mode	Test Date :	June 10, 2015
Temperature :	21 °C	Humidity :	55 %
Test Result:	PASS	Test By:	Sance
Measured Distance:	3m		

Freq. (MHz)	Ant. Pol.	Emission Level (dBUV)		Limit 3m (dBUV/m)		Margin (dB)	
		Peak	AV	Peak	AV	Peak	AV
2396.460	H	66.50	50.65	74.00	54.00	-7.50	-3.35
2396.460	V	60.80	49.79	74.00	54.00	-13.20	-4.21
2484.457	H	68.10	50.92	74.00	54.00	-5.90	-3.08
2484.457	V	64.85	50.59	74.00	54.00	-9.15	-3.41

Note: (1) Emission Level= Reading Level + Factor
(2) Factor= Antenna Gain + Cable Loss – Amplifier Gain
(3) Horn antenna used for the emission over 1000MHz.

7. Antenna requirement

7.1 Measurement Procedure

According to of FCC part 15C section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.2 Measurement Results

The antenna is integrated on the main PCB and no consideration of replacement, and the best case gain of the antenna is -1dBi. So, the antenna is consider meet the requirement.

8. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Nov. 24, 2014	Nov. 23, 2015
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Nov. 27, 2014	Nov. 26, 2015
Positioning Controller	UC	UC 3000	N/A	0~360°, 1-4m	N/A	N/A
Color Monitor	SUNSPO	SP-140A	N/A	N/A	N/A	N/A
Single Phase Power Line Filter	SAEMC	PF201A-32	110210	32A	N/A	N/A
3 Phase Power Line Filter	SAEMC	PF401A-200	110318	200A	N/A	N/A
DC Power Filter	SAEMC	PF301A-200	110245	200A	N/A	N/A
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Nov. 08, 2014	Nov. 07, 2015
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Nov. 08, 2014	Nov. 07, 2015
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Nov. 08, 2014	Nov. 07, 2015
Horn Antenna	Schwarzbeck	BBHA9170	9170-372	15GHz~26.5GHz	Oct.24, 2014	Oct.23, 2015
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Nov. 06, 2014	Nov. 05, 2015
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Oct.11, 2014	Oct.10, 2015
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Sep. 02, 2014	Sep. 01, 2015
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Nov. 04, 2014	Nov. 03, 2015
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Nov. 08, 2014	Nov. 07, 2015

---End---