



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Cisco Systems Inc.
Applicant Address	125 West Tasman Drive San Jose, CA 95134-1706
FCC ID	LDKASA-AP702
Manufacturer's company	Wistron NeWeb Corporation
Manufacturer Address	20 Park Avenue II, Hsinchu Science Park, Hsinchu 308 Taiwan

Product Name	ASA 5506-X WiFi Internal Module
Brand Name	CISCO
Model No.	ASA5506-AP702
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Jun. 12, 2014
Final Test Date	Aug. 05, 2014
Submission Type	Original Equipment

Statement

Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r02 and KDB 662911 D01 v02r01.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies	7
3.5. Table for Test Modes	8
3.6. Table for Testing Locations.....	9
3.7. Table for Supporting Units	10
3.8. Table for Parameters of Test Software Setting	11
3.9. EUT Operation during Test	11
3.10. Duty Cycle.....	12
3.11. Test Configurations	13
4. TEST RESULT	16
4.1. AC Power Line Conducted Emissions Measurement.....	16
4.2. Maximum Conducted Output Power Measurement.....	20
4.3. Power Spectral Density Measurement	25
4.4. 6dB Spectrum Bandwidth Measurement	36
4.5. Radiated Emissions Measurement	44
4.6. Emissions Measurement	66
4.7. Antenna Requirements	88
5. LIST OF MEASURING EQUIPMENTS	89
6. MEASUREMENT UNCERTAINTY.....	91
APPENDIX A. TEST PHOTOS	A1 ~ A8
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3
APPENDIX C. RADIATED EMISSION CO-LOCATION REPORT	.C1 ~ C3


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR461329AA	Rev. 01	Initial issue of report	Jan. 16, 2015

1. CERTIFICATE OF COMPLIANCE

Product Name : ASA 5506-X WIFI Internal Module
Brand Name : CISCO
Model No. : ASA5506-AP702
Applicant : Cisco Systems Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jun. 12, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen
SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	11.98 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	9.33 dB
4.3	15.247(e)	Power Spectral Density	Complies	12.30 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.41 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.10 dB
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From host system
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth
Channel Band Width (99%)	< For Non-Beamforming Mode > MCS0 (HT20): 17.50 MHz < For Beamforming Mode > MCS0 (HT20): 17.50 MHz
Maximum Conducted Output Power	< For Non-Beamforming Mode > MCS0 (HT20): 20.30 dBm < For Beamforming Mode > MCS0 (HT20): 20.30 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11b/g

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From host system
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	<For Non-Beamforming Mode> 11b: 13.97 MHz ; 11g: 16.53 MHz <For Beamforming Mode> 11g: 16.53 MHz
Maximum Conducted Output Power	<For Non-Beamforming Mode> 11b: 20.59 dBm ; 11g: 20.67 dBm <For Beamforming Mode> 11g: 20.67 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description	
Beamforming Function	☒ With beamforming for 802.11g/n in 2.4GHz and 802.11a/n in 5GHz	☐ Without beamforming

Antenna and Band width

Antenna	Two(TX)
Band width Mode	20 MHz
IEEE 802.11b	V
IEEE 802.11g	V
IEEE 802.11n	V

Note: The EUT only supports 20MHz in 2.4GHz.

IEEE 11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	MCS 0-15
Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20. Note 2: Modulation modes consist of below configuration: HT20: IEEE 802.11n		

3.2. Accessories

N/A

3.3. Table for Filed Antenna

Band	Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
2.4G	1	WNC	EAAH-N32	PIFA Antenna	I-PEX	2.97
	2	WNC	EAAH-N32	PIFA Antenna	I-PEX	2.97
5G	1	WNC	EAAH-N32	PIFA Antenna	I-PEX	3.89
	2	WNC	EAAH-N32	PIFA Antenna	I-PEX	3.89

Note: Beamforming Gain = $10 \cdot \log(2) = 3.01 \text{ dBi}$

<For 2.4GHz Band>

For IEEE 802.11b/g/n mode (2TX/2RX)

Ant. 1 and Ant. 2 can be used as transmitting/receiving antenna.


Ant. 1 and Ant. 2 could transmit/receive simultaneously.

<For 5GHz Band>

For IEEE 802.11a/n mode (2TX/2RX)

Ant. 1 and Ant. 2 can be used as transmitting/receiving antenna.

Ant. 1 and Ant. 2 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There is one bandwidth system.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	802.11n HT20	MCS0	1/6/11	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Power Spectral Density	802.11n HT20	MCS0	1/6/11	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
6dB Spectrum Bandwidth	802.11n HT20	MCS0	1/6/11	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 th Harmonic	802.11n HT20	MCS0	1/6/11	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Band Edge Emissions	802.11n HT20	MCS0	1/6/11	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2

Note: There are two modes of EUT, one is beamforming mode, and the other is non-beamforming mode for 802.11g/n in 2.4GHz and 802.11a/n in 5GHz, Beamforming mode and non-beamforming mode has been test and record in this test report.

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. Normal Link

For Radiated Emission test:

Mode 1. Normal Link - EUT laying

Mode 2. Normal Link - EUT standing

Mode 1 is the worst case, so it was selected to record in this test report.

For Co-location MPE and Radiated Emission Co-location Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to Appendix B) and Radiated Emission Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6430	DoC
NB	DELL	E6430	DoC
NB	DELL	E6430	DoC
Fixture	Kenton	55RNAA77.DG2	N/A

For Test Site No: 03CH01-CB <Below 1GHz>

Support Unit	Brand	Model	FCC ID
NB	DELL	M1340	DoC
NB	DELL	E6430	DoC
NB	DELL	D420	DoC
Fixture	Kenton	55RNAA77.DG2	N/A

For Test Site No: 03CH01-CB <Above 1GHz>

Support Unit	Brand	Model	FCC ID
NB	DELL	M1340	DoC
Fixture	Kenton	55RNAA77.DG2	N/A

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
NB	DELL	E6220	DoC
Fixture	Kenton	55RNAA77.DG2	N/A

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

<For Non-Beamforming Mode>

Power Parameters of IEEE 802.11n

Test Software Version	ART2-GUI Version : 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 HT20	17	16.5	17

Power Parameters of IEEE 802.11b/g

Test Software Version	ART2-GUI Version : 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	16	17	17
IEEE 802.11g	17	17	17

<For Beamforming Mode>

Power Parameters of IEEE 802.11n

Test Software Version	ART2-GUI Version : 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 HT20	17	16.5	17

Power Parameters of IEEE 802.11g

Test Software Version	ART2-GUI Version : 2.3		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g	17	17	17

3.9. EUT Operation during Test

<For Non-Beamforming Mode>

The EUT was programmed to be in continuously transmitting mode.

<For Beamforming Mode>

For conducted mode in Output power and power density:

In this project, directional gain <6dBi so that output power and power density are not required to reduce power limit.

For radiated mode in bandedge and other spurious emission:

The EUT was programmed to be in continuously transmitting mode.

The measured result was added array gain $10 \cdot \log(2) = 3.01$ dBi as worse case in beamforming mode.

3.10. Duty Cycle

<For Non-Beamforming Mode>


Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11n MCS0 HT20	1.280	1.325	96.60%	0.15	0.78
802.11b	8.220	8.240	99.76%	0.01	0.01
802.11g	1.370	1.415	96.82%	0.14	0.73

<For Beamforming Mode>

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11n MCS0 HT20	1.280	1.325	96.60%	0.15	0.78
802.11g	1.370	1.415	96.82%	0.14	0.73

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length(m)
1	Power cable	No	1.8m
2	RJ-45 to RS-232 cable	No	1.5m
3	RJ-45 cable	No	10m


3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shielded	Length(m)
1	Power cable	No	3m
2	RJ-45 cable	No	10m
3	RJ-45 to RS-232 cable	No	1.5m

Test Configuration: above 1GHz



Item	Connection	Shielded	Length(m)
1	Power cable	No	3m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	55%
Test Engineer	Parody Lin	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over	Limit	LISN	Read	Cable		
	MHz	dBuV	Limit	Line	Factor	Level	Loss	Pol/Phase	Remark
			dB	dBuV	dB	dBuV	dB		
1	0.17584	23.50	-31.18	54.68	0.08	23.26	0.16	LINE	AVERAGE
2	0.17584	26.79	-37.89	64.68	0.08	26.55	0.16	LINE	QP
3	0.48890	33.25	-12.94	46.19	0.08	32.98	0.18	LINE	AVERAGE
4	0.48890	37.32	-18.87	56.19	0.08	37.05	0.18	LINE	QP
5	1.345	21.89	-34.11	56.00	0.10	21.57	0.22	LINE	QP
6	1.345	15.65	-30.35	46.00	0.10	15.33	0.22	LINE	AVERAGE
7	3.190	21.94	-34.06	56.00	0.14	21.52	0.28	LINE	QP
8	3.190	17.56	-28.44	46.00	0.14	17.14	0.28	LINE	AVERAGE
9	7.407	20.71	-29.29	50.00	0.21	20.14	0.36	LINE	AVERAGE
10	7.407	25.40	-34.60	60.00	0.21	24.83	0.36	LINE	QP
11	12.516	27.00	-33.00	60.00	0.29	26.31	0.41	LINE	QP
12	12.516	22.65	-27.35	50.00	0.29	21.96	0.41	LINE	AVERAGE

Temperature	24°C	Humidity	55%
Test Engineer	Parody Lin	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	LISN Factor	Read Level	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.18346	21.35	-32.97	54.33	0.08	21.11	0.16	NEUTRAL	AVERAGE
2	0.18346	27.31	-37.01	64.33	0.08	27.07	0.16	NEUTRAL	QP
3	0.48632	34.25	-11.98	46.23	0.09	33.98	0.18	NEUTRAL	AVERAGE
4	0.48632	37.76	-18.47	56.23	0.09	37.49	0.18	NEUTRAL	QP
5	1.381	16.37	-29.63	46.00	0.10	16.04	0.22	NEUTRAL	AVERAGE
6	1.381	21.72	-34.28	56.00	0.10	21.39	0.22	NEUTRAL	QP
7	2.794	18.21	-27.79	46.00	0.14	17.80	0.27	NEUTRAL	AVERAGE
8	2.794	21.87	-34.13	56.00	0.14	21.46	0.27	NEUTRAL	QP
9	4.696	24.22	-31.78	56.00	0.17	23.73	0.31	NEUTRAL	QP
10	4.696	20.24	-25.76	46.00	0.17	19.75	0.31	NEUTRAL	AVERAGE
11	12.516	27.22	-32.78	60.00	0.28	26.53	0.41	NEUTRAL	QP
12	12.516	22.92	-27.08	50.00	0.28	22.23	0.41	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r02 section 9.2.3.2 Measurement using a power meter (PM).
2. Multiple antenna systems was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

<For Non-Beamforming Mode>

Temperature	20°C	Humidity	53%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n
Test Date	Jun. 30, 2014		

Configuration IEEE 802.11n MCS0 HT20

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	17.42	17.08	20.26	30.00	Complies
6	2437 MHz	17.46	17.01	20.25	30.00	Complies
11	2462 MHz	17.26	17.32	20.30	30.00	Complies

Temperature	20°C	Humidity	53%
Test Engineer	Benson Peng	Configurations	IEEE 802.11b/g
Test Date	Jun. 30, 2014		

Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	16.58	15.91	19.27	30.00	Complies
6	2437 MHz	17.96	17.16	20.59	30.00	Complies
11	2462 MHz	17.38	17.16	20.28	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	17.29	17.04	20.18	30.00	Complies
6	2437 MHz	17.82	17.49	20.67	30.00	Complies
11	2462 MHz	17.38	17.22	20.31	30.00	Complies

<For Beamforming Mode>

Temperature	20°C	Humidity	53%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n
Test Date	Aug. 05, 2014		

Configuration IEEE 802.11n MCS0 HT20

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	17.42	17.08	20.26	30.00	Complies
6	2437 MHz	17.46	17.01	20.25	30.00	Complies
11	2462 MHz	17.26	17.32	20.30	30.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SA}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.98\text{dBi} < 6\text{dBi}$, So Power Limit = 30-(5.98-6)=30dBm

Temperature	20°C	Humidity	53%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g
Test Date	Aug. 05, 2014		

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	17.29	17.04	20.18	30.00	Complies
6	2437 MHz	17.82	17.49	20.67	30.00	Complies
11	2462 MHz	17.38	17.22	20.31	30.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ch}} \left\{ \sum_{k=1}^{N_{ant}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.98\text{dBi} < 6\text{dBi}$, So Power Limit = 30-(5.98-6)=30dBm

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

<For Non-Beamforming Mode>

Temperature	20°C	Humidity	53%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 HT20

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	-8.90	-9.18	-6.03	8.00	Complies
6	2437 MHz	-8.81	-9.37	-6.07	8.00	Complies
11	2462 MHz	-8.87	-9.19	-6.02	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{REQ}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.98dBi < 6dBi$, so power limit doesn't need to reduce.

Temperature	20°C	Humidity	53%
Test Engineer	Benson Peng	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	-7.52	-7.94	-4.71	8.00	Complies
6	2437 MHz	-7.09	-7.68	-4.36	8.00	Complies
11	2462 MHz	-7.11	-7.52	-4.30	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{USE}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.98\text{dBi} < 6\text{dBi}$, so power limit doesn't need to reduce.

Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	-8.28	-8.46	-5.36	8.00	Complies
6	2437 MHz	-8.02	-8.43	-5.21	8.00	Complies
11	2462 MHz	-8.39	-8.46	-5.41	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{USE}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 5.98\text{dBi} < 6\text{dBi}$, so power limit doesn't need to reduce.

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2462 MHz / Ant. 1




Date: 30.JUN.2014 20:08:26

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2462 MHz / Ant. 2




Date: 30.JUN.2014 20:07:46

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz / Ant. 1




Date: 30.JUN.2014 19:57:18

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz / Ant. 2




Date: 30.JUN.2014 19:57:49

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 1



Date: 30.JUN.2014 20:02:06

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 2



Date: 30.JUN.2014 20:01:26

<For Beamforming Mode>

Temperature	20°C	Humidity	53%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 HT20

Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	-8.90	-9.18	-6.03	8.00	Complies
6	2437 MHz	-8.81	-9.37	-6.07	8.00	Complies
11	2462 MHz	-8.87	-9.19	-6.02	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{i=1}^{N_{ANT}} \left\{ \sum_{j=1}^{N_{USE}} g_{i,j} \right\}^2}{N_{ANT}} \right] = 5.98\text{dBi} < 6\text{dBi}$, so power limit doesn't need to reduce.

Temperature	20°C	Humidity	53%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g

Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm/3kHz)			Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Total		
1	2412 MHz	-8.28	-8.46	-5.36	8.00	Complies
6	2437 MHz	-8.02	-8.43	-5.21	8.00	Complies
11	2462 MHz	-8.39	-8.46	-5.41	8.00	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{i=1}^{N_{USE}} g_{i,j} \right\}^2}{N_{ANT}} \right] = 5.98\text{dBi} < 6\text{dBi}$, so power limit doesn't need to reduce.

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2462 MHz / Ant. 1




Date: 30.JUN.2014 20:08:26

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2462 MHz / Ant. 2




Date: 30.JUN.2014 20:07:46

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 1



Date: 30.JUN.2014 20:02:06

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 2



Date: 30.JUN.2014 20:01:26

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth= $\geq$ 8.1 Option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

<For Non-Beamforming Mode>

Temperature	20°C	Humidity	53%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 HT20 / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.34	17.43	500	Complies
6	2437 MHz	16.08	17.43	500	Complies
11	2462 MHz	16.28	17.50	500	Complies

Temperature	20°C	Humidity	53%
Test Engineer	Benson Peng	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b / Ant. 1 +Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.06	13.78	500	Complies
6	2437 MHz	10.06	13.84	500	Complies
11	2462 MHz	10.00	13.97	500	Complies


Configuration IEEE 802.11g / Ant. 1 +Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.70	16.15	500	Complies
6	2437 MHz	15.70	16.53	500	Complies
11	2462 MHz	15.12	16.21	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Ant. 1+Ant. 2




Date: 30.JUN.2014 19:41:25

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz / Ant. 1+Ant. 2



Date: 30.JUN.2014 19:38:34

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz / Ant. 1+Ant. 2



Date: 30.JUN.2014 19:39:13

<For Beamforming Mode>

Temperature	20°C	Humidity	53%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 HT20 / Ant. 1+Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.34	17.43	500	Complies
6	2437 MHz	16.08	17.43	500	Complies
11	2462 MHz	16.28	17.50	500	Complies

Temperature	20°C	Humidity	53%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11g


Configuration IEEE 802.11g / Ant. 1+Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.70	16.15	500	Complies
6	2437 MHz	15.70	16.53	500	Complies
11	2462 MHz	15.12	16.21	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Ant. 1+Ant. 2



Date: 30.JUN.2014 19:41:25

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz / Ant. 1+Ant. 2



Date: 30.JUN.2014 19:39:13

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

For Non-Beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For Beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	Normal Link
Test Date	Jul. 04, 2014	Test Mode	Mode 1

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	Normal Link
Test Mode	Mode 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	375.32	36.02	46.00	-9.98	50.08	2.44	14.93	31.43	100	271	HORIZONTAL	Peak
2	500.45	32.13	46.00	-13.87	43.80	2.82	16.92	31.41	200	212	HORIZONTAL	Peak
3	624.61	34.38	46.00	-11.62	43.99	3.18	18.61	31.40	150	108	HORIZONTAL	Peak
4	749.74	36.59	46.00	-9.41	44.74	3.53	19.69	31.37	125	101	HORIZONTAL	Peak
5	874.87	38.51	46.00	-7.49	45.53	3.89	20.24	31.15	100	198	HORIZONTAL	Peak
6	1000.00	40.05	54.00	-13.95	45.58	4.21	21.44	31.18	150	184	HORIZONTAL	Peak

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	127.97	32.23	43.50	-11.27	50.76	1.35	11.69	31.57	100	277	VERTICAL Peak
2	375.32	30.50	46.00	-15.50	44.56	2.44	14.93	31.43	200	118	VERTICAL Peak
3	500.45	28.15	46.00	-17.85	39.82	2.82	16.92	31.41	100	170	VERTICAL Peak
4	624.61	32.32	46.00	-13.68	41.93	3.18	18.61	31.40	200	172	VERTICAL Peak
5	874.87	33.73	46.00	-12.27	40.75	3.89	20.24	31.15	150	12	VERTICAL Peak
6	1000.00	39.94	54.00	-14.06	45.47	4.21	21.44	31.18	125	354	VERTICAL Peak

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

<For Non-Beamforming Mode>

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11n MCS0 HT20 CH 1 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4822.93	33.73	54.00	-20.27	30.59	5.68	32.76	35.30	100	219	HORIZONTAL	Average
2	4825.65	45.35	74.00	-28.65	42.19	5.69	32.77	35.30	100	219	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4824.52	47.10	74.00	-26.90	43.95	5.69	32.76	35.30	100	258	VERTICAL	Peak
2	4825.45	35.65	54.00	-18.35	32.49	5.69	32.77	35.30	100	258	VERTICAL	Average

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11n MCS0 HT20 CH 6 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4871.82	36.25	54.00	-17.75	33.02	5.74	32.80	35.31	100	226	HORIZONTAL Average
2	4873.36	44.59	74.00	-29.41	41.35	5.75	32.80	35.31	100	226	HORIZONTAL Peak
3	7310.77	50.26	74.00	-23.74	41.44	7.06	37.12	35.36	100	112	HORIZONTAL Peak
4	7312.79	38.35	54.00	-15.65	29.53	7.06	37.12	35.36	100	112	HORIZONTAL Average

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4874.07	38.76	54.00	-15.24	35.52	5.75	32.80	35.31	100	274	VERTICAL Average
2	4875.16	51.29	74.00	-22.71	48.06	5.75	32.80	35.32	100	274	VERTICAL Peak
3	7312.57	38.03	54.00	-15.97	29.21	7.06	37.12	35.36	100	169	VERTICAL Average
4	7312.60	49.95	74.00	-24.05	41.13	7.06	37.12	35.36	100	169	VERTICAL Peak

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11n MCS0 HT20 CH 11 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4922.77	46.42	74.00	-27.58	43.11	5.81	32.83	35.33	100	116	HORIZONTAL	Peak
2	4923.55	36.00	54.00	-18.00	32.69	5.81	32.83	35.33	100	116	HORIZONTAL	Average
3	7383.50	39.37	54.00	-14.63	30.45	7.08	37.16	35.32	100	273	HORIZONTAL	Average
4	7384.49	50.80	74.00	-23.20	41.87	7.09	37.16	35.32	100	273	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4922.41	45.88	74.00	-28.12	42.57	5.81	32.83	35.33	100	99	VERTICAL	Peak
2	4924.07	35.97	54.00	-18.03	32.65	5.81	32.84	35.33	100	99	VERTICAL	Average
3	7388.16	38.48	54.00	-15.52	29.54	7.09	37.16	35.31	101	190	VERTICAL	Average
4	7388.33	50.85	74.00	-23.15	41.91	7.09	37.16	35.31	100	190	VERTICAL	Peak

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11b CH 1 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4824.01	53.59	54.00	-0.41	50.44	5.69	32.76	35.30	150	211	HORIZONTAL	Average
2	4824.04	55.79	74.00	-18.21	52.64	5.69	32.76	35.30	150	211	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4824.10	49.40	54.00	-4.60	46.25	5.69	32.76	35.30	100	276	VERTICAL	Average
2	4824.10	51.51	74.00	-22.49	48.36	5.69	32.76	35.30	100	276	VERTICAL	Peak

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11b CH 6 / Ant. 1 +Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4873.91	51.99	74.00	-22.01	48.75	5.75	32.80	35.31	100	269	HORIZONTAL	Peak
2	4874.00	48.15	54.00	-5.85	44.91	5.75	32.80	35.31	100	269	HORIZONTAL	Average
3	7308.05	51.90	74.00	-22.10	43.09	7.06	37.12	35.36	100	211	HORIZONTAL	Peak
4	7310.18	41.89	54.00	-12.11	33.07	7.06	37.12	35.36	100	211	HORIZONTAL	Average

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4873.96	55.76	74.00	-18.24	52.52	5.75	32.80	35.31	100	275	VERTICAL	Peak
2	4874.02	53.04	54.00	-0.96	49.80	5.75	32.80	35.31	100	275	VERTICAL	Average
3	7312.43	49.85	74.00	-24.15	41.03	7.06	37.12	35.36	100	50	VERTICAL	Peak
4	7315.19	38.16	54.00	-15.84	29.34	7.06	37.12	35.36	100	50	VERTICAL	Average

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11b CH 11 / Ant. 1 + Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4923.98	52.77	74.00	-21.23	49.45	5.81	32.84	35.33	100	209	HORIZONTAL	Peak
2	4924.01	49.75	54.00	-4.25	46.43	5.81	32.84	35.33	100	209	HORIZONTAL	Average
3	7385.24	39.58	54.00	-14.42	30.65	7.09	37.16	35.32	100	219	HORIZONTAL	Average
4	7385.24	52.07	74.00	-21.93	43.14	7.09	37.16	35.32	100	219	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4923.97	51.82	74.00	-22.18	48.50	5.81	32.84	35.33	109	276	VERTICAL	Peak
2	4924.03	48.17	54.00	-5.83	44.85	5.81	32.84	35.33	109	276	VERTICAL	Average
3	7381.20	37.49	54.00	-16.51	28.57	7.08	37.16	35.32	100	119	VERTICAL	Average
4	7383.28	50.24	74.00	-23.76	41.32	7.08	37.16	35.32	100	119	VERTICAL	Peak

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11g CH 1 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4824.04	40.09	54.00	-13.91	36.94	5.69	32.76	35.30	136	213	HORIZONTAL	Average
2	4824.60	54.66	74.00	-19.34	51.51	5.69	32.76	35.30	136	213	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4823.87	51.36	74.00	-22.64	48.21	5.69	32.76	35.30	100	277	VERTICAL	Peak
2	4824.32	37.10	54.00	-16.90	33.95	5.69	32.76	35.30	100	277	VERTICAL	Average

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11g CH 6 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4874.30	56.84	74.00	-17.16	53.60	5.75	32.80	35.31	165	221	HORIZONTAL	Peak
2	4874.66	40.75	54.00	-13.25	37.51	5.75	32.80	35.31	165	221	HORIZONTAL	Average
3	7309.91	39.50	54.00	-14.50	30.68	7.06	37.12	35.36	100	210	HORIZONTAL	Average
4	7311.10	54.10	74.00	-19.90	45.28	7.06	37.12	35.36	100	210	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4873.28	53.81	74.00	-20.19	50.57	5.75	32.80	35.31	100	276	VERTICAL	Peak
2	4873.46	38.66	54.00	-15.34	35.42	5.75	32.80	35.31	100	276	VERTICAL	Average
3	7310.49	51.11	74.00	-22.89	42.29	7.06	37.12	35.36	100	202	VERTICAL	Peak
4	7313.34	37.33	54.00	-16.67	28.51	7.06	37.12	35.36	100	202	VERTICAL	Average

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11g CH 11 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4922.91	44.19	74.00	-29.81	40.88	5.81	32.83	35.33	100	291	HORIZONTAL	Peak
2	4924.25	36.33	54.00	-17.67	33.01	5.81	32.84	35.33	100	291	HORIZONTAL	Average
3	7387.42	39.58	54.00	-14.42	30.65	7.09	37.16	35.32	100	130	HORIZONTAL	Average
4	7387.64	50.56	74.00	-23.44	41.63	7.09	37.16	35.32	100	130	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4923.11	44.71	74.00	-29.29	41.40	5.81	32.83	35.33	100	139	VERTICAL	Peak
2	4925.04	36.70	54.00	-17.30	33.38	5.81	32.84	35.33	100	139	VERTICAL	Average
3	7386.72	54.01	74.00	-19.99	45.08	7.09	37.16	35.32	100	312	VERTICAL	Peak
4	7386.79	38.16	54.00	-15.84	29.23	7.09	37.16	35.32	100	312	VERTICAL	Average

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<For Beamforming Mode>

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11n MCS0 HT20 CH 1 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4824.43	37.92	54.00	-16.08	34.77	5.69	32.76	35.30	100	213	HORIZONTAL Average
2	4824.88	54.20	74.00	-19.80	51.05	5.69	32.76	35.30	100	213	HORIZONTAL Peak

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	4823.02	38.16	54.00	-15.84	35.02	5.68	32.76	35.30	100	160	VERTICAL Average
2	4824.12	54.46	74.00	-19.54	51.31	5.69	32.76	35.30	100	160	VERTICAL Peak

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11n MCS0 HT20 CH 6 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4873.00	38.16	54.00	-15.84	34.92	5.75	32.80	35.31	100	110	HORIZONTAL	Average
2	4874.04	53.80	74.00	-20.20	50.56	5.75	32.80	35.31	100	110	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4873.95	37.86	54.00	-16.14	34.62	5.75	32.80	35.31	100	101	VERTICAL	Average
2	4874.17	54.10	74.00	-19.90	50.86	5.75	32.80	35.31	100	101	VERTICAL	Peak

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11n MCS0 HT20 CH 11 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4923.48	54.46	74.00	-19.54	51.15	5.81	32.83	35.33	100	179	HORIZONTAL	Peak
2	4923.99	38.04	54.00	-15.96	34.72	5.81	32.84	35.33	100	179	HORIZONTAL	Average

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4923.19	38.23	54.00	-15.77	34.92	5.81	32.83	35.33	100	184	VERTICAL	Average
2	4924.71	54.27	74.00	-19.73	50.95	5.81	32.84	35.33	100	184	VERTICAL	Peak

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11g CH 1 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4824.08	38.03	54.00	-15.97	34.88	5.69	32.76	35.30	100	221	HORIZONTAL	Average
2	4824.74	53.99	74.00	-20.01	50.84	5.69	32.76	35.30	100	221	HORIZONTAL	Peak

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4823.77	53.57	74.00	-20.43	50.42	5.69	32.76	35.30	100	262	VERTICAL	Peak
2	4824.18	37.95	54.00	-16.05	34.80	5.69	32.76	35.30	100	262	VERTICAL	Average

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11g CH 6 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4873.91	54.70	74.00	-19.30	51.46	5.75	32.80	35.31	100	206	HORIZONTAL	Peak
2	4874.47	38.05	54.00	-15.95	34.81	5.75	32.80	35.31	100	206	HORIZONTAL	Average

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4874.44	54.36	74.00	-19.64	51.12	5.75	32.80	35.31	100	295	VERTICAL	Peak
2	4874.46	37.95	54.00	-16.05	34.71	5.75	32.80	35.31	100	295	VERTICAL	Average

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11g CH 11 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4923.93	54.18	74.00	-19.82	50.86	5.81	32.84	35.33	100	192	HORIZONTAL	Peak
2	4924.97	38.37	54.00	-15.63	35.05	5.81	32.84	35.33	100	192	HORIZONTAL	Average

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	4924.20	54.55	74.00	-19.45	51.23	5.81	32.84	35.33	100	258	VERTICAL	Peak
2	4924.94	38.09	54.00	-15.91	34.77	5.81	32.84	35.33	100	258	VERTICAL	Average

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (30dBc in any 100 kHz bandwidth emission)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Radiated Out of Band Emission Measurement:

- Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.
- The radiated emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit.
Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

For Non-Beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For Beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

<For Non-Beamforming Mode>

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11n MCS0 HT20 CH 1, 6, 11 / Ant. 1 + Ant. 2
Test Date	Jun. 20, 2014		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2390.00	48.19	54.00	-5.81	16.61	3.68	27.90	0.00	100	326 VERTICAL	Average
2	2390.00	64.78	74.00	-9.22	33.20	3.68	27.90	0.00	100	326 VERTICAL	Peak
3	2414.50	110.99			79.40	3.69	27.90	0.00	100	326 VERTICAL	Peak
4	2414.70	99.26			67.67	3.69	27.90	0.00	100	326 VERTICAL	Average

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2390.00	42.14	54.00	-11.86	10.56	3.68	27.90	0.00	135	274 HORIZONTAL	Average
2	2390.00	57.09	74.00	-16.91	25.51	3.68	27.90	0.00	135	274 HORIZONTAL	Peak
3	2429.80	101.70			70.10	3.70	27.90	0.00	135	274 HORIZONTAL	Average
4	2440.00	114.48			82.87	3.71	27.90	0.00	135	274 HORIZONTAL	Peak
5	2483.50	40.52	54.00	-13.48	8.89	3.73	27.90	0.00	135	274 HORIZONTAL	Average
6	2483.50	56.82	74.00	-17.18	25.19	3.73	27.90	0.00	135	274 HORIZONTAL	Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2463.90	108.50			76.88	3.72	27.90	0.00	125	40 HORIZONTAL	Peak
2	2464.20	97.21			65.59	3.72	27.90	0.00	125	40 HORIZONTAL	Average
3	2483.50	47.33	54.00	-6.67	15.70	3.73	27.90	0.00	125	40 HORIZONTAL	Average
4	2483.50	71.17	74.00	-2.83	39.54	3.73	27.90	0.00	125	40 HORIZONTAL	Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1+Ant.2
Test Date	Jun. 20, 2014		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2390.00	41.56	54.00	-12.44	9.98	3.68	27.90	0.00	137	274	HORIZONTAL Average
2	2390.00	57.37	74.00	-16.63	25.79	3.68	27.90	0.00	137	274	HORIZONTAL Peak
3	2413.80	106.69			75.10	3.69	27.90	0.00	137	274	HORIZONTAL Average
4	2414.80	109.12			77.53	3.69	27.90	0.00	137	274	HORIZONTAL Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2388.60	56.50	74.00	-17.50	24.92	3.68	27.90	0.00	100	62	VERTICAL Peak
2	2390.00	39.56	54.00	-14.44	7.98	3.68	27.90	0.00	100	62	VERTICAL Average
3	2436.20	104.80			73.19	3.71	27.90	0.00	100	62	VERTICAL Average
4	2436.20	107.40			75.79	3.71	27.90	0.00	100	62	VERTICAL Peak
5	2483.50	39.12	54.00	-14.88	7.49	3.73	27.90	0.00	100	62	VERTICAL Average
6	2485.10	56.21	74.00	-17.79	24.58	3.73	27.90	0.00	100	62	VERTICAL Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2462.90	106.02			74.40	3.72	27.90	0.00	100	90	VERTICAL Peak
2	2463.70	103.50			71.88	3.72	27.90	0.00	100	90	VERTICAL Average
3	2483.50	40.62	54.00	-13.38	8.99	3.73	27.90	0.00	100	90	VERTICAL Average
4	2483.50	56.94	74.00	-17.06	25.31	3.73	27.90	0.00	100	90	VERTICAL Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2389.70	66.91	74.00	-7.09	35.33	3.68	27.90	0.00	139	280	HORIZONTAL	Peak
2	2390.00	50.63	54.00	-3.37	19.05	3.68	27.90	0.00	139	280	HORIZONTAL	Average
3	2410.60	100.34			68.75	3.69	27.90	0.00	139	280	HORIZONTAL	Average
4	2410.70	111.84			80.25	3.69	27.90	0.00	139	280	HORIZONTAL	Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2379.60	56.81	74.00	-17.19	25.24	3.67	27.90	0.00	132	271	HORIZONTAL	Peak
2	2390.00	41.23	54.00	-12.77	9.65	3.68	27.90	0.00	132	271	HORIZONTAL	Average
3	2436.20	99.83			68.22	3.71	27.90	0.00	132	271	HORIZONTAL	Average
4	2437.80	111.85			80.24	3.71	27.90	0.00	132	271	HORIZONTAL	Peak
5	2483.50	40.05	54.00	-13.95	8.42	3.73	27.90	0.00	132	271	HORIZONTAL	Average
6	2483.50	56.09	74.00	-17.91	24.46	3.73	27.90	0.00	132	271	HORIZONTAL	Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2464.10	111.42			79.80	3.72	27.90	0.00	136	325	VERTICAL	Peak
2	2465.30	98.81			67.19	3.72	27.90	0.00	136	325	VERTICAL	Average
3	2483.50	50.07	54.00	-3.93	18.44	3.73	27.90	0.00	136	325	VERTICAL	Average
4	2483.50	72.56	74.00	-1.44	40.93	3.73	27.90	0.00	136	325	VERTICAL	Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<For Beamforming Mode>

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11n MCS0 HT20 CH 1, 6, 11 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	2390.00	53.90	54.00	-0.10	22.32	3.68	27.90	0.00	100	348	VERTICAL	Average
2	2390.00	69.46	74.00	-4.54	37.88	3.68	27.90	0.00	100	348	VERTICAL	Peak
3	2405.90	102.27			70.68	3.69	27.90	0.00	100	348	VERTICAL	Average
4	2407.10	113.94			82.35	3.69	27.90	0.00	100	348	VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	2390.00	45.88	54.00	-8.12	14.30	3.68	27.90	0.00	100	325	VERTICAL	Average
2	2390.00	58.31	74.00	-15.69	26.73	3.68	27.90	0.00	100	325	VERTICAL	Peak
3	2440.90	104.07			72.46	3.71	27.90	0.00	100	325	VERTICAL	Average
4	2442.70	113.62			82.01	3.71	27.90	0.00	100	325	VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg		
1	2463.80	112.95			81.33	3.72	27.90	0.00	100	325	VERTICAL	Peak
2	2464.30	104.70			73.08	3.72	27.90	0.00	100	325	VERTICAL	Average
3	2483.50	53.55	54.00	-0.45	21.92	3.73	27.90	0.00	100	325	VERTICAL	Average
4	2483.60	72.11	74.00	-1.89	40.48	3.73	27.90	0.00	100	325	VERTICAL	Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	YC Chen	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1+Ant. 2
Test Date	Jun. 20, 2014		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2389.90	66.90	74.00	-7.10	35.32	3.68	27.90	0.00	100	346	VERTICAL	Peak
2	2390.00	52.24	54.00	-1.76	20.66	3.68	27.90	0.00	100	346	VERTICAL	Average
3	2415.70	102.39			70.80	3.69	27.90	0.00	100	346	VERTICAL	Average
4	2415.70	113.39			81.80	3.69	27.90	0.00	100	346	VERTICAL	Peak

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2390.00	45.00	54.00	-9.00	13.42	3.68	27.90	0.00	100	258	HORIZONTAL	Average
2	2390.00	58.92	74.00	-15.08	27.34	3.68	27.90	0.00	100	258	HORIZONTAL	Peak
3	2440.20	102.69			71.08	3.71	27.90	0.00	100	258	HORIZONTAL	Average
4	2440.70	112.75			81.14	3.71	27.90	0.00	100	258	HORIZONTAL	Peak

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2467.30	113.58			81.96	3.72	27.90	0.00	100	326	VERTICAL	Peak
2	2467.40	104.89			73.27	3.72	27.90	0.00	100	326	VERTICAL	Average
3	2483.50	53.90	54.00	-0.10	22.27	3.73	27.90	0.00	100	326	VERTICAL	Average
4	2483.50	72.42	74.00	-1.58	40.79	3.73	27.90	0.00	100	326	VERTICAL	Peak

Item 1, 2 are the fundamental frequency at 2462 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<For Non-Beamforming Mode>

For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 HT20 / Reference Level



Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 30MHz~2400MHz (down 30dBc)





Agilent Spectrum Analyzer - Swept SA

RL RF 50 Ω DC SENSE:INT ALIGN OFF 03:29:01 AM Jun 25, 2014

Stop Freq 26.50000000 GHz PNO: Fast IFGain:Low Trig: Free Run #Atten: 10 dB Avg Type: Log-Pwr

TRACE 1 2 3 4 5
TYPE P P P P P
DET N N N N N

Trace/Det Select Trace

Clear Write Trace Average Max Hold Min Hold View/Blank View More 1 of 3

10 dB/div Log Ref 106.99 dB μ V

Mkr1 26.345 8 GHz
38.498 dB μ V

58.08 dB μ V

Start 2.50 GHz #Res BW 100 kHz #VBW 300 kHz Stop 26.50 GHz Sweep 2.30 s (40001 pts)

MSG STATUS

The image shows the front panel of an Agilent Spectrum Analyzer. The main display is a log-frequency plot with a vertical axis from 17.0 to 97.0 dB and a horizontal axis from 2.50 GHz to 26.50 GHz. A yellow trace shows a noisy signal floor around 30 dB. A green marker 'Mkr1' is placed at 26.3458 GHz with a value of 38.498 dBμV. Another value of 58.08 dBμV is visible on the right side of the plot. The top of the screen shows various settings: 'Stop Freq 26.50000000 GHz', 'PNO: Fast', 'IFGain:Low', 'Trig: Free Run', '#Atten: 10 dB', 'Avg Type: Log-Pwr', and a date/time stamp '03:29:01 AM Jun 25, 2014'. The right side of the screen has a vertical menu with options like 'Trace/Det', 'Select Trace', 'Clear Write', 'Trace Average', 'Max Hold', 'Min Hold', 'View/Blank', and 'More'. The bottom of the screen shows 'Start 2.50 GHz', '#Res BW 100 kHz', '#VBW 300 kHz', 'Stop 26.50 GHz', and 'Sweep 2.30 s (40001 pts)'. There are also status indicators for 'MSG' and 'STATUS' at the very bottom.

Agilent Spectrum Analyzer - Swept SA

RL RF 50 Ω DC SENSE:INT ALIGN OFF 03:26:51 AM Jun 25, 2014

Stop Freq 2.40000000 GHz PNO: Fast IF Gain: Low Trig: Free Run #Atten: 10 dB Avg Type: Log-Pwr

Trace 1 2 3 4 5 TYPE P P P P P P P P DET P P P P P P P P

Trace/Det Select Trace

Clear Write Trace Average Max Hold Min Hold View/Blank View More 1 of 3

10 dB/div Log Ref 106.99 dB μ V


Mkr1 750.01 MHz 40.293 dB μ V

56.06 dB μ V


Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 2.400 GHz Sweep 227 ms (40001 pts)

MSG STATUS


Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Plot on Configuration IEEE 802.11b / Reference Level



Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)



Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)



Plot on Configuration IEEE 802.11g / Reference Level



Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)



[illegible]

Agilent Spectrum Analyzer - Swept SA

R/L RF 50 Ω DC SENSE:INT ALIGN:OFF 03:37:01 AM Jun 25, 2014

Stop Freq 2.40000000 GHz Avg Type: Log-Pwr

PNO: Fast IF Gain: Low Trig: Free Run #Atten: 10 dB

TRACE 1 2 3 4 5
TYPE: R N N N N N N N
DET: P N P N N N N

10 dB/div Ref 106.99 dBμV

Mkr1 625.05 MHz
41.540 dBμV

Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 227 ms (40001 pts)

Stop 2.400 GHz

MSG STATUS

Trace/Det
Select Trace
Clear Write
Trace Average
Max Hold
Min Hold
View/Blank View
More 1 of 3


Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)



<For Beamforming Mode>


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 HT20 / Reference Level




Date: 8.AUG.2014 03:07:12

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 8.AUG.2014 03:09:00

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 8.AUG.2014 03:09:31

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 8.AUG.2014 03:07:39

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 8.AUG.2014 03:08:11

Plot on Configuration IEEE 802.11g / Reference Level




Date: 8.AUG.2014 02:35:52

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 8.AUG.2014 02:38:12

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 8.AUG.2014 02:42:47

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)



Date: 8.AUG.2014 02:49:17

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)



Date: 8.AUG.2014 02:44:14

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9 kHz ~ 2.75 GHz	Apr. 23, 2014	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150 kHz ~ 100 MHz	Nov. 23, 2013	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Nov. 11, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150 kHz ~ 30 MHz	Dec. 04, 2013	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 26, 2014	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Dec. 17, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Dec. 16, 2013	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Oct. 23, 2013	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Nov. 29, 2013	Conducted (TH01-CB)
Signal analyzer	Agilent	N9010A	MY52220519	10Hz~44GHz	Dec. 11, 2013	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 03, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%