

RF Exposure evaluation

Product Name : True Wireless Earbuds
FCC ID : 2AHYV-JBPODS
Test Standard : KDB447498D04 General RF Exposure Guidance v01

According to 447498 D04 Interim General RF Exposure Guidance v01

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Left:

BT:

Ant gain = **5.59** dBi

MAX output power : [-3.349dBm@2402MHz](#)

ERP=-3.349+5.59-2.15=0.091dBm

WORSE CASE:

$10^{0.0091}=1.021\text{mW} < 2.715 \text{ mW}$

Then SAR evaluation is not required

BLE:

Ant gain = **5.59** dBi

MAX output power : [-3.607dBm@2402MHz](#)

ERP=-3.607+5.59-2.15=-0.167dBm

WORSE CASE:

$10^{-0.0167}=0.962\text{mW} < 2.715 \text{ mW}$

Then SAR evaluation is not required

Right:

BT:

Ant gain = **2.41** dBi

MAX output power : [-2.839dBm@2402MHz](#)

ERP=-2.839+2.41-2.15=-2.579dBm

WORSE CASE:

$10^{-0.2579}=0.552\text{mW} < 2.715 \text{ mW}$

Then SAR evaluation is not required

BLE:

Ant gain = **2.41** dBi

MAX output power : [-0.502dBm@2442MHz](#)

ERP=-0.502+2.41-2.15=-0.242dBm

WORSE CASE:

$10^{-0.0242}=0.946\text{mW} < 2.715 \text{ mW}$

Then SAR evaluation is not required