# Shenzhen Huatongwei International Inspection Co., Ltd.



1/F,Bldg 3,Hongfa Hi-tech Industrial Park,Genyu Road,Tianliao,Gongming,Shenzhen,China Phone:86-755-26748019 Fax:86-755-26748089 http://www.szhtw.com.cn



# TEST REPORT

Report Reference No.....:: CHTEW19070025 Report verification:

Project No.....: SHT1906060501EW

FCC ID.....:: ZSW-30-089

Applicant's name.....: b mobile HK Limited

Address..... Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak

Street; Kwai Chung; New Territories; Hong Kong.

Manufacturer....: b mobile HK Limited

Address....: Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak

Street; Kwai Chung; New Territories; Hong Kong.

Test item description .....: **Mobile Phone** 

Trade Mark .....: **Bmobile** 

AX688 Model/Type reference....:

Listed Model(s) .....:

Standard .....:: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample.....: Jun 24, 2019

Date of testing..... Jun 25, 2019- Jul 08, 2019

Date of issue.....: Jul 10, 2019

Result....: **PASS** 

Compiled by

( Position+Printed name+Signature): File administrators Silvia Li

Supervised by

(Position+Printed name+Signature): Project Engineer Xiaodong Zhao

Approved by

(Position+Printed name+Signature): RF Manager Hans Hu

Shenzhen Huatongwei International Inspection Co., Ltd. Testing Laboratory Name .....::

Silvia Li

1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Address.....:

Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Page: 1 of 58

Report No.: CHTEW19070025 Page: 2 of 58 Issued: 2019-07-10

# **Contents**

| <u>1.</u> | TEST STANDARDS AND REPORT VERSION            | 3                                       |
|-----------|--|---|
|           |  |   |
| 1.1.      | Test Standards                               | 3                                       |
| 1.2.      | Report version                               | 3                                       |
| 2         | TEST DESCRIPTION                             |   |
| <u>2.</u> | TEST DESCRIPTION                             | 4                                       |
| <u>3.</u> | SUMMARY                                      | 5                                       |
| 3.1.      | Client Information                           | 5                                       |
| 3.2.      | Product Description                          | 5                                       |
| 3.3.      | Operation state                              | 6                                       |
| 3.4.      | EUT configuration                            | 6                                       |
| 3.5.      | Modifications                                | 6                                       |
| <u>4.</u> | TEST ENVIRONMENT                             | 7                                       |
| 4.1.      | Address of the test laboratory               | 7                                       |
| 4.2.      | Test Facility                                | 7                                       |
| 4.3.      | Environmental conditions                     | 8                                       |
| 4.4.      | Statement of the measurement uncertainty     | 8                                       |
| 4.5.      | Equipments Used during the Test              | 9                                       |
| <u>5.</u> | TEST CONDITIONS AND RESULTS                  | 11                                      |
| 5.1.      | Antenna requirement                          | 11                                      |
| 5.2.      | Conducted Emissions (AC Main)                | 12                                      |
| 5.3.      | Conducted Peak Output Power                  | 15                                      |
| 5.4.      | 20 dB Bandwidth                              | 19                                      |
| 5.5.      | Carrier Frequencies Separation               | 23                                      |
| 5.6.      | Hopping Channel Number                       | 25                                      |
| 5.7.      | Dwell Time                                   | 27                                      |
| 5.8.      | Pseudorandom Frequency Hopping Sequence      | 34                                      |
| 5.9.      | Restricted band (radiated)                   | 35                                      |
| 5.10.     | Band edge and Spurious Emissions (conducted) | 37                                      |
| 5.11.     | Spurious Emissions (radiated)                | 53                                      |
| <u>6.</u> | TEST SETUP PHOTOS                            | 57                                      |
| 7.        | EXTERANAL AND INTERNAL PHOTOS                | 58                                      |
|           |  | • |

Report No.: CHTEW19070025 Page: 3 of 58 Issued: 2019-07-10

# 1. TEST STANDARDS AND REPORT VERSION

## 1.1. Test Standards

The tests were performed according to following standards:

<u>FCC Rules Part 15.247:</u> Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devicese

KDB 558074 D01 15.247 Meas Guidance v05r01: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

# 1.2. Report version

| Revision No. | Date of issue | Description |
|--------------|---------------|-------------|
| N/A          | 2019-07-10    | Original    |
|              |               |             |
|              |               |             |
|              |               |             |
|              |               |             |

Report No.: CHTEW19070025 Page: 4 of 58 Issued: 2019-07-10

# 2. TEST DESCRIPTION

| Test Item                               | Section in CFR 47 | Result | Test Engineer   |
|---|-------------------|--------|-----------------|
| Antenna Requirement                     | 15.203/15.247 (c) | PASS   | Jiongsheng Feng |
| AC Power Line Conducted Emissions       | 15.207            | PASS   | Jiongsheng Feng |
| Conducted Peak Output Power             | 15.247 (b)(1)     | PASS   | Bruce Wong      |
| 20 dB Bandwidth                         | 15.247 (a)(1)     | PASS   | Bruce Wong      |
| Carrier Frequencies Separation          | 15.247 (a)(1)     | PASS   | Bruce Wong      |
| Hopping Channel Number                  | 15.247 (a)(1)     | PASS   | Bruce Wong      |
| Dwell Time                              | 15.247 (a)(1)     | PASS   | Bruce Wong      |
| Pseudorandom Frequency Hopping Sequence | 15.247(b)(4)      | PASS   | Bruce Wong      |
| Restricted band                         | 15.247(d)/15.205  | PASS   | Bruce Wong      |
| Radiated Emissions                      | 15.247(d)/15.209  | PASS   | Bruce Wong      |

Note: The measurement uncertainty is not included in the test result.

Report No.: CHTEW19070025 Page: 5 of 58 Issued: 2019-07-10

# 3. **SUMMARY**

# 3.1. Client Information

| Applicant:    | b mobile HK Limited  |
|---------------|--|
| Address:      | Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong. |
| Manufacturer: | b mobile HK Limited  |
| Address:      | Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong. |

# 3.2. Product Description

| Name of EUT:                           | Mobile Phone   |  |
|--|--|--|
| Trade Mark:                            | Bmobile  |  |
| Model No.:                             | AX688  |  |
| Listed Model(s):                       | -  |  |
| IMEI:                                  | Conducted: 362523432631169<br>Radiated: 362523432631581      |  |
| Power supply:                          | DC 3.7V  |  |
| Adapter information:                   | Input:100-240Va.c., 50/60Hz, 0.15A<br>Output:5.0Vd.c., 500mA |  |
| Hardware version: Bmobile_AX688_HWV1.0 |  |  |
| Software version:                      | Bmobile_AX688_OM_LTM_V001                                    |  |
| Bluetooth                              |  |  |
| Version:                               | Supported BT2.1+EDR  |  |
| Modulation:                            | GFSK, π/4DQPSK, 8DPSK  |  |
| Operation frequency:                   | 2402MHz~2480MHz  |  |
| Channel number:                        | 79   |  |
| Channel separation:                    | 1MHz   |  |
| Antenna type:                          | PIFA Antenna   |  |
| Antenna gain:                          | 1.0dBi   |  |

Report No.: CHTEW19070025 Page: 6 of 58 Issued: 2019-07-10

# 3.3. Operation state

#### > Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

| Channel | Frequency (MHz) |
|---------|-----------------|
| 00      | 2402            |
| 01      | 2403            |
| ÷       | :               |
| 39      | 2441            |
| :       |                 |
| 77      | 2479            |
| 78      | 2480            |

#### > TEST MODE

| _   |              |      | _    |    |
|-----|--------------|------|------|----|
| Ear | D =          | test | itam | ٠. |
|     | $\mathbf{r}$ | 1621 | пеп  | -  |

The engineering test program was provided and enabled to make EUT continuous transmit

For AC power line conducted emissions:

The EUT was set to connect with the Bluetooth instrument under large package sizes transmission.

For Radiated suprious emissions test item:

The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data recorded in the report.

# 3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- supplied by the lab

|  | 1 | Manufacturer: | /          |   |
|--|---|---------------|------------|---|
|  |   |               | Model No.: | / |
|  | 1 | Manufacturer: | /          |   |
|  |   | 1             | Model No.: | / |

#### 3.5. Modifications

No modifications were implemented to meet testing criteria.

Report No.: CHTEW19070025 Page: 7 of 58 Issued: 2019-07-10

# 4. TEST ENVIRONMENT

# 4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd. Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

# 4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

#### IC-Registration No.:5377A-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377A-1.

## ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

Report No.: CHTEW19070025 Page: 8 of 58 Issued: 2019-07-10

### 4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

| Temperature:       | 15~35°C     |
|--------------------|-------------|
| Relative Humidity: | 30~60 %     |
| Air Pressure:      | 950~1050mba |

# 4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

| Test Items                              | Measurement Uncertainty | Notes |
|---|-------------------------|-------|
| Transmitter power conducted             | 0.51 dB                 | (1)   |
| Conducted spurious emissions 9kHz~40GHz | 0.51 dB                 | (1)   |
| Conducted Disturbance 150kHz~30MHz      | 3.02 dB                 | (1)   |
| Radiated Emissions below 1GHz           | 4.90 dB                 | (1)   |
| Radiated Emissions above 1GHz           | 4.96 dB                 | (1)   |
| Occupied Bandwidth                      | 70 Hz                   | (1)   |

<sup>(1)</sup> This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96

Report No.: CHTEW19070025 Page: 9 of 58 Issued: 2019-07-10

# 4.5. Equipments Used during the Test

| •    | Conducted Emission                  |                    |                 |            |                              |                              |
|------|-------------------------------------|--------------------|-----------------|------------|------------------------------|------------------------------|
| Used | Test Equipment                      | Manufacturer       | Model No.       | Serial No. | Last Cal. Date<br>(YY-MM-DD) | Next Cal. Date<br>(YY-MM-DD) |
| •    | Shielded Room                       | Albatross projects | N/A             | N/A        | 2018/09/28                   | 2023/09/27                   |
| •    | EMI Test Receiver                   | R&S                | ESCI            | 101247     | 2018/10/27                   | 2019/10/26                   |
| •    | Artificial Mains                    | SCHWARZBECK        | NNLK 8121       | 573        | 2018/10/27                   | 2019/10/26                   |
| •    | Pulse Limiter                       | R&S                | ESH3-Z2         | 100499     | 2018/10/27                   | 2019/10/26                   |
| •    | RF Connection Cable                 | HUBER+SUHNER       | EF400           | N/A        | 2018/11/15                   | 2019/11/14                   |
| •    | Test Software                       | R&S                | ES-K1           | N/A        | N/A                          | N/A                          |
| 0    | Single Balanced<br>Telecom Pair ISN | FCC                | FCC-TLISN-T2-02 | 20371      | 2018/10/28                   | 2019/10/27                   |
| 0    | Two Balanced<br>Telecom Pairs ISN   | FCC                | FCC-TLISN-T4-02 | 20373      | 2018/10/28                   | 2019/10/27                   |
| 0    | Four Balanced<br>Telecom Pairs ISN  | FCC                | FCC-TLISN-T8-02 | 20375      | 2018/10/28                   | 2019/10/27                   |
| 0    | V-Network                           | R&S                | ESH3-Z6         | 100211     | 2018/10/27                   | 2019/10/26                   |
| 0    | V-Network                           | R&S                | ESH3-Z6         | 100210     | 2018/10/27                   | 2019/10/26                   |
| 0    | 2-Line V-Network                    | R&S                | ESH3-Z5         | 100049     | 2018/10/27                   | 2019/10/26                   |

| •    | Radiated Emission-6th test site |                    |              |            |                              |                              |
|------|---------------------------------|--------------------|--------------|------------|------------------------------|------------------------------|
| Used | Test Equipment                  | Manufacturer       | Model No.    | Serial No. | Last Cal. Date<br>(YY-MM-DD) | Next Cal. Date<br>(YY-MM-DD) |
| •    | Semi-Anechoic<br>Chamber        | Albatross projects | SAC-3m-02    | N/A        | 2018/09/30                   | 2021/09/29                   |
| •    | EMI Test Receiver               | R&S                | ESCI         | 100900     | 2018/10/28                   | 2019/10/27                   |
| •    | Loop Antenna                    | R&S                | HFH2-Z2      | 100020     | 2017/11/20                   | 2020/11/19                   |
| •    | Ultra-Broadband<br>Antenna      | SCHWARZBECK        | VULB9163     | 546        | 2017/04/05                   | 2020/04/04                   |
| •    | Pre-Amplifer                    | SCHWARZBECK        | BBV 9742     | N/A        | 2018/11/15                   | 2019/11/14                   |
| •    | RF Connection Cable             | HUBER+SUHNER       | N/A          | N/A        | 2018/09/28                   | 2019/09/27                   |
| •    | RF Connection Cable             | HUBER+SUHNER       | SUCOFLEX104  | 501184/4   | 2018/09/28                   | 2019/09/27                   |
| •    | Test Software                   | R&S                | ES-K1        | N/A        | N/A                          | N/A                          |
| •    | Turntable                       | Maturo Germany     | TT2.0-1T     | N/A        | N/A                          | N/A                          |
| •    | Antenna Mast                    | Maturo Germany     | CAM-4.0-P-12 | N/A        | N/A                          | N/A                          |

| •    | Radiated emission-7th test site |                    |             |                      |            |                              |  |  |  |  |  |  |  |
|------|---------------------------------|--------------------|-------------|----------------------|------------|------------------------------|--|--|--|--|--|--|--|
| Used | Test Equipment Manufacturer     |                    | Model No.   | Model No. Serial No. |            | Next Cal. Date<br>(YY-MM-DD) |  |  |  |  |  |  |  |
| •    | Semi-Anechoic<br>Chamber        | Albatross projects | SAC-3m-01   | N/A                  | 2018/09/30 | 2021/09/29                   |  |  |  |  |  |  |  |
| •    | Spectrum Analyzer               | R&S                | FSP40       | 100597               | 2018/10/27 | 2019/10/26                   |  |  |  |  |  |  |  |
| •    | Horn Antenna                    | SCHWARZBECK        | 9120D       | 1011                 | 2017/03/27 | 2020/03/26                   |  |  |  |  |  |  |  |
| •    | Pre-amplifier                   | BONN               | BLWA0160-2M | 1811887              | 2018/11/14 | 2019/11/13                   |  |  |  |  |  |  |  |
| •    | Pre-amplifier                   | CD                 | PAP-0102    | 12004                | 2018/11/14 | 2019/11/13                   |  |  |  |  |  |  |  |
| •    | Broadband Pre-<br>amplifier     | SCHWARZBECK        | BBV 9718    | 9718-248             | 2019/04/26 | 2020/04/25                   |  |  |  |  |  |  |  |
| •    | RF Connection Cable             | HUBER+SUHNER       | RE-7-FH     | N/A                  | 2018/11/15 | 2019/11/14                   |  |  |  |  |  |  |  |
| •    | RF Connection Cable             | HUBER+SUHNER       | RE-7-FL     | N/A                  | 2018/11/15 | 2019/11/14                   |  |  |  |  |  |  |  |
| •    | Test Software                   | Audix              | E3          | N/A                  | N/A        | N/A                          |  |  |  |  |  |  |  |

Report No.: CHTEW19070025 Page: 10 of 58 Issued: 2019-07-10

| • | Turntable    | Maturo Germany | TT2.0-1T     | N/A | N/A | N/A |
|---|--------------|----------------|--------------|-----|-----|-----|
| • | Antenna Mast | Maturo Germany | CAM-4.0-P-12 | N/A | N/A | N/A |

| •    | RF Conducted Method             |              |                 |            |                              |                              |  |  |  |  |  |  |  |
|------|---------------------------------|--------------|-----------------|------------|------------------------------|------------------------------|--|--|--|--|--|--|--|
| Used | Test Equipment                  | Manufacturer | Model No.       | Serial No. | Last Cal. Date<br>(YY-MM-DD) | Next Cal. Date<br>(YY-MM-DD) |  |  |  |  |  |  |  |
| •    | Signal and spectrum<br>Analyzer | R&S          | FSV40           | 100048     | 2018/10/28                   | 2019/10/27                   |  |  |  |  |  |  |  |
| •    | Spectrum Analyzer               | Agilent      | N9020A          | MY50510187 | 2018/09/29                   | 2019/09/28                   |  |  |  |  |  |  |  |
| 0    | Radio communication tester      | R&S          | CMW500          | 137688-Lv  | 2018/09/29                   | 2019/09/28                   |  |  |  |  |  |  |  |
| 0    | Test software                   | Tonscend     | JS1120-1(LTE)   | N/A        | N/A                          | N/A                          |  |  |  |  |  |  |  |
| 0    | Test software                   | Tonscend     | JS1120-2(WIFI)  | N/A        | N/A                          | N/A                          |  |  |  |  |  |  |  |
| 0    | Test software                   | Tonscend     | JS1120-3(WCDMA) | N/A        | N/A                          | N/A                          |  |  |  |  |  |  |  |
| 0    | Test software                   | Tonscend     | JS1120-4(GSM)   | N/A        | N/A                          | N/A                          |  |  |  |  |  |  |  |

Report No.: CHTEW19070025 Page: 11 of 58 Issued: 2019-07-10

# 5. TEST CONDITIONS AND RESULTS

# 5.1. Antenna requirement

## Requirement

#### FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of anantenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

#### **Test Result:**

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



Report No.: CHTEW19070025 Page: 12 of 58 Issued: 2019-07-10

# 5.2. Conducted Emissions (AC Main)


#### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.207

| Fraguesov range (MILIT) | Limit (dBuV) |           |  |  |  |
|-------------------------|--------------|-----------|--|--|--|
| Frequency range (MHz)   | Quasi-peak   | Average   |  |  |  |
| 0.15-0.5                | 66 to 56*    | 56 to 46* |  |  |  |
| 0.5-5                   | 56           | 46        |  |  |  |
| 5-30                    | 60           | 50        |  |  |  |

<sup>\*</sup> Decreases with the logarithm of the frequency.

#### **TEST CONFIGURATION**



# **TEST PROCEDURE**


- 1. The EUT was setup according to ANSI C63.10:2013 requirements.
- 2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
- 3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
- 4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
- 5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor,was individually connected through a LISN to the input power source.
- 6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
- 7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
- 8. During the above scans, the emissions were maximized by cable manipulation.

#### **TEST RESULTS**


Note:

- 1) Transd= Cable lose + Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit Level

Report No.: CHTEW19070025 Page: 13 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 14 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 15 of 58 Issued: 2019-07-10


# 5.3. Conducted Peak Output Power

#### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

## **TEST CONFIGURATION**



# **TEST PROCEDURE**

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- 3. Use the following spectrum analyzer settings: Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel RBW≥ the 20 dB bandwidth of the emission being measured, VBW≥RBW Sweep = auto, Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.


#### **TEST MODE:**

Please refer to the clause 3.3


### **TEST RESULTS**

| Modulation type | Channel | Channel Output power (dBm) |      | Limit (dBm) | Result |  |
|-----------------|---------|----------------------------|------|-------------|--------|--|
|                 | 00      | 3.15                       | 3.13 |             |        |  |
| GFSK            | 39      | 3.68                       | 3.65 | ≤ 30.00     | Pass   |  |
|                 | 78      | 1.85                       | 1.80 |             |        |  |
|                 | 00      | 3.58                       | 2.28 |             |        |  |
| π/4DQPSK        | 39      | 4.28                       | 2.63 | ≤ 21.00     | Pass   |  |
|                 | 78      | 2.33                       | 0.99 |             | I      |  |
|                 | 00      | 3.84                       | 2.31 |             |        |  |
| 8DPSK           | 39      | 4.90                       | 2.90 | ≤ 21.00     | Pass   |  |
|                 | 78      | 3.55                       | 1.88 |             |        |  |


Report No.: CHTEW19070025 Page: 16 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 17 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 18 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 19 of 58 Issued: 2019-07-10

## 5.4. 20 dB Bandwidth

#### **LIMIT**

N/A

#### **TEST CONFIGURATION**



## **TEST PROCEDURE**

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- 3. Use the following spectrum analyzer settings: Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW Sweep = auto, Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.


## **TEST MODE:**

Please refer to the clause 3.3


# **TEST RESULTS**

| Modulation type | Channel | 20 dB Bandwidth (MHz) | Limit (MHz) | Result |  |
|-----------------|---------|-----------------------|-------------|--------|--|
|                 | 00      | 0.92                  |             |        |  |
| GFSK            | 39      | 0.92                  | -           | Pass   |  |
|                 | 78      | 0.92                  |             |        |  |
|                 | 00      | 1.33                  |             |        |  |
| π/4DQPSK        | 39      | 1.33                  |             | Pass   |  |
|                 | 78      | 1.33                  |             |        |  |
|                 | 00      | 1.31                  |             |        |  |
| 8DPSK           | 39      | 1.31                  | -           | Pass   |  |
|                 | 78      | 1.31                  |             |        |  |


Report No.: CHTEW19070025 Page: 20 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 21 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 22 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 23 of 58 Issued: 2019-07-10

# 5.5. Carrier Frequencies Separation


#### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively,

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### **TEST CONFIGURATION**



## **TEST PROCEDURE**

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- Use the following spectrum analyzer settings:
  - Span = wide enough to capture the peaks of two adjacent channels
  - RBW ≥ 1% of the span, VBW ≥ RBW
  - Sweep = auto, Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.

#### **TEST MODE:**

Please refer to the clause 3.3

#### **TEST RESULTS**


| ⊠ Passed | ■ Not Applicable |
|----------|------------------|
| <u> </u> |                  |

| Modulation type | Channel | Carrier Frequencies<br>Separation (MHz) | Limit (MHz) * | Result |
|-----------------|---------|---|---------------|--------|
| GFSK            | 39      | 1.00                                    | ≥0.92         | Pass   |
| π/4DQPSK        | 39      | 1.00                                    | ≥0.89         | Pass   |
| 8DPSK           | 39      | 1.00                                    | ≥0.87         | Pass   |

#### Note:

<sup>\*:</sup> GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the section 5.4.  $\pi/4DQPSK$  limit = 2/3 \* The maximum 20 dB Bandwidth for  $\pi/4DQPSK$  modulation on the section 5.4. 8DPSK limit = 2/3 \* The maximum 20 dB Bandwidth for 8DPSK modulation on the section 5.4

Report No.: CHTEW19070025 Page: 24 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 25 of 58 Issued: 2019-07-10

# 5.6. Hopping Channel Number

#### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

#### **TEST CONFIGURATION**



### **TEST PROCEDURE**

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- 3. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW ≥ 1% of the span, VBW ≥ RBW

Sweep = auto, Detector function = peak, Trace = max hold

4. Measure and record the results in the test report.


#### **TEST MODE:**

Please refer to the clause 3.3

#### **TEST RESULTS**

| Modulation type | Modulation type Channel number |        | Result |
|-----------------|--------------------------------|--------|--------|
| GFSK            | 79                             |        |        |
| π/4DQPSK        | 79                             | ≥15.00 | Pass   |
| 8DPSK           | 79                             |        |        |

Report No.: CHTEW19070025 Page: 26 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 27 of 58 Issued: 2019-07-10

#### 5.7. Dwell Time

#### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.

## **TEST CONFIGURATION**



# **TEST PROCEDURE**

- 1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- 3. Use the following spectrum analyzer settings:
  - Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW  $\geq$  RBW
  - Sweep = as necessary to capture the entire dwell time per hopping channel,
  - Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.


#### **TEST MODE:**

Please refer to the clause 3.3


#### **TEST RESULTS**

| Modulation type | Channel Burst Width [ms/hop/ch] |      | Total<br>Hops[hop*ch] | Dwell time<br>(Second) | Limit<br>(Second) | Result |
|-----------------|---------------------------------|------|-----------------------|------------------------|-------------------|--------|
|                 | DH1                             | 0.39 | 319.00                | 0.13                   |                   |        |
| GFSK            | DH3                             | 1.65 | 158.00                | 0.26                   | ≤ 0.40            | Pass   |
|                 | DH5                             | 2.90 | 105.00                | 0.30                   |                   |        |
|                 | 2DH1                            | 0.38 | 316.00                | 0.12                   |                   |        |
| π/4DQPSK        | 2DH3                            | 1.64 | 157.00                | 0.26                   | ≤ 0.40            | Pass   |
|                 | 2DH5                            | 2.88 | 101.00                | 0.29                   |                   |        |
|                 | 3DH1                            | 0.38 | 315.00                | 0.12                   |                   |        |
| 8DPSK           | 3DH3                            | 1.63 | 152.00                | 0.25                   | ≤ 0.40            | Pass   |
|                 | 3DH5                            | 2.88 | 99.00                 | 0.28                   |                   |        |


Report No.: CHTEW19070025 Page: 28 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 29 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 30 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 31 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 32 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 33 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 34 of 58 Issued: 2019-07-10

# 5.8. Pseudorandom Frequency Hopping Sequence


#### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):Frequency hopping systems shall have hopping channel carrier fre-quencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Al-ternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier fre-quencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to chan-nel frequencies that are selected at the system hopping rate from a pseudo ran-domly ordered list of hopping fre-quencies. Each frequency must be used equally on the average by each trans-mitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their cor-responding transmitters and shall shift frequencies in synchronization with the transmitted signals.

#### **TEST RESULTS**


The pseudorandom frequency hopping sequence may be generated in a nice-stage shift register whose 5<sup>th</sup> and 9<sup>th</sup> stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the friststage. The sequence begins with the frist one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An explame of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

Report No.: CHTEW19070025 Page: 35 of 58 Issued: 2019-07-10


# 5.9. Restricted band (radiated)

#### **LIMIT**

#### FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

#### **TEST CONFIGURATION**



#### **TEST PROCEDURE**

- The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3. The EUT waspositioned such that the distance from antenna to the EUT was 3 meters.
- 4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. Thisis repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- The receiver set as follow: RBW=1 MHz, VBW=3 MHz Peak detector for Peak value RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

#### **TEST MODE:**

Please refer to the clause 3.3

## **TEST RESULTS**

#### Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor
- Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.
- 3) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.

Report No.: CHTEW19070025 Page: 36 of 58 Issued: 2019-07-10

| Test channe        | el:                     |                             |                       |                          | CH00              |                           |                       |              |               |
|--------------------|-------------------------|-----------------------------|-----------------------|--------------------------|-------------------|---------------------------|-----------------------|--------------|---------------|
| Frequency<br>(MHz) | Read<br>Level<br>(dBuV) | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Preamp<br>Factor<br>(dB) | Level<br>(dBuV/m) | Limit<br>Line<br>(dBuV/m) | Over<br>Limit<br>(dB) | Polarization | Test<br>value |
| 2310.00            | 35.02                   | 28.05                       | 7.73                  | 38.17                    | 32.63             | 74.00                     | -41.37                | Horizontal   | Peak          |
| 2390.00            | 38.05                   | 27.65                       | 7.84                  | 37.97                    | 35.57             | 74.00                     | -38.43                | Horizontal   | Peak          |
| 2310.00            | 35.35                   | 28.05                       | 7.73                  | 38.17                    | 32.96             | 74.00                     | -41.04                | Vertical     | Peak          |
| 2390.00            | 38.11                   | 27.65                       | 7.84                  | 37.97                    | 35.63             | 74.00                     | -38.37                | Vertical     | Peak          |
| 2310.00            | 23.19                   | 28.05                       | 7.73                  | 38.17                    | 20.80             | 54.00                     | -33.20                | Horizontal   | Average       |
| 2390.00            | 22.99                   | 27.65                       | 7.84                  | 37.97                    | 20.51             | 54.00                     | -33.49                | Horizontal   | Average       |
| 2310.00            | 23.23                   | 28.05                       | 7.73                  | 38.17                    | 20.84             | 54.00                     | -33.16                | Vertical     | Average       |
| 2390.00            | 23.15                   | 27.65                       | 7.84                  | 37.97                    | 20.67             | 54.00                     | -33.33                | Vertical     | Average       |

| Test chann         | el:                     |                             |                       |                          | CH78              |                           |                       |              |               |
|--------------------|-------------------------|-----------------------------|-----------------------|--------------------------|-------------------|---------------------------|-----------------------|--------------|---------------|
| Frequency<br>(MHz) | Read<br>Level<br>(dBuV) | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Preamp<br>Factor<br>(dB) | Level<br>(dBuV/m) | Limit<br>Line<br>(dBuV/m) | Over<br>Limit<br>(dB) | Polarization | Test<br>value |
| 2483.50            | 61.60                   | 27.26                       | 8.04                  | 37.59                    | 59.31             | 74.00                     | -14.69                | Horizontal   | Peak          |
| 2500.00            | 37.36                   | 27.20                       | 8.08                  | 37.38                    | 35.26             | 74.00                     | -38.74                | Horizontal   | Peak          |
| 2483.50            | 59.98                   | 27.26                       | 8.04                  | 37.59                    | 57.69             | 74.00                     | -16.31                | Vertical     | Peak          |
| 2500.00            | 36.16                   | 27.20                       | 8.08                  | 37.38                    | 34.06             | 74.00                     | -39.94                | Vertical     | Peak          |
| 2483.50            | 27.59                   | 27.26                       | 8.04                  | 37.59                    | 25.30             | 54.00                     | -28.70                | Horizontal   | Average       |
| 2500.00            | 22.74                   | 27.20                       | 8.08                  | 37.38                    | 20.64             | 54.00                     | -33.36                | Horizontal   | Average       |
| 2483.50            | 26.70                   | 27.26                       | 8.04                  | 37.59                    | 24.41             | 54.00                     | -29.59                | Vertical     | Average       |
| 2500.00            | 22.23                   | 27.20                       | 8.08                  | 37.38                    | 20.13             | 54.00                     | -33.87                | Vertical     | Average       |


Report No.: CHTEW19070025 Page: 37 of 58 Issued: 2019-07-10

## 5.10. Band edge and Spurious Emissions (conducted)

#### **LIMIT**

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### **TEST CONFIGURATION**



#### **TEST PROCEDURE**


- The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously
- Use the following spectrum analyzer settings:
  RBW = 100 kHz, VBW ≥ RBW, scan up through 10<sup>th</sup> harmonic.
  Sweep = auto, Detector function = peak, Trace = max hold
- 4. Measure and record the results in the test report.

#### **TEST MODE:**


Please refer to the clause 3.3

#### **TEST RESULTS**


 Report No.: CHTEW19070025 Page: 38 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 39 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 40 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 41 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 42 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 43 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 44 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 45 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 46 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 47 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 48 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 49 of 58 Issued: 2019-07-10




Report No.: CHTEW19070025 Page: 50 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 51 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 52 of 58 Issued: 2019-07-10



Report No.: CHTEW19070025 Page: 53 of 58 Issued: 2019-07-10

# 5.11. Spurious Emissions (radiated)


## <u>LIMIT</u>

FCC CFR Title 47 Part 15 Subpart C Section 15.209


| Frequency         | Limit (dBuV/m @3m) | Value      |  |  |  |  |  |
|-------------------|--------------------|------------|--|--|--|--|--|
| 30 MHz ~ 88 MHz   | 40.00              | Quasi-peak |  |  |  |  |  |
| 88 MHz ~ 216 MHz  | 43.50              | Quasi-peak |  |  |  |  |  |
| 216 MHz ~ 960 MHz | 46.00              | Quasi-peak |  |  |  |  |  |
| 960 MHz ~ 1 GHz   | 54.00              | Quasi-peak |  |  |  |  |  |
| Above 1 GHz       | 54.00              | Average    |  |  |  |  |  |
| Above I GIIZ      | 74.00              | Peak       |  |  |  |  |  |

## **TEST CONFIGURATION**

#### ➤ Below 30 MHz




#### > 30 MHz ~1000 MHz



Above 1 GHz

Report No.: CHTEW19070025 Page: 54 of 58 Issued: 2019-07-10



#### **TEST PROCEDURE**

- 1. The EUT was tested according to ANSI C63.10:2013.
- 2. The EUT is placed on a turn table with 0.8 meter above ground for below 1GHz, 1.5 meter above ground for above 1GHz.
- The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
- 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
- 5. Set to the maximum power setting and enable the EUT transmit continuously.
- 6. Use the following spectrum analyzer settings
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold; If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

(3) From 1 GHz to 10<sup>th</sup> harmonic:

RBW=1 MHz, VBW=3 MHz Peak detector for Peak value RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

#### **TEST MODE:**

Please refer to the clause 3.3

#### **TEST RESULTS**

#### 

#### Note:


- 1) Final Level = Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3) Below 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation High channel which it was worst case, so only the worst case's data on the test report.
- 4) Above 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report
- 5) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.


#### > 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Report No.: CHTEW19070025 Page: 55 of 58 Issued: 2019-07-10

#### > 30 MHz ~ 1 GHz





Report No.: CHTEW19070025 Page: 56 of 58 Issued: 2019-07-10

#### ➤ 1 GHz ~ 25 GHz

| CH00               |                         |                             |                       |                          |                   |                        |                       |              |               |
|--------------------|-------------------------|-----------------------------|-----------------------|--------------------------|-------------------|------------------------|-----------------------|--------------|---------------|
| Frequency<br>(MHz) | Read<br>Level<br>(dBuV) | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Preamp<br>Factor<br>(dB) | Level<br>(dBuV/m) | Limit Line<br>(dBuV/m) | Over<br>Limit<br>(dB) | Polarization | Test<br>value |
| 3151.99            | 35.94                   | 28.80                       | 9.30                  | 37.71                    | 36.33             | 74.00                  | -37.67                | Vertical     | Peak          |
| 3607.26            | 34.83                   | 29.30                       | 10.00                 | 37.86                    | 36.27             | 74.00                  | -37.73                | Vertical     | Peak          |
| 5138.58            | 31.65                   | 31.74                       | 12.04                 | 34.94                    | 40.49             | 74.00                  | -33.51                | Vertical     | Peak          |
| 9587.23            | 32.16                   | 39.06                       | 15.95                 | 36.93                    | 50.24             | 74.00                  | -23.76                | Vertical     | Peak          |
| 3080.60            | 40.47                   | 28.76                       | 9.12                  | 37.70                    | 40.65             | 74.00                  | -33.35                | Horizontal   | Peak          |
| 3943.39            | 35.46                   | 29.70                       | 10.44                 | 37.50                    | 38.10             | 74.00                  | -35.90                | Horizontal   | Peak          |
| 7209.02            | 31.34                   | 36.21                       | 14.53                 | 34.74                    | 47.34             | 74.00                  | -26.66                | Horizontal   | Peak          |
| 8593.22            | 31.90                   | 37.27                       | 15.92                 | 34.44                    | 50.65             | 74.00                  | -23.35                | Horizontal   | Peak          |

| CH39               |                         |                             |                       |                          |                   |                        |                       |              |               |
|--------------------|-------------------------|-----------------------------|-----------------------|--------------------------|-------------------|------------------------|-----------------------|--------------|---------------|
| Frequency<br>(MHz) | Read<br>Level<br>(dBuV) | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Preamp<br>Factor<br>(dB) | Level<br>(dBuV/m) | Limit Line<br>(dBuV/m) | Over<br>Limit<br>(dB) | Polarization | Test<br>value |
| 3168.08            | 35.61                   | 28.80                       | 9.35                  | 37.61                    | 36.15             | 74.00                  | -37.85                | Vertical     | Peak          |
| 5204.40            | 32.19                   | 31.49                       | 12.07                 | 34.61                    | 41.14             | 74.00                  | -32.86                | Vertical     | Peak          |
| 7301.36            | 31.70                   | 36.30                       | 14.54                 | 34.79                    | 47.75             | 74.00                  | -26.25                | Vertical     | Peak          |
| 8681.17            | 31.57                   | 37.79                       | 15.95                 | 34.60                    | 50.71             | 74.00                  | -23.29                | Vertical     | Peak          |
| 3184.25            | 34.91                   | 28.80                       | 9.39                  | 37.50                    | 35.60             | 74.00                  | -38.40                | Horizontal   | Peak          |
| 3700.26            | 33.85                   | 29.30                       | 9.99                  | 37.70                    | 35.44             | 74.00                  | -38.56                | Horizontal   | Peak          |
| 5151.68            | 30.99                   | 31.69                       | 12.05                 | 34.86                    | 39.87             | 74.00                  | -34.13                | Horizontal   | Peak          |
| 8593.22            | 31.28                   | 37.27                       | 15.92                 | 34.44                    | 50.03             | 74.00                  | -23.97                | Horizontal   | Peak          |

| CH78               |                         |                             |                       |                          |                   |                        |                       |              |               |
|--------------------|-------------------------|-----------------------------|-----------------------|--------------------------|-------------------|------------------------|-----------------------|--------------|---------------|
| Frequency<br>(MHz) | Read<br>Level<br>(dBuV) | Antenna<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Preamp<br>Factor<br>(dB) | Level<br>(dBuV/m) | Limit Line<br>(dBuV/m) | Over<br>Limit<br>(dB) | Polarization | Test<br>value |
| 3616.45            | 39.26                   | 29.30                       | 10.00                 | 37.87                    | 40.69             | 74.00                  | -33.31                | Vertical     | Peak          |
| 5112.49            | 31.62                   | 31.85                       | 12.04                 | 35.07                    | 40.44             | 74.00                  | -33.56                | Vertical     | Peak          |
| 8042.90            | 31.20                   | 37.06                       | 15.67                 | 34.37                    | 49.56             | 74.00                  | -24.44                | Vertical     | Peak          |
| 9636.16            | 32.49                   | 39.08                       | 16.02                 | 36.97                    | 50.62             | 74.00                  | -23.38                | Vertical     | Peak          |
| 3168.08            | 34.56                   | 28.80                       | 9.35                  | 37.61                    | 35.10             | 74.00                  | -38.90                | Horizontal   | Peak          |
| 5271.06            | 31.52                   | 31.36                       | 12.25                 | 35.00                    | 40.13             | 74.00                  | -33.87                | Horizontal   | Peak          |
| 7376.08            | 31.00                   | 36.30                       | 14.69                 | 34.70                    | 47.29             | 74.00                  | -26.71                | Horizontal   | Peak          |
| 8747.72            | 31.15                   | 37.80                       | 15.97                 | 34.72                    | 50.20             | 74.00                  | -23.80                | Horizontal   | Peak          |

#### Remark:

- 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- $2. \quad \text{The peak level is lower than average limit} (54 \text{ dBuV/m}), \text{ this data is the too weak instrument of signal is unable to test.}$
- 3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Report No.: CHTEW19070025 Page: 57 of 58 Issued: 2019-07-10

# 6. TEST SETUP PHOTOS

Conducted Emissions (AC Mains)




**Radiated Emissions** 





Report No.: CHTEW19070025 Page: 58 of 58 Issued: 2019-07-10



# 7. EXTERANAL AND INTERNAL PHOTOS

Reference to the test report No.: CHTEW19070023

-----End of Report-----