

FCC RF EXPOSURE REPORT

FCC ID: TE7KC120V2

Project No. : 1907C185
Equipment : Kasa Cam
Brand Name : tp-link
Test Model : KC120
Series Model : N/A

Applicant: TP-Link Technologies Co., Ltd.

Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and

Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Manufacturer : TP-Link Technologies Co., Ltd.

Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and

Technology Park, Shennan Rd, Nanshan, Shenzhen, China

Date of Receipt : Jul. 24, 2019

Date of Test : Jul. 25, 2019~Aug. 22, 2019

Issued Date : Sep. 06, 2019

Report Version : R00

Test Sample: Engineering Sample No.: DG19072543

Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part

2.1091

FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by : Mandy Wang

Approved by: Ethan Ma

IAC MRA

ACCREDITED

Certificate #5123.02

Add: No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

Tel: +86-769-8318-3000 Web: www.newbtl.com



REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue	Sep. 06, 2019





1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1 TP-LINK°		N/A	PIFA	N/A	4.42

2. TEST RESULTS

Antenna Gain (dBi)	Antenna Gain (numeric)		Max. Average Output Power (mW)		Limit of Power Density (S) (mW/cm²)	Test Result
4.42	2.7669	19.97	99.3116	0.05470	1	Complies

Note: The calculated distance is 20 cm.

Output power including tune up tolerance.

End of Test Report