

RF Exposure Report

Report No.: SA171208E04-2

FCC ID: Q87-08011

Test Model: WHW03 V2

Series Model: A03 V2

Received Date: Dec. 08, 2017

Test Date: Feb. 05, 2018

Issued Date: June 27, 2018

Applicant: Linksys LLC

Address: 121 Theory Drive, Irvine, CA 92617, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA171208E04-2	Original release.	June 27, 2018

1 Certificate of Conformity

Product: WHOLE HOME WI-FI

Brand: Linksys

Test Model: WHW03 V2

Series Model: A03 V2

Sample Status: ENGINEERING SAMPLE

Applicant: Linksys LLC

Test Date: Feb. 05, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


Prepared by :


Wendy Wu / Specialist

Date:

June 27, 2018

Approved by :


May Chen / Manager

Date:

June 27, 2018

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (P_{out} * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 32cm away from the body of the user.
So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Bluetooth						
Ant No.	Brand	Model	Antenna Gain (dBi)	Frequency rang (GHz)	Antenna type	Connector type
1	Aristotle	RFA-BT-9267	1.69	2.4~2.4835	Dipole	i-pex(MHF)
Zigbee						
Ant No.	Brand	Model	Antenna Gain (dBi)	Frequency rang (GHz)	Antenna type	Connector type
1	Aristotle	RFA-ZB-9267	0.85	2.4~2.4835	Dipole	i-pex(MHF)
WLAN						
Ant No.	Brand	Model	Antenna Gain (dBi)	Frequency rang (GHz)	Antenna type	Connector type
1	Aristotle	RFA-05-9267-L	3.55	5.5~5.825	Dipole	i-pex(MHF)
2	Aristotle	RFA-05-9267-R	3.87	5.5~5.825	Dipole	i-pex(MHF)
3	Aristotle	RFA-25-9267-B-V2	3.12	2.4~2.4835	Dipole	i-pex(MHF)
			3.77	5.18~5.320		
4	Aristotle	RFA-25-9267-F-V2	3.26	2.4~2.4835	Dipole	i-pex(MHF)
			3.68	5.18~5.320		

2.5 Calculation Result of Maximum Conducted Power

For 2.4GHz, 5GHz (U-NII-1 & UNII-3 band), Bluetooth and Zigbee data was copied from the original test report (Report No.: SA171208E04)

WLAN:

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	813.837	6.20	32	0.26365	1
5180-5240	729.665	6.74	32	0.26768	1
5260-5320	250.771	6.74	32	0.09200	1
5500-5720	238.675	6.72	32	0.08716	1
5745-5825	993.777	6.72	32	0.36289	1

NOTE:

2.4GHz: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 6.20\text{dBi}$

5GHz:

UNII-1 & UNII-2A: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 6.74\text{dBi}$

UNII-2C & UNII-3: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 6.72\text{dBi}$

BT-EDR

Frequency Band (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	5.200	1.69	32	0.00060	1

BT-LE

Frequency Band (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	8.241	1.69	32	0.00095	1

Zigbee

Frequency Band (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2405-2475	66.069	0.85	32	0.00624	1

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz (UNII-1) + WLAN 5GHz (UNII-3) + Bluetooth + Zigbee = $0.26365 / 1 + 0.26768 / 1 + 0.36289 / 1 + 0.00095 / 1 + 0.00624 / 1 = 0.90141$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---