



## FCC / ISSED Test Report

**FOR:**

Telular AMETEK

**Model Name:**

VUE2000

**Product Description:**

Asset tracking.

**FCC ID:** MTFVUE2000

**IC ID:** 2175D-VUE2000

**Applied Rules and Standards:**

47 CFR Part 15.247 (DTS)

RSS-247 Issue 2 (DTS) & RSS-Gen Issue 5

**REPORT #:** EMC\_TELUL-094-20001\_15.247\_BT\_DTS-R1

**DATE:** 2021-09-30



A2LA Accredited

IC recognized #  
3462B-1

CABID: US0187

**CETECOM Inc.**

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: [info@cetecom.com](mailto:info@cetecom.com) • <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

**TABLE OF CONTENTS**

<b>1</b>	<b>ASSESSMENT .....</b>	<b>3</b>
<b>2</b>	<b>ADMINISTRATIVE DATA.....</b>	<b>4</b>
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT.....	4
2.2	IDENTIFICATION OF THE CLIENT .....	4
2.3	IDENTIFICATION OF THE MANUFACTURER .....	4
<b>3</b>	<b>EQUIPMENT UNDER TEST (EUT) .....</b>	<b>5</b>
3.1	EUT SPECIFICATIONS .....	5
3.2	EUT SAMPLE DETAILS .....	6
3.3	SUPPORT EQUIPMENT .....	6
3.4	TEST SAMPLE CONFIGURATION.....	6
3.5	JUSTIFICATION FOR WORST CASE MODE OF OPERATION.....	6
<b>4</b>	<b>SUBJECT OF INVESTIGATION .....</b>	<b>7</b>
<b>5</b>	<b>MEASUREMENT RESULTS SUMMARY.....</b>	<b>8</b>
<b>6</b>	<b>MEASUREMENT UNCERTAINTY .....</b>	<b>9</b>
6.1	ENVIRONMENTAL CONDITIONS DURING TESTING: .....	9
6.2	DATES OF TESTING: .....	9
<b>7</b>	<b>MEASUREMENT PROCEDURES.....</b>	<b>10</b>
7.1	RADIATED MEASUREMENT .....	10
7.2	RF CONDUCTED MEASUREMENT PROCEDURE .....	12
<b>8</b>	<b>TEST RESULT DATA.....</b>	<b>13</b>
8.1	RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS.....	13
<b>9</b>	<b>TEST SETUP PHOTOS.....</b>	<b>27</b>
<b>10</b>	<b>TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING .....</b>	<b>27</b>
<b>11</b>	<b>REVISION HISTORY .....</b>	<b>28</b>

## 1 Assessment

The following device as further described in section 3 of this report was evaluated for radiated spurious emissions according to criteria specified in the Code of Federal Regulations Title 47 Parts 15.247 and Industry Canada Radio Standard Specifications RSS 247.

No deviations were ascertained.

Company	Description	Model #
Telular AMETEK	Asset tracking.	VUE2000

### Responsible for Testing Laboratory:

2021-09-30	Compliance	Kevin Wang (EMC Lab Manager)	
Date	Section	Name	Signature

### Responsible for the Report:

2021-09-30	Compliance	Yuchan Lu (Test Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

## 2 Administrative Data

### 2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

<b>Company Name:</b>	CETECOM Inc.
<b>Department:</b>	Compliance
<b>Street Address:</b>	411 Dixon Landing Road
<b>City/Zip Code</b>	Milpitas, CA 95035
<b>Country</b>	USA
<b>Telephone:</b>	+1 (408) 586 6200
<b>Fax:</b>	+1 (408) 586 6299
<b>EMC Lab Manager:</b>	Kevin Wang
<b>Responsible Project Leader:</b>	Cathy Palacios

### 2.2 Identification of the Client / Manufacturer

<b>Client's Name:</b>	Telular AMETEK
<b>Street Address:</b>	3225 Cumberland Blvd. Suite 300
<b>City/Zip Code:</b>	Atlanta, GA 30339
<b>Country:</b>	USA

### 2.1 Identification of the Applicant

<b>Applicant's Name:</b>	Telular Corporation
<b>Applicant's Address:</b>	3225 Cumberland Blvd. Suite 300
<b>City/Zip Code</b>	Atlanta, GA 30339
<b>Country</b>	USA

### 3 Equipment Under Test (EUT)

#### 3.1 EUT Specifications

<b>Model No:</b>	VUE2000
<b>HW Version :</b>	B
<b>SW Version :</b>	EM.00.01.1085,BM.00.01.0048
<b>FCC-ID:</b>	MTFVUE2000
<b>IC-ID:</b>	2175D-VUE2000
<b>HVIN:</b>	VUE2000
<b>PMN:</b>	SkyVue
<b>Product Description:</b>	Asset tracking.
<b>Frequency Range / number of channels:</b>	Manufacture: Laird Connectivity Module name/number: BL654 451-00001 Nominal band: 2400 MHz – 2483.5 MHz; Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 channels
<b>Type(s) of Modulation:</b>	Bluetooth Low Energy, using Dynamic Sequence Spread Spectrum with GFSK modulation.
<b>Modes of Operation:</b>	Bluetooth LE in both advertising and connected mode of operation
<b>Antenna Information as declared:</b>	<ul style="list-style-type: none"> <li>PCB Trace 0 dBi</li> </ul>
<b>Max. Peak Output Power:</b>	Conducted Power 7.56 dBm
<b>Power Supply/ Rated Operating Voltage Range:</b>	Vmin: 10 VDC/ Vnom: 12 VDC / Vmax: 30 VDC
<b>Operating Temperature Range:</b>	Low -40°C, Nominal 25°C, High 70°C
<b>Other Radios included in the device:</b>	❖ <u>LTE</u> <ul style="list-style-type: none"> <li>Manufacture: Telit</li> <li>Module name/number: ME910G1-W1</li> <li>FCC ID: RI7ME910G1W1</li> <li>IC ID: 5131A-ME910G1W1</li> </ul> ❖ <u>GNSS/GPS</u> <ul style="list-style-type: none"> <li>Manufacture: Quectel</li> <li>Module name/number: L86s-M3</li> </ul>
<b>Sample Revision:</b>	<input type="checkbox"/> Prototype Unit; <input checked="" type="checkbox"/> Production Unit; <input type="checkbox"/> Pre-Production

### 3.2 EUT Sample details

EUT #	Sample Number	HW Version	SW Version	Notes/Comments
1	2042550B4F	B	EM.00.01.1085,BM.00.01.0048	Radiated Emissions

### 3.3 Support Equipment

SE #	Description
1	Communication cable and a magnet
2	Laptop, Dell Latitude 7490

### 3.4 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT#1 + AE#1	Special commands through command window used to configure the Bluetooth LE radio to low, mid and high channels and co-transmitting with LTE CAT M1 Band 4 mid Channel (1732.5 MHz) provided by the client that will not be available to the end user. For radiated measurements, the internal antenna was connected.

### 3.5 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter sets on low, mid and high channels, and co-transmitting with LTE CAT M1 Band 4 mid Channel (1732.5 MHz). Based on client declaration, the EUT was configured to the highest duty cycle and maximum output power.

For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

#### **4 Subject of Investigation**

The objective of the evaluation conducted by CETECOM Inc. is to support a request for new equipment authorization under FCC ID: MTFVUE2000 / IC ID: 2175D-VUE2000

The pre-certified module (Laird Connectivity Module BL654) is integrated on the device as described in Section 3. Radiated Spurious Emissions test was performed. Results have been checked to meet limits per Code of Federal Regulations Title 47 Parts 15.247 and Industry Canada Radio Standard Specifications RSS: 247 Issue 2

The conducted module test data that can be obtained under the FCC Filing ID: SQGBL654 / IC ID: 3147A-BL654 is applicable for the host described in section 3.

Testing procedures are based on 558074 D01 DTS Meas Guidance v05r02 – “GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

## 5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
§15.247(a)(1) RSS-247 5.2(1)	Emission Bandwidth	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	■	Complies Note1, 2
§15.247(e) RSS-247 5.2(2)	Power Spectral Density	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	■	Complies Note1, 2
§15.247(b)(1) RSS-247 5.4(4)	Maximum Conducted Output Power and EIRP	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	■	Complies Note1, 2
§15.247(d) RSS-247 5.5	Band edge compliance Unrestricted Band Edges	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	■	Complies Note1, 2
§15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10	Band edge compliance Restricted Band Edges	Nominal	BTLE	<input type="checkbox"/>	<input type="checkbox"/>	■	Complies Note1, 2
§15.247(d); §15.209 RSS-Gen 6.13	TX Spurious emissions- Radiated	Nominal	BTLE	■	<input type="checkbox"/>	<input type="checkbox"/>	Complies
§15.207(a) RSS Gen 8.8	AC Conducted Emissions	Nominal	BTLE	<input type="checkbox"/>	■	<input type="checkbox"/>	Note3

**Note1:** NA= Not Applicable; NP= Not Performed.

**Note2:** The conducted measurements are leveraged from module certification reports FR8130002 for FCC issued Jun 25 2018 and CR8130002 for ISSED issued Jun 25 2018 for compliance against the applicable rules.

**Note3:** The EUT is powered by 12 VDC.

## 6 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor  $k=1$ .

### Radiated measurement

9 kHz to 30 MHz	$\pm 2.5$ dB (Magnetic Loop Antenna)
30 MHz to 1000 MHz	$\pm 2.0$ dB (Biconilog Antenna)
1 GHz to 40 GHz	$\pm 2.3$ dB (Horn Antenna)

### Conducted measurement

150 kHz to 30 MHz	$\pm 0.7$ dB (LISN)
-------------------	---------------------

RF conducted measurement	$\pm 0.5$ dB
--------------------------	--------------

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error. Also used: <http://physics.nist.gov/cuu/Uncertainty/typeb.html>. The above calculated uncertainties apply to direct application of the Substitution method. The Substitution method is always used when the EUT comes closer than 3 dB to the limit.

### 6.1 Environmental Conditions during Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

### 6.2 Dates of Testing:


01/21/2021-01/25/2021

## 7 Measurement Procedures


### 7.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.



### Radiated Emissions Test Setup 30MHz-1GHz Measurements



### Radiated Emissions Test Setup above 1GHz Measurements



### 7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dB $\mu$ V
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:


$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:

Frequency (MHz)	Measured SA (dB $\mu$ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB $\mu$ V/m)
1000	80.5	3.5	14	98.0

## 7.2 RF Conducted Measurement Procedure

Testing procedures are based on 558074 D01 DTS Meas Guidance v05r02 – “GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER SECTION 15.247” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.
- Calculate the conducted power by taking into account attenuation of the cable and the attenuator

## 8 Test Result Data

### 8.1 Radiated Transmitter Spurious Emissions and Restricted Bands

#### 8.1.1 Measurement according to ANSI C63.10 (2013)

##### Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak
  
- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)
  
- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz
  
- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing at distance other than the specified in the standard, the limit conversion is calculated by using 40 dB/decade extrapolation factor as follow: Conversion factor (CF) =  $40 \log (D/d) = 40 \log (300\text{m} / 3\text{m}) = 80\text{dB}$

#### 8.1.2 Limits:

##### FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

## FCC §15.209 &amp; RSS-Gen 8.9

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (μV/m)	Measurement Distance (m)	Field strength @ 3m (dBμV/m)
0.009–0.490	2400/F(kHz) / -----	300	-
0.490–1.705	24000/F(kHz) / -----	30	-
1.705–30.0	30 / (29.5)	30	-
30–88	100	3	40 dBμV/m
88–216	150	3	43.5 dBμV/m
216–960	200	3	46 dBμV/m
Above 960	500	3	54 dBμV/m

## FCC §15.205 &amp; RSS-Gen 8.10

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

\*PEAK LIMIT= 74 dBμV/m

\*AVG. LIMIT= 54 dBμV/m


### 8.1.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
23° C	1	GFSK continuous fixed channel	12 VDC

### 8.1.4 Measurement result:

Plot #	Channel #	Scan Frequency	Limit	Result
1-3	Low	30 MHz – 18 GHz	See section 8.1.2	Pass
4-8	Mid	9 kHz – 26 GHz	See section 8.1.2	Pass
9-11	High	30 MHz – 18 GHz	See section 8.1.2	Pass

### 8.1.5 Measurement Plots:




## Plot #18 Radiated Emissions: 1-3 GHz

Modulation: GFSK

Channel: Low

## Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
1461.857	60.11	----	73.98	13.87	500.0	1000.000	164.0	H	289.0	5.2	
1461.857	----	28.15	53.98	25.83	500.0	1000.000	164.0	H	289.0	5.2	
1500.143	63.39	----	73.98	10.59	500.0	1000.000	195.0	H	292.0	5.3	
1500.143	----	29.11	53.98	24.87	500.0	1000.000	195.0	H	292.0	5.3	
1580.143	59.43	----	73.98	14.55	500.0	1000.000	174.0	H	292.0	5.8	
1580.143	----	43.26	53.98	10.72	500.0	1000.000	174.0	H	292.0	5.8	
1805.857	----	29.22	53.98	24.76	500.0	1000.000	185.0	H	239.0	6.8	
1805.857	64.07	----	73.98	9.91	500.0	1000.000	185.0	H	239.0	6.8	
1881.286	61.22	----	73.98	12.76	500.0	1000.000	140.0	H	276.0	7.4	
1881.286	----	44.24	53.98	9.74	500.0	1000.000	140.0	H	276.0	7.4	



Preview Result 2-QPK      Preview Result 1-PK+      FCC 15.209 PK at 3m  
FCC 15.209 AVG at 3m      Final\_Result PK+      Final\_Result CAV


## Plot #19 Radiated Emissions: 3-18 GHz

Modulation: GFSK


Channel: Low

## Final\_Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
3072.250	51.11	---	73.98	22.87	500.0	1000.000	150.0	H	180.0	-8.3	
3072.250	---	31.97	53.98	22.01	500.0	1000.000	150.0	H	180.0	-8.3	
3461.500	60.78	---	73.98	13.20	500.0	1000.000	245.0	H	195.0	-7.0	
3461.500	---	43.85	53.98	10.13	500.0	1000.000	245.0	H	195.0	-7.0	
5191.750	---	36.57	53.98	17.41	500.0	1000.000	150.0	H	134.0	-2.6	
5191.750	53.88	---	73.98	20.10	500.0	1000.000	150.0	H	134.0	-2.6	



Preview Result 1-PK+ Final\_Result PK+ FCC 15.209 PK at 3m Final\_Result CAV FCC 15.209 AVG at 3m




## Plot #21 Radiated Emissions: 30 MHz – 1GHz

Modulation: GFSK

Channel: Mid

## Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Poi	Azimuth (deg)	Corr. (dB/m)	Comment
521.176	29.14	---	46.02	16.88	500.0	120.000	315.0	V	39.0	25.2	
521.176	---	23.93	---	---	500.0	120.000	315.0	V	39.0	25.2	
613.423	31.83	---	46.02	14.19	500.0	120.000	209.0	H	307.0	27.0	
613.423	---	26.87	---	---	500.0	120.000	209.0	H	307.0	27.0	
697.198	33.50	---	46.02	12.52	500.0	120.000	274.0	H	329.0	29.1	
697.198	---	28.73	---	---	500.0	120.000	274.0	H	329.0	29.1	
707.804	---	28.45	---	---	500.0	120.000	140.0	H	66.0	28.9	
707.804	33.41	---	46.02	12.61	500.0	120.000	140.0	H	66.0	28.9	
795.298	---	29.12	---	---	500.0	120.000	285.0	V	30.0	29.3	
795.298	33.97	---	46.02	12.06	500.0	120.000	285.0	V	30.0	29.3	
957.385	36.52	---	46.02	9.50	500.0	120.000	218.0	H	33.0	30.8	
957.385	---	30.59	---	---	500.0	120.000	218.0	H	33.0	30.8	



Preview Result 2-QPK Final\_Result PK+ Preview Result 1-PK+ Final\_Result QPK FCC 15.209 QP at 3m


## Plot #22 Radiated Emissions: 1-3 GHz

Modulation: GFSK

Channel: Mid

## Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
1461.714	59.71	---	73.98	14.27	500.0	1000.000	162.0	H	282.0	5.2	
1461.714	---	27.90	53.98	26.08	500.0	1000.000	162.0	H	282.0	5.2	
1500.000	61.61	---	73.98	12.37	500.0	1000.000	173.0	H	-2.0	5.2	
1500.000	---	28.02	53.98	25.96	500.0	1000.000	173.0	H	-2.0	5.2	
1539.000	58.66	---	73.98	15.32	500.0	1000.000	140.0	H	232.0	5.5	
1539.000	---	27.52	53.98	26.46	500.0	1000.000	140.0	H	232.0	5.5	
1579.857	---	41.38	53.98	12.60	500.0	1000.000	140.0	H	284.0	5.8	
1579.857	59.06	---	73.98	14.92	500.0	1000.000	140.0	H	284.0	5.8	
1713.714	---	28.96	53.98	25.02	500.0	1000.000	163.0	H	279.0	6.5	
1713.714	68.07	---	73.98	5.91	500.0	1000.000	163.0	H	279.0	6.5	
1881.143	59.96	---	73.98	14.02	500.0	1000.000	140.0	H	273.0	7.4	
1881.143	---	42.70	53.98	11.28	500.0	1000.000	140.0	H	273.0	7.4	



Preview Result 2-QPK      Preview Result 1-PK+      FCC 15.209 PK at 3m  
FCC 15.209 AVG at 3m      Final\_Result PK+      Final\_Result CAV


## Plot #23 Radiated Emissions: 3-18 GHz

Modulation: GFSK

Channel: Mid

## Final Result

Frequency (MHz)	MaxPeak (dBuV/m)	CAverage (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
3461.250	58.93	---	73.98	15.05	500.0	1000.000	243.0	H	185.0	-7.0	
3461.250	---	42.64	53.98	11.34	500.0	1000.000	243.0	H	185.0	-7.0	
5192.250	53.85	---	73.98	20.13	500.0	1000.000	217.0	H	131.0	-2.6	
5192.250	---	36.80	53.98	17.18	500.0	1000.000	217.0	H	131.0	-2.6	



Preview Result 1-PK+ Final\_Result PK+ FCC 15.209 PK at 3m Final\_Result CAV FCC 15.209 AVG at 3m


## Plot #24 Radiated Emissions: 18-26 GHz

Modulation: GFSK

Channel: Mid

## Final Result


Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
24896.422	----	55.74	63.50	7.76	500.0	1000.000	100.0	V	45.0	30.2	
24896.422	69.13	----	83.50	14.37	500.0	1000.000	100.0	V	45.0	30.2	
24991.781	68.89	----	83.50	14.61	500.0	1000.000	100.0	V	344.0	29.3	
24991.781	----	55.22	63.50	8.28	500.0	1000.000	100.0	V	344.0	29.3	
25054.734	69.03	----	83.50	14.47	500.0	1000.000	100.0	V	-6.0	30.3	
25054.734	----	56.18	63.50	7.32	500.0	1000.000	100.0	V	-6.0	30.3	



Preview Result 2-QPK  
FCC 15.209 AVG at 1m

Preview Result 1-PK+  
Final\_Result PK+

FCC 15.209 PK at 1m  
Final\_Result CAV




## Plot #26 Radiated Emissions: 1-3 GHz

Modulation: GFSK

Channel: High

## Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
1539.000	59.50	----	73.98	14.48	500.0	1000.000	140.0	H	286.0	5.5	
1539.000	----	27.63	53.98	26.35	500.0	1000.000	140.0	H	286.0	5.5	
1655.000	----	29.44	53.98	24.54	500.0	1000.000	198.0	V	37.0	6.1	
1655.000	61.64	----	53.98	12.34	500.0	1000.000	198.0	V	37.0	6.1	
1690.143	63.13	----	73.98	10.85	500.0	1000.000	253.0	H	293.0	6.4	
1690.143	----	28.32	53.98	25.66	500.0	1000.000	253.0	H	293.0	6.4	
1805.571	----	32.80	53.98	21.18	500.0	1000.000	186.0	H	241.0	6.8	
1805.571	66.84	----	73.98	7.14	500.0	1000.000	186.0	H	241.0	6.8	
1831.429	61.72	----	73.98	12.26	500.0	1000.000	140.0	H	233.0	7.0	
1831.429	----	32.63	53.98	21.35	500.0	1000.000	140.0	H	233.0	7.0	
1880.857	64.33	----	73.98	9.65	500.0	1000.000	140.0	H	282.0	7.4	
1880.857	----	43.35	53.98	10.63	500.0	1000.000	140.0	H	282.0	7.4	



Preview Result 2-QPK      Preview Result 1-PK+      FCC 15.209 PK at 3m  
FCC 15.209 AVG at 3m      Final\_Result PK+      Final\_Result CAV


## Plot #27 Radiated Emissions: 3-18 GHz

Modulation: GFSK

Channel: High

## Final Result

Frequency (MHz)	MaxPeak (dBuV/m)	C.Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Comment
3461.750	60.33	---	73.98	13.65	500.0	1000.000	244.0	H	189.0	-7.0	
3461.750	---	43.64	53.98	10.34	500.0	1000.000	244.0	H	189.0	-7.0	
5192.250	54.46	---	73.98	19.52	500.0	1000.000	250.0	H	135.0	-2.6	
5192.250	---	37.51	53.98	16.47	500.0	1000.000	250.0	H	135.0	-2.6	



Preview Result 1-PK+ Final\_Result PK+ FCC 15.209 PK at 3m Final\_Result CAV FCC 15.209 AVG at 3m

## 9 Test setup photos

Setup photos are included in supporting file name: "EMC\_TELUL\_094\_20001\_Setup\_Photos.pdf"

## 10 Test Equipment and Ancillaries Used For Testing

Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
ACTIVE LOOP ANTENNA	ETS LINDGREN	6507	00161344	3 YEARS	10/30/2020
BILOG ANTENNA	ETS.LINDGREN	3142E	00166067	3 YEARS	03/12/2020
HORN ANTENNA	EMCO	3115	00035114	3 YEARS	08/10/2020
HORN ANTENNA	ETS.LINDGREN	3117	00215984	3 YEARS	01/26/2018
HORN ANTENNA	ETS LINDGREN	3116	00070497	3 YEARS	09/23/2020
SIGNAL ANALYZER	R&S	FSU26	200065	3 YEARS	07/16/2019
SIGNAL ANALYZER	R&S	FSV 40	101022	3 YEARS	07/15/2019
TEST RECEIVER	R&S	ESU.EMI	100256	3 YEARS	07/16/2019
COMPACT DIGITAL BAROMETER	CONTROL COMPANY	10510-922	200236891	3 YEARS	04/13/2020
DIGITAL THERMOMETER	CONTROL COMPANY	36934-164	181230565	3 YEARS	01/10/2019

Note: Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.

## 11 Revision History

Date	Report Name	Changes to report	Report prepared by
2021-05-13	EMC_TELUL_094_20001_15.247_BT_DTS	Initial version	Yuchan Lu
2021-09-30	EMC_TELUL_094_20001_15.247_BT_DTS-R1	Updated wording Section 1 & 4. Corrected Cell ID Section 3. Added Report references Section 5.	Yuchan Lu

<<The End>>