

FCC RF Test Report

APPLICANT : Sierra Wireless Inc.
EQUIPMENT : Development Platform
BRAND NAME : mangOH
MODEL NAME : Red
FCC ID : N7NRED
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Aug. 01, 2017 and testing was completed on Sep. 15, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	13
3.3 Power Spectral Density Measurement	14
3.4 Conducted Band Edges and Spurious Emission Measurement	16
3.5 Radiated Band Edges and Spurious Emission Measurement	26
3.6 AC Conducted Emission Measurement.....	30
3.7 Antenna Requirements	32
4 LIST OF MEASURING EQUIPMENT	33
5 UNCERTAINTY OF EVALUATION	34
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	
APPENDIX F. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR780117B	Rev. 01	Initial issue of report	Sep. 21, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.17 dB at 4874.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 15.60 dB at 0.1820 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Sierra Wireless Inc.

13811 Wireless Way Richmond, BC Canada V6V 3A4

1.2 Manufacturer

Sierra Wireless Inc.

13811 Wireless Way Richmond, BC Canada V6V 3A4

1.3 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n

Product Specification subjective to this standard	
Antenna Type	WLAN: SMT Antenna Bluetooth: SMT Antenna

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH11-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-


2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted	Mode 1 : Bluetooth Tx + Max power channel
Emission	Mode 2 : WLAN (2.4GHz) Tx + Max power channel
Remark: The worst case of conducted emission is mode 1; only the test data of it was reported.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
2.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
3.	iPod Earphone	Apple	A1285	DoC	UnShielded, 1.2m	N/A
4.	NOTE BOOK	Lenovo	T430	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m

2.5 EUT Operation Test Setup

The RF test items, programmed RF utility, “MT7637” installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	26~27°C
Test Band :	2.4GHz Low	Relative Humidity :	49~50%
Test Channel :	01	Test Engineer :	Blue Lan


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 7.SEP.2017 15:07:13

Low Channel Plot




Date: 7.SEP.2017 15:07:59

Spurious Emission 30MHz~3GHz



Date: 7.SEP.2017 15:08:10

Spurious Emission 2GHz~25GHz




Date: 7.SEP.2017 15:08:19



Test Mode :	802.11b	Temperature :	26~27°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~50%
Test Channel :	06	Test Engineer :	Blue Lan

WLAN 802.11b Channel 06


100kHz PSD reference Level



Date: 7.SEP.2017 15:18:54


Mid Channel Plot

Spurious Emission 30MHz~3GHz



Date: 7.SEP.2017 15:19:06

Spurious Emission 2GHz~25GHz




Date: 7.SEP.2017 15:19:15



Test Mode :	802.11b	Temperature :	26~27°C
Test Band :	2.4GHz High	Relative Humidity :	49~50%
Test Channel :	11	Test Engineer :	Blue Lan


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 7.SEP.2017 15:46:44

High Channel Plot




Date: 7.SEP.2017 15:47:09

Spurious Emission 30MHz~3GHz



Date: 7.SEP.2017 15:48:16

Spurious Emission 2GHz~25GHz




Date: 7.SEP.2017 15:48:25

Test Mode :	802.11g	Temperature :	26~27°C
Test Band :	2.4GHz Low	Relative Humidity :	49~50%
Test Channel :	01	Test Engineer :	Blue Lan


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 7.SEP.2017 16:02:58

Low Channel Plot




Date: 7.SEP.2017 16:04:31

Spurious Emission 30MHz~3GHz



Date: 7.SEP.2017 16:04:01

Spurious Emission 2GHz~25GHz




Date: 7.SEP.2017 16:04:10



Test Mode :	802.11g	Temperature :	26~27°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~50%
Test Channel :	06	Test Engineer :	Blue Lan

WLAN 802.11g Channel 06


100kHz PSD reference Level



Date: 7.SEP.2017 16:09:47


Mid Channel Plot

Spurious Emission 30MHz~3GHz



Date: 7.SEP.2017 16:09:58

Spurious Emission 2GHz~25GHz




Date: 7.SEP.2017 16:10:06



Test Mode :	802.11g	Temperature :	26~27°C
Test Band :	2.4GHz High	Relative Humidity :	49~50%
Test Channel :	11	Test Engineer :	Blue Lan


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 7.SEP.2017 16:17:33

High Channel Plot




Date: 7.SEP.2017 16:17:56

Spurious Emission 30MHz~3GHz



Date: 7.SEP.2017 16:18:09

Spurious Emission 2GHz~25GHz




Date: 7.SEP.2017 16:18:17



Test Mode :	802.11n HT20	Temperature :	26~27°C
Test Band :	2.4GHz Low	Relative Humidity :	49~50%
Test Channel :	01	Test Engineer :	Blue Lan


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 7.SEP.2017 17:04:10

Low Channel Plot




Date: 7.SEP.2017 17:04:54

Spurious Emission 30MHz~3GHz



Date: 7.SEP.2017 17:05:05

Spurious Emission 2GHz~25GHz




Date: 7.SEP.2017 17:05:13

Test Mode :	802.11n HT20	Temperature :	26~27°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~50%
Test Channel :	06	Test Engineer :	Blue Lan

WLAN 802.11n HT20 Channel 06


100kHz PSD reference Level



Date: 7.SEP.2017 17:08:15


Mid Channel Plot

Spurious Emission 30MHz~3GHz



Date: 7.SEP.2017 17:08:27

Spurious Emission 2GHz~25GHz




Date: 7.SEP.2017 17:08:36



Test Mode :	802.11n HT20	Temperature :	26~27°C
Test Band :	2.4GHz High	Relative Humidity :	49~50%
Test Channel :	11	Test Engineer :	Blue Lan


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 7.SEP.2017 17:27:01

High Channel Plot




Date: 7.SEP.2017 17:27:14

Spurious Emission 30MHz~3GHz



Date: 7.SEP.2017 17:27:26

Spurious Emission 2GHz~25GHz



Date: 7.SEP.2017 17:27:34



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1218006	N/A	Oct. 06, 2016	Aug. 23, 2017 ~ Sep. 07, 2017	Oct. 05, 2017	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207363	300MHz~40GHz	Oct. 06, 2016	Aug. 23, 2017 ~ Sep. 07, 2017	Oct. 05, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 25, 2016	Aug. 23, 2017 ~ Sep. 07, 2017	Nov. 24, 2017	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Sep. 15, 2017	N/A	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	Sep. 15, 2017	Nov. 28, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 06, 2016	Sep. 15, 2017	Dec. 05, 2017	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Dec. 29, 2016	Sep. 15, 2017	Dec. 28, 2017	Conduction (CO05-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, V SWR : 2.5:1 max	Jul. 18, 2017	Aug. 28, 2017 ~ Sep. 04, 2017	Jul. 17, 2018	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 10, 2016	Aug. 28, 2017 ~ Sep. 04, 2017	Nov. 09, 2017	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT-N0602	30MHz~1GHz	Oct. 15, 2016	Aug. 28, 2017 ~ Sep. 04, 2017	Oct. 14, 2017	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 07, 2016	Aug. 28, 2017 ~ Sep. 04, 2017	Oct. 06, 2017	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Oct. 20, 2016	Aug. 28, 2017 ~ Sep. 04, 2017	Oct. 19, 2018	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Nov. 10, 2016	Aug. 28, 2017 ~ Sep. 04, 2017	Nov. 09, 2017	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-001018 00-30-10P	1902247	1GHz~18GHz	Jun. 23, 2017	Aug. 28, 2017 ~ Sep. 04, 2017	Jun. 22, 2018	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Oct. 12, 2016	Aug. 28, 2017 ~ Sep. 04, 2017	Oct. 11, 2017	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Aug. 28, 2017 ~ Sep. 04, 2017	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Aug. 28, 2017 ~ Sep. 04, 2017	N/A	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 08, 2016	Aug. 28, 2017 ~ Sep. 04, 2017	Nov. 07, 2017	Radiation (03CH11-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz to 26.5GHz	Jan. 12, 2017	Aug. 28, 2017 ~ Sep. 04, 2017	Jan. 11, 2018	Radiation (03CH11-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.50
--	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
--	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Reece Lin	Temperature:	21~25	°C
Test Date:	2017/8/23~2017/9/7	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	14.50	9.54	0.50	Pass
11b	1Mbps	1	6	2437	14.50	9.54	0.50	Pass
11b	1Mbps	1	11	2462	14.45	9.08	0.50	Pass
11g	6Mbps	1	1	2412	17.80	16.28	0.50	Pass
11g	6Mbps	1	6	2437	18.10	16.28	0.50	Pass
11g	6Mbps	1	11	2462	17.80	16.30	0.50	Pass
HT20	MCS0	1	1	2412	18.35	17.56	0.50	Pass
HT20	MCS0	1	6	2437	18.65	17.24	0.50	Pass
HT20	MCS0	1	11	2462	18.40	17.32	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	13.11	30.00	2.50	15.61	36.00	Pass
11b	1Mbps	1	6	2437	13.14	30.00	2.50	15.64	36.00	Pass
11b	1Mbps	1	11	2462	12.12	30.00	2.50	14.62	36.00	Pass
11g	6Mbps	1	1	2412	18.90	30.00	2.50	21.40	36.00	Pass
11g	6Mbps	1	6	2437	19.50	30.00	2.50	22.00	36.00	Pass
11g	6Mbps	1	11	2462	18.90	30.00	2.50	21.40	36.00	Pass
HT20	MCS0	1	1	2412	18.70	30.00	2.50	21.20	36.00	Pass
HT20	MCS0	1	6	2437	19.80	30.00	2.50	22.30	36.00	Pass
HT20	MCS0	1	11	2462	18.30	30.00	2.50	20.80	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.00	11.05
11b	1Mbps	1	6	2437	0.00	11.06
11b	1Mbps	1	11	2462	0.00	10.00
11g	6Mbps	1	1	2412	0.00	11.52
11g	6Mbps	1	6	2437	0.00	12.90
11g	6Mbps	1	11	2462	0.00	11.25
HT20	MCS0	1	1	2412	0.00	11.00
HT20	MCS0	1	6	2437	0.00	13.70
HT20	MCS0	1	11	2462	0.00	10.88

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-11.17	2.50	8.00	Pass
11b	1Mbps	1	6	2437	-11.24	2.50	8.00	Pass
11b	1Mbps	1	11	2462	-12.74	2.50	8.00	Pass
11g	6Mbps	1	1	2412	-12.77	2.50	8.00	Pass
11g	6Mbps	1	6	2437	-11.60	2.50	8.00	Pass
11g	6Mbps	1	11	2462	-12.46	2.50	8.00	Pass
HT20	MCS0	1	1	2412	-14.32	2.50	8.00	Pass
HT20	MCS0	1	6	2437	-10.64	2.50	8.00	Pass
HT20	MCS0	1	11	2462	-13.47	2.50	8.00	Pass




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Blue Lan	Temperature :	26~27°C
		Relative Humidity :	49~50%

EUT Information

Report NO : 780117
Test Mode : Mode 1
Test Voltage : Power Form System
Phase : Line

ENV216 Auto Test-L



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	42.7	Off	L1	19.6	23.3	66.0
0.182000	48.8	Off	L1	19.5	15.6	64.4
0.246000	38.5	Off	L1	19.5	23.4	61.9
0.342000	35.8	Off	L1	19.5	23.4	59.2
4.718000	27.9	Off	L1	19.6	28.1	56.0
7.046000	36.4	Off	L1	19.6	23.6	60.0
16.078000	31.8	Off	L1	19.7	28.2	60.0


Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	26.2	Off	L1	19.6	29.8	56.0
0.182000	31.0	Off	L1	19.5	23.4	54.4
0.246000	26.2	Off	L1	19.5	25.7	51.9
0.342000	23.9	Off	L1	19.5	25.3	49.2
4.718000	18.2	Off	L1	19.6	27.8	46.0
7.046000	26.1	Off	L1	19.6	23.9	50.0
16.078000	26.0	Off	L1	19.7	24.0	50.0

EUT Information

Report NO : 780117
Test Mode : Mode 1
Test Voltage : Power Form System
Phase : Neutral

ENV216 Auto Test-N



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	40.6	Off	N	19.5	25.4	66.0
0.182000	45.8	Off	N	19.5	18.6	64.4
0.254000	32.2	Off	N	19.5	29.4	61.6
0.318000	36.6	Off	N	19.5	23.2	59.8
0.382000	36.6	Off	N	19.5	21.6	58.2
5.622000	33.9	Off	N	19.6	26.1	60.0
6.718000	29.1	Off	N	19.6	30.9	60.0
16.038000	28.5	Off	N	19.8	31.5	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	22.5	Off	N	19.5	33.5	56.0
0.182000	26.0	Off	N	19.5	28.4	54.4
0.254000	21.4	Off	N	19.5	30.2	51.6
0.318000	24.7	Off	N	19.5	25.1	49.8
0.382000	24.7	Off	N	19.5	23.5	48.2
5.622000	20.8	Off	N	19.6	29.2	50.0
6.718000	18.6	Off	N	19.6	31.4	50.0
16.038000	22.8	Off	N	19.8	27.2	50.0



Appendix C. Radiated Spurious Emission

Test Engineer :	J.C. Liang / Jacky Hung / Ken Wu	Temperature :	26~28°C
		Relative Humidity :	50~55%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		2386.965	56.4	-17.6	74	46.84	26.87	6.36	33.6	305	84	P	H
		2387.07	46.1	-7.9	54	36.54	26.87	6.36	33.6	305	84	A	H
	*	2412	107.19	-	-	97.56	26.92	6.37	33.59	305	84	P	H
	*	2412	104.14	-	-	94.51	26.92	6.37	33.59	305	84	A	H
													H
													H
		2380.665	52.83	-21.17	74	43.33	26.81	6.36	33.6	299	101	P	V
		2382.975	42.7	-11.3	54	33.2	26.81	6.36	33.6	299	101	A	V
	*	2412	100.55	-	-	90.92	26.92	6.37	33.59	299	101	P	V
	*	2412	97.45	-	-	87.82	26.92	6.37	33.59	299	101	A	V
													V
													V
802.11b CH 06 2437MHz		2382.1	53.41	-20.59	74	43.91	26.81	6.36	33.6	300	85	P	H
		2382.1	43.68	-10.32	54	34.18	26.81	6.36	33.6	300	85	A	H
	*	2437	106.29	-	-	96.54	27.03	6.38	33.59	300	85	P	H
	*	2437	103.24	-	-	93.49	27.03	6.38	33.59	300	85	A	H
		2499.44	52.78	-21.22	74	42.83	27.2	6.39	33.57	300	85	P	H
		2484.11	42.1	-11.9	54	32.23	27.14	6.38	33.58	300	85	A	H
		2387.14	51.96	-22.04	74	42.4	26.87	6.36	33.6	300	100	P	V
		2382.1	41.84	-12.16	54	32.34	26.81	6.36	33.6	300	100	A	V
	*	2437	100.11	-	-	90.36	27.03	6.38	33.59	300	100	P	V
	*	2437	97.04	-	-	87.29	27.03	6.38	33.59	300	100	A	V
		2498.53	52.12	-21.88	74	42.17	27.2	6.39	33.57	300	100	P	V
		2484.25	41.46	-12.54	54	31.58	27.14	6.39	33.58	300	100	A	V



802.11b CH 11 2462MHz	*	2462	104.48	-	-	94.66	27.09	6.38	33.58	292	86	P	H
	*	2462	101.41	-	-	91.59	27.09	6.38	33.58	292	86	A	H
		2488.36	53.59	-20.41	74	43.65	27.2	6.39	33.58	292	86	P	H
		2487.12	42.54	-11.46	54	32.66	27.14	6.39	33.58	292	86	A	H
													H
													H
	*	2462	97.39	-	-	87.57	27.09	6.38	33.58	300	108	P	V
	*	2462	94.32	-	-	84.5	27.09	6.38	33.58	300	108	A	V
		2488.04	52.57	-21.43	74	42.63	27.2	6.39	33.58	300	108	P	V
		2487.2	41.58	-12.42	54	31.7	27.14	6.39	33.58	300	108	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	45.83	-28.17	74	67.17	31.62	9.59	62.98	100	0	P	H
													H
													H
													H
		4824	54.79	-19.21	74	76.13	31.62	9.59	62.98	100	240	P	V
		4824	53.49	-0.51	54	74.83	31.62	9.59	62.98	100	240	A	V
													V
													V
802.11b CH 06 2437MHz		4874	46.35	-27.65	74	67.52	31.71	9.56	62.87	100	0	P	H
		7311	43.39	-30.61	74	56.88	37.43	11.31	62.69	100	0	P	H
													H
													H
		4874	55.77	-18.23	74	76.94	31.71	9.56	62.87	108	234	P	V
		4874	53.57	-0.43	54	74.74	31.71	9.56	62.87	108	234	A	V
		7311	43.66	-30.34	74	57.15	37.43	11.31	62.69	100	0	P	V
													V
802.11b CH 11 2462MHz		4924	52.48	-21.52	74	73.45	31.79	9.55	62.75	101	295	P	H
		4924	50.9	-3.1	54	71.87	31.79	9.55	62.75	101	295	A	H
		7386	44.26	-29.74	74	57.5	37.82	11.3	62.74	100	0	P	H
													H
		4924	55.44	-18.56	74	76.85	31.79	9.55	62.75	113	234	P	V
		4924	53.27	-0.73	54	74.68	31.79	9.55	62.75	113	234	A	V
		7386	43.75	-30.25	74	56.99	37.82	11.3	62.74	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.485	68.15	-5.85	74	58.59	26.87	6.36	33.6	307	92	P	H
		2390	53.82	-0.18	54	44.25	26.87	6.36	33.59	307	92	A	H
	*	2412	108.82	-	-	99.19	26.92	6.37	33.59	307	92	P	H
	*	2412	101.16	-	-	91.53	26.92	6.37	33.59	307	92	A	H
													H
													H
		2389.59	56.53	-17.47	74	46.97	26.87	6.36	33.6	352	102	P	V
		2390	43.83	-10.17	54	34.26	26.87	6.36	33.59	352	102	A	V
	*	2412	100.67	-	-	91.04	26.92	6.37	33.59	352	102	P	V
	*	2412	93.67	-	-	84.04	26.92	6.37	33.59	352	102	A	V
													V
													V
802.11g CH 06 2437MHz		2377.9	55.62	-18.38	74	46.19	26.81	6.29	33.6	299	87	P	H
		2389.66	45.67	-8.33	54	36.11	26.87	6.36	33.6	299	87	A	H
	*	2437	110.36	-	-	100.61	27.03	6.38	33.59	299	87	P	H
	*	2437	102.9	-	-	93.15	27.03	6.38	33.59	299	87	A	H
		2494.33	53.98	-20.02	74	44.03	27.2	6.39	33.57	299	87	P	H
		2483.62	43.02	-10.98	54	33.15	27.14	6.38	33.58	299	87	A	H
		2380.84	53.45	-20.55	74	43.95	26.81	6.36	33.6	301	100	P	V
		2387.98	42.76	-11.24	54	33.2	26.87	6.36	33.6	301	100	A	V
	*	2437	104.42	-	-	94.67	27.03	6.38	33.59	301	100	P	V
	*	2437	96.92	-	-	87.17	27.03	6.38	33.59	301	100	A	V
		2496.99	52.46	-21.54	74	42.51	27.2	6.39	33.57	301	100	P	V
		2483.9	41.73	-12.27	54	31.86	27.14	6.38	33.58	301	100	A	V



802.11g CH 11 2462MHz	*	2462	106.75	-	-	96.93	27.09	6.38	33.58	297	93	P	H
	*	2462	98.95	-	-	89.13	27.09	6.38	33.58	297	93	A	H
		2483.6	68.43	-5.57	74	58.56	27.14	6.38	33.58	297	93	P	H
		2483.52	53.26	-0.74	54	43.39	27.14	6.38	33.58	297	93	A	H
													H
													H
	*	2462	101.29	-	-	91.47	27.09	6.38	33.58	296	111	P	V
	*	2462	94.24	-	-	84.42	27.09	6.38	33.58	296	111	A	V
		2484.2	61.01	-12.99	74	51.13	27.14	6.39	33.58	296	111	P	V
		2483.52	47.46	-6.54	54	37.59	27.14	6.38	33.58	296	111	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	55.01	-18.99	74	76.35	31.62	9.59	62.98	100	122	P	H
		4824	42.38	-11.62	54	63.72	31.62	9.59	62.98	100	122	A	H
													H
													H
		4824	60.03	-13.97	74	81.8	31.62	9.59	62.98	100	240	P	V
		4824	46.46	-7.54	54	68.23	31.62	9.59	62.98	100	240	A	V
													V
													V
802.11g CH 06 2437MHz		4874	62.89	-11.11	74	84.06	31.71	9.56	62.87	100	168	P	H
		4874	51.68	-2.32	54	72.85	31.71	9.56	62.87	100	168	A	H
		7311	45.29	-28.71	74	58.78	37.43	11.31	62.69	100	0	P	H
													H
		4874	64.1	-9.9	74	85.27	31.71	9.56	62.87	100	237	P	V
		4874	53.83	-0.17	54	75	31.71	9.56	62.87	100	237	A	V
		7311	40.73	-33.27	74	54.22	37.43	11.31	62.69	100	0	P	V
													V
802.11g CH 11 2462MHz		4924	58.71	-15.29	74	79.68	31.79	9.55	62.75	100	122	P	H
		4924	44.1	-9.9	54	65.07	31.79	9.55	62.75	100	122	A	H
		7386	43.35	-30.65	74	56.59	37.82	11.3	62.74	100	0	P	H
													H
		4924	61.72	-12.28	74	83.13	31.79	9.55	62.75	100	238	P	V
		4924	47.89	-6.11	54	69.3	31.79	9.55	62.75	100	238	A	V
		7386	45.09	-28.91	74	58.71	37.82	11.3	62.74	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.485	67.25	-6.75	74	57.69	26.87	6.36	33.6	304	89	P	H
		2390	53.63	-0.37	54	44.06	26.87	6.36	33.59	304	89	A	H
	*	2412	107.28	-	-	97.65	26.92	6.37	33.59	304	89	P	H
	*	2412	99.84	-	-	90.21	26.92	6.37	33.59	304	89	A	H
													H
													H
		2389.38	65.14	-8.86	74	55.58	26.87	6.36	33.6	352	110	P	V
		2390	50.98	-3.02	54	41.41	26.87	6.36	33.59	352	110	A	V
	*	2412	104.8	-	-	95.17	26.92	6.37	33.59	352	110	P	V
	*	2412	97.08	-	-	87.45	26.92	6.37	33.59	352	110	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2384.62	56.2	-17.8	74	46.7	26.81	6.36	33.6	306	80	P	H
		2389.94	46.19	-7.81	54	36.62	26.87	6.36	33.59	306	80	A	H
	*	2437	111.54	-	-	101.79	27.03	6.38	33.59	306	80	P	H
	*	2437	104.22	-	-	94.47	27.03	6.38	33.59	306	80	A	H
		2492.93	53.66	-20.34	74	43.71	27.2	6.39	33.57	306	80	P	H
		2483.5	43.32	-10.68	54	33.45	27.14	6.38	33.58	306	80	A	H
		2387.7	53.4	-20.6	74	43.84	26.87	6.36	33.6	333	111	P	V
		2389.38	42.74	-11.26	54	33.18	26.87	6.36	33.6	333	111	A	V
	*	2437	105.45	-	-	95.7	27.03	6.38	33.59	333	111	P	V
	*	2437	98.12	-	-	88.37	27.03	6.38	33.59	333	111	A	V
		2493.56	52.94	-21.06	74	42.99	27.2	6.39	33.57	333	111	P	V
		2485.51	42.12	-11.88	54	32.24	27.14	6.39	33.58	333	111	A	V



802.11n HT20 CH 11 2462MHz	*	2462	106.88	-	-	97.06	27.09	6.38	33.58	292	86	P	H
	*	2462	99.84	-	-	90.02	27.09	6.38	33.58	292	86	A	H
		2483.76	70.2	-3.8	74	60.33	27.14	6.38	33.58	292	86	P	H
		2483.52	53.45	-0.55	54	43.58	27.14	6.38	33.58	292	86	A	H
													H
													H
	*	2462	100.67	-	-	90.85	27.09	6.38	33.58	298	111	P	V
	*	2462	93.24	-	-	83.42	27.09	6.38	33.58	298	111	A	V
		2483.52	61.98	-12.02	74	52.11	27.14	6.38	33.58	298	111	P	V
		2483.52	47.39	-6.61	54	37.52	27.14	6.38	33.58	298	111	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	54.63	-19.37	74	75.97	31.62	9.59	62.98	100	123	P	H
		4824	39.82	-14.18	54	61.16	31.62	9.59	62.98	100	123	A	H
													H
													H
		4824	58.92	-15.08	74	80.69	31.62	9.59	62.98	100	240	P	V
		4824	43.69	-10.31	54	65.46	31.62	9.59	62.98	100	240	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		4874	60.81	-13.19	74	81.98	31.71	9.56	62.87	100	166	P	H
		4874	48.16	-5.84	54	69.33	31.71	9.56	62.87	100	166	A	H
		7311	44.48	-29.52	74	57.97	37.43	11.31	62.69	100	0	P	H
													H
		4874	66.27	-7.73	74	87.44	31.71	9.56	62.87	105	238	P	V
		4874	53.25	-0.75	54	74.42	31.71	9.56	62.87	105	238	A	V
		7311	44.8	-29.2	74	58.29	37.43	11.31	62.69	100	0	P	V
													V
802.11n HT20 CH 11 2462MHz		4924	59.63	-14.37	74	80.6	31.79	9.55	62.75	100	121	P	H
		4924	45.83	-8.17	54	66.8	31.79	9.55	62.75	100	121	A	H
		7386	44.63	-29.37	74	57.87	37.82	11.3	62.74	100	0	P	H
													H
		4924	62.42	-11.58	74	83.39	31.79	9.55	62.75	100	240	P	V
		4924	50.51	-3.49	54	71.48	31.79	9.55	62.75	100	240	A	V
		7386	44.46	-29.54	74	58.08	37.82	11.3	62.74	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		84	28.04	-11.96	40	45.51	13.77	1.22	32.48	-	-	P	H
		194.43	23.69	-19.81	43.5	39.49	14.84	1.69	32.4	-	-	P	H
		227.91	33.16	-12.84	46	47.52	16	1.95	32.38	-	-	P	H
		444.2	36.64	-9.36	46	43.14	23.11	2.7	32.35	100	0	P	H
		769.7	31.14	-14.86	46	31.55	28.28	3.44	32.27	-	-	P	H
		923.7	34.52	-11.48	46	32.31	29.7	3.79	31.44	-	-	P	H
													H
													H
													H
													H
													H
													H
		49.17	31.51	-8.49	40	48.44	14.53	1.02	32.49	100	0	P	V
		179.58	29.04	-14.46	43.5	44.72	14.95	1.69	32.41	-	-	P	V
		279.75	28.44	-17.56	46	39.73	18.77	2.22	32.37	-	-	P	V
		730.5	32.44	-13.56	46	33.66	27.63	3.4	32.38	-	-	P	V
		832.7	33.44	-12.56	46	32.96	28.74	3.6	32.01	-	-	P	V
		936.3	34.73	-11.27	46	31.86	30.21	3.82	31.33	-	-	P	V
													V
													V
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	J.C. Liang / Jacky Hung / Ken Wu	Temperature :	26~28°C
		Relative Humidity :	50~55%





Note symbol

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 15	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 15
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 15	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 15







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15	Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15
Avg.	Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15	Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : 15	Left blank
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : 15	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 780117 Setting : 15	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 780117 Setting : 15
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 780117 Setting : 15	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 780117 Setting : 15







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : 15	Left blank
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : 15	Left blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 13	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 13
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 13	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 13







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The plot shows a blue line representing the spectrum with a sharp peak at 2462 MHz. A red horizontal line indicates the peak level at approximately 87.5 dBuV/m. The x-axis ranges from 2460 to 2500 MHz, and the y-axis ranges from 17.5 to 140 dBuV/m. Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 780117 Setting : 13	 Level (dBuV/m) vs Frequency (MHz) plot for Fundamental polarization. The plot shows a blue line representing the spectrum with a sharp peak at 2462 MHz. A red horizontal line indicates the peak level at approximately 87.5 dBuV/m. The x-axis ranges from 1000 to 3000 MHz, and the y-axis ranges from 17.5 to 140 dBuV/m. Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 780117 Setting : 13
Avg.	 Level (dBuV/m) vs Frequency (MHz) plot for Vertical polarization. The plot shows a blue line representing the spectrum with a sharp peak at 2462 MHz. A red horizontal line indicates the average level at approximately 52.5 dBuV/m. The x-axis ranges from 2460 to 2500 MHz, and the y-axis ranges from 17.5 to 140 dBuV/m. Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 780117 Setting : 13	 Level (dBuV/m) vs Frequency (MHz) plot for Fundamental polarization. The plot shows a blue line representing the spectrum with a sharp peak at 2462 MHz. A red horizontal line indicates the average level at approximately 52.5 dBuV/m. The x-axis ranges from 1000 to 3000 MHz, and the y-axis ranges from 17.5 to 140 dBuV/m. Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 780117 Setting : 13







2.4GHz 2400~2483.5MHz





WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 19
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 19



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : ID	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : ID
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : ID	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : ID





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HV Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : ID	Left blank
Avg.	 Site : 03CH11-HV Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : ID	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 780117 Setting : ID	Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 780117 Setting : ID
Avg.	Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 780117 Setting : ID	Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 780117 Setting : ID







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HV Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : ID	Left Blank
Avg.	 Site : 03CH11-HV Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : ID	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A







2.4GHz 2400~2483.5MHz





WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 19
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 19







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : Z1	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : Z1
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : Z1	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : Z1





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HV Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : Z1	Left blank
Avg.	 Site : 03CH11-HV Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : Z1	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 780117 Setting : Z1	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 780117 Setting : Z1
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 780117 Setting : Z1	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Project : 780117 Setting : Z1







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HV Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : Z1	Left Blank
Avg.	 Site : 03CH11-HV Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 780117 Setting : Z1	Left Blank





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A





WIFI	2.4GHz 2400~2483.5MHz Fundamental @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Level (dBuV/m) Frequency (MHz) Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A	 Level (dBuV/m) Frequency (MHz) Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A
Avg.	 Level (dBuV/m) Frequency (MHz) Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A	 Level (dBuV/m) Frequency (MHz) Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A





2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 780117 Setting : 15





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-9FY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 15	 Site : 03CH11-9FY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 15





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-9V Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 13	 Site : 03CH11-9V Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 13



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 780117 Setting : 19





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-9FY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1D	 Site : 03CH11-9FY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1D





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH11-9V Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A	Site : 03CH11-9V Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 19	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 19





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m																					
ANT	802.11n HT20 CH06 2437MHz																					
1	Horizontal	Vertical																				
Peak Avg.	<table><tr><td>Site</td><td>: 03CH11-9FY</td></tr><tr><td>Condition</td><td>: PEAK_74 3m HORN 9120D-HF HORIZONTAL</td></tr><tr><td>Detector</td><td>: Peak</td></tr><tr><td>Project</td><td>: 780117</td></tr><tr><td>Setting</td><td>: Z1</td></tr></table>	Site	: 03CH11-9FY	Condition	: PEAK_74 3m HORN 9120D-HF HORIZONTAL	Detector	: Peak	Project	: 780117	Setting	: Z1	<table><tr><td>Site</td><td>: 03CH11-9FY</td></tr><tr><td>Condition</td><td>: PEAK_74 3m HORN 9120D-HF VERTICAL</td></tr><tr><td>Detector</td><td>: Peak</td></tr><tr><td>Project</td><td>: 780117</td></tr><tr><td>Setting</td><td>: Z1</td></tr></table>	Site	: 03CH11-9FY	Condition	: PEAK_74 3m HORN 9120D-HF VERTICAL	Detector	: Peak	Project	: 780117	Setting	: Z1
	Site	: 03CH11-9FY																				
Condition	: PEAK_74 3m HORN 9120D-HF HORIZONTAL																					
Detector	: Peak																					
Project	: 780117																					
Setting	: Z1																					
Site	: 03CH11-9FY																					
Condition	: PEAK_74 3m HORN 9120D-HF VERTICAL																					
Detector	: Peak																					
Project	: 780117																					
Setting	: Z1																					



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH11-9V Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 780117 Setting : 1A	Site : 03CH11-9V Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 780117 Setting : 1A




Emission below 1GHz
2.4GHz WIFI 802.11g (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11g LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH11-HY Condition : QP 3m BT-LOG 6111D-LF_ETC HORIZONTAL Detector : Peak Project : 780117	 Site : 03CH11-HY Condition : QP 3m BT-LOG 6111D-LF_ETC VERTICAL Detector : Peak Project : 780117

Appendix E. Duty Cycle Plots


Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
802.11b	100	-	-	10Hz
802.11g	100	-	-	10Hz
2.4GHz 802.11n HT20	100	-	-	10Hz

802.11b



Date: 24.AUG.2017 11:55:02


802.11g



Date: 24.AUG.2017 11:55:52



802.11n HT20




Date: 24.AUG.2017 11:56:29


Appendix F. Setup Photographs

<Conducted Emission>

Mode 1

Remote View





Rear View



<Radiated Emission>

LF



HF

