

RF Exposure Evaluation Declaration

Product Name : HD 180 Degree Wi-Fi Camera
Trade Name : D-Link
Model No. : DCS-8100LH
FCC ID. : KA2CS8100LHA1

Applicant : D-Link Corporation

Address : No.289, Sinhu 3rd Rd., Neihu District, Taipei
City 114, Taiwan, R.O.C.

Tested : Feb. 07, 2017 ~ May 19, 2017
Issued Date : May 22, 2017
Report No. : 1740183R-RF-US-Exp
Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd.

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

WiFi

Product	HD 180 Degree Wi-Fi Camera
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 1.5 dBi or 1.41 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	78.5236	0.02203
6	2437	56.8853	0.01596
11	2462	54.7016	0.01534

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	38.4592	0.01079
6	2437	39.4457	0.01106
11	2462	38.1944	0.01071

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

WiFi

Product	HD 180 Degree Wi-Fi Camera
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 1.5 dBi or 1.41 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (20MHz)			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	2412	29.6483	0.00832
6	2437	30.8319	0.00865
11	2462	29.9226	0.00839

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².

BT 4.0

Product	HD 180 Degree Wi-Fi Camera
Test Mode	Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber are 1.5 dBi or 1.41 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

GFSK			
Bluetooth Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
00	2402	1.8239	0.00051
19	2440	2.9444	0.00083
39	2480	4.1495	0.00116

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm².