

FCC SAR REPORT

Applicant: TECNO MOBILE LIMITED

Address of Applicant: FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE
19-25 SHAN MEI STREET FOTAN NT HONGKONG

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: KI7

Trade mark: TECNO

FCC ID: 2ADYY-KI7

Applicable standards: FCC 47 CFR Part 2.1093

Date of Test: 02 Dec., 2022 ~ 12 Dec., 2022

Test Result: Maximum Reported 1-g SAR (W/kg)
Head: 1.320 Body: 0.603 Hotspot: 0.648

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the JYT product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	05 Jan., 2023	Original

Tested by:

Zora . Huang

Date:

05 Jan., 2023

Test Engineer

Reviewed by:

Janet . Wei

Date:

05 Jan., 2023

Project Engineer

3 Contents

1	COVER PAGE.....	1
2	VERSION	2
3	CONTENTS	3
4	SAR RESULTS SUMMARY.....	5
5	GENERAL INFORMATION.....	7
5.1	CLIENT INFORMATION.....	7
5.2	GENERAL DESCRIPTION OF EUT	7
5.3	MAXIMUM RF OUTPUT POWER.....	9
5.4	ENVIRONMENT OF TEST SITE	11
5.5	TEST SAMPLE PLAN	11
5.6	TEST LOCATION	11
6	INTRODUCTION.....	12
6.1	INTRODUCTION	12
6.2	SAR DEFINITION	12
7	RF EXPOSURE LIMITS	13
7.1	UNCONTROLLED ENVIRONMENT.....	13
7.2	CONTROLLED ENVIRONMENT	13
7.3	RF EXPOSURE LIMITS	13
8	SAR MEASUREMENT SYSTEM.....	14
8.1	E-FIELD PROBE.....	15
8.2	ROBOT	16
8.3	PHANTOM.....	17
8.4	DEVICE HOLDER.....	17
8.5	TEST EQUIPMENT LIST	18
9	TISSUE SIMULATING LIQUIDS	19
10	SAR SYSTEM VERIFICATION.....	21
11	EUT TESTING POSITION.....	23
11.1	HANDSET REFERENCE POINTS	23
11.2	POSITIONING FOR CHEEK / TOUCH	24
11.3	POSITIONING FOR EAR / 15° TILT	24
11.4	SAR EVALUATIONS NEAR THE MOUTH/JAW REGIONS OF THE SAM PHANTOM	25
11.5	BODY WORN ACCESSORY CONFIGURATIONS	25
11.6	WIRELESS ROUTER (HOTSPOT) CONFIGURATIONS	26
12	MEASUREMENT PROCEDURES	27
12.1	SPATIAL PEAK SAR EVALUATION	27
12.2	POWER REFERENCE MEASUREMENT.....	28
12.3	AREA & ZOOM SCAN PROCEDURES.....	28
12.4	VOLUME SCAN PROCEDURES	29
12.5	SAR AVERAGED METHODS	29
12.6	POWER DRIFT MONITORING	29
13	CONDUCTED RF OUTPUT POWER.....	30
13.1	GSM CONDUCTED POWER	30
13.2	WCDMA CONDUCTED POWER	32
13.3	LTE CONDUCTED POWER	35
13.4	WLAN 2.4 GHz BAND CONDUCTED POWER	66
13.5	WLAN 5.2GHz BAND CONDUCTED POWER	67
13.6	WLAN 5.8GHz BAND CONDUCTED POWER	68
13.7	BLUETOOTH CONDUCTED POWER	69
13.8	NFC CONDUCTED POWER	70
14	EXPOSURE POSITIONS CONSIDERATION	71
14.1	EUT ANTENNA LOCATIONS.....	71
14.2	TEST POSITIONS CONSIDERATION	72
15	SAR TEST RESULTS SUMMARY	73
15.1	STANDALONE HEAD SAR DATA.....	73

15.2	STANDALONE BODY SAR	78
15.3	BODY SAR IN HOTSPOT MODE	81
15.4	REPEATED SAR MEASUREMENT	85
15.5	DUT HOLDER PERTURBATION UNCERTAINTY EVALUATION	86
15.6	MULTI-BAND SIMULTANEOUS TRANSMISSION CONSIDERATIONS	87
15.7	SAR SIMULTANEOUS TRANSMISSION ANALYSIS	88
15.8	MEASUREMENT UNCERTAINTY	89
16	REFERENCE	90
APPENDIX A: PLOTS OF SAR SYSTEM CHECK		91
APPENDIX B: PLOTS OF SAR TEST DATA		100
APPENDIX C: SYSTEM CALIBRATION CERTIFICATE		136

4 SAR Results Summary

The maximum results of Specific Absorption Rate (SAR) found during test as below:
<Highest Reported standalone SAR Summary>

Exposure Position	Frequency Band	Reported 1-g SAR (W/kg)	Equipment Class	Highest Reported 1-g SAR (W/kg)
Head	GSM 850	0.635	PCE	1.320
	PCS 1900	1.273		
	WCDMA Band II	0.463		
	WCDMA Band IV	0.971		
	WCDMA Band V	0.374		
	LTE Band 2	1.227		
	LTE Band 5	0.559		
	LTE Band 7	1.137		
	LTE Band 12&Band 17	0.317		
	LTE Band 41&Band 38	0.472		
	LTE Band 66&Band 4	1.320		
	WLAN 2.4 GHz	0.290	DTS	
	WLAN 5.2 GHz	0.157	NII	
	WLAN 5.8 GHz	0.153	DSS	
Bluetooth	0.043			
Body (10 mm Gap)	GSM 850	0.462	PCE	0.603
	PCS 1900	0.603		
	WCDMA Band II	0.230		
	WCDMA Band IV	0.313		
	WCDMA Band V	0.238		
	LTE Band 2	0.521		
	LTE Band 5	0.233		
	LTE Band 7	0.394		
	LTE Band 12&Band 17	0.122		
	LTE Band 41&Band 38	0.251		
	LTE Band 66&Band 4	0.299		
	WLAN 2.4 GHz	0.080	DTS	
	WLAN 5.2 GHz	0.102	NII	
	WLAN 5.8 GHz	0.084	DSS	
Bluetooth	0.023			
Hotspot (10 mm Gap)	GSM 850	0.462	PCE	0.648
	PCS 1900	0.648		
	WCDMA Band II	0.234		
	WCDMA Band IV	0.313		
	WCDMA Band V	0.238		
	LTE Band 2	0.521		
	LTE Band 5	0.233		
	LTE Band 7	0.394		
	LTE Band 12&Band 17	0.122		
	LTE Band 41&Band 38	0.251		
	LTE Band 66&Band 4	0.299		
	WLAN 2.4 GHz	0.082	DTS	

	WLAN 5.2 GHz	0.102	NII	
	WLAN 5.8 GHz	0.084		
	Bluetooth	0.023	DSS	

< Highest Reported simultaneous SAR Summary>

Exposure Position	Frequency Band	Reported 1-g SAR (W/kg)	Equipment Class	Highest Reported Simultaneous Transmission 1-g SAR (W/kg)
Right Cheek	WWAN	1.320	PCE	1.443
	WLAN 2.4 GHz	0.123	DTS	
	NFC	0.000	DXX	

Note:

1. The highest simultaneous transmission is scalar summation of Reported standalone SAR per FCC KDB 690783 D01 v01r03, and scalar SAR summation of all possible simultaneous transmission scenarios are < 1.6W/kg.
2. This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.
3. For FDD-LTE Band 17 is full covered by FDD-LTE Band 12, so only FDD-LTE Band 12 was tested.
4. For TDD-LTE Band 38 is full covered by TDD-LTE Band 41, so only TDD-LTE Band 41 was tested.
5. For FDD-LTE Band 4 is full covered by FDD-LTE Band 66, so only FDD-LTE Band 66 was tested.

5 General Information

5.1 Client Information

Applicant:	TECNO MOBILE LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Manufacturer:	TECNO MOBILE LIMITED
Address:	FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25 SHAN MEI STREET FOTAN NT HONGKONG
Factory:	SHENZHEN TECNO TECHNOLOGY CO., LTD.
Address:	101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R.China

5.2 General Description of EUT

Product Name:	Mobile Phone				
Model No.:	KI7				
Category of device	Portable device				
Operation Frequency:	GSM :	GSM850: 824.2~848.8 MHz		PCS 1900: 1850.2~1909.8 MHz	
	WCDMA :	Band II: 1852.4~1907.6 MHz		Band V: 826.4~846.6 MHz	
		Band IV: 1712.4~1752.6 MHz			
	LTE :	Band 2 :1850MHz~1910MHz		Band 4 :1710MHz~1755MHz	
		Band 5 :824MHz~849MHz		Band 7: 2500MHz~2570MHz	
		Band 12: 698MHz~716MHz		Band 17: 704MHz~716MHz	
		Band 38: 2570MHz~2620MHz		Band 41: 2535MHz~2655MHz	
		Band 66 :1710MHz~1780MHz			
	Wi-Fi:	2412MHz~2462MHz		5150MHz-5250MHz	
		5725MHz-5850MHz			
	Bluetooth: 2402 MHz ~ 2480 MHz				
	NFC : 13.56MHz				
Modulation technology:	GSM:	☒ Voice(GMSK)	☒ GPRS(GMSK)	☒ EGPRS(GMSK, 8PSK)	
	WCDMA:	☒ RMC(QPSK)	☒ HSUPA(QPSK)	☒ HSDPA(QPSK,16QAM)	
	LTE:	☒ QPSK	☒ 16QAM	☒ 64QAM	
	Wi-Fi:	☒ 802.11b(DSSS)		☒ 802.11a/g/n/ac (OFDM)	
	Bluetooth:	☒ BDR(GFSK)	☒ EDR(π/4-DQPSK, 8DPSK)	☒ LE(GFSK)	
	NFC :	ASK			
Antenna Type:	Internal Antenna				
Antenna Gain:	GSM 850: -6.33dBi; PCS 1900: -1.25dBi WCDMA Band II: -1.25dBi; WCDMA Band V: -6.33dBi WCDMA Band IV: -0.97dBi LTE Band 2: -1.25dBi; LTE Band 4: -0.97dBi LTE Band 5: -6.33dBi; LTE Band 7: 0.63dBi LTE Band 12: -4.60dBi; LTE Band 17: -4.60dBi LTE Band 38: 0.63dBi; LTE Band 41: 0.63dBi LTE Band 66: -0.97dBi Bluetooth: -1.38dBi; 2.4G Wi-Fi: -1.38dBi; 5G Wi-Fi: -3.29dBi				

(E)GPRS Class:	(E)GPRS Class: 12	
Dimensions (L*W*H):	169 mm (L)× 76 mm (W)× 9 mm (H)	
Accessories information:	Adapter: Model: U180TSA Input: AC100-240V, 50/60Hz, 0.6A Output: DC 5.0V, 2.4A or 7.5V, 2.4A 18.0W Max	Battery: Rechargeable Li-ion polymer Battery 3.85V/4900mAh
		Headset: Support headset

5.3 Maximum RF Output Power

Mode	Average Power (dBm)	
	GSM 850	PCS 1900
GSM (Voice)	33.98	31.07
GPRS (1 TX Slot)	34.02	31.02
GPRS (2 TX Slots)	33.03	30.07
GPRS (3 TX Slots)	31.06	28.06
GPRS (4 TX Slots)	29.99	27.01
EGPRS (1 TX Slot)	28.30	27.05
EGPRS (2 TX Slots)	27.16	26.10
EGPRS (3 TX Slots)	24.85	24.06
EGPRS (4 TX Slots)	23.63	23.06

Mode	Average Power (dBm)		
	WCDMA Band II	WCDMA Band IV	WCDMA Band V
AMR 12.2 kbps	23.95	23.69	23.92
RMC 12.2 kbps	23.94	23.76	23.96
HSDPA Sub-test 1	22.91	22.77	22.96
HSDPA Sub-test 2	22.39	22.25	22.48
HSDPA Sub-test 3	22.40	22.27	22.43
HSDPA Sub-test 4	22.42	22.25	22.46
HSUPA Sub-test 1	20.98	20.81	20.94
HSUPA Sub-test 2	21.37	21.27	21.40
HSUPA Sub-test 3	21.89	21.75	21.93
HSUPA Sub-test 4	21.01	20.82	20.94
HSUPA Sub-test 5	22.96	22.80	22.95

Mode	Average Power (dBm)					
	LTE Band 2	LTE Band 5	LTE Band 7	LTE Band 12	LTE Band 41	LTE Band 66
BW/1.4 MHz	23.78	24.15	/	23.85	/	23.79
BW/3.0 MHz	23.69	24.05	/	23.84	/	23.77
BW/5.0 MHz	23.72	24.07	23.58	23.95	23.69	23.84
BW/10 MHz	23.75	24.17	23.61	23.92	23.87	23.78
BW/15 MHz	23.65	/	23.53	/	23.74	23.71
BW/20 MHz	23.80	/	23.70	/	23.85	23.75

WLAN 2.4 GHz Band Average Power (dBm)				
Mode/Band	b	g	n (HT-20)	n (HT-40)
WLAN 2.4GHz	16.96	14.37	13.43	13.49

WLAN 5.2 GHz Band Average Power (dBm)						
Mode/Band	a	ac 20	ac 40	ac 80	n 20	n 40
WLAN 5.2GHz	14.33	14.07	13.85	13.70	13.55	13.94

WLAN 5.8 GHz Band Average Power (dBm)						
Mode/Band	a	ac 20	ac 40	ac 80	n 20	n 40
WLAN 5.8GHz	14.48	14.28	14.26	13.79	14.30	14.08

Bluetooth Average Power (dBm)							
Mode/Band	1 Mbps (GFSK)	2 Mbps ($\pi/4$ DQPSK)	3 Mbps (8DPSK)	BLE PHY 1M	BLE PHY 2M	BLE Coded PHY S=2	BLE Coded PHY S=8
Bluetooth	7.72	7.29	7.46	-2.71	-2.82	-2.79	-2.78

NFC Band Average Power (dBm)	
Mode/Band	ASK
NFC	-43.81

5.4 Environment of Test Site

Temperature:	18°C ~25 °C
Humidity:	35%~75% RH
Atmospheric Pressure:	1010 mbar

5.5 Test Sample Plan

Sample Number	Used for Test Items
2#	SAR
<i>Remark: JianYan Testing Group Shenzhen Co., Ltd. is only responsible for the test project data of the above samples, and will keep the above samples for a month.</i>	

5.6 Test Location

JianYan Testing Group Shenzhen Co., Ltd.
No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community,Xinqiao Street,
Bao'an District, Shenzhen, Guangdong, People's Republic of China.
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info-JYTee@lets.com, Website: <http://jyt.lets.com>

6 Introduction

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength. However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

7 RF Exposure Limits

7.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

7.3 RF Exposure Limits

SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
SPATIAL PEAK SAR Brain	1.6	8.0
SPATIAL AVERAGE SAR Whole Body	0.08	0.4
SPATIAL PEAK SAR Hands, Feet, Ankles, Wrists	4.0	20

Note:

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

8 SAR Measurement System




Fig. 8.1 MVG COMOSAR System Configurations

These measurements were performed with the automated near-field scanning system COMOSAR from MVG. The system is based on a high precision robot (working range: 850 mm), which positions the probes with a positional repeatability of better than ± 0.02 mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit.

The SAR measurements were conducted with dosimetric probe (manufactured by MVG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure described in SAR standard with accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated with the procedure described in SAR standard and found to be better than ± 0.25 dB. The phantom used was the SAM Phantom as described in FCC supplement C, IEEE P1528.

The MVG COMOSAR system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

8.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by MVG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.


➤ E-Field Probe Specification

Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Model	SSE2
Frequency Range	150 MHz to 6 GHz
Dynamic Range	0.01W/kg to 100W/kg
Probe linearity	<0.25dB
Dimensions	Overall length: 330 mm Tip diameter: 2.5 mm Distance between dipoles / probe extremity: 1 mm

Fig. 8.2 Photo of E-Field Probe

➤ E-Field Probe Calibration

Probe calibration is realized, in compliance with EN/IEC 62209-1/-2 and IEEE 1528 std, with CALISAR, MVG proprietary calibration system. The calibration is performed with the technique using reference waveguide.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\sigma} \cos^2 \left(\pi \frac{y}{a} \right) e^{-(2\pi/\sigma)z}$$

Where :

- P_{fw} = Forward Power
- P_{bw} = Backward Power
- a and b = Waveguide Dimensions
- σ = Skin Depth

Keithley configuration

Rate=Medium; Filter=ON; RDGS=10; FILTER TYPE=MOVING AVERAGE; RANGE AUTO

After each calibration, a SAR measurement performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

The Calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N) = SAR(N)/V_{lin}(N) \quad (N=1,2,3)$$

The linearized output voltage V_{lin}(N) is obtained from the displayed output voltage V(N) using

$$V_{lin}(N) = V(N) * (1 + V(N)/DCP(N)) \quad N=1,2,3$$

Where the DCP is the dipole compression point in mV

8.2 Robot

The COMOSAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA-KRC2sr) from KUKA is used. The KUKA robot series have many features that are important for our application:

- High precision (repeatability 0.02 mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)



Fig. 8.4 Photo of Robot

8.3 Phantom

<SAM Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 27 liters	
Dimensions	Length: 1000mm; Width: 500mm; Height: 200mm	
Material	Fiberglass based	
Relative permittivity	3-4	
Loss tangent	0.02	
Measurement Areas	Left Head, Right Head, Flat phantom	

Fig. 8.7 Photo of SAM Phantom

The phantom developed by MVG is produced in accordance with the specified in the standards. It has been designed to fit the COMOSAR phantom tables and is delivered with a plastic cover to prevent liquid evaporation.

8.4 Device Holder

The positioning system is made of an extremely stable material, which ensures easy handling and reproducible positioning. It also allows correct positioning of the dipoles referenced by the IEEE, ANSI and IEC.

<Device Holder for SAM Phantom>

Model	Handset Positioning System	
Material properties	The positioning system is made of PETP. This material offers a low permittivity of 3.2 and low loss, with a loss tangent of 0.005 to minimize the influence of the DUT on measurement results.	
Mechanical properties	The positioning system developed by MVG allows a positioning resolution better than 1 mm. The system is fixed on a bottom rail “x axis” so that the positioning system can be quickly moved from the right to the left part of the phantom. In addition, it can be moved on a perpendicular “y axis” and the height can be adapted. The system is also composed of three rotation points for accurate positioning of the device's acoustical output.	
Accuracy and precision	A curved rail on the top part allows the fast switch from the cheek to the tilt position. The required 15° angle for the tilt position can be easily checked thanks to a printed scale on the curved rail with a tolerance of ± 1°	

Fig. 8.9 Photo of Device Holder

8.5 Test Equipment List

Manufacturer	Equipment Description	Model	Management Number	Cal. Information	
				Last Cal.	Due Date
MVG	COMOSAR DOSIMETRIC E FIELD PROBE	SSE2	WXJ076	06.30.2022	06.29.2023
MVG	COMOSAR 750 MHz REFERENCE DIPOLE	SID750	WXJ076-4	01.14.2021	01.13.2024
MVG	COMOSAR 835 MHz REFERENCE DIPOLE	SID835	WXJ076-5	01.14.2021	01.13.2024
MVG	COMOSAR 1750 MHz REFERENCE DIPOLE	SID1750	WXJ076-8	01.14.2021	01.13.2024
MVG	COMOSAR 1900 MHz REFERENCE DIPOLE	SID1900	WXJ076-9	01.14.2021	01.13.2024
MVG	COMOSAR 2450 MHz REFERENCE DIPOLE	SID2450	WXJ076-12	01.14.2021	01.13.2024
MVG	COMOSAR 2600 MHz REFERENCE DIPOLE	SID2600	WXJ076-13	01.14.2021	01.13.2024
MVG	COMOSAR 5200-5800 MHz REFERENCE DIPOLE	SID5000	WXJ076-21	01.14.2021	01.13.2024
KEITHLEY	DIGIT MULTIMETER	DMM6500	WXJ076-1	10.17.2022	10.16.2025
MVG	MVG Measurement Software	OpenSAR	Version: V5_01_09	N.C.R	N.C.R
MVG	COMOSAR IEEE SAM PHANTOM	N/A	WXG009-2	N.C.R	N.C.R
MVG	COMOSAR IEEE SAM PHANTOM	N/A	WXG009-3	N.C.R	N.C.R
MVG	MOBILE PHONE POSITIONNING SYSTEM	N/A	WXG009-4	N.C.R	N.C.R
KUKA	Robot	KR 6 R900 sixx	WXG009-1	N.C.R	N.C.R
Anritsu	Universal Radio Communication Analyzer	MT8820C	WXJ008-5	03.03.2021	03.02.2023
R&S	Universal Radio Communication Tester	CMU200	WXJ008-2	03.30.2022	03.29.2024
KEYSIGHT	Network Analyzer	E5071C	WXJ091	03.30.2022	03.29.2023
KEYSIGHT	EPM Series Power Meter	N1914A	WXJ075	06.29.2022	06.28.2023
KEYSIGHT	E-Series Power Sensor	E9300H	WXJ075-1	06.29.2022	06.28.2023
KEYSIGHT	E-Series Power Sensor	E9300H	WXJ075-2	06.29.2022	06.28.2023
KEYSIGHT	Signal Generator	N5173B	WXJ006-3	06.29.2022	06.28.2023
Huber Suhner	RF Cable	SUCOFLEX	WXG008-13	See Note 3	
Huber Suhner	RF Cable	SUCOFLEX	WXG008-14	See Note 3	
Huber Suhner	RF Cable	SUCOFLEX	WXG008-15	See Note 3	
Weinschel	Attenuator	23-3-34	WXG008-16	See Note 3	
Anritsu	Directional Coupler	MP654A	WXG008-17	See Note 3	
MVG	LIMESAR DIELECTRIC PROBE	SCLMP	WXG009-5	See Note 4	
TXC	Broadband Amplifier	BBA018000	WXG008-11	See Note 5	

Note:

- The calibration certificate of MVG can be referred to appendix C of this report.
- Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
- The Insertion Loss calibration of Dual Directional Coupler and Attenuator were characterized via the network analyzer and compensated during system check.
- The dielectric probe kit was calibrated via the network analyzer, with the specified procedure (calibrated in pure water) and calibration kit (standard) short circuit, before the dielectric measurement. The specific procedure and calibration kit are provided by MVG.
- In system check we need to monitor the level on the spectrum analyzer, and adjust the power amplifier level to have precise power level to the dipole; the measured SAR will be normalized to 1 W input power according to the ratio of 1 W to the input power to the dipole. For system check, the calibration of the power amplifier is deemed not critically required for correct measurement; the spectrum analyzer is critical and we do have calibration for it
- Attenuator insertion loss is calibrated by the network Analyzer, which the calibration is valid, before system check.
- N.C.R means No Calibration Requirement.

9 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 9.1, for body SAR testing, the liquid height from the center of the flat phantom to liquid top surface is larger than 15 cm, which is shown in Fig. 9.2.



Fig. 9.1 Photo of Liquid Height for Head SAR
(depth>15cm)



Fig. 9.2 Photo of Liquid Height for Body SAR
(depth>15cm)

The relative permittivity and conductivity of the tissue material should be within $\pm 5\%$ of the values given in the table below recommended by the FCC OET 65 supplement C and RSS 102 Issue 5.

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

(ϵ_r = relative permittivity, σ = conductivity and ρ = 1000 kg/m

The dielectric parameters of liquids were verified prior to the SAR evaluation using a MVG Liquid measurement Kit and an Agilent Network Analyser.

The following table shows the measuring results for simulating liquid.

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target(σ)	Permittivity Target(ϵ_r)	Delta (σ)%	Delta (ϵ_r)%	Limit (%)	Date (mm/dd/yy)
750	22.8	0.90	42.53	0.89	41.90	1.12	1.50	±5	12.02.2022
835	22.8	0.92	42.33	0.90	41.50	2.22	2.00	±5	12.02.2022
1750	22.4	1.35	39.66	1.37	40.10	-1.46	-1.10	±5	12.06.2022
1900	22.4	1.39	39.70	1.40	40.00	-0.71	-0.75	±5	12.06.2022
2450	22.5	1.82	39.88	1.80	39.20	1.11	1.73	±5	12.10.2022
2600	22.5	1.97	39.55	1.96	39.00	0.51	1.41	±5	12.10.2022
5200	22.7	4.62	35.89	4.66	36.00	-0.86	-0.31	±5	12.12.2022
5800	22.7	5.19	34.78	5.27	35.30	-1.52	-1.47	±5	12.12.2022

10 SAR System Verification

Each ComoSAR system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the OpenSAR software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

➤ Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

➤ System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig.10.1 System Verification Setup Diagram




Fig.10.2 Photo of Dipole setup



➤ System Verification Results

Comparing to the original SAR value provided by MVG, the verification data should be within its specification of 10%. The table as below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix C of this report.

Date (mm/dd/yy)	Frequency (MHz)	Power fed onto dipole (mW)	Measured 1g SAR (W/kg)	Normalized to 1W 1g SAR (W/kg)	1W Target 1g SAR (W/kg)	Deviation (%)
12.02.2022	750	100	0.869	8.69	8.57	1.40
12.02.2022	835	100	0.966	9.66	9.57	0.94
12.06.2022	1750	100	3.590	35.90	36.5	-1.64
12.06.2022	1900	100	3.942	39.42	39.6	-0.45
12.10.2022	2450	40	2.137	53.43	52.92	0.95
12.10.2022	2600	40	2.250	56.25	55.47	1.41
12.12.2022	5200	40	3.068	76.70	76.67	0.04
12.12.2022	5800	40	3.120	78.00	78.36	-0.46

11 EUT Testing Position

This EUT was tested in nine different positions. They are right cheek/right tilted/left cheek/left tilted for head, Front/Back/ Left /Right /Top of the EUT with phantom 10 mm gap, as illustrated below, please refer to Appendix B for the test setup photos.

11.1 Handset Reference Points

- The vertical centreline passes through two points on the front side of the handset – the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- The horizontal line is perpendicular to the vertical centreline and passes the center of the acoustic output. The horizontal line is also tangential to the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centreline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Fig.11.1 Illustration for Front, Back and Side of SAM Phantom




Fig. 11.2 Illustration for Handset Vertical and Horizontal Reference Lines

11.2 Positioning for Cheek / Touch

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see below figure)



Fig. 11.3 Illustration for Cheek Position

11.3 Positioning for Ear / 15° Tilt

- To position the device in the “cheek” position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see figure below).



Fig.11.4 Illustration for Tilted Position

11.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR locations identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

11.5 Body Worn Accessory Configurations

- To position the device parallel to the phantom surface with either keypad up or down.
- To adjust the device parallel to the flat phantom.
- To adjust the distance between the device surface and the flat phantom to 10 mm or holster surface and the flat phantom to 0 mm.




Fig.11.5 Illustration for Body Worn Position

11.6 Wireless Router (Hotspot) Configurations

Some battery-operated handsets have the capability to transmit and receive internet connectivity through simultaneous transmission of WIFI in conjunction with a separate licensed transmitter. The FCC has provided guidance in KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. Therefore, SAR must be evaluated for each frequency transmission and mode separately and summed with the WIFI transmitter according to KDB 648474 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.




Fig.11.6 Illustration for Hotspot Position

12 Measurement Procedures

The measurement procedures are as below:

<Conducted power measurement>

- For WWAN power measurement, use base station simulator to configure EUT WWAN transition in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- Read the WWAN RF power level from the base station simulator.
- For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- Connect EUT RF port through RF cable to the power meter or spectrum analyzer, and measure WLAN/BT output power.

<Conducted power measurement>

- Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- Place the EUT in positions as Appendix B demonstrates.
- Set scan area, grid size and other setting on the OpenSAR software.
- Measure SAR results for the highest power channel on each testing position.
- Find out the largest SAR result on these testing positions of each band.
- Measure SAR results for other channels in worst SAR testing position if the Reported SAR or highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

12.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The OpenSAR software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a “cube” measurement. The measured volume must include the 1g and 10 g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- Extraction of the measured data (grid and values) from the Zoom Scan.
- Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters).
- Generation of a high-resolution mesh within the measured volume.
- Interpolation of all measured values from the measurement grid to the high-resolution grid
- Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- Calculation of the averaged SAR within masses of 1g and 10g.

12.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

12.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <u>area scan based 1-g SAR estimation</u> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

12.4 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remains in the same test position for all measurements and all volume scans use the same spatial resolution and grid spacing. When all volume scans are completed, the software can combine and subsequently superpose these measurement data to calculate the multiband SAR.

12.5 SAR Averaged Methods

In the COMOSAR system, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method, which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1g and 10g cubes, the extrapolation distance should not be larger than 5 mm.

12.6 Power Drift Monitoring

All SAR testing is under the EUT with a full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. If the power drifts more than 5%, the SAR will be retested.

13 Conducted RF Output Power

13.1 GSM Conducted Power

Band: GSM 850	Burst Average Power (dBm)			Frame-Average Power(dBm)		
Channel	128	190	251	128	190	251
Frequency (MHz)	824.2	836.6	848.8	824.2	836.6	848.8
GSM (GMSK, Voice)	33.96	33.98	33.76	24.93	24.95	24.73
GPRS (GMSK, 1 TX slot)	33.99	34.02	33.80	24.96	24.99	24.77
GPRS (GMSK, 2 TX slots)	33.02	33.03	32.82	27.00	27.01	26.80
GPRS (GMSK, 3 TX slots)	31.04	31.06	30.84	26.78	26.80	26.58
GPRS (GMSK, 4 TX slots)	29.99	29.97	29.77	26.98	26.96	26.76
EGPRS (8PSK, 1 TX slot)	28.30	28.20	28.14	19.27	19.17	19.11
EGPRS (8PSK, 2 TX slots)	27.16	27.07	27.02	21.14	21.05	21.00
EGPRS (8PSK, 3 TX slots)	24.83	24.85	24.82	20.57	20.59	20.56
EGPRS (8PSK, 4 TX slots)	23.63	23.53	23.46	20.62	20.52	20.45

Remark:

- The frame-averaged power is linearly reported the maximum burst averaged power over 8 time slots. The calculated method are shown as below:
The duty cycle "x" of different time slots as below:
1 TX slot is 1/8, 2 TX slots is 2/8, 3 TX slots is 3/8 and 4 TX slots is 4/8
Based on the calculation formula:
Frame-averaged power = Burst averaged power + 10 log (x)
So,
Frame-averaged power (1 TX slot) = Burst averaged power (1 TX slot)– 9.03
Frame-averaged power (2 TX slots) = Burst averaged power (2 TX slots)– 6.02
Frame-averaged power (3 TX slots) = Burst averaged power (3 TX slots)– 4.26
Frame-averaged power (4 TX slots) = Burst averaged power (4 TX slots) – 3.01
- CS1 coding scheme was used in GPRS conducted power measurements and SAR testing, MCS5 coding scheme was used in EGPRS conducted power measurements and SAR testing (if necessary).

Note:

- For Head SAR testing, GSM Voice mode should be evaluated, therefore the EUT was set in GSM 850 Voice mode.
- For Body worn SAR testing, GSM Voice, GPRS and EGPRS mode should be evaluated, therefore the EUT was set in GPRS 2 TX slots mode due to the highest frame-averaged power..
- For Hotspot mode SAR testing, GPRS and EGPRS mode should be evaluated, therefore the EUT was set in GPRS 2 TX slots mode due to the highest frame-averaged power.
- For GPRS multi time slots SAR measurement, when the measured maximum output power levels are within 0.25 dB of each other, test the configuration with the most number of time slots.
- Per KDB447498 D04v01, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- The EUT do not support DTM and VoIP function.

Band: PCS 1900	Burst Average Power (dBm)			Frame-Average Power(dBm)		
Channel	512	661	810	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8	1850.2	1880.0	1909.8
GSM (GMSK, Voice)	30.82	31.07	30.70	21.79	22.04	21.67
GPRS (GMSK, 1 TX slot)	30.80	31.02	30.65	21.77	21.99	21.62
GPRS (GMSK, 2 TX slots)	29.83	30.07	29.70	23.81	24.05	23.68
GPRS (GMSK, 3 TX slots)	27.83	28.06	27.73	23.57	23.80	23.47
GPRS (GMSK, 4 TX slots)	26.71	27.01	26.67	23.70	24.00	23.66
EGPRS (8PSK, 1 TX slot)	27.05	26.76	26.72	18.02	17.73	17.69
EGPRS (8PSK, 2 TX slots)	26.10	25.71	25.76	20.08	19.69	19.74
EGPRS (8PSK, 3 TX slots)	24.06	23.82	23.84	19.80	19.56	19.58
EGPRS (8PSK, 4 TX slots)	23.06	22.80	22.84	20.05	19.79	19.83

Remark:

3. The frame-averaged power is linearly reported the maximum burst averaged power over 8 time slots. The calculated method are shown as below:
The duty cycle "x" of different time slots as below:
1 TX slot is 1/8, 2 TX slots is 2/8, 3 TX slots is 3/8 and 4 TX slots is 4/8
Based on the calculation formula:
Frame-averaged power = Burst averaged power + 10 log (x)
So,
Frame-averaged power (1 TX slot) = Burst averaged power (1 TX slot)– 9.03
Frame-averaged power (2 TX slots) = Burst averaged power (2 TX slots)– 6.02
Frame-averaged power (3 TX slots) = Burst averaged power (3 TX slots)– 4.26
Frame-averaged power (4 TX slots) = Burst averaged power (4 TX slots) – 3.01
4. CS1 coding scheme was used in GPRS conducted power measurements and SAR testing, MCS5 coding scheme was used in EGPRS conducted power measurements and SAR testing (if necessary).

Note:

7. For Head SAR testing, GSM Voice mode should be evaluated, therefore the EUT was set in GSM 1900 Voice mode.
8. For Body worn SAR testing, GSM Voice, GPRS and EGPRS mode should be evaluated, therefore the EUT was set in GPRS 2 TX slots mode due to the highest frame-averaged power..
9. For Hotspot mode SAR testing, GPRS and EGPRS mode should be evaluated, therefore the EUT was set in GPRS 2 TX slots mode due to the highest frame-averaged power.
10. For GPRS multi time slots SAR measurement, when the measured maximum output power levels are within 0.25 dB of each other, test the configuration with the most number of time slots.
11. Per KDB447498 D04v01, the maximum output power channel is used for SAR testing and for further SAR test reduction.
12. The EUT do not support DTM and VoIP function.

13.2 WCDMA Conducted Power

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Rohde & Schwarz CMU200 referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table 1

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	CM (dB) ⁽²⁾
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15 ⁽³⁾	15/15 ⁽³⁾	64	12/15 ⁽³⁾	24/15	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5
Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$ Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. Note 3: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.						

HSDPA Sub-test setup configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Rohde & Schwarz CMU200 referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table 2

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

HSUPA Sub-test setup configuration

WCDMA Conducted Power:

WCDMA Average power (dBm)			
Band	WCDMA Band V		
Channel	4132	4183	4233
Frequency (MHz)	826.4	836.6	846.6
AMR 12.2 kbps	23.93	23.95	23.80
RMC 12.2 kbps	23.86	23.94	23.87
HSDPA Sub-test 1	22.91	22.90	22.90
HSDPA Sub-test 2	22.39	22.37	22.38
HSDPA Sub-test 3	22.40	22.39	22.37
HSDPA Sub-test 4	22.38	22.42	22.36
HSUPA Sub-test 1	20.97	20.98	20.94
HSUPA Sub-test 2	21.37	21.36	21.32
HSUPA Sub-test 3	21.86	21.89	21.82
HSUPA Sub-test 4	21.01	21.00	20.96
HSUPA Sub-test 5	22.96	22.95	22.92

WCDMA Average power (dBm)			
Band	WCDMA Band IV		
Channel	1312	1413	1513
Frequency (MHz)	1712.4	1732.6	1752.6
AMR 12.2 kbps	23.64	23.71	23.69
RMC 12.2 kbps	23.72	23.76	23.76
HSDPA Sub-test 1	22.77	22.76	22.77
HSDPA Sub-test 2	22.25	22.23	22.24
HSDPA Sub-test 3	22.27	22.22	22.25
HSDPA Sub-test 4	22.21	22.21	22.25
HSUPA Sub-test 1	20.81	20.77	20.81
HSUPA Sub-test 2	21.25	21.21	21.27
HSUPA Sub-test 3	21.75	21.73	21.75
HSUPA Sub-test 4	20.82	20.79	20.78
HSUPA Sub-test 5	22.78	22.75	22.80

WCDMA Average power (dBm)			
Band	WCDMA Band II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
AMR 12.2 kbps	23.92	23.89	23.87
RMC 12.2 kbps	23.88	23.83	23.96
HSDPA Sub-test 1	22.95	22.96	22.96
HSDPA Sub-test 2	22.40	22.42	22.48
HSDPA Sub-test 3	22.43	22.43	22.43
HSDPA Sub-test 4	22.38	22.44	22.46
HSUPA Sub-test 1	20.92	20.92	20.94
HSUPA Sub-test 2	21.40	21.39	21.40
HSUPA Sub-test 3	21.93	21.90	21.93
HSUPA Sub-test 4	20.92	20.94	20.94
HSUPA Sub-test 5	22.94	22.89	22.95

Note:

- Applying the subtest setup in Table C.11.1.3 of 3GPP TS 34.121-1
- Per KDB 941225 D01, RMC 12.2kbps mode is used to evaluate SAR due the highest output power. If AMR 12.2 kbps power is < 0.25dB higher than RMC 12.2kbps, SAR tests with AMR 12.2 kbps can be excluded.
- AMR, HSDPA RF power will not be larger than RMC 12.2kbps, detailed information is included in Tune-up Procure exhibit.

13.3 LTE Conducted Power

13.3.1 Largest channel bandwidth standalone SAR test requirements

QPSK with 1 RB allocation

Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel.⁸ When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

QPSK with 50% RB allocation

The procedures required for 1 RB allocation in section 4.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.⁹

QPSK with 100% RB allocation

For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in sections 4.2.1 and 4.2.2 are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

Higher order modulations

For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in sections 4.2.1, 5.2.2 and 4.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

13.3.2 Other channel bandwidth standalone SAR test requirements

For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section 4.2 to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg. The equivalent channel configuration for the RB allocation, RB offset and modulation etc. is determined for the smaller channel bandwidth according to the same number of RB allocated in the largest channel bandwidth. For example, 50 RB in 10 MHz channel bandwidth does not apply to 5 MHz channel bandwidth; therefore, this cannot be tested in the smaller channel bandwidth. However, 50% RB allocation in 10 MHz channel bandwidth is equivalent to 100% RB allocation in 5 MHz channel bandwidth; therefore, these are the equivalent configurations to be compared to determine the specific channel and configuration in the smaller channel bandwidth that need SAR testing.

13.3.3 TDD LTE configuration setup for SAR measurement

According to KDB 941225 D05v02r03 and April 2013 TCB workshop slides, SAR must be tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- see 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- “special subframe S” contains both uplink and downlink transmissions and must be taken into consideration to determine the transmission duty factor
 - according to the worst case uplink and downlink cyclic prefix requirements for UpPTS to determine the highest SAR test duty factor




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity)

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS)

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$			$7680 \cdot T_s$		
5	$6592 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$20480 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Per 3GPP 36.211 section 4.2, each radio frame of length $T_F=37200 \cdot T_s = 10$ ms consists of two half-frames of length $153600 \cdot T_s = 5$ ms each. Each half-frame consists of five subframes of length $30720 \cdot T_s = 1$ ms. So, the uplink duty factor in special subframe as below:

Special Subframe configuration	Normal cyclic prefix in downlink		Extended cyclic prefix in downlink	
	Duty factor of Uplink		Duty factor of Uplink	
	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	7.14%	8.33%	7.14%	8.33%
1	7.14%	8.33%	7.14%	8.33%
2	7.14%	8.33%	7.14%	8.33%
3	7.14%	8.33%	7.14%	8.33%
4	7.14%	8.33%	14.27%	16.67%
5	14.27%	16.67%	14.27%	16.67%
6	14.27%	16.67%	14.27%	16.67%
7	14.27%	16.67%	14.27%	16.67%
8	14.27%	16.67%	/	/
9	14.27%	16.67%	/	/

Table 4.2-2: Uplink-downlink configurations

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

According to above table:

1. The highest duty factor is configuration 0;
2. The duty factor of uplink in one half-frame with normal cyclic prefix is: $(3\text{ms} + 0.143\text{ms})/5\text{ms}=62.86\%$;
3. The duty factor of uplink in one half-frame with extended cyclic prefix is: $(3\text{ms} + 0.167\text{ms})/5\text{ms}=63.34\%$;
4. For purpose to get the worst case SAR test duty factor, the duty factor of normal cyclic prefix in uplink scaled-up to the extended cyclic prefix in uplink, the scaling factor is $63.34\%/62.86\%=1.008$, and the scaling factor will be taken into the final measured SAR.

LTE Band 2 part:

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					18607	18900	19193
					1850.7MHz	1880.0MHz	1909.3MHz
Band 2	1.4	QPSK	1	0	23.57	23.57	23.53
			1	2	23.72	23.78	23.73
			1	5	23.56	23.56	23.58
			3	0	23.69	23.66	23.66
			3	1	23.67	23.65	23.67
			3	2	23.72	23.63	23.70
			6	0	22.68	22.60	22.58
		16QAM	1	0	22.48	22.39	22.31
			1	2	22.67	22.60	22.54
			1	5	22.47	22.41	22.29
			3	0	22.48	22.46	22.43
			3	1	22.48	22.44	22.41
			3	2	22.49	22.42	22.41
			6	0	21.67	21.44	21.58
		64QAM	1	0	21.54	21.40	21.55
			1	2	21.92	21.60	21.63
			1	5	21.82	21.42	21.48
			3	0	21.52	21.33	21.43
			3	1	21.52	21.35	21.39
			3	2	21.52	21.34	21.42
			6	0	20.30	20.32	20.22

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					18615	18900	19185
					1851.5MHz	1880.0MHz	1908.5MHz
Band 2	3	QPSK	1	0	23.66	23.62	23.60
			1	7	23.69	23.62	23.69
			1	14	23.66	23.60	23.69
			8	0	22.61	22.61	22.60
			8	4	22.61	22.52	22.59
			8	7	22.60	22.54	22.58
			15	0	22.55	22.48	22.56
		16QAM	1	0	22.51	22.34	22.46
			1	7	22.44	22.35	22.48
			1	14	22.47	22.41	22.46
			8	0	21.64	21.60	21.60
			8	4	21.61	21.58	21.58
			8	7	21.60	21.56	21.55
			15	0	21.52	21.45	21.47
		64QAM	1	0	21.45	21.47	21.58
			1	7	21.45	21.47	21.59
			1	14	21.44	21.49	21.61
			8	0	20.46	20.53	20.32
			8	4	20.47	20.48	20.29
			8	7	20.49	20.45	20.27
			15	0	20.55	20.37	20.22

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					18625	18900	19175
					1852.5MHz	1880.0MHz	1907.5MHz
Band 2	5	QPSK	1	0	23.56	23.60	23.51
			1	12	23.72	23.71	23.61
			1	24	23.58	23.57	23.58
			12	0	22.58	22.56	22.67
			12	6	22.57	22.60	22.65
			12	11	22.63	22.61	22.64
			25	0	22.66	22.58	22.62
		16QAM	1	0	22.42	22.49	22.61
			1	12	22.58	22.60	22.71
			1	24	22.44	22.52	22.65
			12	0	21.56	21.55	21.74
			12	6	21.59	21.57	21.67
			12	11	21.62	21.51	21.69
			25	0	21.59	21.59	21.54
		64QAM	1	0	21.37	22.01	21.57
			1	12	21.46	22.09	21.72
			1	24	21.30	22.28	21.55
			12	0	20.44	20.51	20.40
			12	6	20.44	20.46	20.37
			12	11	20.45	20.47	20.37
			25	0	20.49	20.42	20.29

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					18650	18900	19150
					1855.0MHz	1880.0MHz	1905.0MHz
Band 2	10	QPSK	1	0	23.69	23.62	23.56
			1	24	23.75	23.67	23.67
			1	49	23.60	23.62	23.61
			25	0	22.55	22.63	22.61
			25	12	22.56	22.65	22.62
			25	24	22.60	22.65	22.60
			50	0	22.63	22.61	22.55
		16QAM	1	0	22.52	22.35	22.49
			1	24	22.60	22.51	22.62
			1	49	22.47	22.36	22.59
			25	0	21.65	21.72	21.58
			25	12	21.65	21.70	21.56
			25	24	21.63	21.73	21.58
			50	0	21.65	21.66	21.55
		64QAM	1	0	21.38	21.49	21.58
			1	24	21.53	21.62	21.62
			1	49	21.40	21.41	21.59
			25	0	20.40	20.54	20.36
			25	12	20.45	20.49	20.34
			25	24	20.39	20.51	20.36
			50	0	20.41	20.40	20.23

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					18675	18900	19125
					1857.5MHz	1880.0MHz	1902.5MHz
Band 2	15	QPSK	1	0	23.57	23.57	23.48
			1	37	23.65	23.64	23.60
			1	74	23.30	23.43	23.59
			36	0	22.58	22.66	22.65
			36	16	22.61	22.65	22.65
			36	35	22.58	22.67	22.63
			75	0	22.65	22.64	22.58
		16QAM	1	0	22.52	22.50	22.26
			1	37	22.62	22.59	22.37
			1	74	22.54	22.45	22.32
			36	0	21.58	21.61	21.61
			36	16	21.54	21.65	21.59
			36	35	21.56	21.66	21.57
			75	0	21.62	21.60	21.58
		64QAM	1	0	21.44	21.70	21.53
			1	37	21.48	21.83	21.60
			1	74	21.27	21.61	21.53
			36	0	20.43	20.58	20.34
			36	16	20.44	20.50	20.38
			36	35	20.51	20.49	20.31
			75	0	20.46	20.54	20.27

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					18700	18900	19100
					1860.0MHz	1880.0MHz	1900.0MHz
Band 2	20	QPSK	1	0	23.42	23.45	23.29
			1	49	23.80	23.70	23.65
			1	99	23.39	23.41	23.41
			50	0	22.47	22.76	22.55
			50	24	22.46	22.73	22.54
			50	49	22.47	22.71	22.60
			100	0	22.54	22.63	22.52
		16QAM	1	0	22.30	22.53	22.09
			1	49	22.62	22.84	22.53
			1	99	22.29	22.49	22.23
			50	0	21.47	21.81	21.66
			50	24	21.46	21.78	21.60
			50	49	21.44	21.79	21.62
			100	0	21.56	21.63	21.54
		64QAM	1	0	21.61	21.59	21.10
			1	49	22.06	21.90	21.42
			1	99	21.65	21.53	21.07
			50	0	20.40	20.66	20.33
			50	24	20.37	20.69	20.43
			50	49	20.44	20.64	20.37
			100	0	20.44	20.53	20.29

LTE Band 5 part:

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20407	20525	20643
					824.7MHz	836.5MHz	848.3MHz
Band 5	1.4	QPSK	1	0	23.93	23.91	23.84
			1	2	24.15	24.08	23.97
			1	5	23.96	23.90	23.84
			3	0	24.03	24.02	23.88
			3	1	24.06	24.01	23.86
			3	2	24.02	24.00	23.86
			6	0	23.04	23.07	22.87
		16QAM	1	0	22.71	22.82	22.67
			1	2	22.89	22.98	22.73
			1	5	22.72	22.80	22.63
			3	0	22.81	22.77	22.70
			3	1	22.81	22.79	22.70
			3	2	22.81	22.78	22.70
			6	0	22.03	22.03	21.72
		64QAM	1	0	22.35	21.95	22.12
			1	2	22.49	22.04	22.20
			1	5	22.35	21.94	22.06
			3	0	22.04	21.84	21.98
			3	1	22.07	21.85	22.00
			3	2	22.08	21.84	22.00
			6	0	20.91	20.85	20.88

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20415	20525	20635
					825.5MHz	836.5MHz	847.5MHz
Band 5	3	QPSK	1	0	23.87	24.05	23.87
			1	7	23.90	24.03	23.83
			1	14	23.96	23.98	23.77
			8	0	22.91	22.96	22.87
			8	4	22.95	22.95	22.83
			8	7	22.95	22.94	22.84
			15	0	22.91	22.90	22.82
		16QAM	1	0	22.96	22.85	22.61
			1	7	22.95	22.78	22.66
			1	14	22.91	22.79	22.61
			8	0	21.98	21.97	21.89
			8	4	21.94	21.97	21.88
			8	7	21.94	21.94	21.83
			15	0	21.86	21.89	21.72
		64QAM	1	0	21.95	22.05	22.19
			1	7	22.01	21.98	22.15
			1	14	22.01	22.01	22.14
			8	0	20.99	21.00	20.85
			8	4	21.02	21.01	20.85
			8	7	20.98	20.97	20.86
			15	0	21.05	20.93	20.78

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20425	20525	20625
					826.5MHz	836.5MHz	846.5MHz
Band 5	5	QPSK	1	0	23.89	23.91	23.85
			1	12	24.07	23.97	23.91
			1	24	23.95	23.89	23.79
			12	0	22.95	22.94	22.88
			12	6	22.90	22.95	22.92
			12	11	22.93	22.97	22.93
			25	0	22.93	22.98	22.87
		16QAM	1	0	22.83	22.94	22.74
			1	12	22.94	23.00	22.79
			1	24	22.83	22.86	22.69
			12	0	21.90	21.94	21.92
			12	6	21.88	21.98	21.91
			12	11	21.91	22.00	21.95
			25	0	21.92	21.97	21.93
		64QAM	1	0	21.88	22.51	22.24
			1	12	22.00	22.52	22.30
			1	24	21.88	22.44	22.14
			12	0	21.03	21.03	21.02
			12	6	21.03	21.01	21.01
			12	11	21.00	20.95	21.05
			25	0	20.98	20.97	20.96

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20450	20525	20600
					829MHz	836.5MHz	844MHz
Band 5	10	QPSK	1	0	23.88	24.00	23.93
			1	24	24.06	24.17	23.92
			1	49	23.96	23.94	23.82
			25	0	23.06	23.04	23.05
			25	12	23.09	22.99	23.08
			25	24	23.07	23.01	23.04
			50	0	23.00	22.98	22.91
		16QAM	1	0	22.95	22.91	22.68
			1	24	23.13	22.97	22.67
			1	49	22.97	22.80	22.62
			25	0	22.01	22.04	22.10
			25	12	22.03	22.05	22.08
			25	24	22.01	22.06	22.07
			50	0	22.02	22.02	21.96
		64QAM	1	0	21.97	22.06	22.21
			1	24	22.05	22.08	22.35
			1	49	21.96	22.05	22.13
			25	0	21.06	20.96	21.08
			25	12	21.05	20.96	21.08
			25	24	21.07	20.97	21.08
			50	0	21.00	20.99	21.01

LTE Band 7 part:

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20775	21100	21425
					2502.5MHz	2535MHz	2567.5MHz
Band 7	5	QPSK	1	0	23.43	23.53	23.32
			1	12	23.55	23.58	23.44
			1	24	23.48	23.48	23.36
			12	0	22.58	22.63	22.48
			12	6	22.59	22.57	22.48
			12	11	22.57	22.61	22.50
			25	0	22.62	22.60	22.53
		16QAM	1	0	22.55	22.65	22.60
			1	12	22.63	22.66	22.71
			1	24	22.58	22.58	22.60
			12	0	21.51	21.62	21.57
			12	6	21.51	21.63	21.55
			12	11	21.58	21.61	21.53
			25	0	21.64	21.64	21.53
		64QAM	1	0	21.53	21.49	21.99
			1	12	21.63	21.53	22.14
			1	24	21.53	21.49	22.00
			12	0	20.59	20.69	20.57
			12	6	20.59	20.66	20.55
			12	11	20.60	20.64	20.50
			25	0	20.65	20.63	20.53

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20800	21100	21400
					2505MHz	2535MHz	2565MHz
Band 7	10	QPSK	1	0	23.47	23.49	23.44
			1	24	23.61	23.59	23.50
			1	49	23.48	23.51	23.39
			25	0	22.58	22.66	22.58
			25	12	22.61	22.68	22.60
			25	24	22.60	22.68	22.62
			50	0	22.63	22.68	22.58
		16QAM	1	0	22.73	22.80	22.43
			1	24	22.75	22.81	22.49
			1	49	22.78	22.77	22.36
			25	0	21.62	21.72	21.62
			25	12	21.63	21.74	21.65
			25	24	21.59	21.71	21.69
			50	0	21.62	21.75	21.60
		64QAM	1	0	21.56	21.64	21.78
			1	24	21.67	21.73	21.86
			1	49	21.61	21.62	21.77
			25	0	20.57	20.65	20.57
			25	12	20.55	20.64	20.55
			25	24	20.60	20.62	20.58
			50	0	20.65	20.69	20.56

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20825	21100	21375
					2507.5MHz	2535MHz	2562.5MHz
Band 7	15	QPSK	1	0	23.40	23.46	23.40
			1	37	23.51	23.53	23.41
			1	74	23.39	23.40	23.34
			36	0	22.62	22.62	22.62
			36	16	22.58	22.63	22.64
			36	35	22.61	22.66	22.66
			75	0	22.69	22.69	22.57
		16QAM	1	0	22.61	22.83	22.34
			1	37	22.70	22.90	22.49
			1	74	22.61	22.79	22.30
			36	0	21.56	21.64	21.49
			36	16	21.56	21.69	21.45
			36	35	21.52	21.68	21.51
			75	0	21.56	21.69	21.56
		64QAM	1	0	21.48	21.81	21.72
			1	37	21.61	21.90	21.80
			1	74	21.43	21.83	21.73
			36	0	20.60	20.66	20.52
			36	16	20.65	20.59	20.51
			36	35	20.55	20.59	20.53
			75	0	20.63	20.69	20.56

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					20850	21100	21350
					2510MHz	2535MHz	2560MHz
Band 7	20	QPSK	1	0	23.32	23.34	23.16
			1	49	23.70	23.68	23.38
			1	99	23.35	23.30	23.12
			50	0	22.52	22.58	22.57
			50	24	22.47	22.62	22.52
			50	49	22.49	22.60	22.54
			100	0	22.49	22.61	22.48
		16QAM	1	0	22.40	22.56	22.38
			1	49	22.79	22.94	22.60
			1	99	22.42	22.57	22.31
			50	0	21.50	21.64	21.62
			50	24	21.46	21.63	21.56
			50	49	21.48	21.62	21.64
			100	0	21.52	21.62	21.53
		64QAM	1	0	21.72	21.71	21.24
			1	49	22.13	22.05	21.62
			1	99	21.72	21.64	21.22
			50	0	20.49	20.63	20.62
			50	24	20.48	20.64	20.57
			50	49	20.53	20.62	20.60
			100	0	20.50	20.63	20.51

LTE Band 12 part:

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					23017	23095	23175
					699.7MHz	707.5MHz	715.3MHz
Band 12	1.4	QPSK	1	0	23.66	23.72	23.65
			1	12	23.73	23.81	23.73
			1	24	23.74	23.69	23.58
			12	0	23.80	23.85	23.78
			12	6	23.78	23.79	23.75
			12	11	23.78	23.79	23.77
			25	0	22.73	22.70	22.67
		16QAM	1	0	22.54	22.50	22.57
			1	12	22.70	22.60	22.79
			1	24	22.54	22.44	22.58
			12	0	22.63	22.55	22.55
			12	6	22.61	22.49	22.56
			12	11	22.62	22.58	22.56
			25	0	21.57	21.69	21.73
		64QAM	1	0	21.49	21.24	21.40
			1	12	21.62	21.36	21.55
			1	24	21.59	21.23	21.41
			12	0	21.26	21.19	21.35
			12	6	21.28	21.18	21.38
			12	11	21.28	21.16	21.39
			25	0	20.15	20.17	20.17

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					23025	23095	23165
					700.5MHz	707.5MHz	714.5MHz
Band 12	3	QPSK	1	0	23.79	23.80	23.78
			1	24	23.81	23.79	23.78
			1	49	23.84	23.76	23.77
			25	0	22.78	22.70	22.86
			25	12	22.80	22.71	22.84
			25	24	22.84	22.73	22.82
			50	0	22.83	22.80	22.82
		16QAM	1	0	22.78	22.71	22.55
			1	24	22.82	22.65	22.57
			1	49	22.81	22.62	22.55
			25	0	21.82	21.75	21.86
			25	12	21.86	21.75	21.79
			25	24	21.81	21.83	21.83
			50	0	21.85	21.67	21.72
		64QAM	1	0	21.17	21.34	21.50
			1	24	21.23	21.21	21.57
			1	49	21.24	21.25	21.51
			25	0	20.30	20.36	20.29
			25	12	20.33	20.31	20.27
			25	24	20.33	20.33	20.22
			50	0	20.41	20.27	20.19

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					23035	23095	23155
					701.5MHz	707.5MHz	713.5MHz
Band 12	5	QPSK	1	0	23.77	23.75	23.67
			1	37	23.95	23.81	23.85
			1	74	23.86	23.67	23.74
			36	0	22.90	22.73	22.81
			36	16	22.89	22.78	22.93
			36	35	22.89	22.79	22.90
			75	0	22.86	22.83	22.93
		16QAM	1	0	22.73	22.82	22.62
			1	37	22.88	22.81	22.76
			1	74	22.66	22.75	22.65
			36	0	21.88	21.77	21.86
			36	16	21.86	21.86	21.90
			36	35	21.87	21.79	21.90
			75	0	21.94	21.83	21.93
		64QAM	1	0	21.14	21.77	21.47
			1	37	21.28	21.87	21.57
			1	74	21.16	21.78	21.49
			36	0	20.42	20.32	20.44
			36	16	20.48	20.32	20.39
			36	35	20.46	20.31	20.46
			75	0	20.41	20.33	20.40

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					23060	23095	23130
					704MHz	707.5MHz	711MHz
Band 12	10	QPSK	1	0	23.77	23.92	23.79
			1	49	23.88	23.80	23.81
			1	99	23.82	23.85	23.82
			50	0	23.00	22.80	22.74
			50	24	22.98	22.85	22.77
			50	49	22.98	22.82	22.78
			100	0	22.99	22.80	22.73
		16QAM	1	0	22.81	22.69	22.51
			1	49	22.97	22.74	22.63
			1	99	22.79	22.73	22.57
			50	0	21.98	21.86	21.77
			50	24	21.99	21.91	21.78
			50	49	21.98	21.83	21.83
			100	0	21.99	21.84	21.86
		64QAM	1	0	21.17	21.20	21.48
			1	49	21.26	21.39	21.68
			1	99	21.20	21.27	21.51
			50	0	20.55	20.30	20.27
			50	24	20.54	20.33	20.28
			50	49	20.53	20.33	20.28
			100	0	20.50	20.33	20.23

LTE Band 41 part:

LTE Band	Band-width (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)				
					40065	40355	40640	40750	41215
					2537.5MHz	2566.5MHz	2595.0MHz	2624.0MHz	2652.5MHz
Band 41	5	QPSK	1	0	23.46	23.50	23.52	23.51	23.54
			1	12	23.68	23.69	23.62	23.66	23.69
			1	24	23.55	23.52	23.51	23.52	23.49
			12	0	22.76	22.74	22.69	22.72	22.72
			12	6	22.76	22.71	22.65	22.69	22.66
			12	11	22.75	22.72	22.73	22.72	22.69
			25	0	22.79	22.74	22.74	22.74	22.68
		16QAM	1	0	22.97	22.83	22.93	22.86	22.69
			1	12	23.15	22.98	23.05	23.00	22.80
			1	24	23.04	22.84	22.95	22.87	22.63
			12	0	21.78	21.75	21.67	21.72	21.71
			12	6	21.79	21.75	21.65	21.71	21.70
			12	11	21.83	21.77	21.63	21.72	21.70
			25	0	21.91	21.80	21.78	21.79	21.69
		64QAM	1	0	21.80	21.94	21.67	21.85	22.07
			1	12	21.96	22.09	21.78	21.98	22.21
			1	24	21.80	21.96	21.65	21.86	22.12
			12	0	20.38	20.55	20.36	20.49	20.72
			12	6	20.42	20.59	20.36	20.51	20.76
			12	11	20.43	20.59	20.35	20.51	20.75
			25	0	20.33	20.50	20.41	20.47	20.66

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)				
					40090	40365	40640	40915	41190
					2540.0MHz	2567.5MHz	2595.0MHz	2622.5MHz	2650.0MHz
Band 41	10	QPSK	1	0	23.67	23.63	23.65	23.63	23.58
			1	24	23.87	23.85	23.80	23.83	23.82
			1	49	23.65	23.61	23.58	23.60	23.56
			25	0	22.78	22.71	22.73	22.71	22.63
			25	12	22.77	22.72	22.73	22.72	22.67
			25	24	22.79	22.72	22.74	22.72	22.64
			50	0	22.82	22.76	22.68	22.73	22.69
		16QAM	1	0	23.01	22.65	22.91	22.73	22.28
			1	24	23.18	22.84	23.07	22.91	22.49
			1	49	22.96	22.60	22.81	22.67	22.23
			25	0	21.92	21.81	21.78	21.80	21.69
			25	12	21.92	21.81	21.78	21.80	21.69
			25	24	21.90	21.79	21.78	21.79	21.68
			50	0	22.00	21.85	21.73	21.81	21.70
		64QAM	1	0	21.28	21.42	21.80	21.54	21.55
			1	24	21.49	21.66	22.02	21.78	21.82
			1	49	21.29	21.46	21.78	21.57	21.63
			25	0	20.34	20.50	20.48	20.49	20.65
			25	12	20.32	20.49	20.44	20.47	20.66
			25	24	20.30	20.47	20.43	20.46	20.64
			50	0	20.41	20.56	20.48	20.53	20.70

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)				
					40115	40375	40640	40900	41165
					2542.5MHz	2568.5MHz	2595.0MHz	2673.5MHz	2647.5MHz
Band 41	15	QPSK	1	0	23.60	23.64	23.57	23.62	23.68
			1	37	23.69	23.72	23.72	23.72	23.74
			1	74	23.57	23.60	23.54	23.58	23.62
			36	0	22.66	22.68	22.71	22.69	22.69
			36	16	22.62	22.67	22.71	22.68	22.72
			36	35	22.64	22.69	22.73	22.70	22.73
			75	0	22.63	22.68	22.71	22.69	22.72
		16QAM	1	0	22.88	22.68	22.86	22.74	22.47
			1	37	23.00	22.73	22.92	22.79	22.46
			1	74	22.86	22.62	22.80	22.68	22.38
			36	0	21.75	21.74	21.70	21.72	21.72
			36	16	21.72	21.71	21.71	21.71	21.70
			36	35	21.72	21.72	21.70	21.71	21.72
			75	0	21.73	21.74	21.73	21.73	21.74
		64QAM	1	0	21.77	21.77	21.72	21.75	21.76
			1	37	21.80	21.88	21.87	21.87	21.95
			1	74	21.79	21.84	21.75	21.81	21.88
			36	0	20.38	20.54	20.40	20.49	20.70
			36	16	20.37	20.53	20.43	20.49	20.68
			36	35	20.39	20.54	20.37	20.48	20.69
			75	0	20.42	20.56	20.42	20.51	20.70

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)				
					40140	40390	40640	40890	41140
					2545.0MHz	2570.0MHz	2595.0MHz	2620.0MHz	2645.0MHz
Band 41	20	QPSK	1	0	23.47	23.43	23.43	23.43	23.39
			1	49	23.85	23.80	23.80	23.80	23.74
			1	99	23.50	23.42	23.38	23.40	23.33
			50	0	22.79	22.72	22.61	22.68	22.64
			50	24	22.78	22.71	22.70	22.71	22.64
			50	49	22.76	22.71	22.70	22.71	22.66
			100	0	22.79	22.71	22.65	22.69	22.62
		16QAM	1	0	22.63	22.31	22.55	22.39	21.99
			1	49	23.01	22.67	22.85	22.73	22.32
			1	99	22.59	22.25	22.47	22.32	21.91
			50	0	21.93	21.84	21.69	21.79	21.74
			50	24	21.96	21.85	21.72	21.81	21.74
			50	49	21.96	21.86	21.67	21.80	21.76
			100	0	21.94	21.81	21.70	21.77	21.67
		64QAM	1	0	21.32	21.38	21.34	21.37	21.44
			1	49	21.65	21.78	21.73	21.76	21.90
			1	99	21.31	21.45	21.34	21.41	21.58
			50	0	20.39	20.58	20.43	20.53	20.77
			50	24	20.30	20.53	20.39	20.48	20.75
			50	49	20.33	20.53	20.35	20.47	20.73
			100	0	20.38	20.54	20.42	20.50	20.69

Note:

1. Per KDB 447498 D04v01 section 3.1.6, the required test channels number is 5 for LTE Band 41.

LTE Band 66 part:

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					131979	132322	132665
					1710.70MHz	1745.00MHz	1779.3MHz
Band 66	1.4	QPSK	1	0	23.62	23.51	23.65
			1	2	23.74	23.68	23.73
			1	5	23.68	23.58	23.69
			3	0	23.72	23.66	23.79
			3	1	23.70	23.62	23.75
			3	2	23.71	23.67	23.77
			6	0	22.72	22.63	22.74
		16QAM	1	0	22.50	22.31	22.54
			1	2	22.61	22.38	22.87
			1	5	22.44	22.34	22.56
			3	0	22.55	22.41	22.52
			3	1	22.54	22.39	22.53
			3	2	22.56	22.42	22.52
			6	0	21.51	21.57	21.75
		64QAM	1	0	21.10	21.35	21.19
			1	2	21.29	21.48	21.48
			1	5	21.07	21.32	21.21
			3	0	21.03	21.01	21.13
			3	1	21.03	21.08	21.13
			3	2	21.05	20.98	21.12
			6	0	19.84	19.84	20.09

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					131987	132322	132657
					1711.50MHz	1745.00MHz	1778.50MHz
Band 66	3	QPSK	1	0	23.67	23.65	23.70
			1	7	23.66	23.72	23.75
			1	14	23.62	23.66	23.77
			8	0	22.70	22.65	22.77
			8	4	22.69	22.66	22.76
			8	7	22.68	22.65	22.79
			15	0	22.63	22.62	22.68
		16QAM	1	0	22.64	22.49	22.44
			1	7	22.68	22.50	22.46
			1	14	22.60	22.46	22.57
			8	0	21.70	21.62	21.76
			8	4	21.70	21.59	21.73
			8	7	21.63	21.61	21.79
			15	0	21.60	21.52	21.61
		64QAM	1	0	20.84	20.97	21.45
			1	7	20.80	20.94	21.46
			1	14	20.83	20.95	21.48
			8	0	19.86	20.01	20.17
			8	4	19.84	20.01	20.19
			8	7	19.79	19.98	20.19
			15	0	19.88	19.91	20.16

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					131997	132322	132647
					1712.50MHz	1745.00MHz	1777.50MHz
Band 66	5	QPSK	1	0	23.56	23.46	23.61
			1	12	23.71	23.66	23.84
			1	24	23.53	23.58	23.67
			12	0	22.55	22.60	22.71
			12	6	22.59	22.61	22.72
			12	11	22.60	22.60	22.71
			25	0	22.61	22.63	22.67
		16QAM	1	0	22.56	22.60	22.53
			1	12	22.65	22.68	22.73
			1	24	22.53	22.59	22.56
			12	0	21.52	21.63	21.70
			12	6	21.54	21.62	21.69
			12	11	21.54	21.62	21.69
			25	0	21.57	21.58	21.74
		64QAM	1	0	20.71	21.39	21.40
			1	12	20.84	21.62	21.57
			1	24	20.77	21.52	21.40
			12	0	19.83	20.02	20.36
			12	6	19.84	20.04	20.34
			12	11	19.84	19.97	20.30
			25	0	19.89	19.97	20.22

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					132022	132322	132622
					1715.00MHz	1745.00MHz	1775.00MHz
Band 66	10	QPSK	1	0	23.57	23.67	23.60
			1	24	23.58	23.78	23.72
			1	49	23.48	23.62	23.72
			25	0	22.51	22.64	22.71
			25	12	22.52	22.63	22.70
			25	24	22.55	22.63	22.69
			50	0	22.62	22.57	22.66
		16QAM	1	0	22.64	22.46	22.34
			1	24	22.58	22.53	22.57
			1	49	22.56	22.48	22.51
			25	0	21.55	21.62	21.63
			25	12	21.52	21.62	21.66
			25	24	21.51	21.64	21.71
			50	0	21.56	21.58	21.58
		64QAM	1	0	20.81	20.90	21.40
			1	24	20.88	21.11	21.62
			1	49	20.74	20.70	21.49
			25	0	19.80	20.02	20.19
			25	12	19.78	20.06	20.20
			25	24	19.81	20.02	20.22
			50	0	19.86	20.04	20.10

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					132047	132322	132597
					1717.50MHz	1745.00MHz	1772.50MHz
Band 66	15	QPSK	1	0	23.58	23.43	23.53
			1	37	23.61	23.61	23.67
			1	74	23.63	23.46	23.71
			36	0	22.64	22.64	22.64
			36	16	22.64	22.70	22.69
			36	35	22.67	22.67	22.66
			75	0	22.62	22.69	22.74
		16QAM	1	0	22.59	22.61	22.36
			1	37	22.61	22.77	22.42
			1	74	22.60	22.57	22.42
			36	0	21.58	21.72	21.57
			36	16	21.59	21.67	21.62
			36	35	21.58	21.70	21.58
			75	0	21.57	21.69	21.71
		64QAM	1	0	20.74	21.12	21.34
			1	37	20.83	21.25	21.46
			1	74	20.69	21.26	21.32
			36	0	19.79	19.99	20.12
			36	16	19.80	19.99	20.15
			36	35	19.82	19.97	20.12
			75	0	19.79	20.00	20.21

LTE Band	Bandwidth (MHz)	Modulation	RB Size	RB Offset	Average Power (dBm)		
					132072	132322	132572
					1720.00MHz	1745.00MHz	1770.00MHz
Band 66	20	QPSK	1	0	23.45	23.35	23.31
			1	49	23.74	23.70	23.75
			1	99	23.35	23.38	23.52
			50	0	22.55	22.64	22.70
			50	24	22.57	22.66	22.70
			50	49	22.54	22.69	22.72
			100	0	22.55	22.65	22.64
		16QAM	1	0	22.35	22.50	22.18
			1	49	22.68	22.93	22.49
			1	99	22.30	22.50	22.31
			50	0	21.53	21.73	21.70
			50	24	21.55	21.70	21.74
			50	49	21.53	21.67	21.71
			100	0	21.53	21.63	21.64
		64QAM	1	0	21.08	20.96	20.84
			1	49	21.36	21.40	21.13
			1	99	21.05	21.21	20.94
			50	0	19.74	20.14	20.14
			50	24	19.76	20.08	20.10
			50	49	19.75	20.10	20.10
			100	0	19.81	20.09	20.14

13.4 WLAN 2.4 GHz Band Conducted Power

Average Power (dBm)				
Channel	Frequency (MHz)	802.11 b	802.11 g	802.11n (HT20)
CH 01	2412	16.93	14.37	13.43
CH 06	2437	16.57	14.04	12.94
CH 11	2462	16.96	14.31	13.26

Average Power (dBm)		
Channel	Frequency (MHz)	802.11n (HT40)
CH 03	2422	13.38
CH 06	2437	13.15
CH 09	2452	13.49

Note:

- SAR test of WLAN 2.4GHz is performed.
- Per KDB 248227 D01v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion.
- Per KDB 248227 D01v02r02, In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. SAR is not required for the following 2.4 GHz OFDM conditions:
 - When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
 - When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
- The output power of all data rate were pre-scan, just the worst case (the lowest data rate) of all mode were shown in report.
- Per KDB 248227 D01V02r02 section 2.2, when the EUT in continuously transmitting mode, the actual duty cycle is 100%, so the duty cycle factor is 1.

13.5 WLAN 5.2GHz Band Conducted Power

Average Power (dBm)				
Channel	Frequency (MHz)	802.11 a	802.11 ac20	802.11 n20
CH 36	5180	14.33	13.45	13.23
CH 40	5200	13.46	13.85	13.30
CH 48	5240	13.47	14.07	13.55

Average Power (dBm)			
Channel	Frequency (MHz)	802.11 ac40	802.11 n40
CH 38	5190	13.85	13.71
CH 46	5230	13.84	13.94

Average Power (dBm)		
Channel	Frequency (MHz)	802.11 ac80
CH 42	5210	13.70

Note:

6. SAR test of WLAN 5.2GHz is performed.
7. Per KDB 248227 D01v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion.
8. The output power of all data rate were pre-scan, just the worst case (the lowest data rate) of all mode were shown in report.
9. Per KDB 248227 D01V02r02 section 2.2, when the EUT in continuously transmitting mode, the actual duty cycle is 100%, so the duty cycle factor is 1.

13.6 WLAN 5.8GHz Band Conducted Power

Average Power (dBm)				
Channel	Frequency (MHz)	802.11 a	802.11 ac20	802.11 n20
CH 149	5745	14.08	13.60	13.71
CH 157	5785	14.41	14.25	14.29
CH 165	5825	14.48	14.28	14.30

Average Power (dBm)			
Channel	Frequency (MHz)	802.11 ac40	802.11 n40
CH 151	5755	13.65	13.74
CH 159	5795	14.26	14.08

Average Power (dBm)		
Channel	Frequency (MHz)	802.11 ac80
CH 155	5775	13.79

Note:

10. SAR test of WLAN 5.8GHz is performed.
11. Per KDB 248227 D01v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion.
12. The output power of all data rate were pre-scan, just the worst case (the lowest data rate) of all mode were shown in report.
13. Per KDB 248227 D01V02r02 section 2.2, when the EUT in continuously transmitting mode, the actual duty cycle is 100%, so the duty cycle factor is 1.

13.7 Bluetooth Conducted Power

Average Power (dBm)				
Channel	Frequency (MHz)	GFSK	$\pi/4$ -DQPSK	8DPSK
CH 00	2402	7.72	7.29	7.46
CH 39	2441	5.86	5.03	5.18
CH 78	2480	6.86	6.06	6.17

Average Power (dBm)					
Channel	Frequency (MHz)	BLE PHY 1M	BLE PHY 2M	BLE Coded PHY S=2	BLE Coded PHY S=8
CH 00	2402	-3.84	-3.96	-3.92	-3.87
CH 20	2442	-2.71	-2.82	-2.79	-2.78
CH 39	2480	-3.23	-3.36	-3.33	-3.36

Note:

1. SAR test of Bluetooth is performed and the mode with highest average power is selected for SAR testing.
2. Per KDB 447498 D04v01 section 2.1.2: 1-mW Test Exemption, SAR test for BLE is not required.
3. The output power of all data rate were pre-scan, just the worst case of all mode were shown in report.
4. Per KDB 248227 D01V02r02 section 2.2, when the EUT in continuously transmitting mode, the actual duty cycle is 100%, so the duty cycle factor is 1.

13.8 NFC Conducted Power

Average Power (dBm)	
Frequency (MHz)	ASK
13.56	-43.81

Note:

6. Per KDB 447498 D04v01 section 2.1.2: 1-mW Test Exemption, SAR test for NFC is not required.

dBm	mW
-43.81	0.00004

7. The output power of all data rate were pre-scan, just the worst case of all mode were shown in report.

14 Exposure Positions Consideration

14.1 EUT Antenna Locations




Fig.14.1 EUT Antenna Locations

Note: This antenna diagram is only used as a reference for the distance from the antenna to each edge. For the specific shape of the antenna, please refer to the physical photo.

14.2 Test Positions Consideration

Distance of Antennas to EUT edge/surface Test distance: 10mm						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
GSM/WCDMA/LTE	<25mm	<25mm	<25mm	152mm	30mm	<25mm
WLAN & Bluetooth	<25mm	<25mm	<25mm	151mm	<25mm	47mm

Test Positions Test distance: 10mm						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
GSM/WCDMA/LTE	Yes	Yes	Yes	No	No	Yes
WLAN & Bluetooth	Yes	Yes	Yes	No	Yes	No

Note:

1. Head/Body-worn/Hotspot mode SAR assessments are required.
2. Referring to KDB 941225 D06 v02r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.
3. Per KDB 447498 D04v01, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user, which is 0 mm for head SAR, 10 mm for hotspot SAR, and 10 mm for body-worn SAR.
4. Per KDB 648474 D04 v01r03, when hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR $> 1.2\text{ W/kg}$

15 SAR Test Results Summary

15.1 Standalone Head SAR Data

➤ GSM Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
1	GSM850/Voice	Right Cheek	190	836.6	33.98	-1.45	34.5	0.632	1.127	0.712
	GSM850/Voice	Right Tilted	190	836.6	33.98	-2.28	34.5	0.549	1.127	0.619
	GSM850/Voice	Left Cheek	190	836.6	33.98	-1.47	34.5	0.412	1.127	0.464
	GSM850/Voice	Left Tilted	190	836.6	33.98	1.43	34.5	0.331	1.127	0.373
	PCS1900/Voice	Right Cheek	661	1880	31.07	1.63	31.5	0.712	1.104	0.786
	PCS1900/Voice	Right Tilted	661	1880	31.07	-3.59	31.5	0.855	1.104	0.944
	PCS1900/Voice	Left Cheek	661	1880	31.07	-1.01	31.5	0.315	1.104	0.348
	PCS1900/Voice	Left Tilted	661	1880	31.07	1.43	31.5	0.461	1.104	0.509
	PCS1900/Voice	Right Tilted	512	1850.2	30.82	-3.77	31.5	0.723	1.169	0.845
2	PCS1900/Voice	Right Tilted	810	1909.8	30.70	-4.88	31.5	1.059	1.202	1.273
	PCS1900/Voice	Right Tilted	810	1909.8	30.70	0.51	31.5	0.986	1.202	1.185
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ WCDMA Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band II/RMC	Right Cheek	9538	1907.6	23.96	-1.85	24.0	0.391	1.009	0.395
3	Band II/RMC	Right Tilted	9538	1907.6	23.96	-0.33	24.0	0.459	1.009	0.463
	Band II/RMC	Left Cheek	9538	1907.6	23.96	-1.09	24.0	0.156	1.009	0.157
	Band II/RMC	Left Tilted	9538	1907.6	23.96	-0.33	24.0	0.266	1.009	0.268
	Band IV/RMC	Right Cheek	1413	1732.6	23.76	-0.26	24.0	0.689	1.057	0.728
	Band IV/RMC	Right Tilted	1413	1732.6	23.76	-2.65	24.0	0.865	1.057	0.914
	Band IV/RMC	Left Cheek	1413	1732.6	23.76	-0.58	24.0	0.312	1.057	0.330
	Band IV/RMC	Left Tilted	1413	1732.6	23.76	0.47	24.0	0.499	1.057	0.527
	Band IV/RMC	Right Tilted	1312	1712.4	23.72	-1.94	24.0	0.698	1.067	0.745
4	Band IV/RMC	Right Tilted	1513	1752.6	23.76	-2.69	24.0	0.919	1.057	0.971
	Band IV/RMC	Right Tilted	1513	1752.6	23.76	1.14	24.0	0.896	1.057	0.947
5	Band V/RMC	Right Cheek	4183	836.6	23.94	-0.43	24.0	0.369	1.014	0.374
	Band V/RMC	Right Tilted	4183	836.6	23.94	0.60	24.0	0.312	1.014	0.316
	Band V/RMC	Left Cheek	4183	836.6	23.94	0.26	24.0	0.215	1.014	0.218
	Band V/RMC	Left Tilted	4183	836.6	23.94	-0.12	24.0	0.115	1.014	0.117
A ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 2(20MHz) QPSK Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band2/1RB#49	Right Cheek	18700	1860	23.80	-0.79	24.0	0.894	1.047	0.936
	Band2/1RB#49	Right Tilted	18700	1860	23.80	3.17	24.0	1.008	1.047	1.055
	Band2/1RB#49	Left Cheek	18700	1860	23.80	-1.08	24.0	0.584	1.047	0.611
	Band2/1RB#49	Left Tilted	18700	1860	23.80	-2.29	24.0	0.751	1.047	0.786
	Band2/1RB#49	Right Cheek	18900	1880	23.70	-1.04	24.0	0.844	1.072	0.905
	Band2/1RB#49	Right Cheek	19100	1900	23.65	1.48	24.0	0.812	1.084	0.880
6	Band2/1RB#49	Right Tilted	18900	1880	23.70	-2.71	24.0	1.145	1.072	1.227
	Band2/1RB#49	Right Tilted	19100	1900	23.65	-2.40	24.0	1.102	1.084	1.195
	Band2/50%RB#0	Right Cheek	18900	1880	22.76	1.57	23.0	0.712	1.057	0.753
	Band2/50%RB#0	Right Tilted	18900	1880	22.76	-0.48	23.0	0.802	1.057	0.848
	Band2/50%RB#0	Left Cheek	18900	1880	22.76	-0.36	23.0	0.486	1.057	0.514
	Band2/50%RB#0	Left Tilted	18900	1880	22.76	-1.22	23.0	0.677	1.057	0.716
	Band2/50%RB#0	Right Tilted	18700	1860	22.47	1.91	23.0	0.711	1.13	0.803
	Band2/50%RB#0	Right Tilted	19100	1900	22.60	0.96	23.0	0.795	1.096	0.871
	Band2/100%RB#0	Right Cheek	19100	1900	22.63	-1.45	23.0	0.631	1.089	0.687
	Band2/100%RB#0	Right Tilted	19100	1900	22.63	-1.45	23.0	0.688	1.089	0.749
	Band2/1RB#49	Right Tilted	18900	1880	23.70	-1.64	24.0	1.102	1.072	1.181
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 5(10MHz) QPSK Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
7	Band5/1RB#24	Right Cheek	20525	836.5	24.17	-1.32	24.5	0.518	1.079	0.559
	Band5/1RB#24	Right Tilted	20525	836.5	24.17	-2.24	24.5	0.487	1.079	0.525
	Band5/1RB#24	Left Cheek	20525	836.5	24.17	-2.30	24.5	0.463	1.079	0.500
	Band5/1RB#24	Left Tilted	20525	836.5	24.17	-4.25	24.5	0.413	1.079	0.446
	Band5/50%RB#24	Right Cheek	20450	829	23.09	0.27	23.5	0.456	1.099	0.501
	Band5/50%RB#24	Right Tilted	20450	829	23.09	-2.00	23.5	0.421	1.099	0.463
	Band5/50%RB#24	Left Cheek	20450	829	23.09	1.29	23.5	0.386	1.099	0.424
	Band5/50%RB#24	Left Tilted	20450	829	23.09	1.50	23.5	0.371	1.099	0.408
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 7(20MHz) QPSK Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band7/1RB#49	Right Cheek	20850	2510	23.70	0.32	24.0	0.992	1.072	1.063
	Band7/1RB#49	Right Tilted	20850	2510	23.70	-3.59	24.0	0.991	1.072	1.062
	Band7/1RB#49	Left Cheek	20850	2510	23.70	-1.49	24.0	0.401	1.072	0.430
	Band7/1RB#49	Left Tilted	20850	2510	23.70	0.09	24.0	0.386	1.072	0.414
8	Band7/1RB#49	Right Cheek	21100	2535	23.68	-2.36	24.0	1.057	1.076	1.137
	Band7/1RB#49	Right Cheek	21350	2560	23.38	0.14	24.0	0.984	1.153	1.135
	Band7/1RB#49	Right Tilted	21100	2535	23.68	3.45	24.0	1.054	1.076	1.134
	Band7/1RB#49	Right Tilted	21350	2560	23.38	2.22	24.0	0.978	1.153	1.128
	Band7/50%RB#24	Right Cheek	21100	2535	22.62	1.38	23.0	0.786	1.091	0.858
	Band7/50%RB#24	Right Tilted	21100	2535	22.62	0.62	23.0	0.722	1.091	0.788
	Band7/50%RB#24	Left Cheek	21100	2535	22.62	1.07	23.0	0.346	1.091	0.377
	Band7/50%RB#24	Left Tilted	21100	2535	22.62	-0.13	23.0	0.325	1.091	0.355
	Band7/50%RB#0	Right Cheek	20850	2510	22.52	-1.88	23.0	0.712	1.117	0.795
	Band7/50%RB#0	Right Cheek	21350	2560	22.57	0.37	23.0	0.761	1.104	0.840
	Band7/100%RB#0	Right Cheek	21100	2535	22.61	-0.37	23.0	0.686	1.094	0.750
	Band7/100%RB#0	Right Tilted	21100	2535	22.61	-0.90	23.0	0.674	1.094	0.737
	Band7/1RB#49	Right Cheek	21100	2535	23.65	0.33	24.0	0.981	1.084	1.063
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 12(10MHz) QPSK Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
9	Band12/1RB#24	Right Cheek	23095	707.5	23.92	0.00	24.0	0.311	1.019	0.317
	Band12/1RB#24	Right Tilted	23095	707.5	23.92	-1.02	24.0	0.298	1.019	0.304
	Band12/1RB#24	Left Cheek	23095	707.5	23.92	-1.87	24.0	0.251	1.019	0.256
	Band12/1RB#24	Left Tilted	23095	707.5	23.92	1.49	24.0	0.233	1.019	0.237
	Band12/50%RB#12	Right Cheek	23060	704	23.00	1.49	23.5	0.286	1.122	0.321
	Band12/50%RB#12	Right Tilted	23060	704	23.00	-1.59	23.5	0.244	1.122	0.274
	Band12/50%RB#12	Left Cheek	23060	704	23.00	1.40	23.5	0.213	1.122	0.239
	Band12/50%RB#12	Left Tilted	23060	704	23.00	0.14	23.5	0.204	1.122	0.229
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ TDD-LTE Band41(20MHz) QPSK Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
10	Band41/1RB#49	Right Cheek	40140	2545	23.85	0.89	24.0	0.452	1.035	1.008	0.472
	Band41/1RB#49	Right Tilted	40140	2545	23.85	-1.28	24.0	0.357	1.035	1.008	0.372
	Band41/1RB#49	Left Cheek	40140	2545	23.85	0.97	24.0	0.213	1.035	1.008	0.222
	Band41/1RB#49	Left Tilted	40140	2545	23.85	1.70	24.0	0.123	1.035	1.008	0.128
	Band41/50%RB#49	Right Cheek	40140	2545	22.79	-1.62	23.0	0.423	1.05	1.008	0.448
	Band41/50%RB#49	Right Tilted	40140	2545	22.79	-0.78	23.0	0.312	1.05	1.008	0.330
	Band41/50%RB#49	Left Cheek	40140	2545	22.79	-1.49	23.0	0.194	1.05	1.008	0.205
	Band41/50%RB#49	Left Tilted	40140	2545	22.79	-0.20	23.0	0.112	1.05	1.008	0.119
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

➤ FDD-LTE Band 66(20MHz) QPSK Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band66/1RB#49	Right Cheek	132572	1770	23.75	-1.05	24.0	0.891	1.059	0.944
	Band66/1RB#49	Right Tilted	132572	1770	23.75	0.50	24.0	1.056	1.059	1.118
	Band66/1RB#49	Left Cheek	132572	1770	23.75	1.42	24.0	0.512	1.059	0.542
	Band66/1RB#49	Left Tilted	132572	1770	23.75	0.68	24.0	0.753	1.059	0.797
	Band66/1RB#49	Right Cheek	132072	1720	23.74	1.26	24.0	0.926	1.062	0.983
	Band66/1RB#49	Right Cheek	132322	1745	23.70	0.45	24.0	0.851	1.072	0.912
11	Band66/1RB#49	Right Tilted	132072	1720	23.74	-0.62	24.0	1.243	1.062	1.320
	Band66/1RB#49	Right Tilted	132322	1745	23.70	-2.09	24.0	0.951	1.072	1.019
	Band66/50%RB#49	Right Cheek	132572	1770	22.72	0.65	23.0	0.746	1.067	0.796
	Band66/50%RB#49	Right Tilted	132572	1770	22.72	-1.84	23.0	0.896	1.067	0.956
	Band66/50%RB#49	Left Cheek	132572	1770	22.72	0.21	23.0	0.481	1.067	0.513
	Band66/50%RB#49	Left Tilted	132572	1770	22.72	0.85	23.0	0.721	1.067	0.769
	Band66/50%RB#24	Right Tilted	132072	1720	22.57	-0.75	23.0	0.812	1.104	0.896
	Band66/50%RB#49	Right Tilted	132322	1745	22.69	-0.91	23.0	0.861	1.074	0.925
	Band66/100%RB#0	Right Cheek	132322	1745	22.65	-2.13	23.0	0.688	1.084	0.746
	Band66/100%RB#0	Right Tilted	132322	1745	22.65	0.06	23.0	0.721	1.084	0.782
	Band66/1RB#49	Right Tilted	132072	1720	23.74	0.36	24.0	1.125	1.062	1.195
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ WLAN 2.4 GHz Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
	2.4GHz/802.11b	Right Cheek	11	2462	16.96	2.33	17.0	0.161	1.009	1.000	0.162
	2.4GHz/802.11b	Right Tilted	11	2462	16.96	0.18	17.0	0.122	1.009	1.000	0.123
12	2.4GHz/802.11b	Left Cheek	11	2462	16.96	-1.65	17.0	0.287	1.009	1.000	0.290
	2.4GHz/802.11b	Left Tilted	11	2462	16.96	-1.45	17.0	0.249	1.009	1.000	0.251
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

➤ WLAN 5.2 GHz Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
	5.2GHz/802.11a	Right Cheek	36	5180	14.33	1.31	14.5	0.086	1.04	1.000	0.089
	5.2GHz/802.11a	Right Tilted	36	5180	14.33	-1.55	14.5	0.071	1.04	1.000	0.074
13	5.2GHz/802.11a	Left Cheek	36	5180	14.33	-3.46	14.5	0.151	1.04	1.000	0.157
	5.2GHz/802.11a	Left Tilted	36	5180	14.33	0.08	14.5	0.137	1.04	1.000	0.142
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

➤ WLAN 5.8 GHz Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
	5.8GHz/802.11a	Right Cheek	165	5825	14.48	1.67	14.5	0.096	1.005	1.000	0.096
	5.8GHz/802.11a	Right Tilted	165	5825	14.48	1.73	14.5	0.078	1.005	1.000	0.078
14	5.8GHz/802.11a	Left Cheek	165	5825	14.48	-0.15	14.5	0.152	1.005	1.000	0.153
	5.8GHz/802.11a	Left Tilted	165	5825	14.48	-0.95	14.5	0.125	1.005	1.000	0.126
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

➤ Bluetooth Head SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
	BT/GFSK	Right Cheek	0	2402	7.72	0.60	8.0	0.025	1.067	1.000	0.027
	BT/GFSK	Right Tilted	0	2402	7.72	-1.63	8.0	0.015	1.067	1.000	0.016
15	BT/GFSK	Left Cheek	0	2402	7.72	-0.24	8.0	0.040	1.067	1.000	0.043
	BT/GFSK	Left Tilted	0	2402	7.72	1.33	8.0	0.031	1.067	1.000	0.033
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

Note:

- Per KDB 447498 D04v01, for each exposure position, if the highest output power channel Reported SAR ≤ 0.8 W/kg, other channels SAR testing is not necessary.
- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is ≥ 0.8 W/kg.
- Per KDB 941225 D05v02r05, 100% RB allocation SAR measurement is not required when the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg.
- Per KDB 248227 D01v02r02, for 802.11b DSSS , when the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required in that exposure configuration.
- Per KDB 248227 D01v02r02, OFDM SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. Cuz the maximum output power specified for OFDM and DSSS are 28.18mW(14.5dBm) and 50.12mW(17.0dBm), the scaled SAR would be $0.290 \times (28.18/50.12) = 0.163$ W/Kg < 1.2 W/kg, therefore, SAR is not required for OFDM.
- According to KDB 865664 D02v01r02, SAR plot is required for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination.

15.2 Standalone Body SAR

➤ GSM Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	GPRS850/2 slots	Front	190	836.6	33.03	-0.59	33.5	0.252	1.114	0.281
16	GPRS850/2 slots	Back	190	836.6	33.03	-0.51	33.5	0.415	1.114	0.462
	GPRS1900/2 slots	Front	661	1880	30.07	-0.90	30.5	0.231	1.104	0.255
17	GPRS1900/2 slots	Back	661	1880	30.07	-4.43	30.5	0.546	1.104	0.603
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ WCDMA Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band II/RMC	Front	9538	1907.6	23.96	-0.15	24.0	0.118	1.009	0.119
18	Band II/RMC	Back	9538	1907.6	23.96	-2.71	24.0	0.228	1.009	0.230
	Band IV/RMC	Front	1413	1732.6	23.76	-1.45	24.0	0.186	1.057	0.197
19	Band IV/RMC	Back	1413	1732.6	23.76	-0.06	24.0	0.296	1.057	0.313
	Band V/RMC	Front	4183	836.6	23.94	-1.87	24.0	0.177	1.014	0.179
20	Band V/RMC	Back	4183	836.6	23.94	0.32	24.0	0.235	1.014	0.238
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 2(20MHz) QPSK Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band2/1RB#49	Front	18700	1860	23.80	-1.81	24.0	0.286	1.047	0.299
21	Band2/1RB#49	Back	18700	1860	23.80	1.67	24.0	0.498	1.047	0.521
	Band2/50%RB#0	Front	18900	1880	22.76	-0.09	23.0	0.231	1.057	0.244
	Band2/50%RB#0	Back	18900	1880	22.76	-1.31	23.0	0.451	1.057	0.477
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 5(10MHz) QPSK Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band5/1RB#24	Front	20525	836.5	24.17	-0.06	24.5	0.186	1.079	0.201
22	Band5/1RB#24	Back	20525	836.5	24.17	-0.82	24.5	0.216	1.079	0.233
	Band5/50%RB#24	Front	20450	829	23.09	-1.15	23.5	0.172	1.099	0.189
	Band5/50%RB#24	Back	20450	829	23.09	1.90	23.5	0.200	1.099	0.220
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 7(20MHz) QPSK Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band7/1RB#49	Front	20850	2510	23.70	1.31	24.0	0.210	1.072	0.225
23	Band7/1RB#49	Back	20850	2510	23.70	3.48	24.0	0.368	1.072	0.394
	Band7/50%RB#24	Front	21100	2535	22.62	0.95	23.0	0.186	1.091	0.203
	Band7/50%RB#24	Back	21100	2535	22.62	1.98	23.0	0.326	1.091	0.356
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 12(10MHz) QPSK Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band12/1RB#24	Front	23095	707.5	23.92	-1.68	24.0	0.096	1.019	0.098
24	Band12/1RB#24	Back	23095	707.5	23.92	-2.73	24.0	0.120	1.019	0.122
	Band12/50%RB#12	Front	23060	704	23.00	-0.65	23.5	0.081	1.122	0.091
	Band12/50%RB#12	Back	23060	704	23.00	1.24	23.5	0.112	1.122	0.126
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ TDD-LTE Band 41(20MHz) QPSK Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
	Band41/1RB#49	Front	40140	2545	23.85	0.13	24.0	0.121	1.035	1.008	0.126
25	Band41/1RB#49	Back	40140	2545	23.85	-1.12	24.0	0.241	1.035	1.008	0.251
	Band41/50%RB#49	Front	40140	2545	22.79	0.33	23.0	0.110	1.050	1.008	0.116
	Band41/50%RB#49	Back	40140	2545	22.79	-1.43	23.0	0.216	1.050	1.008	0.229
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

➤ FDD-LTE Band 66(20MHz) QPSK Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band66/1RB#49	Front	132572	1770	23.75	1.90	24.0	0.186	1.059	0.197
26	Band66/1RB#49	Back	132572	1770	23.75	-2.19	24.0	0.282	1.059	0.299
	Band66/50%RB#49	Front	132572	1770	22.72	0.13	23.0	0.153	1.067	0.163
	Band66/50%RB#49	Back	132572	1770	22.72	-1.63	23.0	0.251	1.067	0.268
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ WLAN 2.4GHz Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
27	2.4GHz/802.11b	Front	11	2462	16.96	-1.89	17.0	0.079	1.009	1.000	0.080
	2.4GHz/802.11b	Back	11	2462	16.96	-0.51	17.0	0.075	1.009	1.000	0.076
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

➤ WLAN 5.2GHz Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
	5.2GHz/802.11a	Front	36	5180	14.33	2.49	14.5	0.077	1.040	1.000	0.080
28	5.2GHz/802.11a	Back	36	5180	14.33	-0.75	14.5	0.098	1.040	1.000	0.102
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

➤ WLAN 5.8GHz Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
	5.8GHz/802.11a	Front	165	5825	14.48	1.52	14.5	0.069	1.005	1.000	0.069
29	5.8GHz/802.11a	Back	165	5825	14.48	-0.52	14.5	0.084	1.005	1.000	0.084
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

➤ Bluetooth Body SAR

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
	BT/GFSK	Front	0	2402	7.72	-1.99	8.0	0.021	1.067	1.000	0.022
30	BT/GFSK	Back	0	2402	7.72	-0.84	8.0	0.022	1.067	1.000	0.023
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

Note:

1. Body-worn SAR testing was performed at 10mm separation, and this distance is determined by the handset manufacturer that there will be body-worn accessories that users may acquire at the time of equipment certification, to enable users to purchase aftermarket body-worn accessories with the required minimum separation.
2. Per KDB 941225 D06v02r01, when the same wireless modes and device transmission configurations are required for testing body-worn accessories and hotspot mode, it is not necessary to test body-worn accessory SAR for the same device orientation if the test separation distance for hotspot mode is more conservative than that used for body-worn accessories.
3. Per KDB 648474 D04v01r03, when the Reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
4. The WLAN SAR perform the front and back position, due considered the simultaneous SAR for body-worn.
5. Per KDB 447498 D04v01, for each exposure position, if the highest output channel Reported SAR ≤ 0.8 W/kg, other channels SAR testing is not necessary.
6. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is ≥ 0.8 W/kg.
7. Per KDB 941225 D05v02r05, 100% RB allocation SAR measurement is not required when the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg.
8. According to KDB 865664 D02v01r02, SAR plot is required for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination.
9. Highlight part of test data means repeated test.

15.3 Body SAR in Hotspot Mode

➤ GSM Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	GPRS850/2 slots	Front	190	836.6	33.03	-0.59	33.5	0.252	1.114	0.281
16	GPRS850/2 slots	Back	190	836.6	33.03	-0.51	33.5	0.415	1.114	0.462
	GPRS850/2 slots	Left	190	836.6	33.03	-0.83	33.5	0.213	1.114	0.237
	GPRS850/2 slots	Top	190	836.6	33.03	-4.50	33.5	0.240	1.114	0.267
	GPRS1900/2 slots	Front	661	1880	30.07	-0.90	30.5	0.231	1.104	0.255
	GPRS1900/2 slots	Back	661	1880	30.07	-4.43	30.5	0.546	1.104	0.603
	GPRS1900/2 slots	Left	661	1880	30.07	-4.83	30.5	0.124	1.104	0.137
31	GPRS1900/2 slots	Top	661	1880	30.07	-4.15	30.5	0.587	1.104	0.648
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ WCDMA Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
	Band II/RMC	Front	9538	1907.6	23.96	-0.15	24.0	0.118	1.009	0.119
	Band II/RMC	Back	9538	1907.6	23.96	-2.71	24.0	0.228	1.009	0.230
	Band II/RMC	Left	9538	1907.6	23.96	0.46	24.0	0.102	1.009	0.103
32	Band II/RMC	Top	9538	1907.6	23.96	-0.01	24.0	0.232	1.009	0.234
	Band IV/RMC	Front	1413	1732.6	23.76	-1.45	24.0	0.186	1.057	0.197
19	Band IV/RMC	Back	1413	1732.6	23.76	-0.06	24.0	0.296	1.057	0.313
	Band IV/RMC	Left	1413	1732.6	23.76	-1.16	24.0	0.152	1.057	0.161
	Band IV/RMC	Top	1413	1732.6	23.76	1.84	24.0	0.260	1.057	0.275
	Band V/RMC	Front	4183	836.6	23.94	-1.87	24.0	0.177	1.014	0.179
20	Band V/RMC	Back	4183	836.6	23.94	0.32	24.0	0.235	1.014	0.238
	Band V/RMC	Left	4183	836.6	23.94	0.01	24.0	0.126	1.014	0.128
	Band V/RMC	Top	4183	836.6	23.94	0.59	24.0	0.186	1.014	0.189
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 2(20MHz) QPSK Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
21	Band2/1RB#49	Front	18700	1860	23.80	-1.81	24.0	0.286	1.047	0.299
	Band2/1RB#49	Back	18700	1860	23.80	1.67	24.0	0.498	1.047	0.521
	Band2/1RB#49	Left	18700	1860	23.80	-1.04	24.0	0.156	1.047	0.163
	Band2/1RB#49	Top	18700	1860	23.80	-3.71	24.0	0.491	1.047	0.514
	Band2/50%RB#0	Front	18900	1880	22.76	-0.09	23.0	0.231	1.057	0.244
	Band2/50%RB#0	Back	18900	1880	22.76	-1.31	23.0	0.451	1.057	0.477
	Band2/50%RB#0	Left	18900	1880	22.76	-0.40	23.0	0.136	1.057	0.144
	Band2/50%RB#0	Top	18900	1880	22.76	1.10	23.0	0.421	1.057	0.445
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 5(10MHz) QPSK Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
22	Band5/1RB#24	Front	20525	836.5	24.17	-0.06	24.5	0.186	1.079	0.201
	Band5/1RB#24	Back	20525	836.5	24.17	-0.82	24.5	0.216	1.079	0.233
	Band5/1RB#24	Left	20525	836.5	24.17	-1.10	24.5	0.102	1.079	0.110
	Band5/1RB#24	Top	20525	836.5	24.17	-1.14	24.5	0.177	1.079	0.191
	Band5/50%RB#24	Front	20450	829	23.09	-1.15	23.5	0.172	1.099	0.189
	Band5/50%RB#24	Back	20450	829	23.09	1.90	23.5	0.200	1.099	0.220
	Band5/50%RB#24	Left	20450	829	23.09	1.89	23.5	0.155	1.099	0.170
	Band5/50%RB#24	Top	20450	829	23.09	0.96	23.5	0.123	1.099	0.135
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 7(20MHz) QPSK Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
23	Band7/1RB#49	Front	20850	2510	23.70	1.31	24.0	0.210	1.072	0.225
	Band7/1RB#49	Back	20850	2510	23.70	3.48	24.0	0.368	1.072	0.394
	Band7/1RB#49	Left	20850	2510	23.70	0.43	24.0	0.152	1.072	0.163
	Band7/1RB#49	Top	20850	2510	23.70	-0.99	24.0	0.317	1.072	0.340
	Band7/50%RB#24	Front	21100	2535	22.62	0.95	23.0	0.186	1.091	0.203
	Band7/50%RB#24	Back	21100	2535	22.62	1.98	23.0	0.326	1.091	0.356
	Band7/50%RB#24	Left	21100	2535	22.62	0.42	23.0	0.122	1.091	0.133
	Band7/50%RB#24	Top	21100	2535	22.62	0.63	23.0	0.241	1.091	0.263
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ FDD-LTE Band 12(10MHz) QPSK Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	Reported SAR _{1g} (W/kg)
24	Band12/1RB#24	Front	23095	707.5	23.92	-1.68	24.0	0.096	1.019	0.098
	Band12/1RB#24	Back	23095	707.5	23.92	-2.73	24.0	0.120	1.019	0.122
	Band12/1RB#24	Left	23095	707.5	23.92	-0.77	24.0	0.081	1.019	0.083
	Band12/1RB#24	Top	23095	707.5	23.92	1.65	24.0	0.115	1.019	0.117
	Band12/50%RB#12	Front	23060	704	23.00	-0.65	23.5	0.081	1.122	0.091
	Band12/50%RB#12	Back	23060	704	23.00	1.24	23.5	0.112	1.122	0.126
	Band12/50%RB#12	Left	23060	704	23.00	-0.61	23.5	0.062	1.122	0.070
	Band12/50%RB#12	Top	23060	704	23.00	-0.48	23.5	0.096	1.122	0.108
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g					

➤ TDD-LTE Band 41(20MHz) QPSK Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
25	Band41/1RB#49	Front	40140	2545	23.85	0.13	24.0	0.121	1.035	1.008	0.126
	Band41/1RB#49	Back	40140	2545	23.85	-1.12	24.0	0.241	1.035	1.008	0.251
	Band41/1RB#49	Left	40140	2545	23.85	-0.50	24.0	0.103	1.035	1.008	0.107
	Band41/1RB#49	Top	40140	2545	23.85	-0.05	24.0	0.168	1.035	1.008	0.175
	Band41/50%RB#49	Front	40140	2545	22.79	0.33	23.0	0.110	1.050	1.008	0.116
	Band41/50%RB#49	Back	40140	2545	22.79	-1.43	23.0	0.216	1.050	1.008	0.229
	Band41/50%RB#49	Left	40140	2545	22.79	0.65	23.0	0.086	1.050	1.008	0.091
	Band41/50%RB#49	Top	40140	2545	22.79	0.67	23.0	0.136	1.050	1.008	0.144
ANSI / IEEE C95.1 – SAFETY LIMIT					1.6 W/kg (mW/g)						
Spatial Peak					Averaged over 1g						
Uncontrolled Exposure/General Population											

➤ FDD-LTE Band 66(20MHz) QPSK Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
26	Band66/1RB#49	Front	132572	1770	23.75	1.90	24.0	0.186	1.059		0.197
	Band66/1RB#49	Back	132572	1770	23.75	-2.19	24.0	0.282	1.059		0.299
	Band66/1RB#49	Left	132572	1770	23.75	1.99	24.0	0.121	1.059		0.128
	Band66/1RB#49	Top	132572	1770	23.75	-1.38	24.0	0.224	1.059		0.237
	Band66/50%RB#49	Front	132572	1770	22.72	0.13	23.0	0.153	1.067		0.163
	Band66/50%RB#49	Back	132572	1770	22.72	-1.63	23.0	0.251	1.067		0.268
	Band66/50%RB#49	Left	132572	1770	22.72	1.61	23.0	0.110	1.067		0.117
	Band66/50%RB#49	Top	132572	1770	22.72	-0.84	23.0	0.160	1.067		0.171
ANSI / IEEE C95.1 – SAFETY LIMIT					1.6 W/kg (mW/g)						
Spatial Peak					Averaged over 1g						
Uncontrolled Exposure/General Population											

➤ WLAN 2.4GHz Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
33	2.4GHz/802.11b	Front	11	2462	16.96	-1.89	17.0	0.079	1.009	1.000	0.080
	2.4GHz/802.11b	Back	11	2462	16.96	-0.51	17.0	0.075	1.009	1.000	0.076
	2.4GHz/802.11b	Right	11	2462	16.96	-2.56	17.0	0.081	1.009	1.000	0.082
	2.4GHz/802.11b	Top	11	2462	16.96	-1.95	17.0	0.072	1.009	1.000	0.073
ANSI / IEEE C95.1 – SAFETY LIMIT					1.6 W/kg (mW/g)						
Spatial Peak					Averaged over 1g						
Uncontrolled Exposure/General Population											

➤ WLAN 5.2GHz Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
28	5.2GHz/802.11a	Front	36	5180	14.33	2.49	14.5	0.077	1.040	1.000	0.080
	5.2GHz/802.11a	Back	36	5180	14.33	-0.75	14.5	0.098	1.040	1.000	0.102
	5.2GHz/802.11a	Right	36	5180	14.33	4.90	14.5	0.091	1.040	1.000	0.095
	5.2GHz/802.11a	Top	36	5180	14.33	-3.59	14.5	0.096	1.040	1.000	0.100
ANSI / IEEE C95.1 – SAFETY LIMIT					1.6 W/kg (mW/g)						
Spatial Peak					Averaged over 1g						
Uncontrolled Exposure/General Population											

➤ WLAN 5.8GHz Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
29	5.8GHz/802.11a	Front	165	5825	14.48	1.52	14.5	0.069	1.005	1.000	0.069
	5.8GHz/802.11a	Back	165	5825	14.48	-0.52	14.5	0.084	1.005	1.000	0.084
	5.8GHz/802.11a	Right	165	5825	14.48	0.01	14.5	0.076	1.005	1.000	0.076

5.8GHz/802.11a	Top	165	5825	14.48	0.83	14.5	0.079	1.005	1.000	0.079
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population				1.6 W/kg (mW/g) Averaged over 1g						

➤ Bluetooth Body SAR in Hotspot mode

Plot No.	Band/Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Power Drift (dB)	Tune-Up Limit (dBm)	Meas. SAR _{1g} (W/kg)	Scaling Factor	D.C Factor	Reported SAR _{1g} (W/kg)
	BT/GFSK	Front	0	2402	7.72	-1.99	8.0	0.021	1.067	1.000	0.022
30	BT/GFSK	Back	0	2402	7.72	-0.84	8.0	0.022	1.067	1.000	0.023
	BT/GFSK	Right	0	2402	7.72	1.96	8.0	0.021	1.067	1.000	0.022
	BT/GFSK	Top	0	2402	7.72	1.07	8.0	0.019	1.067	1.000	0.020
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					1.6 W/kg (mW/g) Averaged over 1g						

Note:

- Per KDB 447498 D04v01, for each exposure position, if the highest output channel Reported SAR ≤ 0.8 W/kg, other channels SAR testing is not necessary.
- Additional WLAN SAR testing was performed for simultaneous transmission analysis.
- For Hotspot SAR testing, per KDB 941225 D06v02r01, for EUT dimension ≥ 9 cm*5cm, the test distance is 10mm. SAR must be measured for all surfaces and sides with a transmitting antenna located within 2.5cm from that surface or edge.
- Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA output power is < 0.25 dB higher than RMC 12.2kbps, or Reported SAR with RMC 12.2kbps setting is ≤ 1.2 W/kg, HSDPA SAR evaluation can be excluded.
- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is ≥ 0.8 W/kg.
- Per KDB 648474 D04v01r03, when the Reported SAR for a body-worn accessory measured without a headset connected to the handset is > 1.2 W/kg, SAR testing with a headset connected to the handset is required.
- Per KDB 941225 D05v02r05, 100% RB allocation SAR measurement is not required when the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel.
- According to KDB 865664 D02v01r02, SAR plot is required for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination.
- Highlight part of test data means repeated test.

15.4 Repeated SAR measurement

Band/ Mode	Test Position	CH.	Freq. (MHz)	Measured SAR (W/kg)				
				Original	1 st Repeated		2 nd Repeated	
					Value	Ratio	Value	Ratio
PCS1900/Voice	Right Tilted	810	1909.8	1.059	0.986	1.07	/	/
Band IV/RMC	Right Tilted	1513	1752.6	0.919	0.896	1.03	/	/
Band2/1RB#49	Right Tilted	18900	1880	1.145	1.102	1.04	/	/
Band7/1RB#49	Right Cheek	21100	2535	1.057	0.981	1.08		
Band66/1RB#49	Right Tilted	132072	1720	1.243	1.125	1.10		
ANSI / IEEE C95.1 – SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population				1.6 W/kg (mW/g) Averaged over 1g				

Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg
2. Per KDB 865664 D01v01r04, if the ratio of *original* and *repeated* is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.

15.5 DUT holder perturbation uncertainty evaluation

1. According to TCB workshop, Oct 2016:
When the highest reported SAR of an antenna is > 1.2 W/kg, holder perturbation verification is required for each antenna, using the highest SAR configuration among all applicable frequency bands.
2. When the highest reported SAR of an antenna is > 1.2 W/kg, holder perturbation verification is required for each antenna, using the highest SAR configuration among all applicable frequency bands.
3. According to IEEE 1528-2013 section E.4.1, When it is unknown if a device holder perturbs the fields of a test device, the SAR uncertainty shall be assessed with a flat phantom (see Clause 5) by comparing the SAR with and without the device holder according to the following tests:
 - a) With device holder: 1 g or 10 g peak spatial-average SAR is measured with the handset fixed in the holder in a manner similar to the way it was held when tested for the head SAR position. The handset horizontal and vertical centerlines (see Clause 6) are aligned parallel to the bottom of the flat phantom and the device is in direct contact with the phantom. The test shall be performed with the antenna position and device operational configuration corresponding to that where the highest head SAR was previously measured for each frequency band.
 - b) Without device holder: 1 g or 10 g peak spatial-average SAR is measured with the handset placed on a low-loss foam block or support in the position identical to that tested with the device holder. The relative permittivity and loss tangent of the foam material shall be less than 1.2 and 10⁻⁵, respectively.

Test result:

Plot	Band/ Mode	Test Position	CH.	Freq. (MHz)	Test configuration	Measured SAR (W/kg) Averaged over 1g
34	Band66/1RB#49	Front	132072	1720	With device holder	0.940
35	Band66/1RB#49	Front	132072	1720	Without device holder	0.918

The following equation is used to computed the SAR tolerance,

$$SAR_{\text{tolerance}} [\%] = 100 \times \left(\frac{SAR_{\text{w/ holder}} - SAR_{\text{w/o holder}}}{SAR_{\text{w/o holder}}} \right)$$

Therefore, the $SAR_{\text{tolerance}} = 100 \times [(0.940 - 0.918) / 0.918] = 2.4\%$.

15.6 Multi-Band Simultaneous Transmission Considerations

➤ Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D04v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the EUT are shown in below Figure and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.




Fig.15.1 Simultaneous Transmission Paths

➤ Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D04v01, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D04v01 Appendix E, E.1), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$SAR_{est} = 1.6 \cdot P_{ant} / P_{th} \text{ [W/kg]}.$$

Mode	Max. Power (dBm)	Max. Power (mW)	Exposure Position	Head	Body	Hotspot
NFC	-43.81	0.00004	Estimated SAR (W/kg)	0.000	0.000	0.000

Note:

1. Per KDB 447498 D04v01 section 2.1.2: 1-mW Test Exemption, $P_{th}=1\text{mW}$.

➤ Multi-Band simultaneous Transmission Consideration

Simultaneous Transmission Consideration	Position	Applicable Combination
	Head	WWAN (Voice) + WLAN 2.4 GHz/5.2GHz/5.8GHz+NFC
		WWAN (Voice) + Bluetooth + NFC
	Body	WWAN (Voice) + WLAN 2.4 GHz/5.2GHz/5.8GHz+NFC
		WWAN (Voice) + Bluetooth + NFC
	Hotspot	WWAN (Data) + WLAN 2.4 GHz/5.2GHz/5.8GHz+NFC
		WWAN (Data) + Bluetooth + NFC

Note:

1. WLAN 2.4GHz Band, WLAN 5.2GHz Band, WLAN 5.8GHz Band and Bluetooth share the same antenna, and cannot transmit simultaneously.
2. GSM/WCDMA/LTE shares the same antenna, and cannot transmit simultaneously.
3. The Report SAR summation is calculated based on the same configuration and test position.
4. Per KDB 447498 D04v01, simultaneous transmission SAR is compliant if,
 - i. Scalar SAR summation < 1.6 W/kg.
 - ii. $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iii. Simultaneously transmission SAR measurement, and the Reported multi-band SAR < 1.6 W/kg

15.7 SAR Simultaneous Transmission Analysis

➤ Simultaneous Transmission

➤

Position		Standalone SAR(W/kg)					Σ SAR _{1g} (W/kg)		
		1	2	3	4	5	1+2+5	1+3+5	1+4+5
		WWAN	2.4G WLAN	5G WLAN	BT	NFC			
Head	Right Cheek	1.137	0.162	0.096	0.027	0.000	1.299	1.233	1.164
	Right Tilted	1.320	0.123	0.078	0.016	0.000	1.443	1.398	1.336
	Left Cheek	0.611	0.290	0.157	0.043	0.000	0.901	0.768	0.654
	Left Tilted	0.797	0.251	0.142	0.033	0.000	1.048	0.939	0.830
Body-worn	Front	0.299	0.080	0.080	0.022	0.000	0.379	0.379	0.321
	Back	0.603	0.076	0.102	0.023	0.000	0.679	0.705	0.626
Hotspot	Front	0.299	0.080	0.080	0.022	0.000	0.379	0.379	0.321
	Back	0.603	0.076	0.102	0.023	0.000	0.679	0.705	0.626
	Left	0.237	/	/	/	0.000	0.237	0.237	0.237
	Right	/	0.082	0.095	0.022	0.000	0.082	0.095	0.022
	Top	0.648	0.073	0.100	0.020	0.000	0.721	0.748	0.668
	Bottom	/	/	/	/	0.000	/	/	/

➤ Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D04v01.

15.8 Measurement Uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

16 Reference

- [1]. FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
- [2]. ANSI/IEEE Std. C95.1-1992, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, September 1992
- [3]. IEEE Std. 1528-2013, “Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, September 2013
- [4]. OpenSAR V5 Software User Manual
- [5]. FCC KDB 248227 D01 v02r02, “SAR GUIDANCE FOR IEEE 802.11 (Wi-Fi) TRANSMITTERS”, October 2015
- [6]. FCC KDB 447498 D04 v01, “RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES”, November 2021
- [7]. FCC KDB 648474 D04 v01r03, “SAR EVALUATION CONSIDERATIONS FOR WIRELESS HANDSETS”, October 2015
- [8]. FCC KDB 941225 D01 v03r01, “3G SAR MEASUREMENT PROCEDURES”, October 2015
- [9]. FCC KDB 941225 D05 v02r05, “SAR EVALUATION CONSIDERATIONS FOR LTE DEVICES”, Dec 2015
- [10]. FCC KDB 941225 D06 v02r01, “SAR EVALUATION PROCEDURES FOR PORTABLE DEVICES WITH WIRELESS ROUTER CAPABILITIES”, October 2015
- [11]. FCC KDB 865664 D01 v01r04, “SAR MEASUREMENT REQUIREMENTS FOR 100 MHz TO 6 GHz”, August 2015

Appendix A: Plots of SAR System Check

System check at 750 MHz

Date of measurement: 2/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.70
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels	Middle
Signal	CW (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	750.000000
Relative permittivity (real part)	42.531432
Conductivity (S/m)	0.900000

C. SAR Surface and Volume




Maximum location: X=3.00, Y=2.00 ; SAR Peak: 1.19 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.570213
SAR 1g (W/Kg)	0.869024
Variation (%)	2.390000

E. Z Axis Scan



System check at 835 MHz

Date of measurement: 2/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.73
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	835.000000
Relative permittivity (real part)	42.330000
Conductivity (S/m)	0.922044

C. SAR Surface and Volume




Maximum location: X=3.00, Y=3.00 ; SAR Peak: 1.50 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.620142
SAR 1g (W/Kg)	0.96630
Variation (%)	2.7540000

E. Z Axis Scan



System check at 1750 MHz


Date of measurement: 6/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.05
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1750
Channels	Middle
Signal	CW (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	1750.000000
Relative permittivity (real part)	39.660422
Conductivity (S/m)	1.350374

C. SAR Surface and Volume

Maximum location: X=3.00, Y=1.00 ; SAR Peak: 5.69 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	1.903010
SAR 1g (W/Kg)	3.590114
Variation (%)	1.420000

E. Z Axis Scan

System check at 1900 MHz

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.00
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	1900.000000
Relative permittivity (real part)	39.700000
Conductivity (S/m)	1.390100

C. SAR Surface and Volume




Maximum location: X=3.00, Y=1.00 ; SAR Peak: 6.27 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	2.011121
SAR 1g (W/Kg)	3.942042
Variation (%)	0.690000

E. Z Axis Scan



System check at 2450 MHz

Date of measurement: 10/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.46
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	2450.000000
Relative permittivity (real part)	39.880000
Conductivity (S/m)	1.823051

C. SAR Surface and Volume




Maximum location: X=5.00, Y=0.00 ; SAR Peak: 2.67 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.968317
SAR 1g (W/Kg)	2.137017
Variation (%)	-1.620000

E. Z Axis Scan



System check at 2600 MHz

Date of measurement: 10/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.27
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels	Middle
Signal	CW (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	2600.000000
Relative permittivity (real part)	39.550000
Conductivity (S/m)	1.970122

C. SAR Surface and Volume




Maximum location: X=3.00, Y=0.00 ; SAR Peak: 3.24 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.976115
SAR 1g (W/Kg)	2.250112
Variation (%)	-0.120000

E. Z Axis Scan



System check at 5200 MHz

Date of measurement: 12/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.71
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	5200.000000
Relative permittivity (real part)	35.890322
Conductivity (S/m)	4.620026

C. SAR Surface and Volume




Maximum location: X=0.00, Y=-2.00 ; SAR Peak: 9.13 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.946431
SAR 1g (W/Kg)	3.068401
Variation (%)	0.190000

E. Z Axis Scan



System check at 5800 MHz


Date of measurement: 12/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.94
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	5800.000000
Relative permittivity (real part)	34.781421
Conductivity (S/m)	5.190255

C. SAR Surface and Volume

Maximum location: X=6.00, Y=-1.00 ; SAR Peak: 8.48 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.953221
SAR 1g (W/Kg)	3.120324
Variation (%)	0.520000

E. Z Axis Scan

Appendix B: Plots of SAR Test Data

SAR Measurement at GSM850 (Cheek, Right)


Date of measurement: 2/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.73
Area Scan	dx=15mm dy=15mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Right head
Device Position	Cheek
Band	GSM850
Channels	Middle
Signal	TDMA (Crest factor: 8.0)

B. Permittivity


Frequency (MHz)	836.599976
Relative permittivity (real part)	42.350000
Conductivity (S/m)	0.921634

C. SAR Surface and Volume

Maximum location: X=-15.00, Y=14.00 ; SAR Peak: 0.94 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.406585
SAR 1g (W/Kg)	0.632196
Variation (%)	-1.450000

E. Z Axis Scan

SAR Measurement at GSM1900 (Tilt, Right)


Date of measurement: 6/12/2022

A. Experimental conditions.


Probe	SN 18/21 EPG0354
ConvF	2.00
Area Scan	dx=15mm dy=15mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Tilt
Band	GSM1900
Channels	High
Signal	TDMA (Crest factor: 8.0)

B. Permittivity

Frequency (MHz)	1909.800049
Relative permittivity (real part)	40.020000
Conductivity (S/m)	1.400011

C. SAR Surface and Volume**D. SAR 1g & 10g**

SAR 10g (W/Kg)	0.521755
SAR 1g (W/Kg)	1.059219
Variation (%)	-4.880000

E. Z Axis Scan

SAR Measurement at Band2_WCDMA1900 (Tilt, Right)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.00
Area Scan	dx=15mm dy=15mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Tilt
Band	Band2_WCDMA1900
Channels	High
Signal	WCDMA (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	1907.600000
Relative permittivity (real part)	39.900000
Conductivity (S/m)	1.400001

C. SAR Surface and Volume




Maximum location: X=5.00, Y=13.00 ; SAR Peak: 0.78 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.238399
SAR 1g (W/Kg)	0.458778
Variation (%)	-0.330000

E. Z Axis Scan



SAR Measurement at CUSTOM (WCDMA 1700) (Tilt, Right)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.05
Area Scan	dx=15mm dy=15mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Tilt
Band	Band4_WCDMA1700
Channels	High
Signal	WCDMA (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	1752.599976
Relative permittivity (real part)	39.694255
Conductivity (S/m)	1.351441

C. SAR Surface and Volume




Maximum location: X=-3.00, Y=20.00 ; SAR Peak: 1.60 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.470424
SAR 1g (W/Kg)	0.919344
Variation (%)	-2.690000

E. Z Axis Scan



SAR Measurement at Band5_WCDMA850 (Cheek, Right)

Date of measurement: 2/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.73
Area Scan	dx=15mm dy=15mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Right head
Device Position	Cheek
Band	Band5_WCDMA850
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	836.599976
Relative permittivity (real part)	42.590000
Conductivity (S/m)	0.920215

C. SAR Surface and Volume




Maximum location: X=-16.00, Y=13.00 ; SAR Peak: 0.52 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.248823
SAR 1g (W/Kg)	0.369118
Variation (%)	-0.430000

E. Z Axis Scan



SAR Measurement at LTE band 2 (Tilt, Right)


Date of measurement: 6/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.00
Area Scan	dx=15mm dy=15mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Tilt
Band	LTE band 2
Channels	Middle
Signal	LTE (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.619818
Conductivity (S/m)	1.386506

C. SAR Surface and Volume

Maximum location: X=3.00, Y=18.00 ; SAR Peak: 1.92 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.580879
SAR 1g (W/Kg)	1.144965
Variation (%)	-2.710000

E. Z Axis Scan

SAR Measurement at LTE band 5 (Cheek, Right)


Date of measurement: 2/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.73
Area Scan	dx=15mm dy=15mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 5
Channels	Middle
Signal	LTE (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	836.500000
Relative permittivity (real part)	41.960000
Conductivity (S/m)	0.915612

C. SAR Surface and Volume

Maximum location: X=-14.00, Y=16.00 ; SAR Peak: 0.73 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.345103
SAR 1g (W/Kg)	0.517754
Variation (%)	-1.320000

E. Z Axis Scan

SAR Measurement at LTE band 7 (Cheek, Right)

Date of measurement: 10/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.27
Area Scan	dx=12mm dy=12mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 7
Channels	Middle
Signal	LTE (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	2535.000000
Relative permittivity (real part)	39.366661
Conductivity (S/m)	1.960249

C. SAR Surface and Volume




Maximum location: X=-9.00, Y=28.00 ; SAR Peak: 1.94 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.537877
SAR 1g (W/Kg)	1.057456
Variation (%)	-2.360000

E. Z Axis Scan



SAR Measurement at LTE band 12 (Cheek, Right)

Date of measurement: 2/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.70
Area Scan	dx=15mm dy=15mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 12
Channels	Middle
Signal	LTE (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	707.500000
Relative permittivity (real part)	42.126044
Conductivity (S/m)	0.891440

C. SAR Surface and Volume




Maximum location: X=-13.00, Y=15.00 ; SAR Peak: 0.42 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.213543
SAR 1g (W/Kg)	0.311181
Variation (%)	0.000000

E. Z Axis Scan



SAR Measurement at LTE band 41 (Cheek, Right)


Date of measurement: 10/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.27
Area Scan	dx=12mm dy=12mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 41
Channels	Low
Signal	LTE (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	2545.000000
Relative permittivity (real part)	39.366681
Conductivity (S/m)	1.954630

C. SAR Surface and Volume

Maximum location: X=-11.00, Y=26.00 ; SAR Peak: 0.85 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.232987
SAR 1g (W/Kg)	0.451972
Variation (%)	0.890000

E. Z Axis Scan

SAR Measurement at CUSTOM (LTE Band 66) (Tilt, Right)


Date of measurement: 6/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.05
Area Scan	dx=15mm dy=15mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Tilt
Band	LTE band 66
Channels	Low
Signal	LTE (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	1720.000000
Relative permittivity (real part)	39.454615
Conductivity (S/m)	1.352253

C. SAR Surface and Volume

Maximum location: X=5.00, Y=14.00 ; SAR Peak: 2.08 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.660923
SAR 1g (W/Kg)	1.243360
Variation (%)	-0.620000

E. Z Axis Scan

SAR Measurement at IEEE 802.11b ISM (Cheek, Left)

Date of measurement: 10/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.46
Area Scan	dx=12mm dy=12mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Left head
Device Position	Cheek
Band	IEEE 802.11b ISM
Channels	High
Signal	IEEE802.b (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	2462.000000
Relative permittivity (real part)	39.960020
Conductivity (S/m)	1.820812

C. SAR Surface and Volume




Maximum location: X=-19.00, Y=14.00 ; SAR Peak: 0.48 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.161574
SAR 1g (W/Kg)	0.287091
Variation (%)	-1.650000

E. Z Axis Scan



SAR Measurement at CUSTOM (5.2GHz_802.11a) (Cheek, Left)

Date of measurement: 12/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.71
Area Scan	dx=10mm dy=10mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm,Complete
Phantom	Left head
Device Position	Cheek
Band	IEEE 802.11a
Channels	Low
Signal	IEEE802.a (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	5180.000000
Relative permittivity (real part)	35.770000
Conductivity (S/m)	4.617732

C. SAR Surface and Volume




Maximum location: X=-19.00, Y=27.00 ; SAR Peak: 0.42 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.098996
SAR 1g (W/Kg)	0.151121
Variation (%)	-3.460000

E. Z Axis Scan



SAR Measurement at CUSTOM (5.8GHz_802.11a) (Cheek, Left)


Date of measurement: 12/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.94
Area Scan	dx=10mm dy=10mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm,Complete
Phantom	Left head
Device Position	Cheek
Band	IEEE 802.11a
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	5825.000000
Relative permittivity (real part)	35.014699
Conductivity (S/m)	5.201473

C. SAR Surface and Volume

Maximum location: X=-18.00, Y=26.00 ; SAR Peak: 0.35 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.091100
SAR 1g (W/Kg)	0.152242
Variation (%)	-0.150000

E. Z Axis Scan

SAR Measurement at Bluetooth (Cheek, Left)

Date of measurement: 10/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.46
Area Scan	dx=12mm dy=12mm
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Left head
Device Position	Cheek
Band	Bluetooth
Channels	Low
Signal	Bluetooth (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	2402.000000
Relative permittivity (real part)	39.803241
Conductivity (S/m)	1.815538

C. SAR Surface and Volume




Maximum location: X=-27.00, Y=12.00 ; SAR Peak: 0.05 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.030474
SAR 1g (W/Kg)	0.039812
Variation (%)	-0.240000

E. Z Axis Scan



SAR Measurement at CUSTOM (GPRS8502Txslots) (Body, Validation Plane)


Date of measurement: 2/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.70
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	GSM850
Channels	Middle
Signal	TDMA (Crest factor: 4.0)

B. Permittivity


Frequency (MHz)	836.599976
Relative permittivity (real part)	42.350000
Conductivity (S/m)	0.921634

C. SAR Surface and Volume

Maximum location: X=9.00, Y=-10.00 ; SAR Peak: 0.62 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.258144
SAR 1g (W/Kg)	0.414964
Variation (%)	-0.510000

E. Z Axis Scan

SAR Measurement at CUSTOM (GPRS19002Txslots) (Body, Validation Plane)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.00
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	GSM1900
Channels	Middle
Signal	TDMA (Crest factor: 4.0)

B. Permittivity

Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.000020
Conductivity (S/m)	1.400001

C. SAR Surface and Volume




Maximum location: X=2.00, Y=2.00 ; SAR Peak: 0.86 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.305760
SAR 1g (W/Kg)	0.545764
Variation (%)	-4.430000

E. Z Axis Scan



SAR Measurement at Band2_WCDMA1900 (Body, Validation Plane)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.00
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	Band2_WCDMA1900
Channels	High
Signal	WCDMA (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	1907.600000
Relative permittivity (real part)	39.900000
Conductivity (S/m)	1.400001

C. SAR Surface and Volume




Maximum location: X=-13.00, Y=17.00 ; SAR Peak: 0.36 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.132046
SAR 1g (W/Kg)	0.228246
Variation (%)	-2.710000

E. Z Axis Scan



SAR Measurement at CUSTOM (WCDMA 1700) (Body, Validation Plane)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.05
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	Band4_WCDMA1700
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	1732.599976
Relative permittivity (real part)	39.581824
Conductivity (S/m)	1.350012

C. SAR Surface and Volume




Maximum location: X=7.00, Y=-11.00 ; SAR Peak: 0.49 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.176842
SAR 1g (W/Kg)	0.296442
Variation (%)	-0.060000

E. Z Axis Scan



SAR Measurement at Band5_WCDMA850 (Body, Validation Plane)

Date of measurement: 2/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.73
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	Band5_WCDMA850
Channels	Middle
Signal	WCDMA (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	836.599976
Relative permittivity (real part)	42.590000
Conductivity (S/m)	0.920215

C. SAR Surface and Volume




Maximum location: X=5.00, Y=-12.00 ; SAR Peak: 0.36 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.149642
SAR 1g (W/Kg)	0.234967
Variation (%)	0.320000

E. Z Axis Scan



SAR Measurement at LTE band 2 (Body, Validation Plane)


Date of measurement: 6/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.00
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 2
Channels	Low
Signal	LTE (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	1860.000000
Relative permittivity (real part)	39.619823
Conductivity (S/m)	1.378651

C. SAR Surface and Volume

Maximum location: X=-1.00, Y=3.00 ; SAR Peak: 0.79 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.282508
SAR 1g (W/Kg)	0.497921
Variation (%)	1.670000

E. Z Axis Scan

SAR Measurement at LTE band 5 (Body, Validation Plane)


Date of measurement: 2/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.73
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 5
Channels	Middle
Signal	LTE (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	836.500000
Relative permittivity (real part)	41.960000
Conductivity (S/m)	0.915612

C. SAR Surface and Volume

Maximum location: X=3.00, Y=-12.00 ; SAR Peak: 0.32 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.138179
SAR 1g (W/Kg)	0.215880
Variation (%)	-0.820000

E. Z Axis Scan

SAR Measurement at LTE band 7 (Body, Validation Plane)


Date of measurement: 10/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.27
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 7
Channels	Low
Signal	LTE (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	2510.000000
Relative permittivity (real part)	39.266616
Conductivity (S/m)	1.960749

C. SAR Surface and Volume

Maximum location: X=7.00, Y=-24.00 ; SAR Peak: 0.61 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.235038
SAR 1g (W/Kg)	0.367945
Variation (%)	3.480000

E. Z Axis Scan

SAR Measurement at LTE band 12 (Body, Validation Plane)


Date of measurement: 2/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.70
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 12
Channels	Middle
Signal	LTE (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	707.500000
Relative permittivity (real part)	42.126044
Conductivity (S/m)	0.891440

C. SAR Surface and Volume

Maximum location: X=6.00, Y=1.00 ; SAR Peak: 0.16 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.087042
SAR 1g (W/Kg)	0.120419
Variation (%)	-2.730000

E. Z Axis Scan

SAR Measurement at LTE band 41 (Body, Validation Plane)


Date of measurement: 10/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.27
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 41
Channels	Low
Signal	LTE (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	2545.000000
Relative permittivity (real part)	39.366681
Conductivity (S/m)	1.954630

C. SAR Surface and Volume

Maximum location: X=6.00, Y=-24.00 ; SAR Peak: 0.38 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.145845
SAR 1g (W/Kg)	0.241293
Variation (%)	-1.120000

E. Z Axis Scan

SAR Measurement at CUSTOM (LTE Band 66) (Body, Validation Plane)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.05
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Channels	High
Signal	LTE (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	1770.000000
Relative permittivity (real part)	39.745463
Conductivity (S/m)	1.360220

C. SAR Surface and Volume




Maximum location: X=5.00, Y=-12.00 ; SAR Peak: 0.45 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.168605
SAR 1g (W/Kg)	0.281659
Variation (%)	-2.190000

E. Z Axis Scan



SAR Measurement at IEEE 802.11b ISM (Body, Validation Plane)


Date of measurement: 10/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.46
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11b ISM
Channels	High
Signal	IEEE802.b (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	2462.000000
Relative permittivity (real part)	39.960020
Conductivity (S/m)	1.820812

C. SAR Surface and Volume

Maximum location: X=-15.00, Y=7.00 ; SAR Peak: 0.12 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.052712
SAR 1g (W/Kg)	0.078858
Variation (%)	-1.890000

E. Z Axis Scan

SAR Measurement at CUSTOM (5.2GHz_802.11a) (Body, Validation Plane)

Date of measurement: 12/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.71
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11a
Channels	Low
Signal	IEEE802.a (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	5180.000000
Relative permittivity (real part)	35.770000
Conductivity (S/m)	4.617732

C. SAR Surface and Volume




Maximum location: X=13.00, Y=11.00 ; SAR Peak: 0.16 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.073089
SAR 1g (W/Kg)	0.097641
Variation (%)	-0.750000

E. Z Axis Scan



SAR Measurement at CUSTOM (5.8GHz 802.11a) (Body, Validation Plane)


Date of measurement: 12/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	1.94
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11a
Channels	High
Signal	IEEE802.a (Crest factor: 1.0)

B. Permittivity


Frequency (MHz)	5825.000000
Relative permittivity (real part)	35.014699
Conductivity (S/m)	5.201473

C. SAR Surface and Volume

Maximum location: X=11.00, Y=10.00 ; SAR Peak: 0.17 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.059904
SAR 1g (W/Kg)	0.083843
Variation (%)	-0.520000

E. Z Axis Scan

SAR Measurement at Bluetooth (Body, Validation Plane)

Date of measurement: 10/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.46
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	Bluetooth
Channels	Low
Signal	Bluetooth (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	2402.000000
Relative permittivity (real part)	39.803241
Conductivity (S/m)	1.815538

C. SAR Surface and Volume




Maximum location: X=9.00, Y=24.00 ; SAR Peak: 0.03 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.018398
SAR 1g (W/Kg)	0.022362
Variation (%)	-0.840000

E. Z Axis Scan



SAR Measurement at CUSTOM (GPRS19002Txslots) (Body, Validation Plane)


Date of measurement: 6/12/2022

A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.00
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	GSM1900
Channels	Middle
Signal	TDMA (Crest factor: 4.0)

B. Permittivity


Frequency (MHz)	1880.000000
Relative permittivity (real part)	40.000020
Conductivity (S/m)	1.400001

C. SAR Surface and Volume

Maximum location: X=5.00, Y=-10.00 ; SAR Peak: 0.90 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.327499
SAR 1g (W/Kg)	0.587443
Variation (%)	-4.150000

E. Z Axis Scan

SAR Measurement at Band2_WCDMA1900 (Body, Validation Plane)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.00
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	Band2_WCDMA1900
Channels	High
Signal	WCDMA (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	1907.600000
Relative permittivity (real part)	39.900000
Conductivity (S/m)	1.400001

C. SAR Surface and Volume




Maximum location: X=3.00, Y=-12.00 ; SAR Peak: 0.36 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.132970
SAR 1g (W/Kg)	0.231656
Variation (%)	-0.010000

E. Z Axis Scan



SAR Measurement at IEEE 802.11b ISM (Body, Validation Plane)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.46
Area Scan	surf_sam_plan.txt
Zoom Scan	7x7x7,dx=5mm dy=5mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11b ISM
Channels	High
Signal	IEEE802.b (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	2462.000000
Relative permittivity (real part)	39.960020
Conductivity (S/m)	1.820812

C. SAR Surface and Volume




Maximum location: X=6.00, Y=-1.00 ; SAR Peak: 0.13 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.050689
SAR 1g (W/Kg)	0.080868
Variation (%)	-2.560000

E. Z Axis Scan



SAR Measurement at CUSTOM (LTE Band 66) (Body, Validation Plane)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.05
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Channels	Low
Signal	LTE (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	1720.000000
Relative permittivity (real part)	39.454615
Conductivity (S/m)	1.352253

C. SAR Surface and Volume




Maximum location: X=-8.00, Y=20.00 ; SAR Peak: 1.73 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.478809
SAR 1g (W/Kg)	0.940407
Variation (%)	-1.760000

E. Z Axis Scan



SAR Measurement at CUSTOM (LTE Band 66) (Body, Validation Plane)

Date of measurement: 6/12/2022


A. Experimental conditions.

Probe	SN 18/21 EPG0354
ConvF	2.05
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Channels	Low
Signal	LTE (Crest factor: 1.0)

B. Permittivity

Frequency (MHz)	1720.000000
Relative permittivity (real part)	39.454615
Conductivity (S/m)	1.352253

C. SAR Surface and Volume




Maximum location: X=9.00, Y=19.00 ; SAR Peak: 1.62 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.466067
SAR 1g (W/Kg)	0.917607
Variation (%)	-0.850000

E. Z Axis Scan



Appendix C: System Calibration Certificate

Calibration information for E-field probes



COMOSAR E-Field Probe Calibration Report

Ref : ACR.140.1.21.BES.B

Cancel and replace the report ACR.140.1.21.BES.A

**JIANYAN TESTING GROUP SHENZHEN
CO.,LTD.**

**NO.101, BUILDING 8, INNOVATION WISDOM PORT, NO.155
HONGTIAN ROAD, HUANGPU COMMUNITY, XINQIAO
STREET,
BAO'AN DISTRICT, SHENZHEN, GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 18/21 EPG0354**

Calibrated at MVG

Z.I. de la pointe du diable

**Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE**

Calibration date: 05/20/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited COMOSAR E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).

Page: 1/10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.1401.21.BES.B

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	5/20/2021	
Checked by :	Jérôme Luc	Technical Manager	5/20/2021	
Approved by :	Yann Toutain	Laboratory Director	5/21/2021	

	Customer Name
Distribution :	JIANYAN TESTING GROUP SHENZHEN CO.,LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	5/20/2021	Initial release
B	Jérôme Luc	5/21/2021	Change customer address Add picture 1 Add 1450 MHz calibration

Page: 2/10

Template: ACR.DDD.N.YY.MVGB.ISSUE - COMOSAR Probe vH

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.1	Boundary Effect	5
4	Measurement Uncertainty	6
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	8
5.4	Isotropy	9
6	List of Equipment	10



1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 18/21 EPG0354
Product Condition (new / used)	New
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.202 MΩ Dipole 2: R2=0.217 MΩ Dipole 3: R3=0.225 MΩ

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.1 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \Delta SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-d_{be}/\delta} - e^{-(d_{be} + d_{step})/\delta})}{\delta/2} \text{ for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

$SAR_{uncertainty}$	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
Δ_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14$ mm at 3 GHz
ΔSAR_{be}	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.

Page: 5/10

Template: ACR.DDD.N.YY.MVGB.ISSUE, COMOSAR Probe vH

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



The measured worst case boundary effect SAR uncertainty[%] for scanning distances larger than 4mm is 1.0% Limit ,2%).

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	d	Standard Uncertainty (%)
Expanded uncertainty 95 % confidence level k = 2					14 %

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

5.1 SENSITIVITY IN AIR

Normx dipole 1 (μV/(V/m) ²)	Normy dipole 2 (μV/(V/m) ²)	Normz dipole 3 (μV/(V/m) ²)
0.86	0.87	0.90

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
107	101	105


Calibration curves $e_i = f(V)$ (i=1,2,3) allow to obtain E-field value using the formula:

$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.1401.21.BES.B



5.2 LINEARITY



Linearity: $\pm 1.55\%$ ($\pm 0.07\text{dB}$)

Page: 7/10

Template: ACR.DDD.N.YY.MVGB.ISSUE_COMOSAR_Probe.vH

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.140.1.21.BES.B

5.3 SENSITIVITY IN LIQUID

Liquid	Frequency (MHz +/- 100MHz)	ConvF
HL450*	450	1.92
BL450*	450	1.87
HL750	750	1.73
BL750	750	1.81
HL850	835	1.68
BL850	835	1.82
HL900	900	1.88
BL900	900	1.92
HL1450	1450	2.25
BL1450	1450	2.54
HL1750	1750	2.07
BL1750	1750	2.20
HL1900	1900	2.14
BL1900	1900	2.23
HL2100	2100	2.09
BL2100	2100	2.27
HL2300	2300	2.23
BL2300	2300	2.48
HL2450	2450	2.23
BL2450	2450	2.58
HL2600	2600	2.15
BL2600	2600	2.38
HL3300	3300	2.02
BL3300	3300	2.19
HL3500	3500	2.11
BL3500	3500	2.29
HL3700	3700	2.13
BL3700	3700	2.28
HL3900	3900	2.26
BL3900	3900	2.48
HL4200	4200	2.58
BL4200	4200	2.63
HL4600	4600	2.44
BL4600	4600	2.60
HL4900	4900	2.34
BL4900	4900	2.32
HL5200	5200	1.86
BL5200	5200	1.75
HL5400	5400	2.07
BL5400	5400	1.94
HL5600	5600	2.20
BL5600	5600	2.11
HL5800	5800	2.07
BL5800	5800	1.99

* Frequency not cover by COFRAC scope, calibration not accredited

LOWER DETECTION LIMIT: 8mW/kg

Page: 8/10

Template: ACR.DDD.N.YY.MVGB.ISSUE_COMOSAR_Probe.vH

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.140.1.21.BES.B

5.4 ISOTROPY

HL1900 MHz



Page: 9/10

Template: ACR.DDD.N.YY.MVGB.ISSUE: COMOSAR Probe vH

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated. No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Waveguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023

Calibration information for Dipole



SAR Reference Dipole Calibration Report

Ref : ACR.15.5.21.MVGB.B

Cancel and replace the report ACR.15.5.21.MVGB.A

**JIANYAN TESTING GROUP
SHENZHEN CO.,LTD.**

**No.110~116, BUILDING B, JINYUAN BUSINESS BUILDING,
XIXIANG ROAD, BAOAN DISTRICT,
SHENZHEN, GUANGDONG, PR CHINA**

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 750 MHZ

SERIAL NO.: SN 50/20 DIP 0G750-506

Calibrated at MVG

Z.I. de la pointe du diable

**Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE**

Calibration date: 01/14/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.

Page: 1/13



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.5.21.MVGB.B

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Technical Manager	1/15/2021	<i>JLS</i>
Checked by :	Jérôme LUC	Technical Manager	1/15/2021	<i>JLS</i>
Approved by :	Yann Toutain	Laboratory Director	2/8/2021	<i>Yann Toutain</i>

2021.02.0
8 17:46:38
+01'00'

	Customer Name
Distribution :	JianYan Testing Group Shenzhen Co.,Ltd.

Issue	Name	Date	Modifications
A	Jérôme LUC	1/15/2021	Initial release
B	Jérôme LUC	2/8/2021	Change customer name/address



TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results	6
6.1	Return Loss and Impedance In Head Liquid	6
6.2	Return Loss and Impedance In Body Liquid	6
6.3	Mechanical Dimensions	7
7	Validation measurement	7
7.1	Head Liquid Measurement	8
7.2	SAR Measurement Result With Head Liquid	8
7.3	Body Liquid Measurement	11
7.4	SAR Measurement Result With Body Liquid	12
8	List of Equipment	13



1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 750 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID750
Serial Number	SN 50/20 DIP 0G750-506
Product Condition (new / used)	New

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.5.21.MVGB.B

Scan Volume	Expanded Uncertainty
1 g	19 % (SAR)
10 g	19 % (SAR)


6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE IN HEAD LIQUID



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-25.31	-20	54.0 Ω - 3.7 j Ω

6.2 RETURN LOSS AND IMPEDANCE IN BODY LIQUID



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-27.14	-20	54.2 Ω + 1.4 j Ω

Page: 6/13

Template: ACR.DDD.N.YE.MVGB.ISSUE, SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.5.21.MVGB.B

6.3 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 ±1 %		250.0 ±1 %		6.35 ±1 %	
450	290.0 ±1 %		166.7 ±1 %		6.35 ±1 %	
750	176.0 ±1 %	177.03	100.0 ±1 %	100.34	6.35 ±1 %	6.35
835	161.0 ±1 %		89.8 ±1 %		3.6 ±1 %	
900	149.0 ±1 %		83.3 ±1 %		3.6 ±1 %	
1450	89.1 ±1 %		51.7 ±1 %		3.6 ±1 %	
1500	80.5 ±1 %		50.0 ±1 %		3.6 ±1 %	
1640	79.0 ±1 %		45.7 ±1 %		3.6 ±1 %	
1750	75.2 ±1 %		42.9 ±1 %		3.6 ±1 %	
1800	72.0 ±1 %		41.7 ±1 %		3.6 ±1 %	
1900	68.0 ±1 %		39.5 ±1 %		3.6 ±1 %	
1950	66.3 ±1 %		38.5 ±1 %		3.6 ±1 %	
2000	64.5 ±1 %		37.5 ±1 %		3.6 ±1 %	
2100	61.0 ±1 %		35.7 ±1 %		3.6 ±1 %	
2300	55.5 ±1 %		32.6 ±1 %		3.6 ±1 %	
2450	51.5 ±1 %		30.4 ±1 %		3.6 ±1 %	
2600	48.5 ±1 %		28.8 ±1 %		3.6 ±1 %	
3000	41.5 ±1 %		25.0 ±1 %		3.6 ±1 %	
3300	-		-		-	
3500	37.0 ±1 %		26.4 ±1 %		3.6 ±1 %	
3700	34.7 ±1 %		26.4 ±1 %		3.6 ±1 %	
3900	-		-		-	
4200	-		-		-	
4600	-		-		-	
4900	-		-		-	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

Page: 7/13

Template: ACR.DDD.N.YE.MVGB.ISSUE, SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.5.21.MVGB.B

7.1 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 $\pm$ 10 %		0.87 $\pm$ 10 %	
450	43.5 $\pm$ 10 %		0.87 $\pm$ 10 %	
750	41.9 $\pm$ 10 %	41.8	0.89 $\pm$ 10 %	0.82
835	41.5 $\pm$ 10 %		0.90 $\pm$ 10 %	
900	41.5 $\pm$ 10 %		0.97 $\pm$ 10 %	
1450	40.5 $\pm$ 10 %		1.20 $\pm$ 10 %	
1500	40.4 $\pm$ 10 %		1.23 $\pm$ 10 %	
1640	40.2 $\pm$ 10 %		1.31 $\pm$ 10 %	
1750	40.1 $\pm$ 10 %		1.37 $\pm$ 10 %	
1800	40.0 $\pm$ 10 %		1.40 $\pm$ 10 %	
1900	40.0 $\pm$ 10 %		1.40 $\pm$ 10 %	
1950	40.0 $\pm$ 10 %		1.40 $\pm$ 10 %	
2000	40.0 $\pm$ 10 %		1.40 $\pm$ 10 %	
2100	39.8 $\pm$ 10 %		1.49 $\pm$ 10 %	
2300	39.5 $\pm$ 10 %		1.67 $\pm$ 10 %	
2450	39.2 $\pm$ 10 %		1.80 $\pm$ 10 %	
2600	39.0 $\pm$ 10 %		1.96 $\pm$ 10 %	
3000	38.5 $\pm$ 10 %		2.40 $\pm$ 10 %	
3300	38.2 $\pm$ 10 %		2.71 $\pm$ 10 %	
3500	37.9 $\pm$ 10 %		2.91 $\pm$ 10 %	
3700	37.7 $\pm$ 10 %		3.12 $\pm$ 10 %	
3900	37.5 $\pm$ 10 %		3.32 $\pm$ 10 %	
4200	37.1 $\pm$ 10 %		3.63 $\pm$ 10 %	
4600	36.7 $\pm$ 10 %		4.04 $\pm$ 10 %	
4900	36.3 $\pm$ 10 %		4.35 $\pm$ 10 %	

7.2 SAR MEASUREMENT RESULT WITH HEAD LIQUID

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Page: 8/13

Template: ACR.DDD.N.YE.MVGB.ISSUE SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.5.21.MVGB.B

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPG0333
Liquid	Head Liquid Values: ϵ_p : 41.8 σ : 0.82
Distance between dipole center and liquid	15.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=8mm/dy=8mm/dz=5mm$
Frequency	750 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49	8.57 (0.86)	5.55	5.56 (0.56)
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3300	-		-	
3500	67.1		25	
3700	67.4		24.2	
3900	-		-	
4200	-		-	
4600	-		-	
4900	-		-	

Page: 9/13


Template: ACR.DDD.N.YE.MVGB.ISSUE: SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.5.21.MVGB.B



Page: 10/13

Template: ACR.DDD.N.YE.MVGB.ISSUE SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.5.21.MVGB.B

7.3 BODY LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
150	61.9 $\pm$ 10 %		0.80 $\pm$ 10 %	
300	58.2 $\pm$ 10 %		0.92 $\pm$ 10 %	
450	56.7 $\pm$ 10 %		0.94 $\pm$ 10 %	
750	55.5 $\pm$ 10 %	52.9	0.96 $\pm$ 10 %	0.89
835	55.2 $\pm$ 10 %		0.97 $\pm$ 10 %	
900	55.0 $\pm$ 10 %		1.05 $\pm$ 10 %	
915	55.0 $\pm$ 10 %		1.06 $\pm$ 10 %	
1450	54.0 $\pm$ 10 %		1.30 $\pm$ 10 %	
1610	53.8 $\pm$ 10 %		1.40 $\pm$ 10 %	
1800	53.3 $\pm$ 10 %		1.52 $\pm$ 10 %	
1900	53.3 $\pm$ 10 %		1.52 $\pm$ 10 %	
2000	53.3 $\pm$ 10 %		1.52 $\pm$ 10 %	
2100	53.2 $\pm$ 10 %		1.62 $\pm$ 10 %	
2300	52.9 $\pm$ 10 %		1.81 $\pm$ 10 %	
2450	52.7 $\pm$ 10 %		1.95 $\pm$ 10 %	
2600	52.5 $\pm$ 10 %		2.16 $\pm$ 10 %	
3000	52.0 $\pm$ 10 %		2.73 $\pm$ 10 %	
3300	51.6 $\pm$ 10 %		3.08 $\pm$ 10 %	
3500	51.3 $\pm$ 10 %		3.31 $\pm$ 10 %	
3700	51.0 $\pm$ 10 %		3.55 $\pm$ 10 %	
3900	50.8 $\pm$ 10 %		3.78 $\pm$ 10 %	
4200	50.4 $\pm$ 10 %		4.13 $\pm$ 10 %	
4600	49.8 $\pm$ 10 %		4.60 $\pm$ 10 %	
4900	49.4 $\pm$ 10 %		4.95 $\pm$ 10 %	
5200	49.0 $\pm$ 10 %		5.30 $\pm$ 10 %	
5300	48.9 $\pm$ 10 %		5.42 $\pm$ 10 %	
5400	48.7 $\pm$ 10 %		5.53 $\pm$ 10 %	
5500	48.6 $\pm$ 10 %		5.65 $\pm$ 10 %	
5600	48.5 $\pm$ 10 %		5.77 $\pm$ 10 %	
5800	48.2 $\pm$ 10 %		6.00 $\pm$ 10 %	

Page: 11/13

Template: ACR.DDD.N.YE.MVGB.ISSUE SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.5.21.MVGB.B

7.4 SAR MEASUREMENT RESULT WITH BODY LIQUID

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPG0333
Liquid	Body Liquid Values: $\epsilon_{ps}' : 52.9$ $\sigma : 0.89$
Distance between dipole center and liquid	15.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=8mm/dy=8mm/dz=5mm$
Frequency	750 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

Frequency MHz	1 g SAR (W/kg/W)	10 g SAR (W/kg/W)
	measured	measured
750	8.62 (0.86)	5.73 (0.57)





8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023

Dipole Impedance and Return Loss calibration Report


Object: SID750- SN 50/20 DIP 0G750-506
Calibration Date: January 14, 2022
Calibration reference: IEEE Std 1528:2013, IEC 62209-1:2016, FCC KDB 865664 D01
Calibrated By: *Janet Wei* (Janet Wei, SAR project engineer)
Reviewed By: *Winner Zhang* (Winner Zhang, Technical manager)

Environment of Test Site

Temperature:	18 ~ 25 °C
Humidity:	50~60% RH
Atmospheric Pressure:	1011 mbar

Test Data

Measurement Plot for Head TSL In 2022



Comparison with Original report

Items	Calibrated By MVG	Calibrated By JYT In 2022	Deviation	Limit
Impedence for Head TSL	54.0Ω -3.70jΩ	53.68Ω -3.81jΩ	-0.32Ω -0.11jΩ	±5Ω
Return Loss for Head TSL	-25.31	-25.84	2.09%	±20%(No less than 20 dB)

Result

Compliance

JianYan Testing Group Shenzhen Co., Ltd.

No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Telephone: +86 (0) 755 23118282 Fax: +86 (0) 755 23116366, E-mail: info-JYTee@lets.com

Project No.: JYTSZR2211079

Page 160 of 248



SAR Reference Dipole Calibration Report

Ref : ACR.15.6.21.MVGB.B

Cancel and replace the report ACR.15.6.21.MVGB.A

JIANYAN TESTING GROUP SHENZHEN CO.,LTD.

No.110~116, BUILDING B, JINYUAN BUSINESS BUILDING,
XIXIANG ROAD, BAOAN DISTRICT,
SHENZHEN, GUANGDONG, PR CHINA

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 835 MHZ

SERIAL NO.: SN 50/20 DIP 0G835-507

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon

29280 PLOUZANE - FRANCE

Calibration date: 01/14/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.6.21.MVGB.B

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Technical Manager	1/15/2021	<i>JLS</i>
Checked by :	Jérôme LUC	Technical Manager	1/15/2021	<i>JLS</i>
Approved by :	Yann Toutain	Laboratory Director	2/8/2021	<i>Yann Toutain</i>

2021.02.0
8 17:47:44
+01'00'

	Customer Name
Distribution :	JianYan Testing Group Shenzhen Co.,Ltd.

Issue	Name	Date	Modifications
A	Jérôme LUC	1/15/2021	Initial release
B	Jérôme LUC	2/8/2021	Change customer name/address



TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results	6
6.1	Return Loss and Impedance In Head Liquid	6
6.2	Return Loss and Impedance In Body Liquid	6
6.3	Mechanical Dimensions	7
7	Validation measurement	7
7.1	Head Liquid Measurement	8
7.2	SAR Measurement Result With Head Liquid	8
7.3	Body Liquid Measurement	11
7.4	SAR Measurement Result With Body Liquid	12
8	List of Equipment	13



1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 835 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID835
Serial Number	SN 50/20 DIP 0G835-507
Product Condition (new / used)	New

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.6.21.MVGB.B

Scan Volume	Expanded Uncertainty
1 g	19 % (SAR)
10 g	19 % (SAR)


6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE IN HEAD LIQUID



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
835	-30.14	-20	$51.3 \Omega - 2.8 j\Omega$

6.2 RETURN LOSS AND IMPEDANCE IN BODY LIQUID



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
835	-30.96	-20	$47.2 \Omega - 0.4 j\Omega$



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.6.21.MVGB.B

6.3 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 ±1 %		250.0 ±1 %		6.35 ±1 %	
450	290.0 ±1 %		166.7 ±1 %		6.35 ±1 %	
750	176.0 ±1 %		100.0 ±1 %		6.35 ±1 %	
835	161.0 ±1 %	161.29	89.8 ±1 %	89.25	3.6 ±1 %	3.59
900	149.0 ±1 %		83.3 ±1 %		3.6 ±1 %	
1450	89.1 ±1 %		51.7 ±1 %		3.6 ±1 %	
1500	80.5 ±1 %		50.0 ±1 %		3.6 ±1 %	
1640	79.0 ±1 %		45.7 ±1 %		3.6 ±1 %	
1750	75.2 ±1 %		42.9 ±1 %		3.6 ±1 %	
1800	72.0 ±1 %		41.7 ±1 %		3.6 ±1 %	
1900	68.0 ±1 %		39.5 ±1 %		3.6 ±1 %	
1950	66.3 ±1 %		38.5 ±1 %		3.6 ±1 %	
2000	64.5 ±1 %		37.5 ±1 %		3.6 ±1 %	
2100	61.0 ±1 %		35.7 ±1 %		3.6 ±1 %	
2300	55.5 ±1 %		32.6 ±1 %		3.6 ±1 %	
2450	51.5 ±1 %		30.4 ±1 %		3.6 ±1 %	
2600	48.5 ±1 %		28.8 ±1 %		3.6 ±1 %	
3000	41.5 ±1 %		25.0 ±1 %		3.6 ±1 %	
3300	-		-		-	
3500	37.0 ±1 %		26.4 ±1 %		3.6 ±1 %	
3700	34.7 ±1 %		26.4 ±1 %		3.6 ±1 %	
3900	-		-		-	
4200	-		-		-	
4600	-		-		-	
4900	-		-		-	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

Page: 7/13

Template: ACR.DDD.N.YE.MVGB.ISSUE: SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



7.1 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 $\pm$ 10 %		0.87 $\pm$ 10 %	
450	43.5 $\pm$ 10 %		0.87 $\pm$ 10 %	
750	41.9 $\pm$ 10 %		0.89 $\pm$ 10 %	
835	41.5 $\pm$ 10 %	40.6	0.90 $\pm$ 10 %	0.89
900	41.5 $\pm$ 10 %		0.97 $\pm$ 10 %	
1450	40.5 $\pm$ 10 %		1.20 $\pm$ 10 %	
1500	40.4 $\pm$ 10 %		1.23 $\pm$ 10 %	
1640	40.2 $\pm$ 10 %		1.31 $\pm$ 10 %	
1750	40.1 $\pm$ 10 %		1.37 $\pm$ 10 %	
1800	40.0 $\pm$ 10 %		1.40 $\pm$ 10 %	
1900	40.0 $\pm$ 10 %		1.40 $\pm$ 10 %	
1950	40.0 $\pm$ 10 %		1.40 $\pm$ 10 %	
2000	40.0 $\pm$ 10 %		1.40 $\pm$ 10 %	
2100	39.8 $\pm$ 10 %		1.49 $\pm$ 10 %	
2300	39.5 $\pm$ 10 %		1.67 $\pm$ 10 %	
2450	39.2 $\pm$ 10 %		1.80 $\pm$ 10 %	
2600	39.0 $\pm$ 10 %		1.96 $\pm$ 10 %	
3000	38.5 $\pm$ 10 %		2.40 $\pm$ 10 %	
3300	38.2 $\pm$ 10 %		2.71 $\pm$ 10 %	
3500	37.9 $\pm$ 10 %		2.91 $\pm$ 10 %	
3700	37.7 $\pm$ 10 %		3.12 $\pm$ 10 %	
3900	37.5 $\pm$ 10 %		3.32 $\pm$ 10 %	
4200	37.1 $\pm$ 10 %		3.63 $\pm$ 10 %	
4600	36.7 $\pm$ 10 %		4.04 $\pm$ 10 %	
4900	36.3 $\pm$ 10 %		4.35 $\pm$ 10 %	

7.2 SAR MEASUREMENT RESULT WITH HEAD LIQUID

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.6.21.MVGB.B

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPG0333
Liquid	Head Liquid Values: ϵ_p : 40.6 σ : 0.89
Distance between dipole center and liquid	15.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=8mm/dy=8mm/dz=5mm$
Frequency	835 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56	9.57 (0.96)	6.22	6.04 (0.60)
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3300	-		-	
3500	67.1		25	
3700	67.4		24.2	
3900	-		-	
4200	-		-	
4600	-		-	
4900	-		-	

Page: 9/13


Template: ACR.DDD.N.YE.MVGB.ISSUE: SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.6.21.MVGB.B





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.6.21.MVGB.B

7.3 BODY LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
150	61.9 $\pm$ 10 %		0.80 $\pm$ 10 %	
300	58.2 $\pm$ 10 %		0.92 $\pm$ 10 %	
450	56.7 $\pm$ 10 %		0.94 $\pm$ 10 %	
750	55.5 $\pm$ 10 %		0.96 $\pm$ 10 %	
835	55.2 $\pm$ 10 %	52.3	0.97 $\pm$ 10 %	0.94
900	55.0 $\pm$ 10 %		1.05 $\pm$ 10 %	
915	55.0 $\pm$ 10 %		1.06 $\pm$ 10 %	
1450	54.0 $\pm$ 10 %		1.30 $\pm$ 10 %	
1610	53.8 $\pm$ 10 %		1.40 $\pm$ 10 %	
1800	53.3 $\pm$ 10 %		1.52 $\pm$ 10 %	
1900	53.3 $\pm$ 10 %		1.52 $\pm$ 10 %	
2000	53.3 $\pm$ 10 %		1.52 $\pm$ 10 %	
2100	53.2 $\pm$ 10 %		1.62 $\pm$ 10 %	
2300	52.9 $\pm$ 10 %		1.81 $\pm$ 10 %	
2450	52.7 $\pm$ 10 %		1.95 $\pm$ 10 %	
2600	52.5 $\pm$ 10 %		2.16 $\pm$ 10 %	
3000	52.0 $\pm$ 10 %		2.73 $\pm$ 10 %	
3300	51.6 $\pm$ 10 %		3.08 $\pm$ 10 %	
3500	51.3 $\pm$ 10 %		3.31 $\pm$ 10 %	
3700	51.0 $\pm$ 10 %		3.55 $\pm$ 10 %	
3900	50.8 $\pm$ 10 %		3.78 $\pm$ 10 %	
4200	50.4 $\pm$ 10 %		4.13 $\pm$ 10 %	
4600	49.8 $\pm$ 10 %		4.60 $\pm$ 10 %	
4900	49.4 $\pm$ 10 %		4.95 $\pm$ 10 %	
5200	49.0 $\pm$ 10 %		5.30 $\pm$ 10 %	
5300	48.9 $\pm$ 10 %		5.42 $\pm$ 10 %	
5400	48.7 $\pm$ 10 %		5.53 $\pm$ 10 %	
5500	48.6 $\pm$ 10 %		5.65 $\pm$ 10 %	
5600	48.5 $\pm$ 10 %		5.77 $\pm$ 10 %	
5800	48.2 $\pm$ 10 %		6.00 $\pm$ 10 %	

Page: 11/13

Template: ACR.DDD.N.YE.MVGB.ISSUE: SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.15.6.21.MVGB.B

7.4 SAR MEASUREMENT RESULT WITH BODY LIQUID

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPG0333
Liquid	Body Liquid Values: $\epsilon_{ps}' : 52.3$ $\sigma : 0.94$
Distance between dipole center and liquid	15.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=8mm/dy=8mm/dz=5mm$
Frequency	835 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

Frequency MHz	1 g SAR (W/kg/W)	10 g SAR (W/kg/W)
	measured	measured
835	9.77 (0.98)	6.36 (0.64)





8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023

Dipole Impedance and Return Loss calibration Report


Object: SID835 - SN 50/20 DIP 0G835-507
Calibration Date: January 14, 2022
Calibration reference: IEEE Std 1528:2013, IEC 62209-1:2016, FCC KDB 865664 D01
Calibrated By: *Janet Wei* (Janet Wei, SAR project engineer)
Reviewed By: *Winner Zhang* (Winner Zhang, Technical manager)

Environment of Test Site

Temperature:	18 ~ 25 C
Humidity:	50~60% RH
Atmospheric Pressure:	1011 mbar

Test Data

Measurement Plot for Head TSL In 2022



Comparison with Original report

Items	Calibrated By MVG	Calibrated By JYT In 2022	Deviation	Limit
Impedence for Head TSL	51.3Ω -2.8jΩ	51.58Ω +1.70jΩ	0.28Ω -4.50jΩ	±5Ω
Return Loss for Head TSL	-30.14	-32.82	8.89%	±20%(No less than 20 dB)

Result

Compliance

JianYan Testing Group Shenzhen Co., Ltd.

No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Telephone: +86 (0) 755 23118282 Fax: +86 (0) 755 23116366, E-mail: info-JYTee@lets.com

Project No.: JYTSZR2211079

Page 175 of 248