

## FCC RF Exposure

EUT Description: LED control card

Model No.: RHX8-Q1C

Series Model: RHX8-Q2, RHX8-C1, RHX8-32W320, GAS-MUM-STC

Num-stc-rj45

FCC ID: 2BMW2-RHX8-Q1C

Equipment type: Mobile Device equipment

Test procedures according to the technical standards: KDB 447498 D01 V06 and FCC 2.1091.

### 1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F = frequency in MHz

Formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where :

$P_d$  = power density in mW/cm<sup>2</sup>,

$P_{out}$  = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi$  = 3.14;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## 3. Test Result of RF Exposure Evaluation

### WIFI

Modulation	Channel Freq. (MHz)	Conduct ed power (dBm)	Max tune-up power (mW)	Antenna Gain (dBi)	Antenna gain numeric	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
802.11b	2412	17.89	61.51768	2.03	1.60	0.01959162	1
	2437	16.98	49.88844	2.03	1.60	0.015888041	1
	2462	16.89	48.86523	2.03	1.60	0.015562177	1
802.11g	2412	16.92	49.20395	2.03	1.60	0.015670049	1
	2437	16.67	46.45152	2.03	1.60	0.01479348	1
	2462	16.81	47.97334	2.03	1.60	0.015278135	1
802.11n	2412	16.85	48.41723	2.03	1.60	0.015419502	1
	2437	16.76	47.42419	2.03	1.60	0.015103248	1
	2462	16.80	47.86300	2.03	1.60	0.015242997	1

Wifi: Conclusion: the max result 0.01959162: ≤ 1.0 compliance with FCC's RF Exposure.

Conclusion: No SAR is required