

RF Exposure Report

Report No.: MFBCMA-WTW-P23030799B

FCC ID: RAXTMOG4AR

Test Model: TMO-G4AR

Received Date: 2023/3/15

Test Date: 2023/6/26

Issued Date: 2023/6/27

Applicant: Arcadyan Technology Corporation

Address: No.8, Sec.2, Guangfu Rd., Hsinchu City 30071, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	10

Release Control Record

Issue No.	Description	Date Issued
MFBCMA-WTW-P23030799B	Original release.	2023/6/27

1 Certificate of Conformity

Product: 5G Gateway

Brand: T-Mobile

Test Model: TMO-G4AR

Sample Status: Engineering sample

Applicant: Arcadyan Technology Corporation


Test Date: 2023/6/26

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standard: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :



Polly Chien / Specialist

Date:

2023/6/27

Approved by :



Jeremy Lin / Project Engineer

Date:

2023/6/27

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 21 cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna NO.	RF Chain NO.	Brand	Model	Antenna Net Gain (dBi)	Frequency range	Antenna Type	Connector Type	Cable Length (mm)
Wi-Fi + BT	Ant. 0	PSA	RFPCA261017IMLB403_A	1.77	2.4~2.4835 GHz	Dipole	ipex(MHF1)	171
				0.68	5.15~5.25 GHz			
				0.81	5.25~5.35 GHz			
				1.25	5.47~5.725 GHz			
				2.35	5.725~5.85 GHz			
	Ant. 1	PSA	RFPCA261013IMLB402_A	1.49	2.4~2.4835 GHz	Dipole	ipex(MHF1)	130
				0.42	5.15~5.25 GHz			
				1.01	5.25~5.35 GHz			
				1.68	5.47~5.725 GHz			
				2.14	5.725~5.85 GHz			
	Ant. 2	PSA	RFPCA261007IMLB402_A	1.33	2.4~2.4835 GHz	Dipole	ipex(MHF1)	75
				0.71	5.15~5.25 GHz			
				1.12	5.25~5.35 GHz			
				1.54	5.47~5.725 GHz			
				2.13	5.725~5.85 GHz			
	Ant. 3	PSA	RFPCA261008IMLB401_A	1.25	2.4~2.4835 GHz	Dipole	ipex(MHF1)	80
				0.58	5.15~5.25 GHz			
				1.23	5.25~5.35 GHz			
				1.49	5.47~5.725 GHz			
				2.32	5.725~5.85 GHz			
	BT+DFS(RX)	PSA	RFPCA261024IMLB401_A	4.72	2.4~2.4835 GHz	Dipole	ipex(MHF1)	245
				3.90	5.15~5.25 GHz			
				4.23	5.25~5.35 GHz			
				4.43	5.47~5.725 GHz			
				4.43	5.725~5.85 GHz			

Antenna NO.	RF Chain NO.	Brand	Model	Antenna Net Gain (dBi)	Frequency range	Antenna Type	Connector Type	Cable Length (mm)
WWAN Antenna (Internal)	B71 (TRx) (M2)	PSA	RFPCA811609IMMB403_B	3.17	663-698 MHz	Monopole	ipex(MHF1)	94
	B71 (Rx)(M1)		RFPCA811609IMMB402_A	3.10	663-698 MHz	Monopole	ipex(MHF1)	93
	B71 (Rx) (D1)		RFPCA652018IMMB401_A	2.09	663-698 MHz	Monopole	ipex(MHF1)	205
	B71 (Rx)(D2)		RFFPA656320IMMB401_B	2.01	663-698 MHz	Monopole	ipex(MHF1)	189
	B12 (TRx)(M2)	PSA	RFPCA811609IMMB403_B	3.34	698-716 MHz	Monopole	ipex(MHF1)	94
	B12 (Rx)(D2)		RFFPA656320IMMB401_B	2.05	698-716 MHz	Monopole	ipex(MHF1)	189
	B5 (TRx)(M2)	PSA	RFPCA811609IMMB403_B	1.68	824-849 MHz	Monopole	ipex(MHF1)	94
	B5 (Rx) (D2)		RFFPA656320IMMB401_B	0.63	824-849 MHz	Monopole	ipex(MHF1)	189
	B4/B66 (TRx) (M2)	PSA	RFPCA811609IMMB403_B	3.69	1710-1780 MHz	Monopole	ipex(MHF1)	94
	B4/B66 (TRx) (M1)		RFPCA811609IMMB402_A	5.13	1710-1780 MHz	Monopole	ipex(MHF1)	93
	B4/B66 (Rx) (D1)		RFPCA652018IMMB401_A	4.26	1710-1780 MHz	Monopole	ipex(MHF1)	205
	B4/B66 (Rx) (D2)		RFFPA656320IMMB401_B	4.10	1710-1780 MHz	Monopole	ipex(MHF1)	189
	B2/B25 (TRx) (M2)	PSA	RFPCA811609IMMB403_B	3.33	1850-1915 MHz	Monopole	ipex(MHF1)	94
	B2/B25 (TRx) (M1)		RFPCA811609IMMB402_A	4.78	1850-1915 MHz	Monopole	ipex(MHF1)	93
	B2/B25 (Rx) (D1)		RFPCA652018IMMB401_A	3.79	1850-1915 MHz	Monopole	ipex(MHF1)	205
	B2/B25 (Rx) (D2)		RFFPA656320IMMB401_B	4.11	1850-1915 MHz	Monopole	ipex(MHF1)	189
	B41 (TRx) (M2)	PSA	RFPCA811609IMMB403_B	2.78	2496-2690 MHz	Monopole	ipex(MHF1)	94
	B41 (TRx) (M1)		RFPCA811609IMMB402_A	3.02	2496-2690 MHz	Monopole	ipex(MHF1)	93
	B41 (Rx) (Omni-Antenna HC1O)		RFPCA380906IMMB401_A	4.45	2496-2690 MHz	Dipole	ipex(MHF1)	60
	B41 (Rx) (Omni-Antenna HC2O)		RFPCA380912IMMB401_A	3.67	2496-2690 MHz	Dipole	ipex(MHF1)	125
	B41 (Rx) (Semi-Antenna HC1S)		RFPCA474709IMMB401_A	7.59	2496-2690 MHz	Dipole	ipex(MHF1)	96
	B41 (Rx) (Semi-Antenna HC2S)		RFPCA474709IMMB401_A	7.76	2496-2690 MHz	Dipole	ipex(MHF1)	82
	B48 (TRx) (M2)		RFPCA811609IMMB403_B	0.94	3550-3700 MHz	Monopole	ipex(MHF1)	94
	B48 (TRx) (M1)		RFPCA811609IMMB402_A	1.02	3550-3700 MHz	Monopole	ipex(MHF1)	93
	B48 (Rx) (Omni-Antenna HC1O)	PSA	RFPCA380906IMMB401_A	4.64	3550-3700 MHz	Dipole	ipex(MHF1)	60
	B48 (Rx) (Omni-Antenna HC2O)		RFPCA380912IMMB401_A	4.03	3550-3700 MHz	Dipole	ipex(MHF1)	125
	B48 (Rx) (Semi-Antenna HC1S)		RFPCA474709IMMB401_A	7.67	3550-3700 MHz	Dipole	ipex(MHF1)	96
	B48 (Rx) (Semi-Antenna HC2S)		RFPCA474709IMMB401_A	8.01	3550-3700 MHz	Dipole	ipex(MHF1)	82

Antenna NO.	RF Chain NO.	Brand	Model	Antenna Net Gain (dBi)	Frequency range	Antenna Type	Connector Type	Cable Length (mm)
WWAN Antenna (Internal)	B77 (TRx) (M2)	PSA	RFPCA811609IMMB403_B	0.84	3300-4200 MHz	Monopole	ipex(MHF1)	94
	B77(TRx) (M1)		RFPCA811609IMMB402_A	0.91	3300-4200 MHz	Monopole	ipex(MHF1)	93
	B77 (Rx) (Omni-Antenna HC1O)		RFPCA380906IMMB401_A	4.73	3300-4200 MHz	Dipole	ipex(MHF1)	60
	B77 (Rx) (Omni-Antenna HC2O)		RFPCA380912IMMB401_A	4.14	3300-4200 MHz	Dipole	ipex(MHF1)	125
	B77 (Rx) (Semi-Antenna HC1S)		RFPCA474709IMMB401_A	7.98	3300-4200 MHz	Dipole	ipex(MHF1)	96
	B77 (Rx) (Semi-Antenna HC2S)		RFPCA474709IMMB401_A	8.13	3300-4200 MHz	Dipole	ipex(MHF1)	82

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

Antenna No.	RF Chain No.	Brand	Model	Antenna Net Gain (dBi)	Frequency range	Antenna Type	Connector Type	Cable Length (mm)
WWAN Antenna (External)	B71	TAOGLAS	ANT1	0.80	663-698 MHz	PIFA	ipex(MHF)	2000
	B71		ANT2	1.50	663-698 MHz	PIFA	ipex(MHF)	2000
	B71		ANT3	1.90	663-698 MHz	PIFA	ipex(MHF)	2000
	B71		ANT4	1.40	663-698 MHz	PIFA	ipex(MHF)	2000
	B12	TAOGLAS	ANT1	1.20	698-716 MHz	PIFA	ipex(MHF)	2000
	B12		ANT2	1.40	698-716 MHz	PIFA	ipex(MHF)	2000
	B12		ANT3	0.80	698-716 MHz	PIFA	ipex(MHF)	2000
	B12		ANT4	0.80	698-716 MHz	PIFA	ipex(MHF)	2000
	B5	TAOGLAS	ANT1	-1.00	824-849 MHz	PIFA	ipex(MHF)	2000
	B5		ANT2	-1.80	824-849 MHz	PIFA	ipex(MHF)	2000
	B5		ANT3	1.50	824-849 MHz	PIFA	ipex(MHF)	2000
	B5		ANT4	-1.70	824-849 MHz	PIFA	ipex(MHF)	2000
	B4/B66	TAOGLAS	ANT1	4.40	1710-1780 MHz	PIFA	ipex(MHF)	2000
	B4/B66		ANT2	3.70	1710-1780 MHz	PIFA	ipex(MHF)	2000
	B4/B66		ANT3	4.60	1710-1780 MHz	PIFA	ipex(MHF)	2000
	B4/B66		ANT4	3.80	1710-1780 MHz	PIFA	ipex(MHF)	2000
	B2/B25	TAOGLAS	ANT1	4.00	1850-1915 MHz	PIFA	ipex(MHF)	2000
	B2/B25		ANT2	3.50	1850-1915 MHz	PIFA	ipex(MHF)	2000
	B2/B25		ANT3	4.60	1850-1915 MHz	PIFA	ipex(MHF)	2000
	B2/B25		ANT4	3.60	1850-1915 MHz	PIFA	ipex(MHF)	2000
	B41	TAOGLAS	ANT1	3.90	2496-2690 MHz	PIFA	ipex(MHF)	2000
	B41		ANT2	3.80	2496-2690 MHz	PIFA	ipex(MHF)	2000
	B41		ANT3	2.90	2496-2690 MHz	PIFA	ipex(MHF)	2000
	B41		ANT4	4.00	2496-2690 MHz	PIFA	ipex(MHF)	2000
	B48	TAOGLAS	ANT1	2.60	3550-3700 MHz	PIFA	ipex(MHF)	2000
	B48		ANT2	2.30	3550-3700 MHz	PIFA	ipex(MHF)	2000
	B48		ANT3	1.70	3550-3700 MHz	PIFA	ipex(MHF)	2000
	B48		ANT4	2.40	3550-3700 MHz	PIFA	ipex(MHF)	2000
	B77	TAOGLAS	ANT1	3.20	3300-4200 MHz	PIFA	ipex(MHF)	2000
	B77		ANT2	2.80	3300-4200 MHz	PIFA	ipex(MHF)	2000
	B77		ANT3	3.80	3300-4200 MHz	PIFA	ipex(MHF)	2000
	B77		ANT4	2.90	3300-4200 MHz	PIFA	ipex(MHF)	2000

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.5 Calculation Result of Maximum Conducted Power

All data was copied from the original test report (Report No.: MFBCMA-WTW-P23030799 and MFBCMA-WTW-P23030799A)

For Bluetooth

Operation Mode	Evaluation Frequency (MHz)	Max Avg. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
Bluetooth	2402-2480	11.83	4.72	21	0.00633	1	Pass

For WLAN - CDD Mode

Operation Mode	Evaluation Frequency (MHz)	Max Avg. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
WLAN 2.4 GHz	2412-2462	988.614	1.77	21	0.26815	1	Pass
WLAN 5 GHz (U-NII-1 & U-NII-4)	5180-5240 5745-5825	997.474	2.35	21	0.30921	1	Pass
WLAN 5 GHz (U-NII-2A & U-NII-2C)	5260-5320 5500-5720	249.227	1.68	21	0.06621	1	Pass

For WLAN - Beamforming Mode

Operation Mode	Evaluation Frequency (MHz)	Max Avg. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
WLAN 2.4 GHz	2412-2462	641.372	7.48	21	0.64783	1	Pass
WLAN 5 GHz (U-NII-1 & U-NII-4)	5180-5240 5745-5825	863.913	6.62	21	0.71585	1	Pass
WLAN 5 GHz (U-NII-2A & U-NII-2C)	5260-5320 5500-5720	195.65	7.06	21	0.17940	1	Pass

For WWAN+Antenna (Internal)

Operation Mode	Evaluation Frequency (MHz)	Max Avg. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
LTE Band 2	1850.7-1909.3	242.103	4.78	21	0.13133	1	Pass
LTE Band 4	1710.7-1754.3	236.048	5.13	21	0.13879	1	Pass
LTE Band 5	824.7-848.3	245.471	1.68	21	0.06522	0.54933	Pass
LTE Band 12	699.7-715.3	261.216	3.34	21	0.10171	0.46533	Pass
LTE Band 25	1850.7-1914.3	245.471	4.78	21	0.13315	1	Pass
LTE Band 48	3652.5-3690	128.233	1.02	21	0.02927	1	Pass
LTE Band 66	1710.7-1779.3	242.661	5.13	21	0.14268	1	Pass
LTE Band 71	665.5-695.5	264.241	3.17	21	0.09894	0.442	Pass
5G nR Band 25	1852.5-1912.5	178.649	4.78	21	0.09691	1	Pass
5G nR Band 41	2506.02-2679.99	642.688	3.02	21	0.23246	1	Pass
5G nR Band 48	3555-3694.995	80.91	1.02	21	0.01847	1	Pass
5G nR Band 66	1712.5-1777.5	197.242	5.13	21	0.11597	1	Pass
5G nR Band 71	665.5-695.5	252.348	3.17	21	0.09448	0.442	Pass
5G nR Band 77	3460.02-3540	647.143	0.91	21	0.14400	1	Pass
5G nR Band 77	3710.01-3969.99	651.628	0.91	21	0.14499	1	Pass

NOTE:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

For WWAN+Antenna (External)

Operation Mode	Evaluation Frequency (MHz)	Max Avg. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
LTE Band 2	1850.7-1909.3	243.22	4.60	21	0.12658	1	Pass
LTE Band 4	1710.7-1754.3	242.661	4.60	21	0.12628	1	Pass
LTE Band 5	824.7-848.3	251.767	1.50	21	0.06417	0.54933	Pass
LTE Band 12	699.7-715.3	249.459	1.40	21	0.06214	0.46533	Pass
LTE Band 25	1850.7-1914.3	248.855	4.60	21	0.12951	1	Pass
LTE Band 48	3652.5-3690	74.817	2.60	21	0.02457	1	Pass
LTE Band 66	1710.7-1779.3	231.739	4.60	21	0.12060	1	Pass
LTE Band 71	665.5-695.5	259.417	1.90	21	0.07250	0.442	Pass
5G nR Band 25	1852.5-1912.5	258.821	4.60	21	0.13469	1	Pass
5G nR Band 41	2506.02-2679.99	580.764	4.00	21	0.26324	1	Pass
5G nR Band 48	3555-3694.995	68.234	2.60	21	0.02241	1	Pass
5G nR Band 66	1712.5-1777.5	233.346	4.60	21	0.12144	1	Pass
5G nR Band 71	665.5-695.5	295.801	1.90	21	0.08267	0.442	Pass
5G nR Band 77	3460.02-3540	258.226	3.80	21	0.11178	1	Pass
5G nR Band 77	3710.01-3969.99	262.422	3.80	21	0.11359	1	Pass

NOTE:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN+WWAN+Antenna (Internal)**WLAN - CDD Mode**

WLAN 2.4 GHz + LTE Band 71 = $0.26815 / 1 + 0.09713 / 0.442 = 0.48790$

WLAN 2.4 GHz + NR 71 = $0.26815 / 1 + 0.11075 / 0.442 = 0.51872$

WLAN 5 GHz + Bluetooth + LTE Band 71 = $0.30921 / 1 + 0.00633 / 1 + 0.09713 / 0.442 = 0.53529$

WLAN 5 GHz + Bluetooth + NR 71 = $0.30921 / 1 + 0.00633 / 1 + 0.11075 / 0.442 = 0.56611$

WLAN - Beamforming Mode

WLAN 2.4 GHz + LTE Band 71 = $0.64783 / 1 + 0.09713 / 0.442 = 0.86758$

WLAN 2.4 GHz + NR 71 = $0.64783 / 1 + 0.11075 / 0.442 = 0.89840$

WLAN 5 GHz + Bluetooth + LTE Band 71 = $0.71585 / 1 + 0.00633 / 1 + 0.09713 / 0.442 = 0.94193$

WLAN 5 GHz + Bluetooth + NR 71 = $0.71585 / 1 + 0.00633 / 1 + 0.11075 / 0.442 = 0.97275$

WLAN+WWAN+Antenna (External)**WLAN - CDD Mode**

WLAN 2.4 GHz + LTE Band 71 = $0.26815 / 1 + 0.07250 / 0.442 = 0.43218$

WLAN 2.4 GHz + NR 41 = $0.26815 / 1 + 0.26324 / 1 = 0.53139$

WLAN 5 GHz + Bluetooth + LTE Band 71 = $0.30921 / 1 + 0.00633 / 1 + 0.07250 / 0.442 = 0.47957$

WLAN 5 GHz + Bluetooth + NR 41 = $0.30921 / 1 + 0.00633 / 1 + 0.26324 / 1 = 0.57878$

WLAN - Beamforming Mode

WLAN 2.4 GHz + LTE Band 71 = $0.64783 / 1 + 0.07250 / 0.442 = 0.81186$

WLAN 2.4 GHz + NR 41 = $0.64783 / 1 + 0.26324 / 1 = 0.91107$

WLAN 5 GHz + Bluetooth + LTE Band 71 = $0.71585 / 1 + 0.00633 / 1 + 0.07250 / 0.442 = 0.88621$

WLAN 5 GHz + Bluetooth + NR 41 = $0.71585 / 1 + 0.00633 / 1 + 0.26324 / 1 = 0.98542$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---