


ENGINEERING TEST REPORT



800 RF MODULE
Model No.: T1088
FCC ID: IMA-T1088A

Applicant: **Technisonic Industries Ltd.**
240 Traders Blvd E,
Mississauga, Ontario
Canada, L4Z 1W7

Tested in Accordance With

Federal Communications Commission (FCC)
CFR 47, PARTS 2 and 90 (Subpart I)

UltraTech's File No.: TIL-046FCC90

This Test report is Issued under the Authority of
Tri M. Luu, Professional Engineer,
Vice President of Engineering
UltraTech Group of Labs

Date: May 25, 2004



Report Prepared by: Dharmajit Solanki,
RFI Engineer

Tested by: Hung Trinh, EMI/RFI Technician

Issued Date: May 25, 2004

Test Dates: December 10 – 23, 2003,
March 04, 2004

The results in this Test Report apply only to the sample(s) tested, and the sample tested is randomly selected.

UltraTech

3000 Bristol Circle, Oakville, Ontario, Canada, L6H 6G4

Tel.: (905) 829-1570 Fax.: (905) 829-8050

Website: www.ultratech-labs.com Email: vic@ultratech-labs.com, Email: tri@ultratech-labs.com



31040/SIT



C-1376



46390-2049



200093-0



SL2-IN-E-11119R



00-034



TABLE OF CONTENTS

EXHIBIT 1.	SUBMITTAL CHECK LIST.....	3
EXHIBIT 2.	INTRODUCTION	4
2.1.	SCOPE.....	4
2.2.	RELATED SUBMITAL(S)/GRANT(S).....	4
2.3.	NORMATIVE REFERENCES	4
EXHIBIT 3.	PERFORMANCE ASSESSMENT	5
3.1.	CLIENT INFORMATION	5
3.2.	EQUIPMENT UNDER TEST (EUT) INFORMATION.....	5
3.3.	EUT'S TECHNICAL SPECIFICATIONS.....	6
3.4.	LIST OF EUT'S PORTS	7
3.5.	ANCILLARY EQUIPMENT.....	7
3.6.	BLOCK DIAGRAM OF TEST SETUP	8
EXHIBIT 4.	EUT OPERATING CONDITIONS AND CONFIGURATIONS DURING TESTS	9
4.1.	CLIMATE TEST CONDITIONS.....	9
4.2.	OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TEST SIGNALS.....	9
EXHIBIT 5.	SUMMARY OF TEST RESULTS	10
5.1.	LOCATION OF TESTS	10
5.2.	APPLICABILITY & SUMMARY OF EMISSION TEST RESULTS	10
5.3.	MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES.....	11
5.4.	DEVIATION OF STANDARD TEST PROCEDURES	11
EXHIBIT 6.	MEASUREMENTS, EXAMINATIONS & TEST DATA FOR EMC EMISSIONS.....	12
6.1.	TEST PROCEDURES.....	12
6.2.	MEASUREMENT UNCERTAINTIES	12
6.3.	MEASUREMENT EQUIPMENT USED:	12
6.4.	ESSENTIAL/PRIMARY FUNCTIONS AS DECLARED BY THE MANUFACTURER:.....	12
6.5.	RF POWER OUTPUT @ FCC 2.1046 , 90.205 & 90.635	13
6.5.1.	LIMITS @ FCC 90.635	13
6.5.2.	METHOD OF MEASUREMENTS.....	13
6.5.3.	TEST EQUIPMENT LIST.....	13
6.5.4.	TEST ARRANGEMENT.....	13
6.5.5.	TEST DATA	13
6.6.	RF EXPOSURE REQUIRMENTS @ 1.1310 & 2.1091.....	14
6.6.1.	LIMITS.....	14
6.6.2.	METHOD OF MEASUREMENTS.....	14
6.6.3.	TEST DATA	16
6.7.	FREQUENCY STABILITY @ FCC 2.1055 & 90.213	17
6.7.1.	LIMITS @ FCC 90.213	17
6.7.2.	METHOD OF MEASUREMENTS.....	17
6.7.3.	TEST EQUIPMENT LIST.....	17
6.7.4.	TEST ARRANGEMENT.....	17
6.7.5.	TEST DATA	18
6.8.	AUDIO FREQUENCY RESPONSE @ FCC 2.1047(A) & 90.211	19
6.8.1.	LIMITS @ FCC 2.1047(A)	19

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

6.8.2.	METHOD OF MEASUREMENTS.....	19
6.8.3.	TEST EQUIPMENT LIST.....	19
6.8.4.	TEST ARRANGEMENT.....	19
6.8.5.	TEST DATA	20
6.9.	MODULATION LIMITING @ FCC 2.1047(B) & 90.210	24
6.9.1.	LIMITS @ FCC 2.1047(B) AND 90.210	24
6.9.2.	METHOD OF MEASUREMENTS.....	24
6.9.3.	TEST EQUIPMENT LIST.....	24
6.9.4.	TEST ARRANGEMENT.....	24
6.9.5.	TEST DATA	25
6.10.	99% OCCUPIED BANDWIDTH & EMISSION MASK @ FCC 2.1049, 90.209 & 90.210.....	30
6.10.1.	LIMITS @ FCC 90.209 & 90.210	30
6.10.2.	METHOD OF MEASUREMENTS.....	30
6.10.3.	TEST EQUIPMENT LIST.....	30
6.10.4.	TEST ARRANGEMENT.....	30
6.10.5.	TEST DATA	31
6.11.	ADJACENT CHANNEL COUPLED POWER (ACCP) REQUIREMENTS FOR TRANSMITTER @FCC 90.543	92
6.11.1.	EMISSIONS LIMITATION @ 90.543.....	92
6.11.2.	METHOD OF MEASUREMENTS.....	93
6.11.3.	TEST EQUIPMENT LIST.....	94
6.11.4.	TEST ARRANGEMENT.....	94
6.11.5.	TEST DATA	94
6.12.	TRANSMITTER ANTENNA POWER SPURIOUS/HARMONIC CONDUCTED EMISSIONS @ FCC 90.210 98	
6.12.1.	LIMITS @ 90.210	98
6.12.2.	METHOD OF MEASUREMENTS.....	98
6.12.3.	TEST EQUIPMENT LIST.....	98
6.12.4.	TEST ARRANGEMENT.....	98
6.12.5.	TEST DATA	99
6.13.	TRANSMITTER SPURIOUS/HARMONIC RADIATED EMISSIONS @ FCC 90.210.....	114
6.13.1.	LIMITS @ FCC 90.210	114
6.13.2.	METHOD OF MEASUREMENTS.....	114
6.13.3.	TEST EQUIPMENT LIST.....	114
6.13.4.	TEST SETUP	115
6.13.5.	TEST DATA	115
EXHIBIT 7.	MEASUREMENT UNCERTAINTY.....	116
7.1.	RADIATED EMISSION MEASUREMENT UNCERTAINTY	116
EXHIBIT 8.	MEASUREMENT METHODS.....	117
8.1.	CONDUCTED POWER MEASUREMENTS	117
8.2.	RADIATED POWER MEASUREMENTS (ERP & EIRP) USING SUBSTITUTION METHOD.....	118
8.2.1.	MAXIMIZING RF EMISSION LEVEL (E-FIELD).....	118
8.2.2.	MEASURING THE EIRP OF SPURIOUS/HARMONIC EMISSIONS USING SUBSTITUTION METHOD.....	119
8.3.	FREQUENCY STABILITY.....	121
8.4.	EMISSION MASK.....	122
8.5.	SPURIOUS EMISSIONS (CONDUCTED).....	122

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

EXHIBIT 1. SUBMITTAL CHECK LIST

Annex No.	Exhibit Type	Description of Contents	Quality Check (OK)
--	Test Report	<ul style="list-style-type: none">Exhibit 1: Submittal check listsExhibit 2: IntroductionExhibit 3: Performance AssessmentExhibit 4: EUT Operation and Configuration during TestsExhibit 5: Summary of test ResultsExhibit 6: Measurement DataExhibit 7: Measurement UncertaintyExhibit 8: Measurement Methods	OK
1	Test Setup Photos	Photos # 1 to 6	OK
2	External Photos of EUT	Photos # 1 to 2	OK
3	Internal Photos of EUT	Photos # 1 to 6	OK
4	Cover Letters	<ul style="list-style-type: none">Letter from Ultratech for Certification RequestLetter from the Applicant to appoint Ultratech to act as an agentLetter from the Applicant to request for Confidentiality Filing	OK OK OK
5	ID Label/Location Info	ID Label & Location of ID Label <ul style="list-style-type: none">RF Module (internal)TDFM Transceiver (external)	OK OK
6	Block Diagrams	Transceiver Block Diagram	OK
7	Schematic Diagrams	Schematic Diagrams	OK
8	Parts List/Tune Up Info	<ul style="list-style-type: none">Parts ListTune Up Procedure	OK
9	Operational Description	Operation Description	OK
10	RF Exposure Info	RF Exposure Warning	OK
11	Users Manual	Installation and Operational Manual <ul style="list-style-type: none">Motorola XTS 5000 ManualTDFM 600/6000 Manual	OK

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

EXHIBIT 2. INTRODUCTION

2.1. SCOPE

Reference:	FCC Parts 2 and 90
Title:	Telecommunication - Code of Federal Regulations, CFR 47, Parts 2 & 90 Subpart I.
Purpose of Test:	To gain FCC Certification Authorization for Radio operating in the frequency bands 764-869 MHz (12.5 kHz and 25 kHz Channel Spacing).
Test Procedures:	Both conducted and radiated emissions measurements were conducted in accordance with American National Standards Institute ANSI C63.4 - American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
Modular Approval:	This application is for Modular Approval for Airborne mobile and base station application with the antenna gain limit of 3dBi and the minimum antenna separation distance of 70 cm.

2.2. RELATED SUBMITAL(S)/GRANT(S)

None

2.3. NORMATIVE REFERENCES

Publication	Year	Title
FCC CFR 47 Parts 0-19, 80-End	2003	Code of Federal Regulations – Telecommunication
ANSI C63.4	2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
CISPR 22 & EN 55022	2003 2003	Limits and Methods of Measurements of Radio Disturbance Characteristics of Information Technology Equipment
CISPR 16-1	2003	Specification for Radio Disturbance and Immunity measuring apparatus and methods

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

EXHIBIT 3. PERFORMANCE ASSESSMENT

3.1. CLIENT INFORMATION

APPLICANT	
Name:	TECHNISONIC INDUSTRIES LTD.
Address:	240 Traders Blvd E Mississauga, Ontario Canada, L4Z 1W7
Contact Person:	Richard Dalacker Phone #: 905-890-2113 Fax #: 905-890-5338 Email Address: rdalacker@til.ca

MANUFACTURER	
Name:	MOTOROLA INC.
Address:	8000 West Sunrise Boulevard Fort Lauderdale, Florida USA 33322
Contact Person:	Mr. John McCoy Phone #: 954-723-5722 Email Address: john.mccoy@motorola.com

3.2. EQUIPMENT UNDER TEST (EUT) INFORMATION

The following information (with the exception of the Date of Receipt) has been supplied by the applicant.

Brand Name:	TECHNISONIC
Product Name:	800 RF MODULE
Model Name or Number:	T1088
Serial Number:	721CDN0696
Type of Equipment:	Non-broadcast Radio Transmitter Module used in Mobile Station
Oscillator's Frequency	16.8 MHz
CPU's Frequencies	18 MHz, 520 kHz
Transmitting/Receiving Antenna Type:	Non-integral, Antenna gain limit = 3 dBi maximum
Primary User Functions of EUT:	The 800 RF MODULE is a modular Transceiver manufactured by Motorola, it will be used in Technisonic Multiband P25 Airborne Transceiver.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

3.3. EUT'S TECHNICAL SPECIFICATIONS

TRANSMITTER	
Equipment Type:	<input type="checkbox"/> Portable <input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Base station (fixed use)
Intended Operating Environment:	<input type="checkbox"/> Commercial <input type="checkbox"/> Light Industry & Heavy Industry <input checked="" type="checkbox"/> Airborne
Power Supply Requirement:	7.5 Vdc
RF Output Power Rating:	2.8 Watts (conducted)
Operating Frequency Range:	764-869 MHz
Duty cycle:	50 %
RF Output Impedance:	50 Ohms
Channel Spacing:	12.5 kHz & 25 kHz
Occupied Bandwidth (99%):	10.4 kHz (FM voice in 12.5 kHz Channel Spacing) 15.6 kHz (FM voice in 25 kHz Channel Spacing) 10.5 kHz (FM digital in 12.5 kHz Channel Spacing)
Maximum Data Rate:	9600 bps
Emission Designations*:	16K0F3E, 11K0F3E, 11K2F1D
Antenna Connector Type:	Reversed thrust SMA female connector

* For an average case of commercial telephony, the Necessary Bandwidth is calculated as follows:

Bandwidth Calculations :

Carson's Rule for FM modulation is utilized to compute the bandwidth shown in the FCC emission designator. Carson's Rule is: $BW = 2 \times (M + DK)$, where M = Maximum modulating frequency, D = Deviation

1. For FM Voice Modulation:

Channel Spacing = 12.5 KHz, D = 2.5 KHz max., K = 1, M = 3 KHz

$B_n = 2M + 2DK = 2(3) + 2(2.5)(1) = \underline{11 \text{ KHz}}$

emission designation: 11K0F3E

Channel Spacing = 25 KHz, D = 5 KHz max., K = 1, M = 3 KHz

$B_n = 2M + 2DK = 2(3) + 2(5)(1) = \underline{16 \text{ KHz}}$

emission designation: 16K0F3E

2. For FM Digital Modulation: Channel Spacing = 12.5 KHz, Digital Data, D = 3.2 kHz

M = 9.6/2 kb/s, (FM modulation Level 4)

$B_n = 2M + 2DK = 2(9.6/4) + 2(3.2)(1) = \underline{11.2 \text{ KHz}}$

emission designation: 11K2F1D

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

3.4. LIST OF EUT'S PORTS

Port Number	EUT's Port Description	Number of Identical Ports	Connector Type	Cable Type (Shielded/Non-shielded)
1	RF IN/OUT Port	1	Reversed SMA	Shielded
2	I/O Port	1	Controls Flex Assembly Connector	Non-shielded

NOTES:


- (1) *Ports of the EUT which in normal operation were connected to ancillary equipment through interconnecting cables via a representative interconnecting cable to simulate the input/output characteristics. RF input/output was correctly terminated to the 50 Ohm RF Load.*

3.5. ANCILLARY EQUIPMENT

The EUT was tested while connected to the following representative configuration of ancillary equipment necessary to exercise the ports during tests:

Ancillary Equipment # 1	
Description:	Multiband P25 Airborne Transceiver (Test Jig)
Brand name:	Technisonic
Model Name or Number:	TDFM-600/60000
Serial Number:	Pre-production
Cable Length & Type:	Non-shielded ribbon cable
Connected to EUT's Port:	Controls Flex Assembly Connector

3.6. BLOCK DIAGRAM OF TEST SETUP



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 4. EUT OPERATING CONDITIONS AND CONFIGURATIONS DURING TESTS

4.1. CLIMATE TEST CONDITIONS

The climate conditions of the test environment are as follows:

Temperature:	21°C
Humidity:	51%
Pressure:	102 kPa
Power input source:	7.5 Vdc, 24 Vdc

4.2. OPERATIONAL TEST CONDITIONS & ARRANGEMENT FOR TEST SIGNALS

Operating Modes:	The transmitter was operated in a continuous transmission mode with the carrier modulated as specified in the Test Data.
Special Test Software:	N/A
Special Hardware Used:	The Technisonic Multiband P25 Airborne Transceiver, Model TDFM-600/6000 was used for setting & operating the EUT at different operating modes.
Transmitter Test Antenna:	The EUT is tested with the transmitter antenna port terminated to a 50 Ohms RF Load.

Transmitter Test Signals	
Frequency Band(s):	Near lowest, near middle & near highest frequencies in each frequency bands that the transmitter covers:
▪ 764-869 MHz band:	▪ 764.0125, 821.0000 and 868.9875 MHz
Transmitter Wanted Output Test Signals:	
▪ RF Power Output (measured maximum output power):	▪ 2.8 Watts (conducted)
▪ Normal Test Modulation	▪ External FM Sine Wave, Internal Digital
▪ Modulating signal source:	▪ External analog source and internal data source

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

EXHIBIT 5. SUMMARY OF TEST RESULTS

5.1. LOCATION OF TESTS

All of the measurements described in this report were performed at Ultratech Group of Labs located in the city of Oakville, Province of Ontario, Canada.

- Radiated Emissions were performed at the Ultratech's 3 Meter Open Field Test Site (OFTS) situated in the Town of Oakville, province of Ontario.

The above sites have been calibrated in accordance with ANSI C63.4, and found to be in compliance with the requirements of Sec. 2.948 of the FCC Rules. The descriptions and site measurement data of the Oakville Open Field Test Site has been filed with FCC office (FCC File No.: 31040/SIT 1300B3) and Industry Canada office (Industry Canada File No.: IC2049). Last Date of Site Calibration: Nov. 4, 2003.

5.2. APPLICABILITY & SUMMARY OF EMISSION TEST RESULTS

FCC PARAGRAPH.	TEST REQUIREMENTS	APPLICABILITY (YES/NO)
90.205 & 2.1046	RF Power Output	Yes
1.1307, 1.1310, 2.1091 & 2.1093	RF Exposure Limit	Yes
90.213 & 2.1055	Frequency Stability	Yes
90.242(b)(8) & 2.1047(a)	Audio Frequency Response	Not applicable to new standard. However, tests are conducted under FCC's recommendation.
90.210 & 2.1047(b)	Modulation Limiting	Yes
90.543 & 2.1049	Emission Limitation	Yes
90.210 & 2.1049	Emission Mask	Yes
90.210, 2.1057 & 2.1051	Emission Limits - Spurious Emissions at Antenna Terminal	Yes
90.210, 2.1057 & 2.1053	Emission Limits - Field Strength of Spurious Emissions	Yes
90.214	Transient Frequency Behavior	No
800 RF MODULE, Model No.: T1088, by TECHNISONIC INDUSTRIES LTD. has also been tested and found to comply with FCC Part 15, Subpart B - Radio Receivers and Class A Digital Device . The engineering test report has been documented and kept in file and it is available anytime upon FCC request.		

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

5.3. MODIFICATIONS INCORPORATED IN THE EUT FOR COMPLIANCE PURPOSES

None

5.4. DEVIATION OF STANDARD TEST PROCEDURES

None

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 6. MEASUREMENTS, EXAMINATIONS & TEST DATA FOR EMC EMISSIONS

6.1. TEST PROCEDURES

This section contains test results only. Details of test methods and procedures can be found in Exhibit 8 of this report

6.2. MEASUREMENT UNCERTAINTIES

The measurement uncertainties stated were calculated in accordance with requirements of UKAS Document NIS 81 with a confidence level of 95%. Please refer to Exhibit 7 for Measurement Uncertainties.

6.3. MEASUREMENT EQUIPMENT USED:

The measurement equipment used complied with the requirements of the Standards referenced in the Methods & Procedures ANSI C63.4:2003 and CISPR 16-1.

6.4. ESSENTIAL/PRIMARY FUNCTIONS AS DECLARED BY THE MANUFACTURER:

The essential function of the EUT is to correctly communicate data to and from radios over RF link.

6.5. RF POWER OUTPUT @ FCC 2.1046 , 90.205 & 90.635

6.5.1. Limits @ FCC 90.635

Please refer to FCC CFR 47, Part 90, Subpart S, Para. 90.635 for specification details.

Also as per FCC CFR 47, Part 90, Subpart R, Para. 90.541, the transmitter output power of mobile and control Tx must not exceed 30 Watts.

6.5.2. Method of Measurements


Refer to Exhibit 8, § 8.1 (Conducted) and 8.2 (Radiated) of this report for measurement details

6.5.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Attenuator(s)	Weinschel Corp	24-20-34	BJ2357	DC – 8.5 GHz
Power Meter	Hewlett Packard	436A	1725A02249	10 kHz – 50 GHz, sensor dependent
Power Sensor	Hewlett Packard	8481A	2702A68983	10 MHz – 18 GHz

6.5.4. Test Arrangement

- Power at RF Power Output Terminals



6.5.5. Test Data

Transmitter Output Channel	Fundamental Frequency (MHz)	Measured (Average) Low Power (Watts)	Power Rating (Watts)
Lowest	764.0125	0.97	1
Middle	821.0000	0.97	1
Highest	868.9875	1.08	1

Transmitter Output Channel	Fundamental Frequency (MHz)	Measured (Average) High Power (Watts)	Power Rating (Watts)
Lowest	764.0125	2.09	2.8
Middle	821.0000	2.76	2.8
Highest	868.9875	2.75	2.8

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

6.6. RF EXPOSURE REQUIREMENTS @ 1.1310 & 2.1091

6.6.1. Limits

- **FCC 1.1310:-** The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Control Exposures				
300-1500	F/300	6
(B) Limits for General Population/Uncontrolled Exposure				
300-1500	F/1500	6

F = Frequency in MHz

6.6.2. Method of Measurements

Refer to FCC @ 1.1310, 2.1091 and Public Notice DA 00-705 (March 30, 2000)

- In order to demonstrate compliance with MPE requirements (see Section 2.1091), the following information is typically needed:
 - (1) Calculation that estimates the minimum separation distance (20 cm or more) between an antenna and persons required to satisfy power density limits defined for free space.
 - (2) Antenna installation and device operating instructions for installers (professional/unskilled users), and the parties responsible for ensuring compliance with the RF exposure requirement
 - (3) Any caution statements and/or warning labels that are necessary in order to comply with the exposure limits
 - (4) Any other RF exposure related issues that may affect MPE compliance

Calculation Method of RF Safety Distance:

$$S = PG/4\pi r^2 = EIRP/4\pi r^2$$

Where: P: power input to the antenna in mW
EIRP: Equivalent (effective) isotropic radiated power.
S: power density mW/cm²
G: numeric gain of antenna relative to isotropic radiator
r: distance to centre of radiation in cm

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device

$$r = \sqrt{PG/4\pi S}$$

FCC radio frequency exposure limits may not be exceeded at distances closer than r cm from the antenna of this device

- For portable transmitters (see Section 2.1093), or devices designed to operate next to a person's body, compliance is determined with respect to the SAR limit (define in the body tissues) for near-field exposure conditions. If the maximum average output power, operating condition configurations and exposure conditions are comparable to those of existing cellular and PCS phones., an SAR evaluation may be required in order to determine if such a device complies with SAR limit. When SAR evaluation data is not available, and the additional supporting information cannot assure compliance, the Commission may request that an SAR evaluation be performed, as provided for in Section 1.1307(d)

6.6.3. Test Data

Antenna Gain Limit specified by Manufacturer: 3 dBi

Measured Maximum RF Conducted Power (watts)	Calculated EIRP (watts)	Laboratory's Recommended Minimum RF Safety Distance r (cm)	Manufacturer's specified antenna separation distance (cm)
2.76	5.50	30.0	70.0

Note 1: RF EXPOSURE DISTANCE LIMITS: $r = (PG/4\pi S)^{1/2} = (EIRP/4\pi S)^{1/2}$
 $S = F/1500 = 764/1500 = 0.509 \text{ mW/cm}^2$

$$r = (PG/4\pi S)^{1/2} = (EIRP/4\pi S)^{1/2} = (5507/4\pi \times 0.509)^{1/2} = 29.4 \text{ cm}$$

Evaluation of RF Exposure Compliance Requirements	
RF Exposure Requirements	Compliance with FCC Rules
Minimum calculated separation distance between antenna and persons required: 29.4 cm	Manufacturer' instruction for separation distance between antenna and persons required: 70 cm
Antenna installation and device operating instructions for installers (professional/unskilled users), and the parties responsible for ensuring compliance with the RF exposure requirement	Please refer to page 1 of Users Manual
Caution statements and/or warning labels that are necessary in order to comply with the exposure limits	Please refer to page 3-1 of the Users/ Manual and FCC RF Exposure folder
Any other RF exposure related issues that may affect MPE compliance	N/A

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
 Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
 May 25, 2004

6.7. FREQUENCY STABILITY @ FCC 2.1055 & 90.213

6.7.1. Limits @ FCC 90.213

Please refer to FCC CFR 47, Part 90, Subpart I, Para. 90.213 for specification details.

FREQUENCY RANGE (MHz)	MOBILE STATIONS (ppm)	
	> 2 W	≤ 2 W
806-821	2.5	2.5
821-824	1.5	1.5
851-866	2.5	2.5
866-869	1.5	1.5

FREQUENCY RANGE (MHz)	MOBILE STATIONS (ppm)	
	12.5 kHz Ch. Spacing	25 kHz Ch. Spacing
764-776	1.5	2.5
794-806	1.5	2.5


6.7.2. Method of Measurements

Refer to Exhibit 8, § 8.3 of this report for measurement details

6.7.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
EMI Receiver/ EMI Receiver	Hewlett Packard	HP 8593EM	3412A00103	9 kHz – 26.5 GHz
Attenuator(s)	Bird	DC – 22 GHz
Temperature & Humidity Chamber	Tenney	T5	9723B	-40° to +60° C range

6.7.4. Test Arrangement



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

6.7.5. Test Data

Product Name:	800 RF MODULE
Model No.:	T1088
Center Frequency:	806.00 MHz
Full Power Level:	34.4 dBm
Frequency Tolerance Limit:	1.5 ppm or 1146.0 Hz
Max. Frequency Tolerance Measured:	+870 Hz or +1.14 ppm
Input Voltage Rating:	7.5 Vdc, 1.8 Amps

CENTER FREQUENCY & RF POWER OUTPUT VARIATION			
Ambient Temperature (°C)	Supply Voltage (Nominal)	Supply Voltage (85% of Nominal)	Supply Voltage (115% of Nominal)
	7.5 Volts dc	6.4 Volts dc	8.6 Volts dc
	Hz	Hz	Hz
-30	+870	N/A	N/A
-20	+669	N/A	N/A
-10	+409	N/A	N/A
0	+69	N/A	N/A
+10	+14	N/A	N/A
+20	0	- 14	- 20
+30	-283	N/A	N/A
+40	-566	N/A	N/A
+50	-747	N/A	N/A

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.8. AUDIO FREQUENCY RESPONSE @ FCC 2.1047(A) & 90.211

6.8.1. Limits @ FCC 2.1047(a)

Recommended audio filter attenuation characteristics are given below:

RF Band	Audio band	Minimum Attenuation Rel. to 1 kHz Attenuation
406.1 – 960 MHz	3 – 20 kHz 20 – 30 kHz	$60 \log_{10}(f/3)$ dB where f is in kHz 50dB


6.8.2. Method of Measurements

The rated audio input signal was applied to the input of the audio low-pass filter (or of all modulation stages) using an audio oscillator, this input signal level and its corresponding output signal were then measured and recorded using the FFT (Audio) EMI Receiver. Tests were repeated at different audio signal frequencies from 0 to 50 kHz.

6.8.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Modulation Analyzer	Hewlett Packard	8910B	3226A04606	150 kHz – 1300 MHz
Function Generator	Stanford Research Systems	DS345	34591	1μHz – 30.2 MHz
FFT Digital Spectrum	Advantest	R9211E	82020336	--
Attenuator	Weinschel Crop.	46-20-34	BM1347	DC-18 GHz

6.8.4. Test Arrangement



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

6.8.5. Test Data

6.8.5.1. Audio Frequency Response of All Modulation States - 12.5 kHz Channel Spacing

FREQUENCY (kHz)	AUDIO IN (dBV)	AUDIO OUT (dBV)	ATTEN. (OUT - IN) (dB)	ATTEN. wrt. 1 kHz (dB)	FCC LIMIT (dB)	PASS/ FAIL
0.10	-12.6	-67.0	-54.4	-63.4	--	PASS
0.20	-12.6	-57.0	-44.4	-53.4	--	PASS
0.40	-12.6	-25.8	-13.2	-22.2	--	PASS
0.60	-12.6	-14.7	-2.1	-11.1	--	PASS
0.80	-12.6	-8.4	4.3	-4.7	--	PASS
1.00	-12.6	-3.6	9.0	0.0	--	PASS
1.20	-12.6	-0.6	12.0	3.0	--	PASS
1.40	-12.6	2.0	14.6	5.6	--	PASS
1.60	-12.6	3.6	16.2	7.2	--	PASS
1.80	-12.6	3.7	16.3	7.3	--	PASS
2.00	-12.6	3.7	16.3	7.3	--	PASS
2.50	-12.6	3.6	16.3	7.3	--	PASS
3.00	-12.6	3.8	16.4	7.4	0.0	PASS
3.50	-12.6	-50.6	-38.0	-47.0	-4.0	PASS
4.00	-12.6	-50.6	-38.0	-47.0	-7.5	PASS
5.00	-12.6	<-60.0	<-47.4	<-56.4	-13.3	PASS
6.00	-12.6	<-60.0	<-47.4	<-56.4	-18.1	PASS
7.00	-12.6	<-60.0	<-47.4	<-56.4	-22.1	PASS
8.00	-12.6	<-60.0	<-47.4	<-56.4	-25.6	PASS
9.00	-12.6	<-60.0	<-47.4	<-56.4	-28.6	PASS
10.00	-12.6	<-60.0	<-47.4	<-56.4	-31.4	PASS
15.00	-12.6	<-60.0	<-47.4	<-56.4	-41.9	PASS
15.00	-12.6	<-60.0	<-47.4	<-56.4	-41.9	PASS
20.00	-12.6	<-60.0	<-47.4	<-56.4	-49.4	PASS
22.00	-12.6	<-60.0	<-47.4	<-56.4	-50.0	PASS
24.00	-12.6	<-60.0	<-47.4	<-56.4	-50.0	PASS
26.00	-12.6	<-60.0	<-47.4	<-56.4	-50.0	PASS
28.00	-12.6	<-60.0	<-47.4	<-56.4	-50.0	PASS
30.00	-12.6	<-60.0	<-47.4	<-56.4	-50.0	PASS
40.00	-12.6	<-60.0	<-47.4	<-56.4	-50.0	PASS
50.00	-12.6	<-60.0	<-47.4	<-56.4	-50.0	PASS


ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

AUDIO FREQUENCY REPSONSE @ FCC 2.987(a) & 90.242b(8)
Technisonic 800 FM Transceiver (12.5 kHz Channel Spacing)



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

6.8.5.2. Audio Frequency Response of All Modulation States - 25 kHz Channel Spacing

FREQUENCY (kHz)	AUDIO IN (dBV)	AUDIO OUT (dBV)	ATTEN. (OUT - IN) (dB)	ATTEN. wrt. 1 kHz (dB)	FCC LIMIT @22.915D (dB)	PASS/ FAIL
0.10	-9.6	<-40.0	-30.4	-45.1	--	PASS
0.20	-9.6	<-40.0	-30.4	-45.1	--	PASS
0.40	-9.6	-16.6	-7.0	-21.7	--	PASS
0.60	-9.6	-5.9	3.7	-11.0	--	PASS
0.80	-9.6	0.4	10.0	-4.7	--	PASS
1.00	-9.6	5.1	14.7	0.0	--	PASS
1.10	-9.6	4.3	13.9	-0.8	--	PASS
1.20	-9.6	-11.8	-2.2	-16.9	--	PASS
1.40	-9.6	-10.3	-0.7	-15.4	--	PASS
1.50	-9.6	-10.3	-0.7	-15.4	--	PASS
1.60	-9.6	-10.3	-0.7	-15.4	--	PASS
1.80	-9.6	-10.1	-0.5	-15.2	--	PASS
2.00	-9.6	-10.1	-0.5	-15.2	--	PASS
2.20	-9.6	-10.1	-0.5	-15.2	--	PASS
2.40	-9.6	-10.1	-0.5	-15.2	--	PASS
2.50	-9.6	-10.1	-0.5	-15.2	--	PASS
2.60	-9.6	-10.1	-0.5	-15.2	--	PASS
2.80	-9.6	-10.0	-0.4	-15.1	--	PASS
3.00	-9.6	-10.1	-0.5	-15.2	0.0	PASS
3.50	-9.6	-41.1	-31.5	-46.2	-4.0	PASS
4.00	-9.6	<-62.0	<-52.4	<-67.1	-7.5	PASS
4.50	-9.6	<-62.0	<-52.4	<-67.1	-10.6	PASS
5.00	-9.6	<-62.0	<-52.4	<-67.1	-13.3	PASS
6.00	-9.6	<-62.0	<-52.4	<-67.1	-18.1	PASS
7.00	-9.6	<-62.0	<-52.4	<-67.1	-22.1	PASS
8.00	-9.6	<-62.0	<-52.4	<-67.1	-25.6	PASS
9.00	-9.6	<-62.0	<-52.4	<-67.1	-28.6	PASS
10.00	-9.6	<-62.0	<-52.4	<-67.1	-31.4	PASS
15.00	-9.6	<-62.0	<-52.4	<-67.1	-41.9	PASS
15.00	-9.6	<-62.0	<-52.4	<-67.1	-41.9	PASS
20.00	-9.6	<-62.0	<-52.4	<-67.1	-49.4	PASS
22.00	-9.6	<-62.0	<-52.4	<-67.1	-50.0	PASS
24.00	-9.6	<-62.0	<-52.4	<-67.1	-50.0	PASS
26.00	-9.6	<-62.0	<-52.4	<-67.1	-50.0	PASS
28.00	-9.6	<-62.0	<-52.4	<-67.1	-50.0	PASS
30.00	-9.6	<-62.0	<-52.4	<-67.1	-50.0	PASS
40.00	-9.6	<-62.0	<-52.4	<-67.1	-50.0	PASS
50.00	-9.6	<-62.0	<-52.4	<-67.1	-50.0	PASS


ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

AUDIO FREQUENCY REPSONSE @ FCC 2.987(a) & 90.242b(8)
Technisonic 800 FM Transceiver (25 kHz Channel Spacing)



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

6.9. MODULATION LIMITING @ FCC 2.1047(B) & 90.210

6.9.1. Limits @ FCC 2.1047(b) and 90.210

Recommended frequency deviation characteristics are given below:

- 2.5 kHz for 12.5 kHz Channel Spacing System
- 5 kHz for 25 kHz Channel Spacing System

6.9.2. Method of Measurements


For Audio Transmitter:- The carrier frequency deviation was measured with the tone input signal level varied from 0 Vp to audio input rating level plus 16 dB at frequencies 0.1, 0.5, 1.0, 3.0 and 5.0 kHz. The maximum deviation was recorded at each test condition.

For Data Transmitter with Maximum Frequency Deviation set by Factory:- The EUT was set at maximum frequency deviation, and its peak frequency deviation was then measured using EUT's internal random data source.

6.9.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Modulation Analyzer	Hewlett Packard	8910B	3226A04606	150 KHz – 1300 MHz
Function Generator	Stanford Research Systems	DS345	34591	1µHz – 30.2 MHz
Attenuator	Weinchel Corp.	46-20-34	BM1347	DC – 18 GHz

6.9.4. Test Arrangement



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

6.9.5. Test Data

6.9.5.1. Data Modulation Limiting: FM modulation with random data and Modulation Limiter set at a Maximum Frequency Deviation (Factory Setting).

6.9.5.1.1. 12.5 kHz Channel Spacing

Data Baud Rate	Peak Deviation (kHz)	Recommended Maximum Limit (kHz)
9600	3.2	2.5

6.9.5.1.2. 25 kHz Channel Spacing

Data Baud Rate	Peak Deviation (kHz)	Recommended Maximum Limit (kHz)
N/A	N/A	5 kHz

* FM Data modulation is not available for 25 kHz channel spacing operation

6.9.5.2. Voice Modulation Limiting:

6.9.5.2.1. 12.5 kHz Channel Spacing

MODULATING SIGNAL LEVEL (mVrms)	PEAK FREQUENCY DEVIATION (kHz) at the following modulating frequency:					MAXIMUM LIMIT (kHz)
	0.1 kHz	0.5 kHz	1.0 kHz	3.0 kHz	5.0 kHz	
50	0.7	0.7	0.7	1.6	0.7	2.5
100	0.7	0.7	0.8	2.7	0.7	2.5
150	0.7	0.7	1.1	2.7	0.7	2.5
200	0.7	0.7	1.3	2.5	0.7	2.5
250	0.7	0.8	1.5	2.5	0.7	2.5
300	0.7	0.8	1.7	2.5	0.7	2.5
350	0.7	0.8	1.9	2.5	0.7	2.5
400	0.7	0.8	1.9	2.5	0.7	2.5
450	0.7	0.9	2.2	2.5	0.7	2.5
500	0.7	0.9	2.4	2.5	0.7	2.5
600	0.7	0.9	2.4	2.5	0.7	2.5
700	0.7	1.2	2.3	2.5	0.7	2.5
800	0.7	1.4	2.3	2.5	0.7	2.5
900	0.7	1.6	2.5	2.5	0.7	2.5
1000	0.7	1.9	2.5	2.5	0.7	2.5
1500	0.7	2.4	2.4	2.5	0.7	2.5
2000	0.7	2.4	2.4	2.5	0.7	2.5
2500	0.7	2.4	2.4	2.5	0.7	2.5
3000	0.7	2.4	2.4	2.5	0.7	2.5
3500	0.7	2.4	2.4	2.5	0.7	2.5
4000	0.7	2.4	2.4	2.5	0.7	2.5
4500	0.7	2.4	2.3	2.5	0.7	2.5
5000	0.7	2.4	2.3	2.5	0.7	2.5
5500	0.7	2.4	2.3	2.5	0.7	2.5
6000	0.7	2.4	2.2	2.5	0.7	2.5
6500	0.7	2.4	2.2	2.5	0.7	2.5
7000	0.7	2.4	2.2	2.5	0.7	2.5

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Voice Signal Input Level = STD MOD Level + 16 dB = 47.96 dBmVrms + 16 = 63.96 dBmV or 1.57 Vrms

MODULATING FREQUENCY (KHz)	PEAK FREQUENCY DEVIATION (KHz)	MAXIMUM LIMIT (KHz)
0.1	0.7	2.5
0.2	0.7	2.5
0.4	2.1	2.5
0.6	2.4	2.5
0.8	2.4	2.5
1.0	2.4	2.5
1.2	2.0	2.5
1.4	1.5	2.5
1.6	2.1	2.5
1.8	2.1	2.5
2.0	2.2	2.5
2.5	2.6	2.5
3.0	2.6	2.5
3.5	0.7	2.5
4.0	0.7	2.5
4.5	0.7	2.5
5.0	0.7	2.5
6.0	0.7	2.5
7.0	0.7	2.5
8.0	0.7	2.5
9.0	0.7	2.5
10.0	0.7	2.5

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.9.5.2.2. 25 kHz Channel Spacing

MODULATING SIGNAL LEVEL (mVrms)	PEAK FREQUENCY DEVIATION (kHz) at the following modulating frequency:					MAXIMUM LIMIT (kHz)
	0.1 kHz	0.5 kHz	1.0 kHz	3.0 kHz	5.0 kHz	
50	0.7	0.7	0.9	2.5	0.7	5
100	0.7	0.7	1.4	5.0	0.7	5
150	0.7	0.7	1.6	5.0	0.7	5
200	0.7	0.8	2.1	5.0	0.7	5
250	0.7	0.9	2.5	5.0	0.7	5
300	0.7	0.9	2.6	5.0	0.7	5
350	0.7	1.0	2.9	5.0	0.7	5
400	0.7	1.0	2.9	5.0	0.7	5
450	0.7	1.1	3.2	5.0	0.7	5
500	0.7	1.2	3.7	5.0	0.7	5
600	0.7	1.3	4.4	5.0	0.7	5
700	0.7	1.8	4.8	5.0	0.7	5
800	0.7	2.3	4.8	5.0	0.7	5
900	0.7	2.6	4.6	5.0	0.7	5
1000	0.7	3.5	4.0	5.0	0.7	5
1500	0.7	4.5	3.9	5.0	0.7	5
2000	0.7	4.6	3.9	5.0	0.7	5
2500	0.7	4.1	4.5	5.0	0.7	5
3000	0.7	4.5	4.5	5.0	0.7	5
3500	0.7	4.5	3.6	5.0	0.7	5
4000	0.7	4.5	3.5	5.0	0.7	5
4500	0.7	4.5	3.5	5.0	0.7	5
5000	0.7	4.9	4.3	5.0	0.7	5
5500	0.7	4.9	4.5	5.0	0.7	5
6000	0.7	4.7	4.1	5.0	0.7	5
6500	0.7	4.7	3.6	5.0	0.7	5
7000	0.7	4.7	3.6	5.0	0.7	5

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Voice Signal Input Level = STD MOD Level + 16 dB = 50.88 dBmVrms + 16 = 66.88 dBmV or 2.208Vrms

MODULATING FREQUENCY (KHz)	PEAK FREQUENCY DEVIATION (KHz)	MAXIMUM LIMIT (KHz)
0.1	0.7	5
0.2	1.5	5
0.4	4.8	5
0.6	4.6	5
0.8	4.3	5
1.0	4.5	5
1.2	4.1	5
1.4	4.2	5
1.6	3.2	5
1.8	4.9	5
2.0	4.2	5
2.5	4.9	5
3.0	5.0	5
3.5	0.7	5
4.0	0.7	5
4.5	0.7	5
5.0	0.7	5
6.0	0.7	5
7.0	0.7	5
8.0	0.7	5
9.0	0.7	5
10.0	0.7	5

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

6.10. 99% OCCUPIED BANDWIDTH & EMISSION MASK @ FCC 2.1049, 90.209 & 90.210

6.10.1. Limits @ FCC 90.209 & 90.210

Emissions shall be attenuated below the mean output power of the transmitter as follows:

FREQUENCY RANGE (MHz)	Maximum Authorized BW (KHz)	CHANNEL SPACING (KHz)	Recommended Max. FREQ. DEVIATION (KHz)	FCC APPLICABLE MASK @ FCC 90.210
806-821/ 851-866	20	25	5	MASK B (Voice) & MASK G (Data)
821-824/ 866-869	20	12.5	5	MASK B (Voice) & MASK H (Data)


6.10.2. Method of Measurements

Refer to Exhibit 8, § 8.4 of this report for measurement details

6.10.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
EMI Receiver/ EMI Receiver	Hewlett Packard	HP 8593EM	3412A00103	9 kHz – 26.5 GHz
Attenuator(s)	Bird	DC – 22 GHz
Audio Oscillator	Hewlett Packard	HP 204C	0989A08798	DC to 1.2 MHz

6.10.4. Test Arrangement



6.10.5. Test Data

6.10.5.1. 99% Occupied Bandwidth

Frequency (MHz)	Channel Spacing (kHz)	Modulation	Measured 99% OBW (kHz)	Recommended 99% OBW (kHz)
764.0125	12.5	FM Analog Voice	10.2	11.25
766.0000	12.5	FM Analog Voice	10.1	11.25
775.9875	12.5	FM Analog Voice	10.2	11.25
794.0125	12.5	FM Analog Voice	10.2	11.25
803.0125	12.5	FM Analog Voice	10.0	11.25
806.0000	12.5	FM Analog Voice	10.0	11.25
821.0000	12.5	FM Analog Voice	10.4	11.25
823.9875	12.5	FM Analog Voice	10.2	11.25
866.0000	12.5	FM Analog Voice	10.1	11.25
868.9875	12.5	FM Analog Voice	10.1	11.25
764.0125	25.0	FM Analog Voice	15.2	20.0
766.0000	25.0	FM Analog Voice	15.2	20.0
775.9875	25.0	FM Analog Voice	15.3	20.0
794.0125	25.0	FM Analog Voice	15.3	20.0
803.0125	25.0	FM Analog Voice	14.9	20.0
806.0000	25.0	FM Analog Voice	15.0	20.0
813.5000	25.0	FM Analog Voice	15.4	20.0
821.0000	25.0	FM Analog Voice	15.6	20.0
851.0125	25.0	FM Analog Voice	15.2	20.0
858.5000	25.0	FM Analog Voice	15.1	20.0
866.0000	25.0	FM Analog Voice	15.0	20.0
764.0125	12.5	FM digital Synthesized	9.7	11.25
766.0000	12.5	FM digital Synthesized	9.7	11.25
775.9875	12.5	FM digital Synthesized	10.3	11.25
794.0125	12.5	FM digital Synthesized	9.8	11.25
803.0125	12.5	FM digital Synthesized	9.6	11.25
806.0000	12.5	FM digital Synthesized	9.6	11.25
821.0000	12.5	FM digital Synthesized	10.3	11.25
823.9875	12.5	FM digital Synthesized	10.5	11.25
866.0000	12.5	FM digital Synthesized	9.7	11.25
868.9875	12.5	FM digital Synthesized	9.6	11.25

Conform. Please refer to following Plots # 1 through # 31 for details of measurements.


ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot #: 1 99% Occupied Bandwidth Measurement, Freq: 764.0125 MHz
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot #: 2 99% Occupied Bandwidth Measurement, Freq: 766.00 MHz
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

Plot #: 3 99% Occupied Bandwidth Measurement, Freq: 775.9875 MHz
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 4 99% Occupied Bandwidth Measurement, Freq: 794.0125 MHz
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 5 99% Occupied Bandwidth Measurement, Freq: 803.0125 MHz
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 6 **99% Occupied Bandwidth Measurement, Freq: 806.00 MHz**
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 7 **99% Occupied Bandwidth Measurement, Freq: 821.00 MHz**
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 8 **99% Occupied Bandwidth Measurement, Freq: 823.9875 MHz**
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 9 **99% Occupied Bandwidth Measurement, Freq: 866.00 MHz**
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 10 99% Occupied Bandwidth Measurement, Freq: 868.9875 MHz
12.5 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 11 99% Occupied Bandwidth Measurement, Freq: 764.0125 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 12 99% Occupied Bandwidth Measurement, Freq: 766.00 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

**Plot #: 13 99% Occupied Bandwidth Measurement, Freq: 775.9875 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal**




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 14 99% Occupied Bandwidth Measurement, Freq: 794.0125 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

**Plot #: 15 99% Occupied Bandwidth Measurement, Freq: 803.0125 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal**




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 16 99% Occupied Bandwidth Measurement, Freq: 806.00 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 17 99% Occupied Bandwidth Measurement, Freq: 813.50 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 18 99% Occupied Bandwidth Measurement, Freq: 821.00 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

**Plot #: 19 99% Occupied Bandwidth Measurement, Freq: 851.0125 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal**




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 20 99% Occupied Bandwidth Measurement, Freq: 858.50 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 21 99% Occupied Bandwidth Measurement, Freq: 866.00 MHz
25 kHz Channel Spacing, FM Modulation, 2.5 kHz Sine wave signal




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

**Plot #: 22 99% Occupied Bandwidth Measurement, Freq: 764.0125 MHz
12.5 kHz Channel Spacing, Digital Modulation**




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 23 99% Occupied Bandwidth Measurement, Freq: 766.00 MHz
12.5 kHz Channel Spacing, Digital Modulation




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

**Plot #: 24 99% Occupied Bandwidth Measurement, Freq: 775.9875 MHz
12.5 kHz Channel Spacing, Digital Modulation**




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 25 99% Occupied Bandwidth Measurement, Freq: 794.0125 MHz
12.5 kHz Channel Spacing, Digital Modulation




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

**Plot #: 26 99% Occupied Bandwidth Measurement, Freq: 803.0125 MHz
12.5 kHz Channel Spacing, Digital Modulation**




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 27 99% Occupied Bandwidth Measurement, Freq: 806.00 MHz
12.5 kHz Channel Spacing, Digital Modulation




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 28 99% Occupied Bandwidth Measurement, Freq: 821.00 MHz
12.5 kHz Channel Spacing, Digital Modulation




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

**Plot #: 29 99% Occupied Bandwidth Measurement, Freq: 823.9875 MHz
12.5 kHz Channel Spacing, Digital Modulation**




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot #: 30 99% Occupied Bandwidth Measurement, Freq: 866.00 MHz
12.5 kHz Channel Spacing, Digital Modulation




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

**Plot #: 31 99% Occupied Bandwidth Measurement, Freq: 868.9875 MHz
12.5 kHz Channel Spacing, Digital Modulation**



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

6.10.5.2. Emission Masks

Conform.


- Please refer to Plots # 32 and # 33 for Details of Emission Mask B (Voice) Measurements in high power mode for 12.5 kHz Channel Spacing operation in 821-824 MHz Band.
- Please refer to Plots # 34 and # 35 for Details of Emission Mask B (Voice) Measurements in high power mode for 12.5 kHz Channel Spacing operation in 866-869 MHz Band.
- Please refer to Plots # 36 and # 37 for Details of Emission Mask B (Voice) Measurements in low power mode for 12.5 kHz Channel Spacing operation in 821-824 MHz Band.
- Please refer to Plots # 38 and # 39 for Details of Emission Mask B (Voice) Measurements in low power mode for 12.5 kHz Channel Spacing operation in 866-869 MHz Band.
- Please refer to Plots # 40 through # 42 for Details of Emission Mask B (Voice) Measurements in high power mode for 25 kHz Channel Spacing operation in 806-821 MHz Band.
- Please refer to Plots # 43 through # 45 for Details of Emission Mask B (Voice) Measurements in high power mode for 25 kHz Channel Spacing operation in 851-866 MHz Band.
- Please refer to Plots # 46 through # 48 for Details of Emission Mask B (Voice) Measurements in low power mode for 25 kHz Channel Spacing operation in 806-821 MHz Band.
- Please refer to Plots # 49 through # 51 for Details of Emission Mask B (Voice) Measurements in low power mode for 25 kHz Channel Spacing operation in 851-866 MHz Band.
- Please refer to Plots # 52 and # 53 for Details of Emission Mask H (Data) Measurements in high power mode for 12.5 kHz Channel Spacing operation in 821-824 MHz Band.
- Please refer to Plots # 54 and # 55 for Details of Emission Mask H (Data) Measurements in high power mode for 12.5 kHz Channel Spacing operation in 866-869 MHz Band.
- Please refer to Plots # 56 and # 57 for Details of Emission Mask H (Data) Measurements in low power mode for 12.5 kHz Channel Spacing operation in 821-824 MHz Band.
- Please refer to Plots # 58 and # 59 for Details of Emission Mask H (Data) Measurements in low power mode for 12.5 kHz Channel Spacing operation in 866-869 MHz Band.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

Plot # 32 **Emission Mask B (Voice), High Power, Freq. 821.00 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 33 **Emission Mask B (Voice), High Power, Freq. 823.9875 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 34 Emission Mask B (Voice), High Power, Freq. 866.00 MHz
FM Modulation with 2.5 kHz Sine wave signal, 12.5 kHz Channel Spacing



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 35 **Emission Mask B (Voice), High Power, Freq. 868.9875 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 36 **Emission Mask B (Voice), Low Power, Freq. 821.00 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 37 **Emission Mask B (Voice), Low Power, Freq. 823.9875 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 38 **Emission Mask B (Voice), Low Power, Freq. 866.00 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 39 **Emission Mask B (Voice), Low Power, Freq. 868.9875 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 40 **Emission Mask B (Voice), High Power, Freq. 806.00 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 41 **Emission Mask B (Voice), High Power, Freq. 813.50 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 42 Emission Mask B (Voice), High Power, Freq. 821.00 MHz
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 43 Emission Mask B (Voice), High Power, Freq. 851.0125 MHz
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 44 Emission Mask B (Voice), High Power, Freq. 858.50 MHz
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 45 Emission Mask B (Voice), High Power, Freq. 866.00 MHz
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 46 Emission Mask B (Voice), Low Power, Freq. 806.00 MHz
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 47 Emission Mask B (Voice), Low Power, Freq. 813.50 MHz
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

Plot # 48 **Emission Mask B (Voice), Low Power, Freq. 821.00 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 49 **Emission Mask B (Voice), Low Power, Freq. 851.0125 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 50 **Emission Mask B (Voice), Low Power, Freq. 858.50 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 51 **Emission Mask B (Voice), Low Power, Freq. 866.00 MHz**
FM Modulation with 2.5 kHz Sine wave signal, 25 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 52 **Emission Mask H (Data), High Power, Freq. 821.00 MHz**
Digital Modulation, 12.5 kHz Channel Spacing



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 53 **Emission Mask H (Data), High Power, Freq. 823.9875 MHz**
Digital Modulation, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 54 **Emission Mask H (Data), High Power, Freq. 866.00 MHz**
Digital Modulation, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 55 **Emission Mask H (Data), High Power, Freq. 868.9875 MHz**
Digital Modulation, 12.5 kHz Channel Spacing



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 56 **Emission Mask H (Data), Low Power, Freq. 821.00 MHz**
Digital Modulation, 12.5 kHz Channel Spacing



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 57 **Emission Mask H (Data), Low Power, Freq. 823.9875 MHz**
Digital Modulation, 12.5 kHz Channel Spacing



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 58 **Emission Mask H (Data), Low Power, Freq. 866.00 MHz**
Digital Modulation, 12.5 kHz Channel Spacing




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 59 **Emission Mask H (Data), Low Power, Freq. 868.9875 MHz**
Digital Modulation, 12.5 kHz Channel Spacing



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

6.11. ADJACENT CHANNEL COUPLED POWER (ACCP) REQUIREMENTS FOR TRANSMITTER @FCC 90.543

6.11.1. Emissions Limitation @ 90.543

Transmitters designed to operate in 764-776 MHz and 794-806 MHz frequency bands must meet the emissions as per below:

12.5 kHz Mobile Transmitter ACCP Requirements

Offset from Center Frequency (kHz)	Measurement Bandwidth (kHz)	Maximum ACCP Relative (dBc)	Maximum ACCP Absolute (dBm)
9.375	6.25	-40	(\1\)
15.625	6.25	-60	-45
21.875	6.25	-60	-45
37.5	25	-65	-50
62.5	25	-65	-50
87.5	25	-65	-50
150	100	-65	-50
250	100	-65	-50
<ls-thn-eq>400 to receive band	30(s)	-75	-55
in the receive band	30(s)	-100	-70

\1\ Not specified.

25 kHz Mobile Transmitter ACCP Requirements

Offset from Center Frequency (kHz)	Measurement Bandwidth (kHz)	Maximum ACCP Relative (dBc)	Maximum ACCP Absolute (dBm)
15.625	6.25	-40	(\1\)
21.875	6.25	-60	-45
37.5	25	-65	-50
62.5	25	-65	-50
87.5	25	-65	-50
150	100	-65	-50
250	100	-65	-50
<ls-thn-eq> 400 to receive band	30(s)	-75	-55
in the receive band	30(s)	-100	-70

\1\ Not specified.

Note: As per FCC 02-272, sixth notice of proposed rule making adopted on September 27, 2002, FCC proposed deletion of ACCP absolute (dbm) values for Mobiles.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

6.11.2. Method of Measurements

- (b) ACCP measurement procedure. The following are procedures for making transmitter measurements. For time division multiple access (TDMA) systems, the measurements are to be made under TDMA operation only during time slots when the transmitter is on. All measurements must be made at the input to the transmitter's antenna. Measurement bandwidth used below implies an instrument that measures the power in many narrow bandwidths (e.g. 300 Hz) and integrates these powers across a larger band to determine power in the measurement bandwidth.
- (1) Setting reference level. Using a spectrum analyzer capable of ACCP measurements, set the measurement bandwidth to the channel size. For example, for a 6.25 kHz transmitter, set the measurement bandwidth to 6.25 kHz; for a 150 kHz transmitter, set the measurement bandwidth to 150 kHz. Set the frequency offset of the measurement bandwidth to zero and adjust the center frequency of the spectrum analyzer to give the power level in the measurement bandwidth. Record this power level in dBm as the "reference power level".
 - (2) Measuring the power level at frequency offsets $<600\text{kHz}$. Using a spectrum analyzer capable of ACCP measurements, set the measurement bandwidth as shown in the tables above. Measure the ACCP in dBm. These measurements should be made at maximum power. Calculate the coupled power by subtracting the measurements made in this step from the reference power measured in the previous step. The absolute ACCP values must be less than the values given in the table for each condition above.
 - (3) Measuring the power level at frequency offsets $>600\text{kHz}$. Set a spectrum analyzer to 30 kHz resolution bandwidth, 1 MHz video bandwidth and sample mode detection. Sweep $\pm 6\text{ MHz}$ from the carrier frequency. Set the reference level to the RMS value of the transmitter power and note the absolute power. The response at frequencies greater than 600 kHz must be less than the values in the tables above.
 - (4) Upper power limit measurement. The absolute coupled power in dBm measured above must be compared to the table entry for each given frequency offset. For those mobile stations with power control, these measurements should be repeated with power control at maximum power reduction. The absolute ACCP at maximum power reduction must be less than the values in the tables above.
 - (c) Out-of-band emission limit. On any frequency outside of the frequency ranges covered by the ACCP tables in this section, the power of any emission must be reduced below the unmodulated carrier power (P) by at least $43 + 10 \log (P)$ dB.
 - (d) Authorized bandwidth. Provided that the ACCP requirements of this section are met, applicants may request any authorized bandwidth that does not exceed the channel size.
 - (e) For operations in the 764 to 776 MHz and 794 to 806 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.
 - (f) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.


[63 FR 58651, Nov. 2, 1998, as amended at 65 FR 66655, Nov. 7, 2000]

[[Page 425]]

6.11.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
EMI Receiver/ EMI Receiver	Hewlett Packard	HP 8593EM	3412A00103	9 kHz – 26.5 GHz
Attenuator(s)	Bird	DC – 22 GHz
Audio Oscillator	Hewlett Packard	HP 204C	0989A08798	DC to 1.2 MHz

6.11.4. Test Arrangement



6.11.5. Test Data

We like to submit the test data supplied by the Motorola Inc., submitted to FCC for this Radio. This Module (EUT) is an identical unit with the one tested by Motorola except its enclosure (body cover). The conducted emissions results will remain same for both type of unit (with & without enclosure).

MOTOROLA INC.

FCC ID: AZ489FT5806

Adjacent Channel Coupled Power Ratios

794.075 MHz 25.0 kHz Channel Spacing ANALOG						
Emission Designator 16K0F3E						
Ref Power Level (dBm) = 13.3						
Offset (kHz)	Meas BW (kHz)		LOWER		UPPER	Spec (dBc)
15.625	6.250		-76.7		-76.8	-40
21.875	6.250		-79.9		-80.0	-60
37.500	25.000		-75.5		-75.5	-65
62.500	25.000		-76.1		-76.1	-65
87.500	25.000		-76.2		-76.1	-65
150.000	100.000		-70.6		-70.5	-65
250.000	100.000		-71.2		-71.2	-65
350.000	100.000		-71.4		-71.4	-65
>400K - 12M	30 (Swept)		< -75			-75
12M - RX Band	30 (Swept)		< -75			-75
in RX Band	30 (Swept)		< -100			-100

794.075 MHz 12.5 kHz Channel Spacing ANALOG						
Emission Designator 11K0F3E						
Ref Power Level (dBm) = 13.4						
Offset (kHz)	Meas BW (kHz)		LOWER		UPPER	Spec (dBc)
9.375	6.250		-55.0		-55.2	-40
15.625	6.250		-77.7		-78.0	-60
21.875	6.250		-80.0		-80.2	-60
37.500	25.000		-75.5		-75.6	-65
62.500	25.000		-76.1		-76.1	-65
87.500	25.000		-76.2		-76.2	-65
150.000	100.000		-70.7		-70.6	-65
250.000	100.000		-71.2		-71.2	-65
350.000	100.000		-71.5		-71.4	-65
>400K - 12M	30 (Swept)		< -75			-75
12M - RX Band	30 (Swept)		< -75			-75
in RX Band	30 (Swept)		< -100			-100

Note: This transmitter does not incorporate automatic power control. Therefore, it was tested to comply to the Maximum ACCP Relative (dBc) limits of FCC Rule Part 90.543(a).

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

MOTOROLA INC.

FCC ID: AZ489FT5806

Adjacent Channel Coupled Power Ratios

794.075 MHZ 12.5 kHz Channel Spacing DIGITAL DATA						
Emission Designator 8K1F3D						
Ref Power Level (dBm) = 14.1						
Offset (kHz)	Meas BW (kHz)		LOWER		UPPER	Spec (dBc)
9.375	6.250		-43.7		-50.0	-40
15.625	6.250		-77.7		-78.1	-60
21.875	6.250		-80.2		-80.2	-60
37.500	25.000		-75.5		-75.6	-65
62.500	25.000		-76.0		-76.0	-65
87.500	25.000		-76.0		-76.1	-65
150.000	100.000		-70.5		-70.5	-65
250.000	100.000		-71.1		-71.1	-65
350.000	100.000		-71.3		-71.2	-65
>400K - 12M	30 (Swept)		< -75			-75
12M - RX Band	30 (Swept)		< -75			-75
in RX Band	30 (Swept)		< -100			-100

794.075 MHZ 12.5 kHz Channel Spacing DIGITAL VOICE						
Emission Designator 8K1F3E						
Ref Power Level (dBm) = 14.1						
Offset (kHz)	Meas BW (kHz)		LOWER		UPPER	Spec (dBc)
9.375	6.250		-43.7		-50.0	-40
15.625	6.250		-77.7		-78.1	-60
21.875	6.250		-80.2		-80.2	-60
37.500	25.000		-75.5		-75.6	-65
62.500	25.000		-76.0		-76.0	-65
87.500	25.000		-76.0		-76.1	-65
150.000	100.000		-70.5		-70.5	-65
250.000	100.000		-71.1		-71.1	-65
350.000	100.000		-71.3		-71.2	-65
>400K - 12M	30 (Swept)		< -75			-75
12M - RX Band	30 (Swept)		< -75			-75
in RX Band	30 (Swept)		< -100			-100

Note: This transmitter does not incorporate automatic power control. Therefore, it was tested to comply to the Maximum ACCP Relative (dBc) limits of FCC Rule Part 90.543(a).

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

MOTOROLA INC.

FCC ID: AZ489FT5806

Adjacent Channel Coupled Power Ratios

794.075 MHz 12.5 kHz Channel Spacing DES ENCRYPTION Emission Designator 8K1F3E						
Ref Power Level (dBm) = 14.1						
Offset (kHz)	Meas BW (kHz)		LOWER		UPPER	Spec (dBc)
9.375	6.250		-44.3		-49.3	-40
15.625	6.250		-77.8		-78.2	-60
21.875	6.250		-80.2		-80.3	-60
37.500	25.000		-75.4		-75.5	-65
62.500	25.000		-76.1		-76.1	-65
87.500	25.000		-76.0		-76.1	-65
150.000	100.000		-70.5		-70.6	-65
250.000	100.000		-71.1		-71.1	-65
350.000	100.000		-71.2		-71.3	-65
>400K - 12M	30 (Swept)		< -75			-75
12M - RX Band	30 (Swept)		< -75			-75
in RX Band	30 (Swept)		< -100			-100

Note: This transmitter does not incorporate automatic power control. Therefore, it was tested to comply to the Maximum ACCP Relative (dBc) limits of FCC Rule Part 90.543(a).

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

6.12. TRANSMITTER ANTENNA POWER SPURIOUS/HARMONIC CONDUCTED EMISSIONS @ FCC 90.210

6.12.1. Limits @ 90.210

Emissions shall be attenuated below the mean output power of the transmitter as follows:

FCC Rules	Frequency Range	Attenuation Limit (dBc)
90.210(b) – Voice	10 MHz to Lowest frequency of the radio to 10 th harmonic of the highest frequency of the radio	43+10*log(P) or -13 dBm
90.210(d) – Voice & data	10 MHz to Lowest frequency of the radio to 10 th harmonic of the highest frequency of the radio	50+10*log(P) or -20 dBm or 70 dBc whichever is less


6.12.2. Method of Measurements

Refer to Exhibit 8 § 8.5 of this report for measurement details

6.12.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
EMI Receiver/ EMI Receiver	Hewlett Packard	HP 8593EM	3412A00103	9 kHz – 26.5 GHz
Attenuator(s)	Bird	DC – 22 GHz
Audio Oscillator	Hewlett Packard	HP 204C	0989A08798	DC to 1.2 MHz
Highpass Filter, Microphase	Microphase	CR220HID	IIT111000AC	Cut-off Frequency at 600 MHz, 1.3 GHz or 4 GHz

6.12.4. Test Arrangement



6.12.5. Test Data

Remarks:

- The transmitter conducted emissions were scanned from 10 MHz to 10 GHz at 12.5 kHz channel spacing / FM voice modulation, 12.5 kHz channel spacing / FM digital modulation and 25 kHz channel spacing / FM voice modulation and the results were found the same. The following tables show test data measured with the transmitter set at 12.5 kHz channel spacing / FM voice modulation as representative.
- The most stringent limit = $50 + 10 \cdot \log(P \text{ in watts})$ were applied for both 12.5 kHz and 25 kHz channel spacing operation for worst case of measurements.

6.12.5.1. High Power Setting (33.20 dBm) at Lowest Frequency (764.0125 MHz)

Fundamental Frequency:		764.0125 MHz			
RF Output Power:		33.20 dBm (Conducted)			
Modulation:		FM modulation with 2.5 kHz Sine Wave Signal			
FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
1523.0	-35.8	-69.0	-53.2	-15.8	PASS
The emissions were scanned from 10 MHz to 10 GHz and all emissions within 20 dB below the limits were recorded. Please refer to plots # 60 & 61 for details of measurement.					

6.12.5.2. High Power Setting (34.41 dBm) at Middle Frequency (821.00 MHz)

Fundamental Frequency:		821.00 MHz			
RF Output Power:		34.41 dBm (Conducted)			
Modulation:		FM modulation with 2.5 kHz Sine Wave Signal			
FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
10 -10000	**	**	-54.4	< -20.0	PASS
The emissions were scanned from 10 MHz to 10 GHz and all emissions within 20 dB below the limits were recorded. Please refer to plots # 62 & 63 for details of measurement.					

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

6.12.5.3. High Power Setting (34.39 dBm) at Highest Frequency (868.9875 MHz)

Fundamental Frequency:	868.9875 MHz				
RF Output Power:	34.39 dBm (Conducted)				
Modulation:	FM modulation with 2.5 kHz Sine Wave Signal				
FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
4336.67	-31.9	-66.3	-54.4	-11.9	PASS

The emissions were scanned from 10 MHz to 10 GHz and all emissions within 20 dB below the limits were recorded. Please refer to plots # 64 & 65 for details of measurement.

6.12.5.4. Low Power Setting (29.86 dBm) at Lowest Frequency (764.0125 MHz)

Fundamental Frequency:	764.0125 MHz				
RF Output Power:	29.86 dBm (Conducted)				
Modulation:	FM modulation with 2.5 kHz Sine Wave Signal				
FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
1523.0	-37.9	-67.8	-49.9	-17.9	PASS

The emissions were scanned from 10 MHz to 10 GHz and no emissions within 20 dB below the limits were found. Please refer to plots # 66 & 67 for details of measurement.

6.12.5.5. Low Power Setting (29.86 dBm) at Middle Frequency (821.0 MHz)

Fundamental Frequency:	821.0 MHz				
RF Output Power:	29.86 dBm (Conducted)				
Modulation:	FM modulation with 2.5 kHz Sine Wave Signal				
FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
10 -10000	**	**	-49.9	< -20.0	PASS

The emissions were scanned from 10 MHz to 10 GHz and no emissions within 20 dB below the limits were found. Please refer to plots # 68 & 69 for details of measurement.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

6.12.5.6. Low Power Setting (30.33 dBm) at Highest Frequency (868.9875 MHz)


Fundamental Frequency:	868.9875 MHz				
RF Output Power:	30.33 dBm (Conducted)				
Modulation:	FM modulation with 2.5 kHz Sine Wave Signal				
FREQUENCY (MHz)	TRANSMITTER CONDUCTED ANTENNA EMISSIONS		LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
	(dBm)	(dBc)			
10 -10000	**	**	-50.4	< -20.0	PASS
The emissions were scanned from 10 MHz to 10 GHz and no emissions within 20 dB below the limits were found. Please refer to plots # 70 & 71 for details of measurement.					

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

Plot # 60 **Transmitter Antenna Power Conducted Emissions.**
Freq. 764.0125 MHz, High Power




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 61 **Transmitter Antenna Power Conducted Emissions.**
Freq. 764.0125 MHz, High Power




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 62 **Transmitter Antenna Power Conducted Emissions.**
Freq. 821.00 MHz, High Power




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 63 **Transmitter Antenna Power Conducted Emissions.**
Freq. 821.00 MHz, High Power




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 64 **Transmitter Antenna Power Conducted Emissions.**
Freq. 868.9875 MHz, High Power




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 65 **Transmitter Antenna Power Conducted Emissions.**
Freq. 868.9875 MHz, High Power




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 66 **Transmitter Antenna Power Conducted Emissions.**
Freq. 764.0125 MHz, Low Power



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

Marker 1 [T1]
 -37.92 dBm
 1.52304609 GHz

Ref Lvl
 10 dBm

RBW 100 kHz
 VBW 1 MHz
 SWT 10 s
 Unit dBm
 RF Att 0 dB

20.4 dB Offset


▼1 [T1] -37.92 dBm
 1.52304609 GHz
 ▼2 [T1] -59.18 dBm
 2.28056112 GHz
 ▼3 [T1] -56.78 dBm
 3.81362725 GHz

20 dBm
 MAX

Start 1 GHz
 900 MHz
 Stop 10 GHz

Date: 9. DEC. 2003 14:19:42

Plot # 68 **Transmitter Antenna Power Conducted Emissions.**
Freq. 821.0 MHz, Low Power




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

Plot # 69 **Transmitter Antenna Power Conducted Emissions.**
Freq. 821.0 MHz, Low Power




ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

Plot # 70 **Transmitter Antenna Power Conducted Emissions.**
Freq. 868.9875 MHz, Low Power



ULTRATECH GROUP OF LABS


3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

Plot # 71 **Transmitter Antenna Power Conducted Emissions.**
Freq. 868.9875 MHz, Low Power



ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

6.13. TRANSMITTER SPURIOUS/HARMONIC RADIATED EMISSIONS @ FCC 90.210

6.13.1. Limits @ FCC 90.210

Emissions shall be attenuated below the mean output power of the transmitter as follows:

FCC Rules	Frequency Range	Attenuation Limit (dBc)
90.210(b) – Voice	10 MHz to Lowest frequency of the radio to 10 th harmonic of the highest frequency of the radio	43+10*log(P) or -13 dBm
90.210(d) – Voice & data	10 MHz to Lowest frequency of the radio to 10 th harmonic of the highest frequency of the radio	50+10*log(P) or -20 dBm or 70 dBc whichever is less

6.13.2. Method of Measurements

The spurious/harmonic ERP measurements are using substitution method specified in Exhibit 8, § 8.2 of this report and its value in dBc is calculated as follows:

- (1) If the transmitter's antenna is an integral part of the EUT, the ERP is measured using substitution method.
- (2) If the transmitter's antenna is non-integral and diverse, the lowest ERP of the carrier with 0 dBi antenna gain is used for calculation of the spurious/harmonic emissions in dBc:
Lowest ERP of the carrier = EIRP – 2.15 dB = P_c + G – 2.15 dB = xxx dBm (conducted) + 0 dBi – 2.15 dB
- (3) Spurious /harmonic emissions levels expressed in dBc (dB below carrier) are as follows:

$$\text{ERP of spurious/harmonic (dBc)} = \text{ERP of carrier (dBm)} - \text{ERP of spurious/harmonic emission (dBm)}$$

6.13.3. Test Equipment List

Test Instruments	Manufacturer	Model No.	Serial No.	Frequency Range
Spectrum Analyzer/ EMI Receiver	Hewlett Packard	HP 8546A	...	9 kHz to 5.6 GHz with built-in 30 dB Gain Pre-selector, QP, Average & Peak Detectors.
RF Amplifier	Com-Power	PA-102		1 MHz to 1 GHz, 30 dB gain nominal
Microwave Amplifier	Hewlett Packard	HP 83017A		1 GHz to 26.5 GHz, 30 dB nominal
Biconilog Antenna	EMCO	3142	10005	30 MHz to 2 GHz
Dipole Antenna	EMCO	3121C	8907-434	30 GHz – 1 GHz
Dipole Antenna	EMCO	3121C	8907-440	30 GHz – 1 GHz
Horn Antenna	EMCO	3155	9701-5061	1 GHz – 18 GHz
Horn Antenna	EMCO	3155	9911-5955	1 GHz – 18 GHz
RF Signal Generator	Hewlett Packard	HP 83752B	3610A00457	0.01 – 20 GHz

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

6.13.4. Test Setup

Please refer to Photo 1 to 2 in Annex 1 for detailed of test setup.

6.13.5. Test Data

Remarks:

- The transmitter radiated emissions were scanned from 10 MHz to 8.5 GHz at 12.5 kHz channel spacing / FM voice modulation, 12.5 kHz channel spacing / FM digital modulation and 25 kHz channel spacing / FM voice modulation and the results were found the same. The following tables show test data measured with the transmitter set at 12.5 kHz channel spacing / FM voice modulation as representative.
- The most stringent limit = $50 + 10 \cdot \log(P \text{ in watts})$ were applied for both 12.5 kHz and 25 kHz channel spacing operation with high power setting for worst case of measurements.

6.13.5.1. Near Lowest Frequency (764.0125 MHz) with High Power Setting (33.2 dBm)

FREQUENCY (MHz)	E-FIELD @3m (dBuV/m)	ERP measured by Substitution Method (dBm) (dBc)		EMI DETECTOR (Peak/QP)	ANTENNA POLARIZATION (H/V)	LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
1528	67.7	-23.4	-56.6	PEAK	V	-53.2	-3.4	PASS
1528	66.9	-25.5	-58.7	PEAK	H	-53.2	-5.5	PASS

The emissions were scanned from 10 MHz to 8 GHz and all emissions within 20 dB below the limits were recorded.

6.13.5.2. Near Middle Frequency (821.0 MHz) with High Power Setting (34.4 dBm)

FREQUENCY (MHz)	E-FIELD @3m (dBuV/m)	ERP measured by Substitution Method (dBm) (dBc)		EMI DETECTOR (Peak/QP)	ANTENNA POLARIZATION (H/V)	LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
1642	60.7	-30.7	-65.1	PEAK	V	-54.4	-10.7	PASS
1642	57.3	-36.8	-71.2	PEAK	H	-54.4	-16.8	PASS
4105	58.5	-33.4	-67.8	PEAK	V	-54.4	-13.4	PASS
4105	54.2	-40.6	-75.0	PEAK	H	-54.4	-20.6	PASS

The emissions were scanned from 10 MHz to 8.5 GHz and all emissions within 20 dB below the limits were recorded.

6.13.5.3. Highest Frequency (868.9875 MHz) with High Power Setting (34.4 dBm)

FREQUENCY (MHz)	E-FIELD @3m (dBuV/m)	ERP measured by Substitution Method (dBm) (dBc)		EMI DETECTOR (Peak/QP)	ANTENNA POLARIZATION (H/V)	LIMIT (dBc)	MARGIN (dB)	PASS/ FAIL
1738	65.1	-24.1	-58.5	PEAK	V	-54.4	-4.1	PASS
1738	59.9	-33.6	-68.0	PEAK	H	-54.4	-13.6	PASS
4345	64.1	-26.5	-60.9	PEAK	V	-54.4	-6.5	PASS
4345	57.1	-38.1	-72.5	PEAK	H	-54.4	-18.1	PASS

The emissions were scanned from 10 MHz to 8.5 GHz and all emissions within 20 dB below the limits were recorded.

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90
May 25, 2004

EXHIBIT 7. MEASUREMENT UNCERTAINTY

The measurement uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 and NIS 81 (1994)

7.1. RADIATED EMISSION MEASUREMENT UNCERTAINTY

CONTRIBUTION (Radiated Emissions)	PROBABILITY DISTRIBUTION	UNCERTAINTY (+ dB)	
		3 m	10 m
Antenna Factor Calibration	Normal (k=2)	± 1.0	± 1.0
Cable Loss Calibration	Normal (k=2)	± 0.3	± 0.5
EMI Receiver specification	Rectangular	± 1.5	± 1.5
Antenna Directivit	Rectangular	± 0.5	± 0.5
Antenna factor variation with height	Rectangular	± 2.0	± 0.5
Antenna phase center variation	Rectangular	0.0	± 0.2
Antenna factor frequency interpolation	Rectangular	± 0.25	± 0.25
Measurement distance variation	Rectangular	± 0.6	± 0.4
Site imperfections	Rectangular	± 2.0	± 2.0
Mismatch: Receiver VRC $\Gamma_1 = 0.2$ Antenna VRC $\Gamma_R = 0.67(\text{Bi}) 0.3 (\text{Lp})$ Uncertainty limits $20\text{Log}(1+\Gamma_1\Gamma_R)$	U-Shaped	+1.1 -1.25	± 0.5
System repeatability	Std. Deviation	± 0.5	± 0.5
Repeatability of EUT		-	-
Combined standard uncertainty	Normal	+2.19 / -2.21	+1.74 / -1.72
Expanded uncertainty U	Normal (k=2)	+4.38 / -4.42	+3.48 / -3.44

Calculation for maximum uncertainty when 3m biconical antenna including a factor of k=2 is used:

$$U = 2u_c(y) = 2x(+2.19) = +4.38 \text{ dB} \quad \text{And} \quad U = 2u_c(y) = 2x(-2.21) = -4.42 \text{ dB}$$

ULTRATECH GROUP OF LABS

3000 Bristol Circle, Oakville, Ontario, Canada L6H 6G4
Tel. #: 905-829-1570, Fax. #: 905-829-8050, Email: vic@ultratech-labs.com, Website: <http://www.ultratech-labs.com>

File #: TIL-046FCC90

May 25, 2004

All test results contained in this engineering test report are traceable to National Institute of Standards and Technology (NIST)

EXHIBIT 8. MEASUREMENT METHODS

8.1. CONDUCTED POWER MEASUREMENTS

- The following shall be applied to the combination(s) of the radio device and its intended antenna(e).
- If the RF level is user adjustable, all measurements shall be made with the highest power level available to the user for that combination.
- The following method of measurement shall apply to both conducted and radiated measurements.
- The radiated measurements are performed at the Ultratech Calibrated Open Field Test Site.
- The measurement shall be performed using normal operation of the equipment with modulation.

Test procedure shall be as follows:

Step 1: Duty Cycle measurements if the transmitter's transmission is transient

- Using a EMI Receiver with the frequency span set to 0 Hz and the sweep time set at a suitable value to capture the envelope peaks and the duty cycle of the transmitter output signal;
- The duty cycle of the transmitter, $x = \text{Tx on} / (\text{Tx on} + \text{Tx off})$ with $0 < x < 1$, is measure and recorded in the test report. For the purpose of testing, the equipment shall be operated with a duty cycle that is equal or more than 0.1.


Step 2: Calculation of Average EIRP. See Figure 1

- The average output power of the transmitter shall be determined using a wideband, calibrated RF average power meter with the power sensor with an integration period that exceeds the repetition period of the transmitter by a factor 5 or more. The observed value shall be recorded as "A" (in dBm);
- The e.i.r.p. shall be calculated from the above measured power output "A", the observed duty cycle x, and the applicable antenna assembly gain "G" in dBi, according to the formula:

$$\text{EIRP} = \text{A} + \text{G} + 10\log(1/x)$$

$$\{ X = 1 \text{ for continuous transmission} \Rightarrow 10\log(1/x) = 0 \text{ dB} \}$$

Figure 1.



8.2. RADIATED POWER MEASUREMENTS (ERP & EIRP) USING SUBSTITUTION METHOD

8.2.1. Maximizing RF Emission Level (E-Field)

- (a) The measurements was performed with full rf output power and modulation.
- (b) Test was performed at listed 3m open area test site (listed with FCC, IC, ITI, NVLAP, ACA & VCCI).
- (c) The transmitter under test was placed at the specified height on a non-conducting turntable (80 cm height)
- (d) The BICONILOG antenna (20 MHz to 1 GHz) or HORN antenna (1 GHz to 18 GHz) was used for measuring.
- (e) Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level

Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor

$E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB/m)}$

- (f) Set the EMI Receiver and #2 as follows:

Center Frequency:	test frequency
Resolution BW:	100 kHz
Video BW:	same
Detector Mode:	positive
Average:	off
Span:	3 x the signal bandwidth

- (g) The test antenna was lowered or raised from 1 to 4 meters until the maximum signal level was detected.
- (h) The transmitter was rotated through 360° about a vertical axis until a higher maximum signal was received.
- (i) The test antenna was lowered or raised again from 1 to 4 meters until a maximum was obtained. This level was recorded.
- (j) The recorded reading was corrected to the true field strength level by adding the antenna factor, cable loss and subtracting the pre-amplifier gain.
- (k) The above steps were repeated with both transmitters' antenna and test receiving antenna placed in vertical and horizontal polarization. Both readings with the antennas placed in vertical and horizontal polarization shall be recorded.
- (l) Repeat for all different test signal frequencies

8.2.2. Measuring the EIRP of Spurious/Harmonic Emissions using Substitution Method

- (a) Set the EMI Receiver (for measuring E-Field) and Receiver #2 (for measuring EIRP) as follows:

Center Frequency:	equal to the signal source
Resolution BW:	10 kHz
Video BW:	same
Detector Mode:	positive
Average:	off
Span:	3 x the signal bandwidth

- (b) Load an appropriate correction factors file in EMI Receiver for correcting the field strength reading level

Total Correction Factor recorded in the EMI Receiver = Cable Loss + Antenna Factor
 $E \text{ (dBuV/m)} = \text{Reading (dBuV)} + \text{Total Correction Factor (dB/m)}$

- (c) Select the frequency and E-field levels obtained in the Section 8.2.1 for ERP/EIRP measurements.
(d) Substitute the EUT by a signal generator and one of the following transmitting antenna (substitution antenna):
 ♦ DIPOLE antenna for frequency from 30-1000 MHz or
 ♦ HORN antenna for frequency above 1 GHz }.
(e) Mount the transmitting antenna at 1.5 meter high from the ground plane.
(f) Use one of the following antenna as a receiving antenna:
 ♦ DIPOLE antenna for frequency from 30-1000 MHz or
 ♦ HORN antenna for frequency above 1 GHz }.
(g) If the DIPOLE antenna is used, tune it's elements to the frequency as specified in the calibration manual.
(h) Adjust both transmitting and receiving antenna in a VERTICAL polarization.
(i) Tune the EMI Receivers to the test frequency.
(j) Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.
(k) The transmitter was rotated through 360° about a vertical axis until a higher maximum signal was received.
(l) Lower or raise the test antenna from 1 to 4 meters until the maximum signal level was detected.
(m) Adjust input signal to the substitution antenna until an equal or a known related level to that detected from the transmitter was obtained in the test receiver.
(n) Record the power level read from the Average Power Meter and calculate the ERP/EIRP as follows:

$$P = P1 - L1 = (P2 + L2) - L1 = P3 + A + L2 - L1$$

$$EIRP = P + G1 = P3 + L2 - L1 + A + G1$$

$$ERP = EIRP - 2.15 \text{ dB}$$

$$\text{Total Correction factor in EMI Receiver \# 2} = L2 - L1 + G1$$

Where: P: Actual RF Power fed into the substitution antenna port after corrected.
P1: Power output from the signal generator
P2: Power measured at attenuator A input
P3: Power reading on the Average Power Meter
EIRP: EIRP after correction
ERP: ERP after correction

- (o) Adjust both transmitting and receiving antenna in a HORIZONTAL polarization, then repeat step (k) to (o)
(p) Repeat step (d) to (o) for different test frequency
(q) Repeat steps (c) to (j) with the substitution antenna oriented in horizontal polarization.
(r) Actual gain of the EUT's antenna is the difference of the measured EIRP and measured RF power at the RF port. Correct the antenna gain if necessary.:

Figure 2





Figure 3



8.3. FREQUENCY STABILITY

Refer to FCC @ 2.1055.

- (a) The frequency stability shall be measured with variation of ambient temperature as follows: From -30 to +50 centigrade except that specified in subparagraph (2) & (3) of this paragraph.
- (b) Frequency measurements shall be made at extremes of the specified temperature range and at intervals of not more than 10 centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stability circuitry need be subjected to the temperature variation test.
- (d) The frequency stability supply shall be measured with variation of primary supply voltage as follows:
 - (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
 - (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.
 - (3) The supply voltage shall be measured at the input to the cable normally provide with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.
- (e) When deemed necessary, the Commission may require tests of frequency stability under conditions in addition to those specifically set out in paragraphs (a), (b), (c) and (d) of this section. (For example, measurements showing the effect of proximity to large metal objects, or of various types of antennas, may be required for portable equipment).

8.4. EMISSION MASK

Voice or Digital Modulation Through a Voice Input Port @ 2.1049(c)(i): - The transmitter was modulated by a 2.5 KHz tone signal at an input level 16 dB greater than that required to produce 50% modulation (e.g.: ± 2.5 KHz peak deviation at 1 KHz modulating frequency). The input level was established at the frequency of maximum response of the audio modulating circuit.

Digital Modulation Through a Data Input Port @ 2.1049(h): - Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudo-random generators or other devices required in normal service. Additionally, the Emission Masks shall be shown for operation with any devices used for modifying the spectrum when such devices are operational at the discretion of the user.

The following EMI Receiver bandwidth shall be used for measurement of Emission Mask/Out-of-Band Emission Measurements:

- (1) For 25 kHz Channel Spacing: RBW = 300 Hz
- (2) For 12.5 kHz or 6.25 kHz Channel Spacings: RBW = 100 Hz

The all cases the Video Bandwidth shall be equal or greater than the measuring bandwidth.

8.5. SPURIOUS EMISSIONS (CONDUCTED)

With transmitter modulation characteristics described in Out-of-Band Emissions measurements @ 2.1049, the transmitter spurious and harmonic emissions were scanned. The spurious and harmonic emissions were measured with the EMI Receiver controls set as RBW = 30 kHz minimum, VBW \geq RBW and SWEEP TIME = AUTO). The transmitter was operated at a full rated power output, and modulated as follows:

FCC CFR 47, Para. 2.1057 - Frequency spectrum to be investigated:- The spectrum was investigated from the lowest radio generated in the equipment up to at least the 10th harmonic of the carrier frequency or to the highest frequency practicable in the present state of the art of measuring techniques, whichever is lower. Particular attention should be paid to harmonics and subharmonics of the carrier frequency. Radiation at the frequencies of multiplier stages should be checked. The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

FCC CFR 47, Para. 2.1051 - Spurious Emissions at Antenna Terminal:- The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of the harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.