

FCC 47 CFR MPE REPORT

Beijing Xiaomi Electronics Co.,Ltd

XIAOMI Soundbar 3.1ch

Model Number: S26-S

FCC ID: 2AIMRMITVS26

Prepared for:	Beijing Xiaomi Electronics Co.,Ltd
	Room 802,8F,Building 5,No.15,Kechuang Ten Street, Beijing Economic & Technological Development Zone, Beijing, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2109198
Date of Test:	Aug. 31~Sep. 14, 2021
Date of Report:	Sep. 22, 2021

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Antenna	Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)
Bluetooth	GFSK	2402	2.75	1.8836	2±1
		2441	2.64	1.8365	2±1
		2480	2.22	1.6672	2±1
	8-DPSK	2402	3.91	2.4604	3±1
		2441	3.80	2.3988	3±1
		2480	3.35	2.1627	3±1
5.8G Wireless	GFSK	5727	10.65	11.6145	10±1
		5785	10.06	10.1391	10±1
		5848	9.87	9.7051	9±1

3. Calculated Result and Limit

Mode	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
2.4G Band						
Bluetooth	3	4.00	2.512	0.0009	1	Complies
5.8G Wireless	11	1.56	1.432	0.0005	1	Complies

Bluetooth +5.8G Wireless

MAX Power Density (S) (mW/cm ²) Bluetooth	MAX Power Density (S) (mW/cm ²) 5.8G Wireless	Power Density (S) (mW/cm ²) Total	Limited of Power Density (S) (mW/cm ²)	Test Result
0.0009	0.0005	0.0014	1	Complies

End of Test Report