



RF - TEST REPORT

- FCC Part 15.247, RSS-247 -

Type / Model Name : 2392755

Product Description : BLE module

Applicant : Hilti Corporation

Address : Feldkircherstrasse 100

9494 SCHAAN, LIECHTENSTEIN

Manufacturer : Hilti Corporation

Address : Feldkircherstrasse 100

9494 SCHAAN, LIECHTENSTEIN

Test Result according to the standards
listed in clause 1 test standards:

POSITIVE

Test Report No. : 80183253-03 Rev_3

29. January 2025

Date of issue



Deutsche
Akkreditierungsstelle
D-PL-12030-01-03
D-PL-12030-01-04

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

Contents

1	TEST STANDARDS	3
2	EQUIPMENT UNDER TEST	4
2.1	Information provided by the Client	4
2.2	Sampling	4
2.3	General remarks	4
2.4	Photo documentation of the EUT – Detailed photos see ATTACHMENT A	4
2.5	Equipment type	4
2.6	Short description of the equipment under test (EUT)	4
2.7	Variants of the EUT	4
2.8	Operation frequency and channel plan	5
2.9	Transmit operating modes	5
2.10	Antenna	5
2.11	Power supply system utilised	5
2.12	Peripheral devices and interface cables	6
2.13	Determination of worst-case conditions for final measurement	6
3	TEST RESULT SUMMARY	7
3.1	Revision history of test report	7
3.2	Final assessment	8
4	TEST ENVIRONMENT	9
4.1	Address of the test laboratory	9
4.2	Environmental conditions	9
4.3	Statement of the measurement uncertainty	9
4.4	Conformity Decision Rule	10
4.5	Measurement protocol for FCC and ISED	10
5	TEST CONDITIONS AND RESULTS	13
5.1	EBW and OBW	13
5.2	Maximum peak radiated output power	16
5.3	Power spectral density	19
5.4	Radiated emissions in restricted bands	21
5.5	Spurious emissions	34
5.6	Antenna application	39
5.7	Transmitter frequency stability	40
6	USED TEST EQUIPMENT AND ACCESSORIES	46

ATTACHMENT A and B as separate supplements

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules and Regulations Part 15, Subpart A - General (March 2024)

Part 15, Subpart A, Section 15.31

Measurement standards

Part 15, Subpart A, Section 15.33

Frequency range of radiated measurements

Part 15, Subpart A, Section 15.35

Measurement detector functions and bandwidths

FCC Rules and Regulations Part 15, Subpart C - Intentional Radiators (March 2024)

Part 15, Subpart C, Section 15.203

Antenna requirement

Part 15, Subpart C, Section 15.204
modifications

External radio frequency power amplifiers and antenna

Part 15, Subpart C, Section 15.205

Restricted bands of operation

Part 15, Subpart C, Section 15.207

Conducted limits

Part 15, Subpart C, Section 15.209

Radiated emission limits, general requirements

Part 15, Subpart C, Section 15.247

Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz and
5725 - 5850 MHz

ANSI C63.10: 2013

Testing Unlicensed Wireless Devices

KDB 558074 D01 v05r02

Guidance for compliance measurements on DTS; FHSS and hybrid
system devices operating under Section 15.247 of the FCC rules,
April 2, 2019.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

2 EQUIPMENT UNDER TEST

2.1 Information provided by the Client

Please note, we do not take any responsibility for information provided by the client or his representative which may have an influence on the validity of the test results.

2.2 Sampling

The customer is responsible for the choice of sample. Sample configuration, start-up and operation is carried out by the customer or according his/her instructions.

2.3 General remarks

None.

2.4 Photo documentation of the EUT – Detailed photos see ATTACHMENT A

2.5 Equipment type

BLE device

2.6 Short description of the equipment under test (EUT)

The EUT is a BLE module intended to establish communication between different devices. The module uses wireless BLE communication. System devices incorporating the BLE module are i.e. the rotating laser or the automatic tripod as part of the Hilti rotating laser platform.

Number of tested samples:	2
Serial number:	N/A (pre-production samples)
Firmware version:	0.1.1-135 (radiated sample)
	1.0.0-233 (conducted sample)

2.7 Variants of the EUT

There are no variants.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

2.8 Operation frequency and channel plan

The operating frequency is 2400 MHz to 2483.5 MHz.

Channel plan:

Channel No.	Frequency (MHZ)	Channel No.	Frequency (MHZ)
37	2402	18	2442
0	2404	19	2444
1	2406	20	2446
2	2408	21	2448
3	2410	22	2450
4	2412	23	2452
5	2414	24	2454
6	2416	25	2456
7	2418	26	2458
8	2420	27	2460
9	2422	28	2462
10	2424	29	2464
38	2426	30	2466
11	2428	31	2468
12	2430	32	2470
13	2432	33	2472
14	2434	34	2474
15	2436	35	2476
16	2438	36	2478
17	2440	39	2480

Note: The marked frequencies are used for testing.

2.9 Transmit operating modes

The EUT uses GFSK modulation and may provide following data rates:

- 125 kbps

(kbps = kilobits per second)

2.10 Antenna

The following antenna shall be used with the EUT:

Number	Characteristic	Model number	Plug	Frequency range (GHz)	Gain (dBi)
1	Omni	PCB inverted F antenna	PCB	2.4 – 2.5	1.1

2.11 Power supply system utilised

Power supply voltage, V_{nom} : 5.0 V DC (battery powered)

IC ID: 5228A-PR4X

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

3 TEST RESULT SUMMARY

FCC Rule Part	RSS Rule Part	Description	Result
15.207(a)	RSS-Gen, 8.8	AC power line conducted emissions	not applicable
15.247(a)(2)	RSS-247, 5.2.(a)	-6 dB EBW	passed
15.247(b)(3)	RSS-247, 5.2(d)	Maximum peak conducted output power	passed
15.247(b)(4)	-	Defacto limit	passed
15.247(d)	RSS-247, 5.5	Out-of-band emission, radiated	passed
15.247(d)	RSS-Gen, 8.10	Emissions in restricted bands	passed
15.247(e)	RSS-247, 5.2(b)	PSD	passed
15.35(c)	RSS-Gen, 8.2	Pulsed operation	passed
15.203	RSS-Gen, 6.8	Antenna requirement	passed
-	RSS-Gen, 6.11	Transmitter frequency stability	passed
-	RSS-Gen, 6.7	99 % Bandwidth	passed

The mentioned new RSS Rule Parts in the above table are related to:
 RSS-Gen, Issue 5 + Amendment 1 + Amendment 2, March 2019
 RSS-247, Issue 3, August 2023

3.1 Revision history of test report

Test report No	Rev.	Issue Date	Changes
80183253-03	0	25 April 2024	Initial test report
	1	24 September 2024	clause 3: correction of references in summary table clause 4.5.3.2.4: correction of table height in text passage clause 5.3.5: correction of PSD values in table clause 5: removing test setup photos (see Attachment B)
	2	16 January 2025	clause 2.6: correction of EUT description clause 3: correction of references in summary table clause 5.3.5: correction of PSD values in table
	3	29 January 2025	clause 5.2.6: adding plots CPC clause 5.3.5: correction of PSD value 2440 MHz in table

The test report with the highest revision number replaces the previous test reports.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

3.2 Final assessment

The equipment under test fulfills the requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 17 October 2023

Testing concluded on : 08 January 2024

Checked by:

Tested by:

Klaus Gegenfurtner
Teamleader Radio

Franz-Xaver Schrettenbrunner
Radio Team

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

CSA Group Bayern GmbH
Ohmstrasse 1-4
94342 STRASSKIRCHEN
GERMANY

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15 - 35 °C

Humidity: 30 - 60 %

Atmospheric pressure: 86 - 106 kPa

4.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. It is noted that the expanded measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor $k = 2$. The true value is located in the corresponding interval with a probability of 95 %. The measurement uncertainty was calculated for all measurements listed in this test report on basis of the ETSI Technical Report TR 100 028 Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1 and Part 2. The results are documented in the quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	± 3.29 dB
20 dB Bandwidth	Center frequency of EUT	95%	$\pm 2.5 \times 10^{-7}$
99% Occupied Bandwidth	Center frequency of EUT	95%	$\pm 2.5 \times 10^{-7}$
Radiated Spurious Emissions	9 kHz to 30 MHz	95%	± 3.53 dB
Radiated Spurious Emissions	30 MHz to 1000 MHz	95%	± 3.71 dB
Radiated Spurious Emissions	1000 MHz to 10000 MHz	95%	± 2.34 dB
Peak conducted output power	902 MHz to 928 MHz	95%	± 0.35 dB
Conducted Spurious Emissions	9 kHz to 10000 MHz	95%	± 2.15 dB

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

4.4 Conformity Decision Rule

The applied conformity decision rule is based on ILAC G8:09/2019 clause 4.2.1 Binary Statement for Simple Acceptance Rule ($w = 0$).

Details can be found in the procedure CSA_B_V50_29.

4.5 Measurement protocol for FCC and ISCED

4.5.1 General information

CSA Group Bayern GmbH is recognized as wireless testing laboratory under the CAB identifier:

FCC: DE 0011

ISED: DE0009

4.5.2 General Standard information

The test methods used comply with ANSI C63.10 - "Testing Unlicensed Wireless Devices".


4.5.2.1 Justification

The equipment under test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions.

4.5.3 Details of test procedures

4.5.3.1 Conducted emission

Test setup according ANSI C63.10



The final level, expressed in dB μ V, is arrived at by taking the reading directly from the Spectrum analyser. This level is compared to the limit.

To convert between dB μ V and μ V, the following conversions apply:

$$\text{dB}\mu\text{V} = 20(\log \mu\text{V})$$

$$\mu\text{V} = \text{Inverse log}(\text{dB}\mu\text{V}/20)$$

Conducted emissions on the 50 Hz and/or 60 Hz power interface of the EUT are measured in the frequency range of 150 kHz to 30 MHz. The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasi-peak detection and a Line Impedance Stabilization Network (LISN) with 50 Ω / 50 μ H (CISPR 16) characteristics. The receiver is protected by means of an impedance matched pulse limiter connected directly to the RF input. Table top equipment is placed on a non-conducting table 80 centimetres above the floor and is positioned 40 centimetres from the vertical ground plane (wall) of the screen room. If the minimum limit margin appears to be less than 20 dB with a peak mode measurement, the emission is re-measured using a tuned receiver with quasi-peak and average detection and recorded on the data sheets.


FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

4.5.3.2 Radiated emission

4.5.3.2.1 OATS1 test site (9 kHz - 30 MHz):


Test setup according ANSI C63.10



Emissions from the EUT are measured in the frequency range of 9 MHz to 30 MHz using a tuned receiver and a calibrated loop antenna. Table top equipment is placed on a 1.0 X 1.5 m non-conducting table 80 centimetres above the ground plane. Cables to simulators/testers (if used in this test) are routed through the centre of the table and to a screened room located outside the test area. The antenna is positioned 3, 10 or 30 metres horizontally from the EUT and is repeated vertically. To locate maximum emissions from the test sample the antenna is varied along the site axis and the EUT is rotated 360 degrees.

4.5.3.2.2 OATS1 test site (30 MHz - 1 GHz):

Test setup according ANSI C63.10.



Spurious emissions from the EUT are measured in the frequency range of 30 MHz to 1000 MHz using a tuned receiver and appropriate broadband linearly polarised antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasi-peak detection. Table top equipment is placed on a 1.0 X 1.5 m non-conducting table 80 centimetres above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. Cables to simulators/testers (if used in this test) are routed through the centre of the table and to a screened room located outside the test area. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 metres and the EUT is rotated 360 degrees. The final level in dBµV/m is calculated by taking the reading from the EMI receiver (Level dBµV) and adding the correction factors and cable loss factor (dB). The FCC limit is subtracted from this result in order to provide the limit margin listed in the measurement protocol.

The resolution bandwidth setting:

30 MHz – 1000 MHz: RBW: 120 kHz

Example:


Frequency (MHz)	Level (dBµV)	+	Factor (dB)	=	Level (dBµV/m)	-	Limit (dBµV/m)	=	Delta (dB)
719.0	75.0	+	32.6	=	107.6	-	110.0	=	-2.4

FCC ID: SDL-PR4X


IC ID: 5228A-PR4X

4.5.3.2.3 Anechoic chamber 1 (1000 MHz – 18000 MHz)

Test setup according ANSI C63.10.



Radiated emissions from the EUT are measured in the frequency range 1 GHz up to 18 GHz as specified in 47 CFR Part 15, Subpart A, Section 15.33, using a spectrum analyser and appropriate linearly polarized antennas. Table top equipment is placed on a non-conducting table, 1.5 metre above the ground plane. The turntable is fully covered with the appropriate absorber (Type VHP-12). Any controlling device is positioned such that it does not significantly influence the measurement results. Interconnecting cables that hang closer than 40 cm to the ground plane are folded back and forth in the centre, forming a bundle 30 cm to 40 cm long. Measurements are made in three orientations of the EUT and the horizontal and vertical polarization planes of measurement antenna in a fully anechoic room. The measurement antenna is adjusted and the EUT orientated to permit the measurement of the maximum emission from the EUT. The conditions determined as worst-case will then be used for the final measurements.

4.5.3.2.4 Anechoic chamber 1 (18 GHz – 40 GHz)

Emissions from the EUT are measured in the frequency range 18 GHz up to 40 GHz as specified in 47 CFR Part 15, Subpart A, Section 15.33, using a spectrum analyser and appropriate linearly polarized antennas. Table top equipment is placed on a non-conducting table, 1.5 metre above the ground plane. The turntable is fully covered with the appropriate absorber (Type VHP-12). Any controlling device is positioned such that it does not significantly influence the measurement results. Interconnecting cables that hang closer than 40 cm to the ground plane are folded back and forth in the centre, forming a bundle 30 cm to 40 cm long. Measurements are made in three orientations of the EUT and the horizontal and vertical polarization planes of measurement antenna in a fully anechoic room. The measurement antenna is adjusted and the EUT orientated to permit the measurement of the maximum emission from the EUT. The conditions determined as worst-case will then be used for the final measurements. Where appropriate, the test distance may be reduced in order to detect emissions under better uncertainty. The limit is adopted.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

5 TEST CONDITIONS AND RESULTS

5.1 EBW and OBW

For test instruments and accessories used see section 6 Part MB.

5.1.1 Description of the test location

Test location: Shielded Room S4

5.1.2 Photo documentation of the test set-up - Detailed photos see attachment B

5.1.3 Applicable standard

According to FCC Part 15, Section 15.247(a)(2):

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 – 2483.5 MHz and 5725 – 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.1.4 Description of Measurement

The bandwidth was measured at an amplitude level reduced from the reference level of a modulated channel by a ratio of -6 dB. The reference level is the level of the highest signal amplitude observed at the transmitter at either the fundamental frequency or the first order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical. An alternative is to use the bandwidth measurement of the analyser.

Spectrum analyser settings for EBW:

RBW: 100 kHz, VBW: 300 kHz, Detector: Max peak, Sweep time: 5 s, Span: 2 EBW;

Spectrum analyser settings for OBW:

RBW: 1-5% OBW, VBW: 3 RBW, Detector: Max peak, Sweep time: 5 s, Span: 2 OBW;

5.1.5 Test result

Channel	Centre frequency (MHz)	6 dB bandwidth (kHz)	Minimum limit (kHz)	99 % bandwidth (kHz)	result
37	2402	526.0	500	1020.9	passed
17	2440	526.0	500	1021.6	passed
39	2480	526.0	500	1023.0	passed

The requirements are **FULFILLED**.

Remarks:


For detailed test result please see the following test protocols

FCC ID: SDL-PR4X


IC ID: 5228A-PR4X

5.1.6 Test protocols EBW


Channel 37 (2402 MHz)



Channel 17 (2440 MHz)



Channel 39 (2480 MHz)






FCC ID: SDL-PR4X


IC ID: 5228A-PR4X

5.1.7 Test protocols OBW


Channel 37 (2402 MHz)



Channel 17 (2440 MHz)



Channel 39 (2480 MHz)



FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

5.2 Maximum peak radiated output power

For test instruments and accessories used see section 6 Part **CPC 3, CPR 3**.

5.2.1 Description of the test location

Test location: Shielded Room S4
 Anechoic chamber 1

5.2.2 Photo documentation of the test set-up - Detailed photos see attachment B

5.2.3 Applicable standard

According to FCC Part 15, Section 15.247(b)(3):

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

5.2.4 Description of Measurement

The maximum peak radiated output power is measured using a spectrum analyser following the procedure set out in ANSI C63.10, item 11.9.2.2. The EUT is set in TX continuous mode while measuring. The radiated measurement was performed in terms of fieldstrength. Therefore, the formula set out in ANSI C63.10, item 9.5 (Equation 22) is changed into the following term:

$$E = \text{EIRP} - (20 \cdot \log_{10}(3)) + 104.7$$

FCC ID: SDL-PR4X**IC ID: 5228A-PR4X****5.2.5 Test result**

802.15.1, 125 kbps, TX		Test results conducted				
		P (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)	Margin (dB)
Lowest frequency: CH37						
T_{nom}	V_{nom}	8.3	1.1	9.5	36.0	-26.5
Middle frequency: CH17						
T_{nom}	V_{nom}	8.3	1.1	9.4	36.0	-26.6
Highest frequency: CH39						
T_{nom}	V_{nom}	8.4	1.1	9.4	36.0	-24.3




The requirements are **FULFILLED**.**Remarks:** None.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

5.2.6 Test protocols



FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

5.3 Power spectral density

For test instruments and accessories used see section 6 Part MB.

5.3.1 Description of the test location

Test location: Shielded Room S4

5.3.2 Photo documentation of the test set-up - Detailed photos see attachment B

5.3.3 Applicable standard

According to FCC Part 15, Section 15.247(e):

For digitally modulated systems, the power spectral density radiated from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the radiated output power shall be used to determine the power spectral density.

5.3.4 Description of Measurement

The measurement is performed using the procedure set out in 11.10 of ANSI C63.10. The power measurement was done as peak power measurement. Therefore, the PKPSD is measured. The max peak was located and with the spectrum analyser and a marker set to peak.

Spectrum analyser settings:

RBW: 3 kHz, VBW: 10 kHz, Detector: Peak, Sweep time: Auto

5.3.5 Test result

Channel	Centre frequency (MHz)	PSD (dBm/ 3 kHz)	PSD limit (dBm/ 3 kHz)	Margin (dB)	result
37	2402	-7.4	8.0	-15.4	passed
17	2440	-7.5	8.0	-15.5	passed
39	2480	-7.5	8.0	-15.5	passed

Power spectral density limit according to FCC Part 15, Section 15.247(e):

Frequency (MHz)	Power spectral density limit (EIRP)
	(dBm/3 kHz)
2400 - 2483.5	8

The requirements are **FULFILLED**.


Remarks: For detailed test result please see the following test protocols

FCC ID: SDL-PR4X


IC ID: 5228A-PR4X

5.3.6 Test protocols


Channel 37 (2402 MHz)



Channel 17 (2440 MHz)



Channel 39 (2480 MHz)



FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

5.4 Radiated emissions in restricted bands

For test instruments and accessories used see section 6 Part **SER 1, SER 2, SER 3.**

5.4.1 Description of the test location

Test location: OATS 1
 Test location: Anechoic chamber 1
 Test distance: 3 m

5.4.2 Photo documentation of the test set-up - Detailed photos see attachment B

5.4.3 Applicable standard

According to FCC Part 15, Section 15.205(a):

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limit specified in Section 15.209(a).

5.4.4 Description of Measurement

The restricted bands are measured radiated. The span of the spectrum analyser is set wide enough to capture the restricted band and measure the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation. The restricted bands are measured falling emissions into it and the nearest restricted band are checked for emissions also the restricted band for the harmonics of the carrier.

Test receiver settings for SER2:

RBW: 120 MHz, Detector: Quasi peak, Mes. Time: 1 s,

Spectrum analyser settings for SER3:

RBW: 1 MHz, VBW: 3 MHz, Detector: Max. peak, Trace: Max. hold, Sweep: Auto

5.4.5 Test result

$f < 1000 \text{ MHz}$

Frequency (MHz)	Reading Vert. (dB μ V)	Reading Hor. (dB μ V)	Correct. Vert. (dB)	Correct. Hor. (dB)	Level Vert. (dB μ V/m)	Level Hor. (dB μ V/m)	Limit (dB μ V/m)	Dlimit (dB)
120.00	11.0	-4.0	17.3	16.8	28.3	12.8	43.5	-15.2
144.00	4.4	5.0	19.4	18.6	23.8	23.6	43.5	-19.7
192.08	6.3	-0.9	17.6	17.0	23.9	16.1	43.5	-19.6
240.09	6.8	2.3	18.4	18.3	25.2	20.6	46.0	-20.8
288.14	-3.7	-4.1	19.9	20.3	16.2	16.2	46.0	-29.8
336.22	-3.1	-0.9	21.3	21.8	18.2	20.9	46.0	-25.1
480.23	-7.7	-6.1	25.3	25.6	17.6	19.5	46.0	-26.5



Note: Pre-measurements and final measurements have shown no emissions in the frequency range from 9 kHz to 30 MHz. Because of the physical dimensions of the EUT, no emissions can occur.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

f > 1000 MHz


CH37 horizontal




The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X





CH37 vertical




FCC ID: SDL-PR4X

IC ID: 5228A-PR4X




FCC ID: SDL-PR4X

IC ID: 5228A-PR4X





CH17 horizontal





FCC ID: SDL-PR4X

IC ID: 5228A-PR4X






FCC ID: SDL-PR4X

IC ID: 5228A-PR4X


CH17 vertical






FCC ID: SDL-PR4X

IC ID: 5228A-PR4X





CH39 horizontal



FCC ID: SDL-PR4X


IC ID: 5228A-PR4X






FCC ID: SDL-PR4X

IC ID: 5228A-PR4X





CH39 vertical




FCC ID: SDL-PR4X

IC ID: 5228A-PR4X



FCC ID: SDL-PR4X

IC ID: 5228A-PR4X



Radiated limits according to FCC Part 15 Section 15.209(a) for spurious emissions which fall in restricted bands:

Frequency (MHz)	Field strength of spurious emissions		Measurement distance
	(µV/m)	dB(µV/m)	(metres)
0.009-0.490	2400/F (kHz)		300
0.490-1.705	24000/F (kHz)		30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

FCC ID: SDL-PR4X**IC ID: 5228A-PR4X****Restricted bands of operation:**

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.41425 – 8.41475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	Above 38.6

RSS-Gen, Table 6 – Restricted Frequency Bands

MHz	MHz	MHz	GHz
0.090 - 0.110	12.57675 - 12.57725	399.9 - 410	7.250 - 7.750
0.495 - 0.505	13.36 - 13.41	608 - 614	8.025 – 8.500
2.1735 - 2.1905	16.42 - 16.423	960 - 1427	9.0 - 9.2
3.020 - 3.026	16.69475 - 16.69525	1435 - 1626.5	9.3 - 9.5
4.125 - 4.128	16.80425 - 16.80475	1645.5 - 1646.5	10.6 - 12.7
4.17725 - 4.17775	25.5 - 25.67	1660 - 1710	13.25 - 13.4
4.20725 - 4.20775	37.5 - 38.25	1718.8 - 1722.2	14.47 - 14.5
5.677 - 5.683	73 - 74.6	2200 - 2300	15.35 - 16.2
6.215 - 6.218	74.8 - 75.2	2310 - 2390	17.7 - 21.4
6.26775 - 6.26825	108 – 138	2483.5 - 2500	22.01 - 23.12
6.31175 - 6.31225	149.9 - 150.05	2655 - 2900	23.6 - 24.0
8.291 - 8.294	156.52475 - 156.52525	3260 – 3267	31.2 - 31.8
8.362 - 8.366	156.7 - 156.9	3332 - 3339	36.43 - 36.5
8.37625 - 8.38675	162.0125 - 167.17	3345.8 - 3358	Above 38.6
8.41425 - 8.41475	167.72 - 173.2	3500 - 4400	
12.29 - 12.293	240 – 285	4500 - 5150	
12.51975 - 12.52025	322 - 335.4	5350 - 5460	

The requirements are **FULFILLED**.

Remarks: The measurement was performed up to the 10th harmonic. Only the worst-case plots are listed.

FCC ID: SDL-PR4X**IC ID: 5228A-PR4X****5.5 Spurious emissions**

For test instruments and accessories used see section 6 Part **SEC 1-3**.

5.5.1 Description of the test location

Test location: Shielded Room S4

5.5.2 Photo documentation of the test set-up - Detailed photos see attachment B**5.5.3 Applicable standard**

According to FCC Part 15, Section 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

5.5.4 Description of Measurement

The radiated power of the spurious emission from the EUT is measured in a test setup following the procedures set out in ANSI C63.10. If the emission level of the EUT in peak mode complies with the average limit is 20 dB lower, then testing will be stopped and peak values of the EUT will be reported, otherwise the emission will be measured in average mode again and reported.

Test receiver settings for SER2:

RBW: 120 MHz, Detector: Quasi peak, Mes. Time: 1 s,

Spectrum analyser settings for SER3:

RBW: 100 kHz, VBW: 300 kHz, Detector: Max. peak, Trace: Max. hold, Sweep: Auto

5.5.5 Test result

Limit according to FCC Part 15, Section 15.247(d) for emissions falling not in restricted bands:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. Attenuation below the general limits specified in Section 15.209(a) is not required.

Frequency (MHz)	Spurious emission limit
Below 1000	20 dB below the highest level of the desired power
Above 1000	20 dB below the highest level of the desired power

The requirements are **FULFILLED**.

Remarks: For detailed test result please see the following test protocols.





FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

5.5.6 Test protocols



CH37



FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

CH17







FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

CH39







FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

Band edge left CH37



Band edge right CH39



FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

5.6 Antenna application

For test instruments and accessories used see section 6 Part **CPC3** .

5.6.1 Description of the test location

Test location: NONE

5.6.2 Applicable standard

According to FCC Part 15C, Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit that broken antennas can be replaced by the user, but the use of a standard antenna jack is prohibited.

The EUT has an integrated antenna. No other antenna can be used with the device.

The supplied antenna meets the requirements of part 15.203 and 15.204.

Remarks: None.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

5.7 Transmitter frequency stability

For test instruments and accessories used see section 6 Part FE.

5.7.1 Description of the test location

Test location: AREA4

5.7.2 Photo documentation of the test set-up - Detailed photos see attachment B

5.7.3 Applicable standard

According to RSS-GEN, clause 6.11:

Frequency stability is a measure of frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at an appropriate reference temperature and the rated supply voltage.

5.7.4 Description of Measurement

The OBW is measured with a spectrum analyser in a climatic chamber. The centroid frequency is noted.

Spectrum analyser settings for OBW:

RBW: 1-5% OBW, VBW: 3 RBW, Detector: Max peak, Sweep time: 5 s, Span: 2 OBW;

5.7.5 Test result

channel	Temp.	f _{centroid} [MHz]	Deviation [MHz]	Deviation [%]
37	+20 °C	2402.022	0.022	< 0.1
	-20 °C	2402.031	0.031	< 0.1
	+50 °C	2402.009	0.009	< 0.1
17	+20 °C	2440.023	0.023	< 0.1
	-20 °C	2440.030	0.030	< 0.1
	+50 °C	2440.008	0.008	< 0.1
39	+20 °C	2480.024	0.024	< 0.1
	-20 °C	2480.031	0.031	< 0.1
	+50 °C	2480.009	0.009	< 0.1

Limit according to RSS-GEN, clause 8.11:

If the frequency stability of the licence-exempt radio apparatus is not specified in the applicable RSS, the fundamental emissions of the radio apparatus should be kept within at least the central 80% of its permitted operating frequency band in order to minimize the possibility of out-of-band operation. In addition, its occupied bandwidth shall be entirely outside the restricted bands and the prohibited TV bands of 54-72 MHz, 76-88 MHz, 174-216 MHz, and 470-602 MHz, unless otherwise indicated.

The requirements are **FULFILLED**.

Remarks: For detailed test result please see the following test protocols.




FCC ID: SDL-PR4X

IC ID: 5228A-PR4X


5.7.6 Test protocols

T_{nom}

CH37



CH17





FCC ID: SDL-PR4X


IC ID: 5228A-PR4X

CH39



T_{min}

CH37






FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

CH17



CH39






FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

T_{max}

CH37



CH17






FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

CH39



FCC ID: SDL-PR4X

IC ID: 5228A-PR4X

6 USED TEST EQUIPMENT AND ACCESSORIES

All test instruments used are calibrated and verified regularly. The calibration history is available on request.

Test ID	Model Type	Equipment No.	Next Calib.	Last Calib.	Next Verif.	Last Verif.
CPC 3	FSW43	02-02/11-21-001	22/05/2024	22/05/2023		
CPR 3	FSW43	02-02/11-21-001	22/05/2024	22/05/2023		
	AMF-6D-01002000-22-10P	02-02/17-15-004				
	3117	02-02/24-05-009	12/07/2024	12/07/2023		
	BAM 4.5-P	02-02/50-17-024				
	NCD	02-02/50-17-025				
	KK-SF106-2X11N-6,5M	02-02/50-18-016				
	18N-20	02-02/50-21-009	28/05/2024	28/11/2023		
	BAT-EMC 2023.0.8.0	02-02/68-13-001				
FE	FSW43	02-02/11-21-001	22/05/2024	22/05/2023		
	KK-SF104-11SMA-11N-2M	02-02/50-14-003				
MB	FSW43	02-02/11-21-001	22/05/2024	22/05/2023		
SEC 1-3	FSW43	02-02/11-21-001	22/05/2024	22/05/2023		
SER 1	ESCI	02-02/03-05-005	15/12/2024	15/12/2023		
	HFH 2 - Z 2	02-02/24-15-001				
	NW-2000-NB	02-02/50-05-113				
	KK-EF393/U-16N-21N20 m	02-02/50-12-018				
	KK-SD_7/8-2X21N-33,0M	02-02/50-15-028				
SER 2	ESVS 30	02-02/03-05-006	27/07/2024	27/07/2023		
	VULB 9168	02-02/24-05-005	20/04/2024	20/04/2023	03/05/2024	03/05/2023
	NW-2000-NB	02-02/50-05-113				
	KK-EF393/U-16N-21N20 m	02-02/50-12-018				
	KK-SD_7/8-2X21N-33,0M	02-02/50-15-028				
	50F-003 N 3 dB	02-02/50-21-010				
SER 3	FSW43	02-02/11-21-001	22/05/2024	22/05/2023		
	AMF-6D-01002000-22-10P	02-02/17-15-004				
	LNA-40-18004000-33-5P	02-02/17-20-002				
	3117	02-02/24-05-009	12/07/2024	12/07/2023		
	BBHA 9170	02-02/24-05-013	21/03/2026	21/03/2023	21/03/2024	21/03/2023
	BAM 4.5-P	02-02/50-17-024				
	NCD	02-02/50-17-025				
	KK-SF106-2X11N-6,5M	02-02/50-18-016				
	KMS116-GL140SE-KMS116-	02-02/50-20-026				
	BAT-EMC 2023.0.8.0	02-02/68-13-001				

SER1 measurements were performed after 15/12/2023.

CPR 3 measurements were performed before 28/11/2023.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.