

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BT

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.86	1.93	2±1	3	2.00	<5	0.61847	3.00	YES
	2.441	2.82	1.91	2±1	3	2.00	<5	0.62347	3.00	YES
	2.480	2.38	1.73	2±1	3	2.00	<5	0.62843	3.00	YES
π/4-DQPSK	2.402	3.60	2.29	3±1	4	2.51	<5	0.77860	3.00	YES
	2.441	3.48	2.23	3±1	4	2.51	<5	0.78490	3.00	YES
	2.480	3.03	2.01	3±1	4	2.51	<5	0.79114	3.00	YES
8-DPSK	2.402	3.89	2.45	3±1	4	2.51	<5	0.77860	3.00	YES
	2.441	3.66	2.32	3±1	4	2.51	<5	0.78490	3.00	YES
	2.480	3.30	2.14	3±1	4	2.51	<5	0.79114	3.00	YES

BLE:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
BLE(1M)	2.402	2.86	1.93	2±1	3	2.00	<5	0.61847	3.00	YES
	2.440	2.87	1.94	2±1	3	2.00	<5	0.62334	3.00	YES
	2.480	2.26	1.68	2±1	3	2.00	<5	0.62843	3.00	YES
BLE(2M)	2.402	3.00	2.00	3±1	4	2.51	<5	0.77860	3.00	YES
	2.440	3.04	2.01	3±1	4	2.51	<5	0.78474	3.00	YES
	2.480	2.54	1.79	2±1	3	2.00	<5	0.62843	3.00	YES

Conclusion:

For the max result : $0.79114 \leq 3.0$ for 1g SAR, SAR is not required.

Signature:

Alex

Date: 2025-04-29

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.