

FCC RF Exposure Evaluation

1. Product Information

FCC ID	FSUGG242
Product Name	1080 degree Force Feedback Racing wheel
Test Model	SpeedMaster X5 FF
Power Supply	DC 10.8V from adapter
Modulation Type	GFSK
Antenna Type	PCB Antenna
Antenna Gain	2.32dBi
Frequency Range	2402MHz - 2480MHz
Exposure Category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

2. Evaluation Method and Limit

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f²) *	6
30 – 300	61.4	0.163	1.0	6

删除[User]: SHENZHEN LCS COMPLIANCE TEST

设置格式[User]: 字体: (默认) Arial, 小五, 加粗, 非

删除[Administrator]: 2AW5W-CPW-1

设置格式[User]: 字体: (默认) Arial, 英语(英国), (中

删除[w-]: SMQAX8AX92BGTJ-CQ-F202AHPZ-CHS

删除[Administrator]:

设置格式[User]: 字体: (默认) Arial, 加粗, 英语(英国)

设置格式[User]: 字体: (默认) Arial, 加粗, 英语(英国)

设置格式[User]: 字体: (默认) Arial, 加粗, 英语(英国)

设置格式[User]: 字体: (默认) Arial, 加粗, 英语(英国)

设置格式[User]: 字体: (默认) Arial, 加粗, 英语(英国)

设置格式[User]: 字体: (默认) Arial, 加粗, 英语(英国)

删除[Administrator]:

设置格式[w-]: 字体: (默认) Arial, 加粗, 字体颜色:

删除[w-]: CTL2302172031-WFCTL2305309011CTL

设置格式[User]: 字体: (默认) Arial, 字体颜色: 自动

设置格式[w-]: (中文) 英语(美国)

设置格式[w-]: 字体颜色: 自动设置, (中文) 英语(美国)

删除[User]: FCC ID: 2AVHP-VPIXEL-S

删除[Administrator]: 2AVHP

删除[User]:

删除[Administrator]:

删除[Administrator]: 2AW5W-CPW-1

删除[w-]: SMQAX8AX92BGTJ-CQ-F202AHPZ-CHS65FSU-X5FF

删除[User]: 2AVHP-VPIXEL-S

删除[Administrator]: 2AVHP

删除[w-]: 1080° Force Feedback Racing wheel

设置格式[w-]: 字体: (默认) Calibri, 五号

删除[w-]: Bluetooth moduleSpeakerWireless CarPlay

设置格式[w-]: 字体: (默认) Calibri, 五号

删除[User]: VPIXEL Phantom Wireless audio and video

删除[Administrator]: Model Number

设置格式[w-]: 字体: (默认) Calibri, 五号

删除[w-]: CQ_F20_01 IQ-6512DJBTCPW-1, CPW-1a,

<u>300 – 1500</u> <u>1500 – 100,000</u>	<u> </u> <u> </u>	<u> </u> <u> </u>	<u>f/300</u> <u>5</u>	<u>6</u> <u>6</u>
--	----------------------	----------------------	--------------------------	----------------------

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure				
Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
<u>0.3 – 3.0</u>	<u>614</u>	<u>1.63</u>	<u>(100) *</u>	<u>30</u>
<u>3.0 – 30</u>	<u>824/f</u>	<u>2.19/f</u>	<u>(180/f²)*</u>	<u>30</u>
<u>30 – 300</u>	<u>27.5</u>	<u>0.073</u>	<u>0.2</u>	<u>30</u>
<u>300 – 1500</u>	<u> </u>	<u> </u>	<u>f/1500</u>	<u>30</u>
<u>1500 – 100,000</u>	<u> </u>	<u> </u>	<u>1.0</u>	<u>30</u>

F=frequency in MHz
*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

S=PG/4πR²

Where: S=power density
P=power input to antenna
G=power gain of the antenna in the direction of interest relative to an isotropic radiator
R=distance to the center of radiation of the antenna

5. Antenna Information

SpeedMaster X5 FF can only use antennas certificated as follows provided by manufacturer;

<u>Antenna type and antenna number</u>	<u>Operate frequency band</u>	<u>Maximum antenna gain</u>	<u>Note</u>
<u>PCB Antenna</u>	<u>2402MHz-2480MHz</u>	<u>2.32dBi</u>	<u>Bluetooth Antenna</u>

6.Conducted Power Results

<u>[BLE Max Conducted Power]</u>		
<u>Mode</u>	<u>Frequency (MHz)</u>	<u>Maximum Peak Conducted Output Power (dBm)</u>
<u>1M</u>	<u>2402</u>	<u>-4.86</u>
	<u>2440</u>	<u>-4.39</u>
	<u>2480</u>	<u>-4.49</u>
<u>2M</u>	<u>2402</u>	<u>-4.84</u>
	<u>2440</u>	<u>-4.36</u>
	<u>2480</u>	<u>-4.45</u>

7.Manufacturing Tolerance

<u><BLE 1M></u>			
<u>GFSK (Peak)</u>			
<u>Channel</u>	<u>2402 MHz</u>	<u>2440 MHz</u>	<u>2480 MHz</u>
<u>Target (dBm)</u>	<u>-5.0</u>	<u>-4.0</u>	<u>-4.0</u>
<u>Tolerance ±(dB)</u>	<u>1.0</u>	<u>1.0</u>	<u>1.0</u>

<BLE 2M > GFSK (Peak)			
Channel	2402 MHz	2440 MHz	2480 MHz
Target (dBm)	-5.0	-4.0	-4.0
Tolerance ±(dB)	1.0	1.0	1.0

8. Evaluation Results

8.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, r =20cm, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain	Antenna Gain	Duty Cycle	MPE	MPE
	dBm	mW	(dBi)	(linear)		(mW/cm²)	Limits (mW/cm²)
GFSK	-3.0	0.5012	2.32	1.7061	100%	0.0002	1.0000

Modulation Type	Output power		Antenna Gain	Antenna Gain	Duty Cycle	MPE	MPE
	dBm	mW	(dBi)	(linear)		(mW/cm²)	Limits (mW/cm²)
GFSK	-3.0	0.5012	2.32	1.7061	100%	0.0002	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

8.2 Simultaneous Transmission MPE

The sample supports a modular, 1 antennas, No need to consider simultaneous transmission;

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

.....THE END OF REPORT.....