

FCC RF EXPOSURE REPORT


FCC ID: 2ACSVHF-LPT270-0F

Project No. : 2111H024
Equipment : HF-LPT270-0(F)
Brand Name : High-Flying
Test Model : HF-LPT270-0(F)
Series Model : N/A
Applicant : High-Flying Electronics Technology Co., Ltd.
Address : Building 17, No.1500 Zu Chongzhi Road, Pudong District, Shanghai, China
Manufacturer : High-Flying Electronics Technology Co., Ltd.
Address : Building 17, No.1500 Zu Chongzhi Road, Pudong District, Shanghai, China
Factory : China Dragon Technology Limited
Address : B4 Building, Haosan NO.1 Industrial Zone, Nanpu Road, Xinqiao Street, Baoan District, Shenzhen
Date of Receipt : Nov. 17, 2021
Date of Test : Nov. 23, 2021~Dec. 17, 2021
Issued Date : Dec. 29, 2021
Report Version : R01
Test Sample : Engineering Sample No.: SH2021111948 for radiated, SH2021111949 for conducted SH2021111946-2 for adapter
Standard(s) : FCC Part 2.1091
FCC Title 47 Part 2.1091
KDB 447498 D01 General RF exposure guidance v06

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.



Prepared by : Antonio long



Approved by : Ryan Wang



TESTING CERT #5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China

TEL: +86-021-61765666

Web: www.newbtl.com

REPORT ISSUED HISTORY

Report Version	Description	Issued Date
R00	Original Issue.	Dec. 24, 2021
R01	Revised report to address TCB's comments.	Dec. 29, 2021

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4G

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Dipole	N/A	3.12

Note: The antenna gain provided by the manufacturer

For BLE

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Dipole	N/A	3.12

Note: The antenna gain provided by the manufacturer.

2. TEST RESULTS

For 2.4G

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. tune up Power (dBm)	Max. tune up Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.12	2.0512	26.50	446.6836	0.150644	1	Complies

For BLE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. tune up Power (dBm)	Max. tune up Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.12	2.0512	14.50	28.1838	0.009505	1	Complies

For the max simultaneous transmission MPE:

Power Density (S) (mW/cm ²)	Power Density (S) (mW/cm ²)	Total	Limit of Power Density (S) (mW/cm ²)	Test Result
2.4GHz	BLE			
0.150644	0.009505	0.16015	1	Complies

Note: The calculated distance is 20 cm.
Output power including tune up tolerance.

End of Test Report