AEGIS LABS, INC.

Class II Permissive Change TEST REPORT

For

Intel(R) PRO/Wireless LAN 3A Mini PCI Adapter Model Number: WM3A2100

MEASUREMENTS PERFORMED IN ACCORDANCE WITH THE FOLLOWING EMISSIONS STANDARD

47 CFR Part 15, Subpart C (Section 15.247)

Test Method:

ANSI C63.4: 1992 American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz



CERTIFICATE NUMBER: 1111.01 To view a copy of the Scope of Accreditation visit <u>www.A2LA2.net</u>

PREPARED FOR:

Dell Computer Corporation One Dell Way Round Rock, TX 78682

Contact(s): Jason Limoges

PREPARED BY:

Aegis Labs, Inc. 22431 Antonio Parkway B160-417 Rancho S. Margarita, CA 92688

Agent(s):

Mr. Steve Kuiper Mr. Rick Candelas

Test Report #:INTEL-030219FTest Date:February 19-March 7, 2003

	REPORT	APPENDICES	TOTAL
	BODY	Ι	
PAGES	19	57	76

The contents of this report shall not be reproduced except in full, without the written approval of Aegis Labs, Inc.

AEGIS LABS, INC 22431 Antonio Parkway B160-417, Rancho Santa Margarita, CA 92688 949-459-7886 TEL 949-459-7869 FAX www.aegislabsinc.com

> Page 1 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.

TABLE OF CONTENTS

SECTION	TITLE	PAGE
	COVER SHEET	01
	TABLE OF CONTENTS	02
1.0	CERTIFICATION OF TEST DATA	03
2.0	ADMINISTRATIVE DATA AND TEST DESCRIPTION	04
3.0	DESCRIPTION OF EUT CONFIGURATION	05
3.1	EUT Description	05
3.1.1	Channel Number and Frequencies	06
3.2	EUT Configuration	07
3.3	EUT and Sub-Assemblies List	08
3.4	Accessory / Host Equipment List	08
3.5	Cabling Diagram and Description	09
4.0	TEST EQUIPMENT SETTINGS AND TEST SETUPS	10
4.1	Conducted Emissions At AC Mains Port.	10
4.1.1	Conducted Emissions At AC Mains Port – Test Setup	11
4.2	Spurious Radiated Emissions	12
4.2.1	Spurious Radiated Emissions – Test Setup.	13
4.3	Maximum Peak Output Power Measurement.	14
4.3.1	Maximum Peak Output Power Measurement– Test Setup	14
4.4	Occupied Bandwidth Measurement	15
4.4.1	Occupied Bandwidth Measurement– Test Setup	15
4.5	Spectral Power Density Measurement	16
4.5.1	Spectral Power Density Measurement– Test Setup	16
4.6	Spurious Emissions Measurement At The Antenna Terminal	17
4.6.1	Spurious Emissions Measurement At The Antenna Terminal– Test Setup.	17
4.7	Band Edge Measurement At The Antenna Terminal	18
4.7.1	Band Edge Measurement At The Antenna Terminal– Test Setup	18
5.0	MODIFICATIONS AND RECOMMENDATIOS	19
APPENDI	CES	
Ι	Data Sheets	

1.0 CERTIFICATION OF TEST DATA

Aegis Labs, Inc. operates as both a Nevada and California Corporation with no organizational or financial relationship with any company, institution, or private individual.

Testing and engineering functions provided by Aegis Labs are furnished through the use of part-time, full-time or consulting engineers with the appropriate qualifications to carry out their duties. The intended purpose of this test report is to describe the measurement procedure and to determine whether the equipment under test "EUT" complies with both the conducted and radiated limits. Limits for emissions testing are described under 47 CFR Part 15, Subpart C (Section 15.247).

The data, data evaluation and equipment configuration represented herein are a true and accurate representation of the Equipment Under Test (EUT) under the requirements specified in the emissions standard as described below. The test results contained in this report are only representative of the test sample tested as described in Section 2.0 of this report.

The test results provided within this report, indicate that the information technology equipment has been found to be in <u>COMPLIANCE</u> with the test specifications based upon the following RF compliance standards:

EMISSIONS STANDARDS	DESCRIPTION	TEST
		RESULTS
FCC 47 CFR, Part 15.207	Conducted Emissions At AC Mains Port	PASSED
CISPR22 Class B Limits	Radiated Emissions (30-1000 MHz)	PASSED
FCC 47 CFR, Part 15.247(c), 15.209	Radiated Emissions (1-26.5 GHz)	PASSED
FCC 47 CFR, Part 15.247(a)(2)	Occupied Bandwidth Measurement	PASSED
FCC 47 CFR, Part 15.247(b)	Maximum Peak Output Power Measurement	PASSED
FCC 47 CFR, Part 15.247(d)	Spectral Power Density Measurement	PASSED
FCC 47 CFR, Part 15.247(c)	Spurious Emissions Measurement At The	PASSED
	Antenna Terminal	
FCC 47 CFR, Part 15.247(c)	Band Edge Measurement At The Antenna	PASSED
	Terminal	

Pass/Fail determination is based upon the nominal values of the test data.

Date:

Prepared By:

03/13/03

Rick Candelas Staff Engineer Aegis Labs, Inc. **Report Approved By:**

Steve J. Kuiper Q/A Manager Aegis Labs, Inc. <u>03/13/03</u> Date:

Page 3 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS

2.0 ADMINISTRATIVE DATA AND TEST DESCRIPTION

DEVICE TESTED:	Trade Name: Intel(R) PRO/Wireless LAN 3A Mini PCI Adapter Model Number: WM3A2100 Serial Number: MY-09Y200-43950-321-012B FCC ID: E2K24CLNS
TEST DATE(S):	February 19-March 7, 2003
DATE EUT RECEIVED:	February 19, 2003
ORIGIN OF TEST SAMPLE(S):	Production
RESPONSIBLE PARTY:	Dell Computer Corporation
	One Dell Way
	Round Rock, TX 78682
CLIENT CONTACT:	Mr. Jason Limoges
MANUFACTURER:	Dell Computer Corporation
TEST LOCATION:	Aegis Labs, Inc. 32231 Trabuco Creek Road Trabuco Canyon, CA 92678 Conducted Site #2 Radiated Site #2
A2LA CERTIFICATE:	1111.01, Valid until February 28, 2004
PURPOSE OF TEST:	To demonstrate compliance with the relevant standards described in Section 1.0 of this report.
TEST(S) PERFORMED:	Refer to Table in Section 1 of this report.

All calibration vendors were responsible for certifying Aegis Labs, Inc. test equipment as per the manufacturer's specifications and that the equipment is calibrated using instruments and standards where the accuracy is traceable to the National Institute of Standards and Technology (NIST). Calibration of all test equipment conforms to ANSI/NCSL Z540-1 and ISO 10012-1 and/or ISO/IEC Guide 17025 compliance (Additionally, other pertinent test equipment will carry MIL-STD-45662A). All calibration documents are on file with Aegis Labs, Inc., with copies provided upon request.

Page 4 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS

3.0 DESCRIPTION OF EUT

3.1 EUT Description

Equipment Under Test (EUT)				
Trade Name:	Intel(R) PRO/Wireless LAN 3A Mini PCI Adapter			
Model Number:	WM3A2100			
Frequency Range:	2.412 – 2.462 GHz			
Type of Transmission:	Direct Sequence Spread Spectrum			
Transfer Rate:	1/2/5.5/11 Mbps			
Number of Channels:	11			
Modulation Type:	DBPSK, DQPSK, CCK			
Antenna Type:	Wistron NeWeb Corp. Triple-Band PIFA Antenna Type & Hitachi Monopole Antenna Type			
Antenna Gain (See Note 2):	Triple-Band PIFA = 2.39 dBi (gain) – 1.03 dB (cable loss) = 1.36 dBi Monopole = 1.10 dBi – (0.90 dB) cable loss = 0.20 dBi			
Transmit Output Power:	16 dBm (Typical) Please see Appendix I (Data Sheets) for actual output power.			
Power Supply:	3.3VDC from computer MPCI slot.			
Number of External Test	2 Antenna Ports (1 Main & 1 Auviliary)			
Ports Exercised:	2 Antenna Ports (1 Main & 1 Auxiliary)			

The Intel(R) PRO/Wireless LAN 3A Mini PCI Adapter is an embedded 2.4 GHz Wireless Local Area Network Mini-PCI adapter. The Mini-PCI Type 3A form factor is designed for notebook computer systems where overall thickness must be kept to an absolute minimum. It is capable of a data rate of up to 11 Mbps at 2.4 GHz. Please refer to Section 3.2 of this report for a further description of the configuration tested.

This report is submitted as a Class II Permissive Change for the currently certified Dell Latitude laptop computer, FCC ID Number: E2K24CNLS with a Bluetooth module installed, FCC ID: IXMUB22111S. Two sets of antenna types were tested (Triple-Band PIFA and monopole antenna types).

- **NOTE 1:** For a more detailed description, please refer to the manufacture's specifications or User's Manual.
- **NOTE 2:** The EUT was tested separately with two different sets of antennas (Triple-Band PIFA and Monopole). (Refer to each antenna specifications for a further description of the antennas).

3.1.1 Channel Number and Frequencies

Eleven channels are provided for the EUT.

Channel	Frequency (MHz)
1	2412
2	2417
3	2422
4	2427
5	2432
6	2437
7	2442
8	2447
9	2452
10	2457
11	2462

Page 6 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS

3.2 EUT Configuration

The EUT was set-up according to the ANSI C63.4: 1992 guidelines for emissions testing. For emissions testing the EUT (Intel(R) PRO/Wireless LAN 3A Mini PCI Adapter, Model Number: WM3A2100) had a loaded antenna connected to both its main and auxiliary ports. All the appropriate test ports were exercised during both the pre-qualification and final evaluation scans.

The EUT was tested in two different configurations.

- 1) With Triple-Band Antennas
- 2) With Monopole Antennas.

For both configurations the EUT was tested installed in the Mini-PCI slot of the Dell host computer. The EUT was then connected to a set of antennas via its main and auxiliary Hirose U.FL-R-SMT ports. Data for both sets of antennas can be found in Appendix I.

The Dell host computer was connected to a Hayes modem, Canon printer, and NEC monitor via its serial, parallel, and video ports respectively.

The low (channel 1), middle (channel 6), and high (channel 11) were tested. The EUT was transmitting and receiving on a continuous basis.

The final data was taken in this mode of operation. The external cables were bundled and routed as shown in the photographs in Appendix I (Data Sheets).

This report documents the emissions of the WLAN radio module when installed in a Dell host computer with a Bluetooth module installed. The Bluetooth module was not re-tested, since the transmitting antennas of both the WLAN and Bluetooth modules are approximately 20cm apart (Refer to the antenna photographs exhibit). The Bluetooth transmitter module has been certified with respect to FCC Part 15 Subpart C requirements (FCC ID: IXMUB22111S).

3.3 EUT and Sub-Assemblies List

EUT and Sub-Assemblies List						
Manufacturer	Equipment Name	Model Number	Serial Number			
Intel Corporation	Intel(R) PRO/Wireless LAN 3A Mini	WM3A2100	MY-09Y200-			
	PCI Adapter		43950-321-			
			012B			
Sub-Assemblies						
Wistron NeWeb	Triple-Band Antenna	СА9-С	None			
Corporation						
Hitachi	Monopole Antenna	HFT04-DL01-				
		Main/Aux	None			

3.4 Accessory / Host Equipment List

Accessory / Host Equipment List						
Manufacturer Equipment Name Model Number Serial Number						
Host Laptop Computer	Dell	Latitude	221131			
AC Adapter	Dell	PA-1650-050	CN-054092-48010-29B-00B9			
Monitor	NEC	JC-1575VMA	2Y785821			
Printer	Canon	BJC-4200	MT1-18			
Modem	Hayes	5362US	A02153623145			

NOTE: All the power cords of the above support equipment are standard non-shielded, 1.8 meters long.

3.5 Cabling Diagram and Description



- Cable 1: This is a 6-foot braid and foil shielded round cable connecting the Dell host computer to the Canon printer. It has a metallic DB-25 type connector at the computer end and a metallic 36-pin centronics type connector at the printer end. The cable is bundled to a length of one meter and the shield of the cable is grounded to the chassis of both devices via the connector shells.
- Cable 2: This is a 6-foot braid and foil shielded round cable connecting the host Dell laptop computer with the NEC monitor. It has metallic DB-15 type connector at the computer end and is hardwired to the monitor. The cable is bundled to a length of one meter and the shield of the cable is grounded to the chassis of both devices via the connector shells.
- Cable 3: This is a 6-foot braid and foil shielded round cable connecting the Dell host computer to the Hayes modem. It has a metallic DB-9 type connector at the computer end and a metallic DB-25 type connector at the modem end. The cable is bundled to a length of one meter and the shield of the cable is grounded to the chassis of both devices via the connector shells.

Page 9 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS

4.0 TEST EQUIPMENT AND TEST SETUPS

The test equipment settings and functions are selected using the guidance of ANSI C63.4-1992. All test equipment setups and operations during conducted and radiated emissions testing are in accordance with this reference document.

4.1 Conducted Emissions At AC Mains Port

During conducted emissions measurements, a spectrum analyzer was used as the measuring instrument along with a preselector and quasi-peak detector. A 10 dB attenuation pad was used for the protection of the spectrum analyzer input stage. The conducted emissions from the EUT in the frequency range from 150 kHz to 30 MHz were captured for graphical display through the use of automated LABVIEW EMI measurement software. All graphical readings were measured in the "Peak" mode only to reduce testing time. Upon completion of the graphical scan, the test lab personnel performed the conducted measurement scan manually using the spectrum analyzer front panel keys. All peak measurements coming within 3 dB of the limit line were "Averaged" and/or "Quasi-Peaked" and denoted appropriately in the EXCEL spreadsheet.

The Equipment Under Test (EUT) was configured as a system with peripherals connected, so that at least one interface port of each type is connected to one external peripheral when tested for conducted emissions according to ANSI C63.4: 1992. The EUT was tested in a tabletop configuration.

The six highest emission readings for Line 1 and Line 2 are highlighted on the data sheets in Appendix I. The graphical scans only reflects peak readings while the tabulated data sheets reflect peak, average, and/or quasi-peak readings which ever applies.

Page 10 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS



4.1.1 Conducted Emissions At AC Mains Port – Test Setup

Page 11 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.

4.2 Spurious Radiated Emissions

A spectrum analyzer was used as the measuring instrumentation along with a preselector and quasi-peak-detector. The pre-amplifiers were used to increase the sensitivity of the instrument. The spectrum analyzer was used in the peak detector mode with the "max-hold" feature activated and in Positive Peak mode. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps. The quasi-peak detector was used only for those readings, which are marked accordingly in the data sheet. The effective measurement bandwidth used for the radiated emissions test was 120 kHz for (30 MHz- 1000 MHz). The spectrum analyzer operated such that the modulation of the signal was filtered out to set the analyzer in linear mode. For testing beyond 1000 MHz a spectrum analyzer capable of taking reading above 1000 MHz was connected to the high frequency amplifier, where these measurement readings were taken with the transducer placed at a 3-meter test distance from the EUT.

The Open Area Test Sites (OATS) was used for radiated emission testing. These test sites are designed according to ANSI C63.4: 1992 and ANSI C63.7: 1992 guidelines. The Measurements were conducted in accordance with ANSI C63.4: 1992 and ANSI C63.7: 1992 requirements.

Broadband biconical, log periodic, and horn antennas were used as transducers during the measurement reading phase. The frequency spans were wide (30 MHz-88 MHz, 88 MHz-216 MHz, 216 MHz- 300 MHz, and 300 MHz- 1000 MHz). After 1000 MHz the horn antenna was used to measure emissions. The six highest emission readings in both horizontal and vertical polarities are highlighted on the data sheets in Appendix I.

Page 12 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS AEGIS LABS, INC.

4.2.1 Spurious Radiated Emissions - Test Setup



Page 13 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS

4.3 Maximum Peak Output Power Measurement

A power meter along with a power sensor was used to measure the maximum peak output power. The low (channel 1), middle (channel 6), and high (channel 11) were measured as well as data rates 1, 5.5, and 11 Mbps.

The EUT maximum peak output power is less than 1 Watt. Please refer to Appendix I for the data sheets.

4.3.1 Maximum Peak Output Power Measurement – Test Setup



Page 14 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS 4.4 Occupied Bandwidth Measurement

A spectrum analyzer was used to measure the occupied bandwidth. The bandwidth was measured using a direct connection from the RF output port of the EUT to the spectrum analyzer using a low loss cable and a DC block. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz.

The EUT bandwidth is at least 500 kHz. Please refer to Appendix I for graphical plots.

4.4.1 Occupied Bandwidth Measurement – Test Setup



Page 15 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS 4.5 Spectral Power Density Measurement

A spectrum analyzer was used to measure the spectral power density. It was measured using a direct connection from the RF output port of the EUT to the spectrum analyzer using a low loss cable and a DC block. The resolution bandwidth was 3 kHz and the video bandwidth was 10 kHz. The highest 4.5 MHz of the signal was used as the frequency span with the sweep rate being 1 second for every 3 kHz of span.

The EUT spectral power density does not exceed 8 dBm in any 3 kHz band. Please refer to Appendix I for graphical plots.

4.5.1 Spectral Power Density Measurement – Test Setup



4.6 Spurious Emissions Measurement At The Antenna Terminal

A spectrum analyzer was used to measure the spurious emissions at the antenna terminal. It was measured using a direct connection from the RF output port of the EUT to the spectrum analyzer using a low loss cable and a DC block. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz. The spans were wide enough to include all the harmonics and emissions that were produced by the intentional radiator.

The EUT RF power that is produced in any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator is at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Please refer to Appendix I for graphical plots.

4.6.1 Spurious Emissions Measurement At The Antenna Terminal – Test Setup



Page 17 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.

4.7 Band Edge Measurement At The Antenna Terminal

A spectrum analyzer was used to measure the band edge measurements at the antenna terminal with the EUT transmitting at 2412 MHz (channel 1) and 2462 MHz (channel 11). It was measured using a direct connection from the RF output port of the EUT to the spectrum analyzer using a low loss cable and a DC block. The resolution bandwidth was 1 MHz and the video bandwidth was 1 MHz. It was verified that the band edge measurements were not above the limit in the restricted bands below 2390 MHz and above 2483.5 MHz. Please refer to Appendix I for graphical plots.

4.7.1 Band Edge Measurement At The Antenna Terminal – Test Setup



Page 18 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS

5.0 MODIFICATIONS AND RECOMMENDATIONS

There were no modifications done to the EUT.

Page 19 of 19 Report Number: INTEL-030219F FCC ID: E2K24CLNS



APPENDIX I

DATA SHEETS

Page 1 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

CLIENT:	Dell Computer Corporation	DATE:	02/20/03
EUT:	Intel(R) PRO/Wireless LAN 3A Mini	PROJECT	INTEL-030219-55
	PCI Adapter	NUMBER:	
MODEL NUMBER:	WM3A2100	TEST ENGINEER:	Rick Candelas
SERIAL NUMBER:	MY-09Y200-43950-321-012B	SITE #:	2
CONFIGURATION:	Installed in Dell laptop computer with	TEMPERATURE:	17 C
	Wistron NeWeb Corporation Triple	HUMIDITY:	50% RH
	Band Antennas	TIME:	10:00 PM

CONDUCTED EMISSIONS AT AC MAINS PORT

Standard:	FCC CFR 47, Part 15.207
Description:	AC Power Conducted Emissions
Results:	Passes FCC Limits

NOTE: During preliminary scans, there wasn't any difference which channel, data rate, or which set of antennas were used with the EUT, therefore only Channel 1 at a data rate of 1 Mbps with the Wistron NeWeb Corporation Triple Band Antennas were used for final testing.

Page 2 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

FCC CLASS B CONDUCTED EMISSIONS – LINE 1						
Freq.	Meter	Detector	Average	Average	Quasi-Peak	Quasi-Peak
(MHz)	Reading (dBuV)	(PK/QP/AV)	Limit (dBuV)	Delta(dB)	Limit (dBuV)	Delta(dB)
0.1521	62.00	PK	55.94	6.06	65.94	-3.94
0.1521	42.51	AV	55.94	-13.43	65.94	-23.43
0.1761	62.80	PK	55.25	7.55	65.25	-2.45
0.1761	41.58	AV	55.25	-13.67	65.25	-23.67
0.1884	59.90	PK	54.90	5.00	64.90	-5.00
0.1884	41.62	AV	54.90	-13.28	64.90	-23.28
0.2151	55.20	РК	54.14	1.06	64.14	-8.94
0.2151	35.21	AV	54.14	-18.93	64.14	-28.93
0.4041	46.80	РК	48.74	-1.94	58.74	-11.94
0.4041	32.47	AV	48.74	-16.27	58.74	-26.27
5.0600	42.70	РК	50.00	-7.30	60.00	-17.30

FCC CLASS B CONDUCTED EMISSIONS – LINE 2						
Freq.	Meter	Detector	Average	Average	Quasi-Peak	Quasi-Peak
(MHz)	Reading (dBuV)	(PK/QP/AV)	Limit (dBuV)	Delta(dB)	Limit (dBuV)	Delta(dB)
0.1518	61.00	PK	55.95	5.05	65.95	-4.95
0.1518	43.12	AV	55.95	-12.83	65.95	-22.83
0.1701	60.40	PK	55.43	4.97	65.43	-5.03
0.1701	42.57	AV	55.43	-12.86	65.43	-22.86
0.1881	60.50	PK	54.91	5.59	64.91	-4.41
0.1881	41.87	AV	54.91	-13.04	64.91	-23.04
0.2025	59.10	PK	54.50	4.60	64.50	-5.40
0.2025	39.45	AV	54.50	-15.05	64.50	-25.05
0.4044	46.00	PK	48.73	-2.73	58.73	-12.73
0.4044	31.54	AV	48.73	-17.19	58.73	-27.19
4.8000	43.00	РК	46.00	-3.00	56.00	-13.00



Page 4 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.



Page 5 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.

TEST EQUIPMENT USED									
Equipment Name	Manufacturer Model		Serial	Calibration	Calibration				
		Number	Number	Due Date	Cycle				
Spectrum Analyzer - RF Section	Hewlett Packard	8568B	2634A03093	11/27/03	1 Year				
Spectrum Analyzer - Display Section	Hewlett Packard	85662A	1833A00389	11/27/03	1 Year				
Quasi-Peak Adapter	Hewlett Packard	85650A	2043A00220	11/28/03	1 Year				
RF Preselector	Hewlett Packard	85685A	2620A000281	05/10/03	1 Year				
Attenuator - 5W-10dB	Pasternack	PE7014-10	N/A	11/03/03	1 Year				
LISN (EUT)	EMCO	3825/2	9108-1848	01/24/04	1 Year				
LISN (Access)	Com-Power	LI-200	12019	01/25/04	1 Year				
LISN (Access)	Com-Power	LI-200	12018	01/25/04	1 Year				
Temperature/Humidity Monitor	Dickson	TH550	7255185	01/18/03	1 Year				

ACCESSORIES EQUIPMENT							
Equipment Name	Manufacturer	Model Number	Serial Number				
Host Laptop Computer	Dell	Latitude	221131				
AC Adapter	Dell	PA-1650-050	CN-054092-48010- 29B-00B9				
Monitor	NEC	JC-1575VMA	2Y785821				
Printer	Canon	BJC-4200	MT1-18				
Modem	Hayes	5362US	A02153623145				

BLOCK DIAGRAM



AEGIS LABS, INC.

CONDUCTED EMISSIONS AT AC MAINS PORT (Continued)

PHOTOGRAPHS



Page 7 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

CLIENT:	Dell Computer Corporation	DATE:	02/20/03
EUT:	Intel(R) PRO/Wireless LAN 3A Mini	PROJECT	INTEL-030219-44
	PCI Adapter	NUMBER:	
MODEL NUMBER:	WM3A2100	TEST ENGINEER:	Rick Candelas
SERIAL NUMBER:	MY-09Y200-43950-321-012B	SITE #:	2
CONFIGURATION:	Installed in Dell laptop computer with	TEMPERATURE:	18 C
	Wistron NeWeb Corporation Triple	HUMIDITY:	47% RH
	Band Antennas	TIME:	5:00 PM

SPURIOUS RADIATED EMISSIONS

Standard:	CISPR22 Class B Limits
Description:	Spurious Emissions Measurements - Radiated
Results:	-1.98 dB (QP) margin @ 576.02 MHz (Horizontal Polarity)

NOTE: During preliminary scans, there wasn't any difference which channel, data rate, or which set of antennas were used with the EUT, therefore only Channel 1 at a data rate of 1 Mbps with the Wistron NeWeb Corporation Triple Band Antennas were used for final testing.

Page 8 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

	Horizontal Open Field Maximized Data							
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)
(MHz)	Reading (dBuV)	Height (cm)	(degrees)	or AVG (dBu	<i>V)</i>	Reading (dBuV)	(dBuV)	+=FAIL
60.09	35.70	250	135			10.88	30.00	-19.12
100.10	39.50	400	90			16.90	30.00	-13.10
120.11	47.60	400	90	42.10	Q	22.92	30.00	-7.08
130.14	43.40	400	90			25.29	30.00	-4.71
150.12	39.70	400	135			22.60	30.00	-7.40
302.65	35.20	300	180			17.79	37.00	-19.21
309.91	38.30	250	180			21.82	37.00	-15.18
320.07	42.10	250	0			26.91	37.00	-10.09
336.06	40.40	250	0			25.03	37.00	-11.97
352.07	37.80	250	0			21.46	37.00	-15.54
368.10	39.30	250	225			23.30	37.00	-13.70
384.06	39.40	250	45			23.60	37.00	-13.40
432.03	47.70	250	90			33.11	37.00	-3.89
450.13	44.50	300	45			30.38	37.00	-6.62
480.04	39.90	200	180			26.91	37.00	-10.09
500.04	39.70	250	0			27.24	37.00	-9.76
528.03	45.40	200	180			33.65	37.00	-3.35
576.02	46.50	150	90	46.23	Q	35.02	37.00	-1.98
624.03	39.60	150	90			29.54	37.00	-7.46
		Vert	ical Open F	ield Maxim	ized	Data		
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)
(MHz)	Reading (dBuV)	Height (cm)	(degrees)	or AVG (dBu	<i>V)</i>	Reading (dBuV)	(dBuV)	+=FAIL
60.09	53.20	100	270	49.25	Q	24.73	30.00	-5.27
64.07	49.40	100	90			24.17	30.00	-5.83
80.10	44.90	100	90			19.02	30.00	-10.98
100.11	46.90	100	180			23.70	30.00	-6.30
120.13	53.20	100	90	48.66	Q	27.98	30.00	-2.02
128.15	42.40	100	90			22.42	30.00	-7.58
130.13	49.00	100	90	45.12	Q	25.32	30.00	-4.68
304.07	41.30	100	0			24.07	37.00	-12.93
309.90	39.30	100	0			22.82	37.00	-14.18
320.08	42.10	100	0			26.91	37.00	-10.09
336.09	42.80	100	0			27.43	37.00	-9.57
352.07	41.30	100	45			24.96	37.00	-12.04
368.11	42.00	100	0			26.01	37.00	-10.99
384.10	39.70	100	0			23.90	37.00	-13.10
400.11	38.10	100	90			22.38	37.00	-14.62
432.01	45.60	100	90			31.01	37.00	-5.99
450.13	41.60	100	90			27.48	37.00	-9.52
480.04	36.90	100	225			23.91	37.00	-13.09
528.03	45.10	100	0			33.35	37.00	-3.65
576.03	43.30	100	90			32.09	37.00	-4.91
624.01	36.80	100	90			26.74	37.00	-10.26

Page 9 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

TEST EQUIPMENT USED									
Equipment Name	Manufacturer	Model Number	Serial Number	Calibration Due Date	Calibration Cycle				
Spectrum Analyzer - RF Section	Hewlett Packard	8568B	2634A03093	11/27/03	1 Year				
Spectrum Analyzer - Display Section	Hewlett Packard	85662A	1833A00389	11/27/03	1 Year				
Quasi-Peak Adapter	Hewlett Packard	85650A	2043A00220	11/28/03	1 Year				
RF Preselector	Hewlett Packard	85685A	2620A000281	05/10/03	1 Year				
Preamplifier	Com-Power	PA-102	1438	04/29/03	1 Year				
Antenna - Biconical	EMCO	3110	9108-1421	02/11/04	1 Year				
Antenna - Log Periodic	Electro-Metrics	EM-6950	1	09/12/03	1 Year				
Temperature/Humidity Monitor	Dickson	TH550	7255185	01/18/04	1 Year				

EUT ACCESSORIES							
Equipment Name	Manufacturer	Model Number	Serial Number				
Laptop	Dell	Latitude	221131				
AC Adapter	Dell	PA-1650-050	CN-054092-48010- 29B-00B9				
Monitor	NEC	JC-1575VMA	2Y785821				
Printer	Canon	BJC-4200	MT1-18				
Modem	Hayes	5362US	A02153623145				

BLOCK DIAGRAM



Page 10 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.

SPURIOUS RADIATED EMISSIONS (Continued)

PHOTOGRAPHS





Page 11 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.

SPURIOUS RADIATED EMISSIONS (Continued)

CLIENT:	Dell Computer Corporation	DATE:	02/19/03
EUT:	Intel(R) PRO/Wireless LAN 3A Mini	PROJECT	INTEL-030219
	PCI Adapter	NUMBER:	
MODEL NUMBER:	WM3A2100	TEST ENGINEER:	Rick Candelas
SERIAL NUMBER:	MY-09Y200-43950-321-012B	SITE #:	2
CONFIGUARTION:	Installed in Dell laptop computer.	TEMPERATURE:	15 C
		HUMIDITY:	69% RH
		TIME:	10:00 AMM

Standard:	FCC CFR 47, Part 15, 15.247(c), 15.209
Description:	Spurious Emissions Measurements - Radiated
Results:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum
	intentional radiator is operating, the radio frequency power that is produced by the intentional
	radiator is at least 20 dB below that in the 100 kHz bandwidth within the band that contains
	the highest level of the desired power, based on either an RF conducted or a radiated
	measurement.

Page 12 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

Fundamental and Band Edge Measurements at Channels 1, 6, & 11 Using Wistron NeWeb Corporation Triple-Band Antennas Aegis Labs, Inc. File #: INTEL-030219-02_

Horizontal Open Field Maximized Data								
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBuV	7)	Reading (dBuV)	(dBuV)	+=FAIL
	(dBuV)							
2411.02	71.00	100	225			103.21		
2389.73	30.83	100	225			62.94	74.00	-11.06
2389.20				17.00	А	49.11	54.00	-4.89
2436.02	70.00	100	225			102.32		
2461.02	69.00	100	225			101.43		
2483.50	30.17	100	225			62.70	74.00	-11.30
2483.50				18.00	A	50.53	54.00	-3.47

Vertical Open Field Maximized Data								
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBu	V)	Reading (dBuV)	(dBuV)	+=FAIL
	(dBuV)							
2412.89	68.33	100	45			100.75		
2390.00	30.00	100	45			62.32	74.00	-11.68
2390.00				16.50	Α	48.82	54.00	-5.18
2436.01	69.67	100	45			102.19		
2461.05	68.67	100	45			101.30		
2483.50	30.33	100	45			63.06	74.00	-10.94
2483.50				17.50	Α	50.23	54.00	-3.77

Page 13 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS







Page 14 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



Page 15 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 16 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



Page 17 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS




Page 18 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



Page 19 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 20 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



Page 21 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

Harmonic Measurements at Channels 1, 6, & 11@ 1Mbps Data Rate Using Wistron NeWeb Corporation Triple-Band Antennas Aegis Labs, Inc. File #: INTEL-030219-17

	Horizontal Open Field Maximized Data									
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)		
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBuV	7)	Reading (dBuV)	(dBuV)	+=FAIL		
	(dBuV)									
4824.13	42.33	100	180			44.33	74.00	-29.67		
4824.13				29.97	Α	31.97	54.00	-22.03		
7235.71	42.50	100	180			47.92	74.00	-26.08		
7235.71				34.65	А	40.07	54.00	-13.93		
9648.46	44.67	100	180			51.79	83.21	-31.42		
4873.59	41.33	100	180			43.50	74.00	-30.50		
4873.59				28.67	Α	30.84	54.00	-23.16		
7310.95	42.33	100	225			47.63	74.00	-26.37		
7310.95				29.43	Α	34.73	54.00	-19.27		
9747.55	44.50	100	225			51.89	82.32	-30.43		
2423.99	41.33	100	225			37.06	74.00	-36.94		
2423.99				29.11	А	24.84	54.00	-29.16		
7386.11	43.33	100	225			48.51	74.00	-25.49		
7386.11				29.83	А	35.01	54.00	-18.99		
9848.03	45.00	100	225			52.67	81.43	-28.76		

Vertical Open Field Maximized Data									
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)	
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBuV	7)	Reading (dBuV)	(dBuV)	+=FAIL	
	(dBuV)								
4824.10	43.17	100	225			45.14	74.00	-28.86	
4824.10				31.62	Α	33.59	54.00	-20.41	
7235.98	42.67	100	225			47.99	74.00	-26.01	
7235.98				29.87	Α	35.19	54.00	-18.81	
9647.75	44.83	100	225			52.00	80.75	-28.75	
4874.01	42.17	100	225			44.29	74.00	-29.71	
4874.01				30.44	Α	32.56	54.00	-21.44	
7310.65	42.33	100	225			47.56	74.00	-26.44	
7310.65				29.25	А	34.48	54.00	-19.52	
9747.58	44.67	100	180			52.16	82.19	-30.03	
4924.04	41.67	100	225			43.94	74.00	-30.06	
4924.04				29.50	Α	31.77	54.00	-22.23	
7385.96	42.67	100	180			47.81	74.00	-26.19	
7395.96				29.98	A	35.10	54.00	-18.90	
9848.44	45.00	100	0			52.82	81.30	-28.48	

Page 22 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

Spurious Emissions Measurements on Ch. 1 @ 1Mbps Data Rate Using Wistron NeWeb Corporation Triple-Band Antennas Aegis Labs, Inc. File #: INTEL-030219-18_

	Horizontal Open Field Maximized Data								
Freq.	Meter	Antenna	Azimuth	Quasi pk Corrected			Limits	Diff (dB)	
(MHz)	Reading (dBuV)	Height (cm)	(degrees)	or AVG (dBuV)		Reading (dBuV)	(dBuV)	+=FAIL	
1000.00	54.17	100	0			43.38	74.00	-30.62	
1000.00				39.29	Α	28.50	54.00	-25.50	
1198.87	54.17	100	315			44.69	74.00	-29.31	
1198.87				35.19	Α	25.71	54.00	-28.29	
1545.02	53.83	100	270			46.08	74.00	-27.92	
1545.02				42.80	A	35.05	54.00	-18.95	

	Vertical Open Field Maximized Data								
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)	
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBu	V)	Reading (dBuV)	(dBuV)	+=FAIL	
	(dBuV)								
1009.18	58.50	200	45			47.91	74.00	-26.09	
1009.18				40.32	Α	29.73	54.00	-24.27	
1198.71	53.83	100	90			44.41	74.00	-29.59	
1198.71				38.36	А	28.94	54.00	-25.06	
1542.77	56.00	125	45			48.26	74.00	-25.74	
1542.77				44.75	А	37.01	54.00	-16.99	
1653.57	55.17	150	45			48.13		48.13	

Fundamental and Band Edge Measurements at Channels 1, 6, & 11 Using Hitachi Monopole Antennas Aegis Labs, Inc. File #: INTEL-030219-57

	Horizontal Open Field Maximized Data								
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)	
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBuV))	Reading (dBuV)	(dBuV)	+=FAIL	
	(dBuV)								
2411.07	70.83	125	225			103.04			
2389.20	30.00	125	225			62.11	74.00	-11.89	
2389.20				17.00	А	49.11	54.00	-4.89	
2436.25	70.67	125	225			102.99			
2461.37	68.33	125	225			100.76			
2483.50	29.17	125	225			61.70	74.00	-12.30	
2483.50				16.83	A	49.36	54.00	-4.64	

	Vertical Open Field Maximized Data								
Freq.	Meter	Antenna	Azimuth	Quasi pk Corrected Limits Diff (a					
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBu	V)	Reading (dBuV)	(dBuV)	+=FAIL	
	(dBuV)				_				
2411.08	69.50	100	225			101.91			
2389.07	31.67	100	225			63.98	74.00	-10.02	
2390.00				16.67	Α	48.99	54.00	-5.01	
2436.25	71.50	100	225			104.02			
2461.37	70.50	100	225			103.13			
2483.50	30.17	100	225			62.90	74.00	-11.10	
2483.50				18.83	Α	51.56	54.00	-2.44	







Page 25 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



Page 26 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 27 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



Page 28 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 29 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



Page 30 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 31 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



Page 32 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

Harmonic Measurements at Channels 1, 6, & 11@ 1Mbps Data Rate Using Hitachi Monopole Antennas Aegis Labs, Inc. File #: INTEL-030219-58

	Horizontal Open Field Maximized Data									
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)		
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBul	V)	Reading (dBuV)	(dBuV)	+=FAIL		
	(dBuV)									
4823.55	42.50	100	135			44.50	74.00	-29.50		
4823.55				29.77	Α	31.77	54.00	-22.23		
7236.25	42.83	100	135			48.25	74.00	-25.75		
7236.25				30.00	Α	35.42	54.00	-18.58		
9648.31	44.83	100	180			51.95	83.04	-31.09		
4873.91	41.00	100	180			43.17	74.00	-30.83		
4873.91				28.52	Α	30.69	54.00	-23.31		
7311.30	43.00	100	180			48.30	74.00	-25.70		
7311.30				29.93	Α	35.23	54.00	-18.77		
9747.72	45.50	100	180			52.89	82.99	-30.10		
4923.68	41.17	100	180			43.51	74.00	-30.49		
4923.68				29.08	А	31.42	54.00	-22.58		
7385.83	43.83	100	180			49.01	74.00	-24.99		
7385.83				30.80	Α	35.98	54.00	-18.02		
9847.97	45.67	100	180			53.34	80.76	-27.42		

Vertical Open Field Maximized Data									
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)	
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBuV	7)	Reading (dBuV)	(dBuV)	+=FAIL	
	(dBuV)								
4824.04	42.67	100	90			44.64	74.00	-29.36	
4824.04				30.98	Α	32.95	54.00	-21.05	
7236.29	42.83	100	135			48.15	74.00	-25.85	
7236.29				30.10	Α	35.42	54.00	-18.58	
9648.10	44.83	100	135			52.00	81.91	-29.91	
4874.06	41.33	100	180			43.45	74.00	-30.55	
4874.06				29.29	Α	31.41	54.00	-22.59	
7310.89	42.50	100	180			47.73	74.00	-26.27	
7310.89				29.87	Α	35.10	54.00	-18.90	
9748.45	45.33	100	180			52.83	84.02	-31.19	
4924.22	41.33	100	225			43.60	74.00	-30.40	
4924.22				29.11	Α	31.38	54.00	-22.62	
7386.20	43.17	100	225			48.31	74.00	-25.69	
7386.20				30.38	А	35.52	54.00	-18.48	
9848.20	45.17	100	135			52.98	83.13	-30.15	

Page 33 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

Spurious Emissions Measurements on Ch. 1 @ 1Mbps Data Rate Using Hitachi Monopole Antennas Aegis Labs, Inc. File #: INTEL-030219-59

	Horizontal Open Field Maximized Data								
Freq.	Meter	Antenna	Azimuth	Quasi pk		Corrected	Limits	Diff (dB)	
(MHz)	Reading (dBuV)	Height (cm)	(degrees)	or AVG (dBuV)		Reading (dBuV)	(dBuV)	+=FAIL	
1000.48	58.33	100	135			47.55	74.00	-26.45	
1000.48				40.71	Α	29.93	54.00	-24.07	
1215.11	52.17	100	135			42.71	74.00	-31.29	
1215.11				36.05	Α	26.59	54.00	-27.41	
1554.60	51.67	125	180			43.92	74.00	-30.08	
1554.60				35.55	Α	27.80	54.00	-26.20	

	Vertical Open Field Maximized Data								
Freq.	Meter	Antenna	Azimuth	Quasi pk Corrected Limits Diff					
(MHz)	Reading	Height (cm)	(degrees)	or AVG (dBu	V)	Reading (dBuV)	(dBuV)	+=FAIL	
	(dBuV)								
1010.51	59.83	125	135			49.26	74.00	-24.74	
1010.51				42.12	Α	31.55	54.00	-22.45	
1215.44	52.33	100	0			42.93	74.00	-31.07	
1215.44				35.59	А	26.19	54.00	-27.81	
1544.11	59.00	100	125			51.26	74.00	-22.74	
1544.11				48.56	Α	40.82	54.00	-13.18	
1650.37	54.00	100	180			46.97		46.97	

TEST EQUIPMENT USED									
Equipment Name Manufacturer Model Serial Calibration Cal									
		Number	Number	Due Date	Cycle				
Spectrum Analyzer	Agilent	8564EC	4046A00387	02/28/04	2 Years				
Preamplifier	Agilent	8449B	3008A01573	04/29/03	1 Year				
Antenna - Horn	EMCO	3115	2230	09/14/03	1 Year				
Temperature/Humidity Monitor	Dickson	TH550	7255185	01/08/03	1 Year				

EUT ACCESSORIES								
Equipment Name	Manufacturer	Model Number	Serial Number					
Laptop	Dell	Latitude	31011					
AC Adapter	Dell	AA22850	B637 3Y 0006 0AB					
Monitor	NEC	JC-1575VMA	2Y785821					
Printer	Canon	BJC-4200	MT1-18					
Modem	Hayes	5362US	A02153623145					

BLOCK DIAGRAM



Page 35 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.

RADI SPURIOUS RADIATED EMISSIONS (Continued)

PHOTOGRAPHS



Page 36 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

MAXIMUM PEAK OUTPUT POWER MEASUREMENT

CLIENT:	Dell Computer Corporation	DATE:	02/19/03
EUT:	Intel(R) PRO/Wireless LAN 3A Mini	PROJECT	INTEL-030219-01
	PCI Adapter	NUMBER:	
MODEL NUMBER:	WM3A2100	TEST ENGINEER:	Rick Candelas
SERIAL NUMBER:	MY-09Y200-43950-321-012B	SITE #:	2
CONFIGUARTION:	Installed in Dell laptop computer.	TEMPERATURE:	15 C
		HUMIDITY:	67% RH
		TIME:	9:00 AM

Standard:	FCC CFR 47, Part 15, 15.247(b)
Description:	Peak Output Power – Conducted
Results:	Maximum Peak Output Power is less than 1 W. 47.86 mW @ Channel 11 at a data rate of 1 Mbps

Frequency (MHz)	Rate	Power	Cable Easter	Power Corrected	Power
(11112)	(mups)	(ubm)	(dB)	(dBm)	(111 vv)
2412.00	1	16.51	0.15	16.66	46.34
2412.00	5.5	16.13	0.15	16.28	42.46
2412.00	11	16.08	0.15	16.23	41.98
2437.00	1	16.57	0.15	16.72	46.99
2437.00	5.5	16.11	0.15	16.26	42.27
2437.00	11	15.97	0.15	16.12	40.93
2462.00	1	16.65	0.15	16.80	47.86
2462.00	5.5	16.17	0.15	16.32	42.85
2462.00	11	16.10	0.15	16.25	42.17

NOTE: Using CRTU Ver. 1.0.0.1000 software provided by Intel Corporation to set power limits.

Page 37 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

OCCUPIED BANDWIDTH MEASUREMENT

CLIENT:	Dell Computer Corporation	DATE:	02/19/03
EUT:	Intel(R) PRO/Wireless LAN 3A Mini	PROJECT	INTEL-030219
	PCI Adapter	NUMBER:	
MODEL NUMBER:	WM3A2100	TEST ENGINEER:	Rick Candelas
SERIAL NUMBER:	MY-09Y200-43950-321-012B	SITE #:	2
CONFIGURATION:	Installed in Dell laptop computer.	TEMPERATURE:	24 C
		HUMIDITY:	50% RH
		TIME:	1:00 PM

Standard:	FCC CFR 47, Part 15, 15.247(a)(2)
Description:	Occupied Bandwidth Measurement
Results:	6dB bandwidth is at least 500 kHz.

TEST RESULTS SUMMARY		
Data	Result	
Channel 1 Occupied Bandwidth	12.58 MHz 6 dB Bandwidth	
Channel 6 Occupied Bandwidth	13.00 MHz 6 dB Bandwidth	
Channel 11 Occupied Bandwidth	13.00 MHz 6dB Bandwidth	



OCCUPIED BANDWIDTH MEASUREMENT (Continued)

Page 39 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



OCCUPIED BANDWIDTH MEASUREMENT (Continued)

Page 40 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



OCCUPIED BANDWIDTH MEASUREMENT (Continued)

Page 41 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

SPECTRAL POWER DENSITY MEASUREMENT

CLIENT:	Dell Computer Corporation	DATE:	02/19/03
EUT:	Intel(R) PRO/Wireless LAN 3A Mini	PROJECT	INTEL-030219
	PCI Adapter	NUMBER:	
MODEL NUMBER:	WM3A2100	TEST ENGINEER:	Rick Candelas
SERIAL NUMBER:	MY-09Y200-43950-321-012B	SITE #:	2
CONFIGURATION:	Installed in Dell laptop computer.	TEMPERATURE:	25 C
		HUMIDITY:	50% RH
		TIME:	2:00 PM

Standard:	FCC CFR 47, Part 15, 15.247(D)
Description:	Power Spectral Density Measurement
Results:	Transmitted power density averaged over any 1 second interval is not greater than 8 dBm in
	any 3 kHz bandwidth within these bands

TEST RESULTS SUMMARY		
Data Result		
Channel 1 Power Spectral Density	-7.66 dBm – Pass	
Channel 6 Power Spectral Density	-6.33 dBm – Pass	
Channel 11 Power Spectral Density	-12.67 dBm - Pass	

Page 42 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



SPECTRAL POWER DENSITY MEASUREMENT (Continued)

Page 43 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



SPECTRAL POWER DENSITY MEASUREMENT (Continued)

Page 44 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS



SPECTRAL POWER DENSITY MEASUREMENT (Continued)

Page 45 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.

SPURIOUS EMISSIONS MEASUREMENT AT THE ANTENNA TERMINAL

CLIENT:	Dell Computer Corporation	DATE:	02/19/03
EUT:	Intel(R) PRO/Wireless LAN 3A Mini	PROJECT	INTEL-030219
	PCI Adapter	NUMBER:	
MODEL NUMBER:	WM3A2100	TEST ENGINEER:	Rick Candelas
SERIAL NUMBER:	MY-09Y200-43950-321-012B	SITE #:	2
CONFIGURATION:	Installed in Dell Laptop Computer.	TEMPERATURE:	20 C
		HUMIDITY:	50% RH
		TIME:	3:00 PM

Standard:	FCC CFR 47, Part 15, 15.247(c)
Description:	Conducted Spurious Emissions
Results:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST RESULTS SUMMARY		
Data	Result	
Channel 1 Spurious Emissions –	Max Spur Signal @ -57.50 dBm – Pass	
Antenna Terminal - 30MHz – 2GHz		
Channel 1 Spurious Emissions –	Max Spur Signal @ -56.00 dBm – Pass	
Antenna Terminal - 2GHz – 10GHz		
Channel 1 Spurious Emissions –	Max Spur Signal @ -50.00 dBm – Pass	
Antenna Terminal - 10GHz – 20GHz		
Channel 1 Spurious Emissions –	Max Spur Signal @ -47.17 dBm – Pass	
Antenna Terminal - 20GHz – 26.5GHz		
Channel 6 Spurious Emissions –	Max Spur Signal @ -57.33 dBm – Pass	
Antenna Terminal - 30MHz – 2GHz		
Channel 6 Spurious Emissions –	Max Spur Signal @ -57.00 dBm – Pass	
Antenna Terminal - 2GHz – 10GHz		
Channel 6 Spurious Emissions –	Max Spur Signal @ -50.50 dBm – Pass	
Antenna Terminal - 10GHz – 20GHz		
Channel 6 Spurious Emissions –	Max Spur Signal @ -47.50 dBm – Pass	
Antenna Terminal - 20GHz – 26.5GHz		
Channel 11 Spurious Emissions –	Max Spur Signal @ -57.83 dBm – Pass	
Antenna Terminal - 30MHz – 2GHz		
Channel 11 Spurious Emissions –	Max Spur Signal @ -56.00 dBm – Pass	
Antenna Terminal - 2GHz – 10GHz		
Channel 11 Spurious Emissions –	Max Spur Signal @ -50.33 dBm – Pass	
Antenna Terminal - 10GHz – 20GHz		
Channel 11 Spurious Emissions –	Max Spur Signal @ -47.00 dBm – Pass	
Antenna Terminal - 20GHz – 26.5GHz		

Page 46 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 47 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 48 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 49 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 50 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 51 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS





Page 52 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

AEGIS LABS, INC.

BAND EDGE EMISSIONS MEASUREMENT AT THE ANTENNA TERMINAL

CLIENT:	Dell Computer Corporation	DATE:	02/19/03
EUT:	Intel(R) PRO/Wireless LAN 3A Mini	PROJECT	INTEL-030219
	PCI Adapter	NUMBER:	
MODEL NUMBER:	WM3A2100	TEST ENGINEER:	Rick Candelas
SERIAL NUMBER:	MY-09Y200-43950-321-012B	SITE #:	2
CONFIGURATION:	Installed in Dell Laptop Computer.	TEMPERATURE:	25 C
		HUMIDITY:	35% RH
		TIME:	4:00 PM

TEST RESULTS SUMMARY		
Data	Result	
Channel 1 Band Edge Measurement	>20 dBc – Pass	
Peak Measurement @ 2390 MHz		
Channel 1 Band Edge Measurement	52.64 dBuV - Pass	
Average Measurement @ 2390 MHz		
Channel 11 Band Edge Measurement	>20 dBc – Pass	
Peak Measurement @ 2483.5 MHz		
Channel 11 Band Edge Measurement	52.60 dBuV - Pass	
Average Measurement @ 2483.5 MHz		

Page 53 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS
CONDUCTED BAND EDGE EMISSIONS MEASUREMENT (Continued)





Page 54 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

CONDUCTED BAND EDGE EMISSIONS MEASUREMENT (Continued)





Page 55 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS

ALL CONDUCTED MEASUREMENTS SETUP

TEST EQUIPMENT USED						
Equipment Name	Manufacturer	Model	Serial	Calibration	Calibration	
		Number	Number	Due Date	Cycle	
Spectrum Analyzer	Agilent	8564EC	4046A00387	02/28/04	2 Years	
DC Block	Inmet	8039	N/A	N/A	N/A	
Power Meter	Rohde & Schwarz	NRVS	DE30863	11/24/03	1 Year	
Power Sensor	Leistungsmesskoph	NRV-Z5	844855/012	11/24/03	1 Year	
Temperature /	Dickson	TH550	7255185	01/08/04	1 Year	
Humidity Monitor						

EUT ACCESSORIES						
Equipment Name	Manufacturer	Model Number	Serial Number			
Laptop	Dell	Latitude	221131			
AC Adapter	Dell	PA-1650-050	CN-054092-48010-29B-00B9			
Monitor	NEC	JC-1575VMA	2Y785821			
Printer	Canon	BJC-4200	MT1-18			
Modem	Hayes	5362US	A02153623145			

BLOCK DIAGRAM



ALL CONDUCTED MEASUREMENTS SETUP (Continued)

PHOTOGRAPHS



Page 57 of 57 Report Number: INTEL-030219F FCC ID: E2K24CLNS