# FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2AUVX-NT35

#### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

#### Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842 / f	4.89 / f	(900 / f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100,000			5	6	

Note: *f* is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

#### Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)	
0.3-1.34	614	1.63	(100)*	30	
1.34-30	824/f	2.19/f	(180/f)*	30	
30-300	27.5	0.073	0.2	30	
300-1500			F/1500	30	
1500-100,000			1.0	30	

Note: f = frequency in MHz

\* = Plane-wave equivalent power density

### MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna,R=20cm

## Test Result of RF Exposure Evaluation

	Tune up Produce power	Maximu m peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm2)	Limit (mW / cm2 )	Result
2.4GWIFI	13±1	14	25.1189	1.8408 (2.65dBi)	0.0092	1	Pass
LTE BAND 2	18±1	19	79.4328	1.4997 (1.76dBi)	0.0237	1	Pass
LTE BAND 4	18±1	19	79.4328	1.3709 (1.37dBi)	0.0217	1	Pass
LTE BAND 12	18±1	19	79.4328	0.5808 (-2.36dBi)	0.0092	0.5	Pass
LTE BAND 13	18±1	19	79.4328	0.9397 (-0.27dBi)	0.01486	0.5	Pass

supported simultaneous transmission:

WIFI+LTE: ∑MPE Ratio =0.0092+0.0237=0.0329≤1,

The result is pass.