

Moonstone Technology(Shaoxing) Co., Ltd.

MPE ASSESSMENT REPORT

Report Type:

FCC MPE assessment report

Model:

RLE51SC

REPORT NUMBER:

2412B0045SHA-003

ISSUE DATE:

Jan 2, 2025

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek



Applicant: Moonstone Technology(Shaoxing) Co., Ltd.
Room 301, 3rd Floor, Building 2, No. 99 Chuangxing Road, Sunduan Street, Yuecheng District, Shaoxing City, Zhejiang Province, China

Manufacturer: Moonstone Technology(Shaoxing) Co., Ltd.
Room 301, 3rd Floor, Building 2, No. 99 Chuangxing Road, Sunduan Street, Yuecheng District, Shaoxing City, Zhejiang Province, China

FCC ID: 2BKDG-RLE51SC

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06

FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:

Project Engineer

Teddy Yin

REVIEWED BY:

Reviewer

Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
2412B0045SHA-003	Rev. 01	Initial issue of report	Jan 2, 2025

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Robotic Vacuum Cleaner
Type/Model/PMN/HVIN:	RLE51SC
Description of EUT:	The appliance covered by this report is automatically battery-powered vacuum cleaner and dry pick up for household indoor use only. The EUT contains WIFI mode and BLE mode.
Rating:	DC 14.4V
EUT type:	<input type="checkbox"/> Table top <input checked="" type="checkbox"/> Floor standing
Software Version:	V1.0
Hardware Version:	V1.0
Sample No.:	A241205-03-001
Sample received date:	Dec 10, 2024
Date of test:	Dec 10~24, 2024

1.2 Technical Specification

WIFI

Frequency Range:	2412MHz ~ 2462MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20, IEEE 802.11n-HT40
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT40: OFDM (64-QAM, 16-QAM, QPSK, BPSK)
Channel Number:	11 Channels for 802.11b, 802.11g and 802.11n(HT20) 7 Channels for 802.11n(HT40)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7 IEEE 802.11n-HT40: Up to MCS7
Channel Separation:	5 MHz
Antenna Information:	1.75dBi, PIFA antenna(Declared by manufacturer)

BLE

Frequency Range:	2402-2480MHz
Support Standards:	Bluetooth LE 5.0
Type of Modulation:	GFSK
Channel Number:	40

TEST REPORT

Data Rate:	1Mbps
Channel Separation:	2MHz
Antenna Information:	1.75dBi, PIFA antenna(Declared by manufacturer)

1.3 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 MPE Assessment

Test result: Pass

2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density S_{eq} (W/m ²)
0-1 Hz	-	$3,2 \times 10^4$	4×10^4	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	4 000/f	5 000/f	-
0,025-0,8 kHz	250/f	4/f	5/f	-
0,8-3 kHz	250/f	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	0,73/f	0,92/f	-
1-10 MHz	$87/f^{1/2}$	0,73/f	0,92/f	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	f/200
2-300 GHz	61	0,16	0,20	10

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 2412B0045SHA-001:

The maximum WIFI EIRP = 19.66dBm = 92.47 mW;

Here R is chosen to be 20cm,

$$S = PG / (4\pi R^2) = 92.47 / (4 * 3.14 * 20 * 20) = 0.0184 \text{ mW/cm}^2$$

As we can see from the test report 2412B0045SHA-002:

The maximum BLE EIRP = 7.73dBm = 5.93 mW;

Here R is chosen to be 20cm,

$$S = PG / (4\pi R^2) = 5.93 / (4 * 3.14 * 20 * 20) = 0.0012 \text{ mW/cm}^2$$

$$S_{\text{sum}} = 0.0184 + 0.0012 = 0.0196 \text{ mW/cm}^2 < 1 \text{ mW/cm}^2$$

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.

***** END *****