

# TEST REPORT

FCC MPE Test for N20-HRDU\_A\_700LTE\_FN  
Certification

**APPLICANT**  
SOLiD, Inc.

**REPORT NO.**  
HCT-RF-2005-FC002

**DATE OF ISSUE**  
May 21, 2020

**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 F ax. +82 31 645 6401



**HCT CO., LTD.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 F ax. +82 31 645 6401

<h1 style="margin: 0;">TEST REPORT</h1> <p style="margin: 0;">FCC MPE Test for N20-HRDU_A_700LTE_FN</p>	<p><b>REPORT NO.</b> HCT-RF-2005-FC002</p> <p><b>DATE OF ISSUE</b> 21 May 2020</p> <p><b>Additional Model</b> -</p>
---	---

<b>Applicant</b>	SOLiD, Inc. 10, 9th Floor, SOLiD Space, Pangyoyeok-ro 220, Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, South Korea
<b>EUT Type</b>	DAS
<b>Model Name</b>	N20-HRDU_A_700LTE_FN
<b>FCC ID</b>	W6UNHA700LFN

This test results were applied only to the test methods required by the standard.

**Tested by**  
Kwang Il Yoon

(signature)

**Technical Manager**  
Jong Seok Lee

(signature)

(signature)  
**HCT CO., LTD.**  
*Soo Chan Lee*  
SooChan Lee / CEO

## REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	May 21, 2020	Initial Release

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

## RF Exposure Statement

### 1. LIMITS

According to § 1.1310 and § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	.....	.....	f/1500	30
1500 - 100.000.....	.....	.....	1.0	30

F = frequency in MHz

\* = Plane-wave equivalent power density

### 2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

## - Lower 700 MHz – LTE 5 MHz (Downlink)

Max Peak output Power at antenna input terminal	44.00	dBm
Max Peak output Power at antenna input terminal	25118.86	mW
Prediction distance	600.00	cm
Prediction frequency	731.50	MHz
Antenna Gain(typical)	16.00	dBi
Antenna Gain(numeric)	39.81	-
Power density at prediction frequency( S)	0.2210	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	0.4877	mW/cm <sup>2</sup>

## - Lower 700 MHz – LTE 10 MHz (Downlink)

Max Peak output Power at antenna input terminal	44.00	dBm
Max Peak output Power at antenna input terminal	25118.86	mW
Prediction distance	600.00	cm
Prediction frequency	734.00	MHz
Antenna Gain(typical)	16.00	dBi
Antenna Gain(numeric)	39.81	-
Power density at prediction frequency( S)	0.2210	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	0.4893	mW/cm <sup>2</sup>

## - Upper 700 MHz – LTE 5 MHz (Downlink)

Max Peak output Power at antenna input terminal	44.00	dBm
Max Peak output Power at antenna input terminal	25118.86	mW
Prediction distance	600.00	cm
Prediction frequency	748.50	MHz
Antenna Gain(typical)	16.00	dBi
Antenna Gain(numeric)	39.81	-
Power density at prediction frequency( S)	0.2210	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	0.4990	mW/cm <sup>2</sup>

## - Upper 700 MHz – LTE 10 MHz (Downlink)

Max Peak output Power at antenna input terminal	44.00	dBm
Max Peak output Power at antenna input terminal	25118.86	mW
Prediction distance	600.00	cm
Prediction frequency	751.00	MHz
Antenna Gain(typical)	16.00	dBi
Antenna Gain(numeric)	39.81	-
Power density at prediction frequency( S)	0.2210	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	0.5007	mW/cm <sup>2</sup>

## - FirstNet – LTE 5 MHz (Downlink)

Max Peak output Power at antenna input terminal	23.00	dBm
Max Peak output Power at antenna input terminal	199.53	mW
Prediction distance	600.00	cm
Prediction frequency	760.50	MHz
Antenna Gain(typical)	16.00	dBi
Antenna Gain(numeric)	39.81	-
Power density at prediction frequency( S)	0.0018	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	0.5070	mW/cm <sup>2</sup>

## - FirstNet – LTE 10 MHz (Downlink)

Max Peak output Power at antenna input terminal	23.00	dBm
Max Peak output Power at antenna input terminal	199.53	mW
Prediction distance	600.00	cm
Prediction frequency	763.00	MHz
Antenna Gain(typical)	16.00	dBi
Antenna Gain(numeric)	39.81	-
Power density at prediction frequency( S)	0.0018	mW/cm <sup>2</sup>
MPE limit for uncontrolled exposure at prediction frequency	0.5087	mW/cm <sup>2</sup>