

## FCC 47 CFR MPE REPORT

Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.

BLUETOOTH SPEAKER

Model Number: CR3110A-GY

Additional Model: BL106, CR3110A-XX

FCC ID: ESX-BL106

|                          |                                                                     |
|--------------------------|---------------------------------------------------------------------|
| Prepared for:            | Guangzhou Panyu Juda Car Audio Equipment Co., Ltd.                  |
|                          | Vtrek Industrial Park, Shibei Industrial Road, Dashi Street,        |
|                          | Panyu Borough, Guangzhou, Guangdong China                           |
|                          |                                                                     |
| Prepared By:             | EST Technology Co., Ltd.                                            |
|                          | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| Tel: 86-769-83081888-808 |                                                                     |

|                 |                      |
|-----------------|----------------------|
| Report Number:  | ESTE-R1905038        |
| Date of Test:   | Mar. 23~May 08, 2019 |
| Date of Report: | May 13, 2019         |



## Maximum Permissible Exposure

### 1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a)、Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|-----------------------------------------|--------------------------------------------------|
| 0.3-3.0               | 614                              | 1.63                              | (100)*                                  | 6                                                |
| 3.0-30                | 1842/f                           | 4.89/f                            | (900/f)*                                | 6                                                |
| 30-300                | 61.4                             | 0.163                             | 1.0                                     | 6                                                |
| 300-1500              |                                  |                                   | F/300                                   | 6                                                |
| 1500-10000            |                                  |                                   | 5                                       | 6                                                |

#### (b)、Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   2 ,   H   2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|-----------------------------------------|--------------------------------------------------|
| 0.3-1.34              | 614                              | 1.63                              | (100)*                                  | 30                                               |
| 1.34-30               | 824/f                            | 2.19/f                            | (180/f)*                                | 30                                               |
| 30-300                | 27.5                             | 0.073                             | 0.2                                     | 30                                               |
| 300-1500              |                                  |                                   | F/1500                                  | 30                                               |
| 1500-10000            |                                  |                                   | 1.0                                     | 30                                               |

Note: f=frequency in MHz; \*Plane-wave equivalent power density

### 2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G) / 0.5/d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2/377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

### 3、Conducted Power Result

#### 3.1 Antenna 0

| Mode   | Frequency<br>(MHz) | Peak output power<br>(dBm) | Peak output power<br>(mW) | Target<br>power<br>(dBm) | Antenna gain |          |
|--------|--------------------|----------------------------|---------------------------|--------------------------|--------------|----------|
|        |                    |                            |                           |                          | (dBi)        | (Linear) |
| GFSK   | 2402               | 0.68                       | 1.169                     | $0 \pm 1$                | 0            | 1        |
|        | 2441               | 0.09                       | 1.021                     | $0 \pm 1$                | 0            | 1        |
|        | 2480               | -0.45                      | 0.902                     | $-0 \pm 1$               | 0            | 1        |
| 8-DPSK | 2402               | 0.56                       | 1.138                     | $0 \pm 1$                | 0            | 1        |
|        | 2441               | -0.01                      | 0.998                     | $-0 \pm 1$               | 0            | 1        |
|        | 2480               | -0.52                      | 0.887                     | $-0 \pm 1$               | 0            | 1        |

### 4、Calculated Result and Limit

| Mode   | Target<br>power<br>(dBm) | Antenna gain |          | Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Limited<br>of<br>Power<br>Density<br>(S)<br>(mW<br>/cm <sup>2</sup> ) | Test<br>Result |
|--------|--------------------------|--------------|----------|------------------------------------------------------|-----------------------------------------------------------------------|----------------|
|        |                          | (dBi)        | (Linear) |                                                      |                                                                       |                |
| GFSK   | 1                        | 0            | 1        | 0.00025                                              | 1                                                                     | Compiles       |
| 8-DPSK | 1                        | 0            | 1        | 0.00025                                              | 1                                                                     | Compiles       |