

11.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.Section G) Unwanted emissions measurement.

<u>Procedure for Unwanted Emissions Measurements Below 1000MHz:</u>

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

<u>Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz:</u>

- RBW = 1 MHz
- VBW ≥ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

• <u>Procedures for Average Unwanted Emissions Measurements Above 1000MHz:</u>

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.


• VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

- Procedures for Average Unwanted Emissions Measurements Above 1000MHz:
 - RBW = 1 MHz
 - VBW = 3 MHz Detector = power averaging (rms), set span/(# of points in sweep) \geq RBW/2.
 - Averaging type = power averaging (RMS)
 - The correction factor shall be offset is $10 \log (1/x)$, where x is the duty cycle.




11.3 Measurement Setup (Block Diagram of Configuration)


Radiated Emission Test Setup 9kHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



11.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

		naulau		UII IESI KES		-10112		
EUT Na	ame	Set Top Box	x		Model Name	S	EI700B2MV	V
Temper	rature	22.8°C Relative Humidity 58.3%				3.3%		
Pressu	re	960hPa			Test Voltage		Normal Voltage	
Test Mo	ode	802.11ac(2	0MHz)_58	25MHz	Antenna	Н	Horizontal	
[w///de]	130 120 110 100 90 80 70 60 50 40 30 20 0 90 80 70 60 50 40 30 20 10 90 80 70 60 50 40 30 70 60 50 90 80 70 60 50 90 80 70 90 80 70 90 80 70 90 80 70 90 80 70 90 80 70 90 80 70 90 80 70 90 80 70 90 80 70 90 80 90 90 80 90 80 90 80 90 80 90 90 80 90 90 80 90 90 80 90 90 80 90 90 80 90 90 80 90 90 80 90 90 90 90 90 90 90 90 90 90 90 90 90	- Horizontal PK	100M	FCC Part 15				16
Peak Da	ata List							
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	60.07	23.92	17.86	40.00	16.08	100	133	Horizontal
2	109.54	32.63	16.57	43.50	10.87	100	324	Horizontal
3	167.74	33.03	15.78	43.50	10.47	100	243	Horizontal
4	222.02	22.76	10.71	46.00	10.04	100	1	Harizantal

Radiated Emission Test Results at 30MHz-1GHz

·····								
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	60.07	23.92	17.86	40.00	16.08	100	133	Horizontal
2	109.54	32.63	16.57	43.50	10.87	100	324	Horizontal
3	167.74	33.03	15.78	43.50	10.47	100	243	Horizontal
4	223.03	33.76	12.71	46.00	12.24	100	1	Horizontal
5	450.01	34.82	21.92	46.00	11.18	100	235	Horizontal
6	834.13	44.45	28.79	46.00	1.55	100	40	Horizontal
Final D	Data List							
1	834.13	28.79	41.93	46.00	4.07	100	40	Horizontal
- 1/	_							

Result: Pass



EUT Na	EUT Name Set Top Box				Model Name	5	SEI700B2MW	
Tempe	rature	22.8°C			Relative Humidity 58.3%		58.3%	
Pressu	re	960hPa	960hPa Test Voltage Norma		Test Voltage		Normal Voltage	
Test M	ode	802.11ac(2	0MHz)_58	25MHz	Antenna	١	Vertical	
	130 120 110			FCC Part 15C				
	100 90 80 70 60 50 40 40 20 10 0 -10 30M * QP Limit * QP Detecto	- Vertical PK	100M	Frequency[Hz]	man alan and	es es esta de la companya de la comp		16
Final D	ata List							
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	70.74	30.56	14.45	40.00	9.44	100	134	Vertical
2	108.57	34.92	16.62	43.50	8.58	100	57	Vertical
3	146.4	30.91	16.73	43.50	12.59	100	182	Vertical
4	239.52	31.26	16.00	46.00	14.74	100	206	Vertical
5	463.59	33.75	23.86	46.00	12.25	100	239	Vertical
6	834.13	41.89	28.79	46.00	4.11	100	316	Vertical

Result: Pass

Note:

- 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- 2. All test modes had been pre-tested, Refer to Chapter 5 of the report for details.



EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	22.8°C	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n20_5180MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz–Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10360.042	46.42	9.14	55.56	68.20	-12.64	peak
15540.063	40.58	10.22	50.80	74.00	-23.20	peak
15540.063	32.40	10.22	42.62	54.00	-11.38	AVG
Remark:						
Factor = Anter	nna Factor + Cabl	le Loss – Pre-a	amplifier.			

Radiated Emission Above 1GHz–Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10360.042	46.89	9.14	56.03	68.20	-12.17	peak
15540.063	40.30	10.22	50.52	74.00	-23.48	peak
15540.063	32.53	10.22	42.75	54.00	-11.25	AVG
Remark:						
Factor = Anter	nna Factor + Cab	le Loss – Pre-ar	nplifier.			

Result: Pass



EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	22.8°C	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n20_5200MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz–Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10400.042	46.35	9.14	55.49	68.20	-12.71	peak
15600.063	40.50	10.22	50.72	74.00	-23.28	peak
15600.063	32.76	10.22	42.98	54.00	-11.02	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Radiated Emission Above 1GHz–Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10400.042	46.51	9.14	55.65	68.20	-12.55	peak
15600.063	40.58	10.22	50.80	74.00	-23.20	peak
15600.063	32.13	10.22	42.35	54.00	-11.65	AVG
Remark:	-	-	-		-	-
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Result: Pass



EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	22.8°C	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n20_5240MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz–Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
10480.042	46.93	9.14	56.07	68.20	-12.13	peak	
15720.063	40.35	10.22	50.57	74.00	-23.43	peak	
15720.063	32.38	10.22	42.60	54.00	-11.40	AVG	
Remark:	Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.							

Radiated Emission Above 1GHz–Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
10480.042	46.99	9.14	56.13	68.20	-12.07	peak
15720.063	40.81	10.22	51.03	74.00	-22.97	peak
15720.063	32.89	10.22	43.11	54.00	-10.89	AVG
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Result: Pass



EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	22.8°C	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n20_5745MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz–Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11490.042	46.04	9.14	55.18	68.20	-13.02	peak
11490.042	36.86	10.22	47.08	74.00	-26.92	AVG
17235.063	40.86	10.22	51.08	54.00	-2.92	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Radiated Emission Above 1GHz–Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11490.042	46.06	9.14	55.20	68.20	-13.00	peak
11490.042	36.07	10.22	46.29	74.00	-27.71	AVG
17235.063	40.05	10.22	50.27	54.00	-3.73	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Result: Pass



EUT Name	Set Top Box	Model Name	SEI700B2MW				
Temperature	22.8°C	Relative Humidity	58.3%				
Pressure	960hPa	Test Voltage	Normal Voltage				
Test Mode	802.11n20_5785MHz	Antenna	Horizontal/Vertical				

Radiated Emission Above 1GHz–Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11570.042	46.18	9.14	55.32	68.20	-12.88	peak
11570.042	36.93	10.22	47.15	74.00	-26.85	AVG
17355.063	40.66	10.22	50.88	54.00	-3.12	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Radiated Emission Above 1GHz–Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11570.042	47.00	9.14	56.14	68.20	-12.06	peak
11570.042	36.97	10.22	47.19	74.00	-26.81	AVG
17355.063	40.92	10.22	51.14	54.00	-2.86	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Result: Pass



EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	22.8°C	Relative Humidity	58.3%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n20_5825MHz	Antenna	Horizontal/Vertical

Radiated Emission Above 1GHz–Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11650.042	46.32	9.14	55.46	68.20	-12.74	peak
11650.042	36.43	10.22	46.65	74.00	-27.35	AVG
17475.063	40.42	10.22	50.64	54.00	-3.36	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Radiated Emission Above 1GHz–Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
11650.042	46.41	9.14	55.55	68.20	-12.65	peak
11650.042	36.04	10.22	46.26	74.00	-27.74	AVG
17475.063	40.38	10.22	50.60	54.00	-3.40	peak
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

Result: Pass

Note:

- 1. The amplitude of other spurious emissions from 1GHz to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Amplifier gain, Margin=Measure Result-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.
- 4. All test modes had been pre-tested. Refer to Chapter 5 of the report for details.




EUT Name	Set Top Box	Model Name	SEI700B2MW				
Temperature	25°C	Relative Humidity	60%				
Pressure	960hPa	Test Voltage	Normal Voltage				
Test Mode	802.11a20_5180MHz	Antenna	Horizontal				

Test Result for Band edge Emission at Restricted bands

Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass




EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11a20_5180MHz	Antenna	Vertical

and adma Emilarian at Destricted bands

Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass




EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n40_5190MHz	Antenna	Horizontal

and adma Emilarian at Destricted bands

Test Graph for Peak Measurement



Test Graph for Average Measurement



Result: Pass




EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n40_5190MHz	Antenna	Vertical

a due Euclasian of Destalated hands . .

Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass




EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11ac80_5210MHz	Antenna	Horizontal

t Posult for Pand adda Emission at Postriated bands

Test Graph for Peak Measurement



Test Graph for Average Measurement




Result: Pass




EUT Name	Set Top Box	Model Name	SEI700B2MW
Temperature	25°C	Relative Humidity	60%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11ac80_5210MHz	Antenna	Vertical

a due Euclasian of Destalated hands . .

Test Graph for Peak Measurement



Test Graph for Average Measurement





Result: Pass

Note:

- 1. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.
- 2. All test modes had been pre-tested, Refer to Chapter 5 of the report for details.



12. AC Power Line Conducted Emission Test

12.1 Measurement limit


Framman	Maximum RF Line Voltage		
Frequency	Q.P (dBµV)	Average (dBµV)	
150kHz~500kHz	66-56	56-46	
500kHz~5MHz	56	46	
5MHz~30MHz	60	50	

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

12.2 Block Diagram of Line Conducted Emission Test





12.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received DC12V by adapter which received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received charging voltage by adapter which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 Ohm load; the second scan had Line 1 connected to a 50 Ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case was reported on the Summary Data page.
- 4. The worst mode is 802.11ac(20MHz)5825MHz, antenna 1 and antenna 2 work together.



12.5 Test Result of Line Conducted Emission Test



MHz	dBµV	dB	dBµV	dB		
0.170000	38.00	6.1	65	27.0	QP	L1
0.194000	35.20	6.1	64	28.7	QP	L1
0.222000	32.00	6.1	63	30.7	QP	L1
0.234000	31.80	6.1	62	30.5	QP	L1
0.274000	27.10	6.1	61	33.9	QP	L1
0.534000	33.40	6.2	56	22.6	QP	L1

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.546000	27.20	6.2	46	18.8	AV	L1
0.790000	14.70	6.2	46	31.3	AV	L1
1.046000	12.80	6.2	46	33.2	AV	L1
1.370000	13.10	6.2	46	32.9	AV	L1
2.618000	13.40	6.3	46	32.6	AV	L1
4.438000	11.80	6.3	46	34.2	AV	L1

Result: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/





MEASUREMENT RESULT: "agc fin"

2024/4/18 10:45

024/4/10 10:	40					
Frequency			Limit dBuV	Margin dB	Detector	Line
MHz	dBµV	dB	αвμν	αв		
0.174000	36.50	6.1	65	28.3	QP	N
0.550000	30.20	6.2	56	25.8	QP	N
0.762000	20.90	6.2	56	35.1	QP	N
0.794000	20.40	6.2	56	35.6	QP	N
1.042000	20.60	6.2	56	35.4	QP	N
1.098000	19.80	6.2	56	36.2	QP	N

MEASUREMENT RESULT: "agc_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.150000	21.70	6.1	56	34.3	AV	Ν
0.178000	21.30	6.1	55	33.3	AV	N
0.434000	9.80	6.1	47	37.4	AV	N
0.546000	16.10	6.2	46	29.9	AV	N
0.786000	8.80	6.2	46	37.2	AV	N
4.386000	8.20	6.3	46	37.8	AV	N

Result: Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/



Report No.: AGC16253240402FR04 Page 177 of 177

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC16253240402AP01

Appendix II: Photographs of EUT

Refer to the Report No.: AGC16253240402AP02

----End of Report----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.