

## RF Exposure Evaluation

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $Pd = (P_{out} * G) / (4 * \pi * r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

## Test Result of RF Exposure Evaluation

### SRD

Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
315MHz	1.74	1.49	0	0.21	PASS
433.92 MHz	-27.96	0.0016	0	0.29	PASS

315MHz antenna gain: -27.8dBi

433.92MHz antenna gain: -2.67dBi

according to ANSI C63.10

$30\text{MHz} < F < 1\text{GHz}$ :  $\text{EIRP (dBm)} = \text{E(dBuv/m)} - 95.2 - 4.7$

So Output power=EIRP-antenna gain

Mode	Antenna gain (dBi)	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
BLE	0.5	1.54	1.43	0.00032	1.000	PASS
GSM850	2.53	25.97	395.367	0.142	0.566	PASS
GSM1900	1.59	22.97	198.153	0.057	1.000	PASS
LTE-B2	1.59	25	316.228	0.091	1.000	PASS
LTE-B4	2.00	25	316.228	0.099	1.000	PASS
LTE-B5	2.53	25	316.228	0.113	0.566	PASS
LTE-B12	3.26	25	316.228	0.133	0.477	PASS
LTE-B13	4.45	25	316.228	0.176	0.525	PASS
LTE-B25	1.59	25	316.228	0.091	1.000	PASS
LTE-B26	3.19	25	316.228	0.131	0.566	PASS
LTE-B66	2.00	25	316.228	0.099	1.000	PASS
LTE-B85	3.26	25	316.228	0.133	0.477	PASS
NB-IOT-B2	1.59	25	316.228	0.091	1.000	PASS
NB-IOT-B4	2.00	25	316.228	0.099	1.000	PASS
NB-IOT-B5	2.53	25	316.228	0.113	0.566	PASS
NB-IOT-B12	3.26	25	316.228	0.133	0.477	PASS
NB-IOT-B13	4.45	25	316.228	0.176	0.525	PASS
NB-IOT-B25	1.59	25	316.228	0.091	1.000	PASS
NB-IOT-B66	2.00	25	316.228	0.099	1.000	PASS
NB-IOT-B71	1.66	25	316.228	0.092	0.465	PASS
NB-IOT-B85	3.26	25	316.228	0.133	0.477	PASS

BLE and cellular Simultaneous Transmission:

$$\sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k}$$

$$BLE + LTE = (0.00032/1) + (0.176/0.525) = 0.336 < 1$$

$$BLE + GSM = (0.00032/1) + (0.142/0.566) = 0.251 < 1$$

The max power density is less than MPE exempt limit, so it is compliance.