

FCC CFR47 PART 15 SUBPART C INDUSTRY CANADA RSS-210 ISSUE 8

MANUFACTURER'S TEST REPORT

FOR

WIRELESS ALARM CONSOLE

MODEL NUMBER: TSSC-VE

FCC ID: CFS8DLTSSCBASE1 IC: 573F-TSSCBASE1

REPORT NUMBER: R11070857-E1

ISSUE DATE: 2016-01-21

Prepared for HONEYWELL SECURITY 2 CORPORATE CENTER DR SUITE 100 PO BOX 9040 MELVILLE, NY, 11747, USA

Prepared by UL LLC

12 LABORATORY DR. RESEARCH TRIANGLE PARK, NC 27709 USA TEL: (919) 549-1400

NVLAP Lab code: 200246-0

Revision History

Ver.	lssue Date	Revisions	Revised By
1	2016-01-20	Initial Issue	Mark Nolting
2	2016-01-21	Revised EUT description in Section 5.1.	Jeff Moser

Page 2 of 26

TABLE OF CONTENTS

1.	AT	TESTATION OF TEST RESULTS	4
2.	TES	ST METHODOLOGY	6
3.	FAG	CILITIES AND ACCREDITATION	6
4.	CA	LIBRATION AND UNCERTAINTY	6
4	.1.	MEASURING INSTRUMENT CALIBRATION	6
4	.2.	SAMPLE CALCULATION	6
4	.3.	MEASUREMENT UNCERTAINTY	7
5.	EQ	UIPMENT UNDER TEST	8
5	.1.	DESCRIPTION OF EUT	8
5	.2.	DESCRIPTION OF AVAILABLE ANTENNAS	8
5	.3.	SOFTWARE AND FIRMWARE	8
5	.4.	WORST-CASE CONFIGURATION AND MODE	8
5	.5.	MODIFICATIONS	8
5	.6.	DESCRIPTION OF TEST SETUP	9
6.	TES	ST AND MEASUREMENT EQUIPMENT1	1
6	.1.	DUTY CYCLE1	2
7.	RAI	DIATED EMISSION TEST RESULTS1	3
7.	.1.	TX RADIATED SPURIOUS EMISSION1	3

Page 3 of 26

1. ATTESTATION OF TEST RESULTS

COMPANY NAME:	HONEYWELL SECURITY 2 CORPORATE CENTER DR SUITE 100 PO BOX 9040 MELVILLE, NY, 11747, USA
EUT DESCRIPTION:	WIRELESS ALARM CONSOLE
MODEL:	TSSC-VE
SERIAL NUMBER:	Non-serialized samples: SRID 2072; SRID 9553 (FCC#3)
DATE TESTED:	12/03/2015, 12/29-12/31/2015, 01/03/2016
EUT DESCRIPTION: MODEL: SERIAL NUMBER: DATE TESTED:	WIRELESS ALARM CONSOLE TSSC-VE Non-serialized samples: SRID 2072; SRID 9553 (FC 12/03/2015, 12/29-12/31/2015, 01/03/2016

APPLICABLE STANDARDS					
STANDARD	TEST RESULTS				
FCC PART 15 SUBPART C	PASS				
(Duty Cycle, fundamental and radiated spurious emissions only.)					
INDUSTRY CANADA RSS-210 Issue 8, Annex 1	PASS				
(Duty Cycle, fundamental and radiated spurious emissions only.)					
INDUSTRY CANADA RSS-GEN Issue 4	PASS				
(Duty Cycle, fundamental and radiated spurious emissions only.)					

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL LLC based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL LLC By:

our

Jeff Moser EMC Program Manager UL – Consumer Technology Division

Prepared By:

Mark Nolting EMC Engineer UL – Consumer Technology Division

Page 5 of 26

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 4, and RSS-210 Issue 8. This report is a manufacturer's specification report that contains only duty-cycle, fundamental and radiated spurious data.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 12 Laboratory Dr., Research Triangle Park, NC 27709, USA and 2800 Suite B Perimeter Park Dr., Morrisville, NC 27560.

12 Laboratory Dr., RTP, NC 27709				
Chamber A				
Chamber C				

2800 Suite B Perimeter Park Dr.,			
Morrisville, NC 27560			
Chamber NORTH			
Chamber SOUTH			

The onsite chambers are covered under Industry Canada company address code 2180C with site numbers 2180C -1 through 2180C-4, respectively.

UL LLC (RTP) is accredited by NVLAP, Laboratory Code 200246-0. The full scope of accreditation can be viewed at <u>http://www.nist.gov/nvlap/</u>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB) 36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

Page 6 of 26

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Disturbance 0.009 to 30 MHz	+/- 3.15
Radiated Disturbance, 30 to 1000 MHz	+/- 5.36
Radiated Emissions, 1-6 GHz	+/- 4.32

Uncertainty figures are valid to a confidence level of 95%.

Page 7 of 26

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a wireless alarm console that contains a 344.94 MHz radio, 802.11 b/g/n (HT20) radio and Z-Wave (908.4 MHz) radio. This report covers the 344.94 MHz radio.

5.2. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes two monopole antennas (for diversity), with each having a maximum gain of 2 dBi.

5.3. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was standard production panel firmware, rev. 2.0.

5.4. WORST-CASE CONFIGURATION AND MODE

The fundamental of the EUT was investigated in two orientations as follows: Table-top and Wall-mount. Additionally, both antennas associated with the device's 344.94MHz transmission were evaluated. For both antennas, the table-top orientation produced the highest emission and, therefore, was deemed the worst-case orientation. Hence, all final radiated testing was performed with the EUT in a table-top orientation.

5.5. MODIFICATIONS

No modifications by the test house were made during testing to achieve compliance.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List						
Description Manufacturer Model Serial Number FCC ID						
EUT AC adapter	Honeywell	300-05763V1	15060548099	N/A		

I/O CABLES

I/O Cable List							
Cable Port # of identical Connector Cable Type Cable		Cable	Remarks				
No		ports	Туре		Length (m)		
1	AC	1	2C AC	N/A	0	Wall-wart AC adapter's	
						AC input.	
2	DC (9V)	1	2C DC	Unshielded	2.4	Wall-wart AC adapter	
						DC output to EUT. Non-	
						detachable.	

TEST SETUP

The EUT was configured as a table-top device. Test software internal to the device exercised its radio card.

Page 9 of 26

SETUP DIAGRAM FOR TESTS



Page 10 of 26

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Equip. ID	Description	Manufacturer	Model Number	Last Cal.	Next Cal.
AT0059	Active Shielded Loop Antenna	EMCO	6502	2015-03-17	2016-03-31
AT0072	Double-Ridged Waveguide Horn Antenna, 1 to 18 GHz	ETS Lindgren	3117	2015-02-17	2016-02-29
AT0073	Hybrid Broadband Antenna, 30-1000MHz	Sunol Sciences Corp.	JB3	2015-06-10	2016-06-30
N-SAC01	Gain-loss string: 0.009- 30MHz	Various	Various	2015-10-07	2016-10-31
N-SAC02	Gain-loss string: 30- 1000MHz	Various	Various	2015-06-04	2016-06-30
N-SAC03	Gain-loss string: 1- 18GHz	Various	Various	2015-09-29	2016-09-30
PRE0101521 (75141)	EMI Test Receiver 9kHz- 7GHz	Rohde & Schwarz	ESCI 7	2015-08-26	2016-08-31
SA0026	Spectrum Analyzer	Agilent	N9030A	2015-03-27	2016-03-31
SOFTEMI	EMI Software	UL	Version 9.5	NA	NA
HI0079	Temp/Humid/Pressure Meter	Springfield Precision	PreciseTemp	2015-07-01	2016-07-31

Test Equipment Used - Radiated Disturbance Emissions Test Equipment (Morrisville - North Chamber)

Page 11 of 26

6.1. DUTY CYCLE

LIMITS

FCC §15.35 (c)

The measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer or radiated field strength. The RBW is set to 100 kHz and the VBW is set to 100 kHz. The sweep time is coupled and the span is set to 0 Hz. The number of pulses is measured and calculated in a 100 ms scan.

CALCULATION

Average Reading = Peak Reading (dBuV/m) + 20log (Duty Cycle), Where Duty Cycle is (# of long pulses * long pulse width) + (# of short pulses * short pulse width) / 100 or T

RESULTS

The manufacturer declared the worst-case duty cycle to be 10%, which translates into a duty cycle correction factor of -20.0dB.

Duty-cycle measurements of device and supporting information to be supplied in a separate document by Honeywell.

7. RADIATED EMISSION TEST RESULTS

7.1. TX RADIATED SPURIOUS EMISSION

LIMITS

FCC §15.231 (b)

IC A1.1.2

In addition to the provisions of § 15.205, the field strength of emissions from Intentional radiators operated under this section shall not exceed the following:

Fundamental	Field Strength of	Field Strength of
Frequency	Fundamental Frequency	Spurious Emissions
(MHz)	(microvolts/meter)	(microvolts/meter)
40.66 - 40.70	2,250	225
70 - 130	1,250	125
130 - 174	1,250 to 3,750	125 to 375
174 - 260	3,750	375
260 - 470	3,750 to 12,500	375 to 1,250
Above 470	12,500	1,250

1 Linear interpolation

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
MHz 0.090 - 0.110 ¹ 0.495 - 0.505 2.1735 - 2.1905 4.125 - 4.128 4.17725 - 4.17775 4.20725 - 4.20775 6.215 - 6.218 6.26775 - 6.26825 6.31175 - 6.31225 8.291 - 8.294 8.362 - 8.366 8.37625 - 8.38675 8.41425 - 8.41475 12.29 - 12.293	MHz 16.42 - 16.423 16.69475 - 16.69525 16.80425 - 16.80475 25.5 - 25.67 37.5 - 38.25 73 - 74.6 74.8 - 75.2 108 - 121.94 123 - 138 149.9 - 150.05 156.52475 - 156.52525 156.7 - 156.9 162.0125 - 167.17	MHz 399.9 - 410 608 - 614 960 - 1240 1300 - 1427 1435 - 1626.5 1645.5 - 1646.5 1660 - 1710 1718.8 - 1722.2 2200 - 2300 2310 - 2390 2483.5 - 2500 2655 - 2900 3260 - 3267 3332 - 3339	GHz 4.5 - 5.15 5.35 - 5.46 7.25 - 7.75 8.025 - 8.5 9.0 - 9.2 9.3 - 9.5 10.6 - 12.7 13.25 - 13.4 14.47 - 14.5 15.35 - 16.2 17.7 - 21.4 22.01 - 23.12 23.6 - 24.0 31.2 - 31.8
12.51975 - 12.52025 12.57675 - 12.57725 13.36 - 13.41	167.72 - 173.2 240 - 285 322 - 335.4	3345.8 - 3358 3600 - 4400	36.43 - 36.5 (²)

Page 13 of 26

FORM NO: 03-EM-F00858

12 Laboratory Dr., RTP, NC 27709

UL LLC

TEL: (919) 549-1400

This report shall not be reproduced except in full, without the written approval of UL LLC.

1 Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz. 2 Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 88	100 **	3
88 216	150 **	3
216 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 72 MHz, 76 88 MHz, 174 216 MHz or 470 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Note: This is a manufacturer's specification report. Verification of restrictions noted in 15.231 (a)(3) and RSS-210 Annex A1.1.1 were not performed. Duty cycle measurements were also not performed.

Page 14 of 26

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz measurements and 1.5 m above the ground plane for above 1GHz measurements. The antenna to EUT distance is 3 meters.

For measurements below 1 GHz the resolution bandwidth is set to 120 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For peak measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz. For average measurements, the resolution and video bandwidths are set as described in ANSI 63.10:2013 for the applicable average measurement.

The spectrum from 9 kHz to 4 GHz is investigated with the transmitter on.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Page 15 of 26

RESULTS

FUNDAMENTAL

ANTENNA 1; HORIZONTAL



Marker	Frequency	Meter	Det	AT0073	Amp/Cbl	DCCF	Corrected	QPk/Pk	QP/Pk	Avg Limit	Margin	Azimuth	Height	Polarity
	(MHz)	Reading		AF	(dB)	(dB)	Reading	Limit	Margin	(dBuV/m)	(dB)	(Degs)	(cm)	
		(dBuV)		(dB/m)			(dBuV/m)	(dBuV/m)	(dB)					
1	344.9472	105.39	Pk	19.1	-29.3	0	95.19	97.25	-2.06	-	-	199	102	н
	344.9472	105.39	Pk	19.1	-29.3	-20	75.19	-	-	77.25	-2.06	199	102	Н
2	* 334.1637	53.96	Qp	18.7	-29.3	0	43.36	46	-2.64	-	-	199	102	Н
3	355.7225	53.27	Pk	19.5	-29.2	0	43.57	77.25	-33.68	-	-	199	102	н
	355.7225	53.27	Pk	19.5	-29.2	-20	23.57	-	-	57.25	-33.68	199	102	н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Qp - Quasi-Peak detector

Page 16 of 26

ANTENNA 1; VERTICAL



Marker	Frequency	Meter	Det	AT0073	Amp/Cbl	DCCF	Corrected	QPk/Pk	QP/Pk	Avg Limit	Margin	Azimuth	Height	Polarity
	(MHz)	Reading		AF	(dB)	(dB)	Reading	Limit	Margin	(dBuV/m)	(dB)	(Degs)	(cm)	
		(dBuV)		(dB/m)			(dBuV/m)	(dBuV/m)	(dB)					
1	344.9452	94.7	Pk	19.1	-29.3	0	84.5	97.25	-12.8	-	-	292	302	V
	344.9452	94.7	Pk	19.1	-29.3	-20	64.5	-	-	77.25	-12.75	292	302	V
2	* 334.15	44.67	Pk	18.7	-29.3	0	34.07	46	-11.93	-	-	292	302	V
3	355.7	44.18	Pk	19.5	-29.2	0	34.48	77.25	-42.77	-	-	292	302	V
	355.7	44.18	Pk	19.5	-29.2	-20	14.48	-	-	57.25	-42.77	292	302	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Page 17 of 26

ANTENNA 2; HORIZONTAL



FCC 15-231 Fundamental - H.TST

Rev 9.5 28 Aug 2015

Marker	Frequency	Meter	Det	AT0073	Amp/Cbl	DCCF	Corrected	QPk/Pk	QP/Pk	Avg Limit	Margin	Azimuth	Height	Polarity
	(MHz)	Reading		AF	(dB)	(dB)	Reading	Limit	Margin	(dBuV/m)	(dB)	(Degs)	(cm)	
		(dBuV)		(dB/m)			(dBuV/m)	(dBuV/m)	(dB)					
1	344.95	102.13	Pk	19.1	-29.3	0	91.93	97.25	-5.32	-	-	82	102	Н
	344.95	102.13	Pk	19.1	-29.3	-20	71.93	-	-	77.25	-5.32	82	102	н
2	* 334.1634	49.83	Qp	18.7	-29.3	0	39.23	46	-6.77	-	-	82	102	Н
3	355.7224	51.36	Pk	19.5	-29.2	0	41.66	77.25	-35.59	-	-	82	102	н
	355.7224	51.36	Pk	19.5	-29.2	-20	21.66	-	-	57.25	-35.59	82	102	Н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Qp - Quasi-Peak detector

Page 18 of 26

ANTENNA 2; VERTICAL



FCC 15-231 Fundamental - U.TST

Rev 9.5 28 Aug 2015

Marker	Frequency	Meter	Det	AT0073	Amp/Cbl	DCCF	Corrected	QPk/Pk	QP/Pk	Avg Limit	Margin	Azimuth	Height	Polarity
	(MHz)	Reading		AF	(dB)	(dB)	Reading	Limit	Margin	(dBuV/m)	(dB)	(Degs)	(cm)	
		(dBuV)		(dB/m)			(dBuV/m)	(dBuV/m)	(dB)					
1	344.9427	91.51	Pk	19.1	-29.3	0	81.31	97.25	-15.94	-	-	358	118	V
	344.9427	91.51	Pk	19.1	-29.3	-20	61.31	-	-	77.25	-15.94	358	118	V
2	* 334.15	41.76	Pk	18.7	-29.3	0	31.16	46	-14.84	-	-	358	118	V
3	355.7	42.03	Pk	19.5	-29.2	0	32.33	77.25	-44.92	-	-	358	118	V
	355.7	42.03	Pk	19.5	-29.2	-20	12.33	-	-	57.25	-44.92	358	118	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Page 19 of 26

TX SPURIOUS EMISSIONS (0.009-30MHz)

Note: All measurements were made at a test distance of 3 m. The limits in the plots and tabular data are the FCC/IC limits extrapolated from the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz – 30 MHz) to the measurement distance to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were 40*Log (specification distance / test distance) per FCC 15.31 (f) (2).

Page 20 of 26



Page 21 of 26

HARMONICS AND TX SPURIOUS EMISSION (30 - 1000 MHz)

ANTENNA 1



Marker	Frequency	Meter	Det	AT0073	Amp/Cbl	DCCF	Corrected	QP/Pk	QP/Pk	Avg Limit	Margin	Azimuth	Height	Polarity
	(MHz)	Reading		AF	(dB)	(dB)	Reading	Limit	Margin	(dBuV/m)	(dB)	(Degs)	(cm)	
		(dBuV)		(dB/m)			(dBuV/m)	(dBuV/m)	(dB)					
1	* 109.9425	37.01	Pk	16.9	-30.7	0	23.21	43.52	-20.31	-	-	0-360	300	Н
4	34.8025	38.32	Pk	22.4	-31.6	0	29.12	40	-10.88	-	-	0-360	102	V
5	52.766	51.43	Qp	12	-31.4	0	32.03	40	-7.97	-	-	291	102	V
2	143.645	38.84	Pk	17.2	-30.5	0	25.54	43.52	-17.98	-	-	0-360	199	Н
3	689.8851	58.82	Pk	24.7	-28.1	0	55.42	77.25	-21.83	-	-	202	102	Н
	689.8851	58.82	Pk	24.7	-28.1	-20	35.42	-	-	57.25	-21.83	202	102	Н
6	689.8851	42	Pk	24.7	-28.1	0	38.6	77.25	-38.65	-	-	10	121	V
	689.8851	42	Pk	24.7	-28.1	-20	18.6	-	-	57.25	-38.65	10	121	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Qp - Quasi-Peak detector

Page 22 of 26

REPORT NO: R11070857-E1 FCC ID: CFS8DLTSSCBASE1

ANTENNA 2



Marker	Frequency	Meter	Det	AT0073	Amp/Cbl	DCCF	Corrected	QP/Pk	QP/Pk	Avg Limit	Margin	Azimuth	Height	Polarity
	(MHz)	Reading		AF	(dB)	(dB)	Reading	Limit	Margin	(dBuV/m)	(dB)	(Degs)	(cm)	
		(dBuV)		(dB/m)			(dBuV/m)	(dBuV/m)	(dB)					
1	* 110.155	37.15	Pk	16.9	-30.7	0	23.35	43.52	-20.17	-	-	0-360	300	н
4	33.145	37.05	Pk	23.7	-31.7	0	29.05	40	-10.95	-	-	0-360	102	V
5	52.77	51.52	Qp	12	-31.4	0	32.12	40	-7.88	-	-	287	100	V
2	143.22	39.37	Pk	17.3	-30.4	0	26.27	43.52	-17.25	-	-	0-360	199	н
3	689.885	66.87	Pk	24.7	-28.1	0	63.47	77.25	-13.78	-	-	27	118	Н
	689.885	66.87	Pk	24.7	-28.1	-20	43.47	-	-	57.25	-13.78	27	118	Н
6	689.885	54.32	Pk	24.7	-28.1	0	50.92	77.25	-26.33	-	-	97	126	V
	689.885	54.32	Pk	24.7	-28.1	-20	30.92	-	-	57.25	-26.33	97	126	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Qp - Quasi-Peak detector

Page 23 of 26

HARMONICS AND TX SPURIOUS EMISSIONS ABOVE 1GHz

ANTENNA 1



Marker	Frequency	Meter	Det	AF AT0072	Amp/Cbl	DCCF	Corrected	Avg Limit	Margin	Peak Limit	Margin	Azimuth	Height	Polarity
	(GHz)	Reading		(dB/m)	(dB)	(dB)	Reading	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(Degs)	(cm)	
		(dBuV)					(dBuV/m)							
1	* 1.035	53.54	Pk	28	-37.8	0	43.74	-	-	74	-30.26	252	143	н
	* 1.035	53.54	Pk	28	-37.8	-20	23.74	54	-30.26	-	-	252	143	н
4	* 3.88	43.92	Pk	33.6	-33.7	0	43.82	54	-10.18	74	-30.18	0-360	101	н
5	* 1.035	51.65	Pk	28	-37.8	0	41.85	-	-	74	-32.15	206	344	V
	* 1.035	51.65	Pk	28	-37.8	-20	21.85	54	-32.15	-	-	206	344	V
6	1.717	43.3	Pk	29.3	-36.4	0	36.2	54	-17.8	74	-37.8	0-360	199	V
2	* 2.5	48.43	Pk	32.1	-35.2	0	45.33	-	-	74	-28.67	115	107	н
	* 2.5	42.87	Av	32.1	-35.2	0	39.77	54	-14.23	-	-	115	107	н
7	* 2.5	42.73	Pk	32.1	-35.2	0	39.63	54	-14.37	74	-34.37	0-360	199	V
3	2.566	42.94	Pk	32.2	-35	0	40.14	54	-13.86	74	-33.86	0-360	199	Н

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Av - Average detection

Page 24 of 26

REPORT NO: R11070857-E1 FCC ID: CFS8DLTSSCBASE1

ANTENNA 2



Marker	Frequency	Meter	Det	AF AT0072	Amp/Cbl	DCCF	Corrected	Avg Limit	Margin	Peak Limit	Margin	Azimuth	Height	Polarity
	(GHz)	Reading		(dB/m)	(dB)	(dB)	Reading	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(Degs)	(cm)	
		(dBuV)					(dBuV/m)							
1	* 1.035	47.81	Pk	28	-37.8	0	38.01	-	-	74	-35.99	350	188	Н
	* 1.035	47.81	Pk	28	-37.8	-20	18.01	54	-35.99	-	-	350	188	н
2	* 1.14	44.75	Pk	28.5	-37.5	0	35.75	54	-18.25	74	-38.25	0-360	200	Н
4	* 3.885	44.39	Pk	33.6	-33.8	0	44.19	54	-9.81	74	-29.81	0-360	101	Н
5	* 1.121	43.76	Pk	28.4	-37.6	0	34.56	54	-19.44	74	-39.44	0-360	200	V
3	* 2.5	48.2	Pk	32.1	-35.2	0	45.1	-	-	74	-28.9	112	107	Н
	* 2.5	42.86	Av	32.1	-35.2	0	39.76	54	-14.24	-	-	112	107	Н
6	* 2.5	41.68	Pk	32.1	-35.2	0	38.58	54	-15.42	74	-35.42	0-360	200	V
7	2.655	42.75	Pk	32.3	-34.8	0	40.25	54	-13.75	74	-33.75	0-360	101	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

Av - Average detection

Page 25 of 26

END OF REPORT

Page 26 of 26