

FCC AND IC CERTIFICATION TEST REPORT

FOR

Applicant	: ION Audio, LLC
Address	: 200 Scenic View Drive, Cumberland, RI 02864 U.S.A.
Equipment under Test	: Speaker
Model No.	: JOB ROCKER MAX; OFFROAD
Trade Mark	: ION
FCC ID	: 2AB3E-IPA81
IC	: 10541A-IPA81
Manufacturer	: ION Audio, LLC
Address	: 200 Scenic View Drive, Cumberland, RI 02864 U.S.A.
Project Code	: iPA81; iPA67

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808

Tel: +86-0769-89201699 [Http://www.dgddt.com](http://www.dgddt.com)

REPORT

TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results	5
2.	General test information	6
2.1.	Description of EUT	6
2.2.	Accessories of EUT.....	6
2.3.	Assistant equipment used for test.....	6
2.4.	Block diagram of EUT configuration for test.....	7
2.5.	Deviations of test standard	7
2.6.	Test environment conditions	7
2.7.	Test laboratory.....	7
2.8.	Measurement uncertainty	8
3.	Equipment used during test	9
4.	Maximum Peak Output Power	10
4.1.	Block diagram of test setup	10
4.2.	Limits.....	10
4.3.	Test Procedure.....	10
4.4.	Test Result.....	10
5.	20dB Bandwidth and 99% Bandwidth	11
5.1.	Block diagram of test setup	11
5.2.	Limits.....	11
5.3.	Test Procedure.....	11
5.4.	Test Result.....	11
5.5.	Original test data	12
6.	Carrier Frequency Separation.....	13
6.1.	Block diagram of test setup	13
6.2.	Limits.....	13
6.3.	Test Procedure.....	13
6.4.	Test Result.....	13
6.5.	Original test data	13
7.	Number Of Hopping Channel	14
7.1.	Block diagram of test setup	14
7.2.	Limits.....	14
7.3.	Test Procedure.....	14
7.4.	Test Result.....	14
7.5.	Original test data	14

8.	Dwell Time.....	15
8.1.	Block diagram of test setup	15
8.2.	Limits.....	15
8.3.	Test Procedure.....	15
8.4.	Test Result.....	15
8.5.	Original test data	16
9.	Radiated emission.....	17
9.1.	Block diagram of test setup	17
9.2.	Limit	18
9.3.	Test Procedure.....	19
9.4.	Test result	20
10.	Band Edge Compliance (radiated method).....	26
10.1.	Block diagram of test setup	26
10.2.	Limit	26
10.3.	Test Procedure.....	26
10.4.	Test result	26
11.	Band Edge Compliance (conducted method)	35
11.1.	Block diagram of test setup	35
11.2.	Limit	35
11.3.	Test result	35
11.4.	Original test data	35
12.	Power Line Conducted Emission	38
12.1.	Block diagram of test setup	38
12.2.	Power Line Conducted Emission Limits(Class B)	38
12.3.	Test Procedure.....	39
12.4.	Test Result.....	39
13.	Antenna Requirements	44
13.1.	Limit	44
13.2.	Result.....	44

TEST REPORT DECLARE

Applicant	:	ION Audio, LLC
Address	:	200 Scenic View Drive, Cumberland, RI 02864 U.S.A.
Equipment under Test	:	Speaker
Model No.	:	JOB ROCKER MAX; OFFROAD
Trade Mark	:	ION
FCC ID	:	2AB3E-IPA81
IC	:	10541A-IPA81
Manufacturer	:	ION Audio, LLC
Address	:	200 Scenic View Drive, Cumberland, RI 02864 U.S.A.

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 1 May 2015.

Test procedure used:

ANSI C63.10:2013, ANSI C63.4:2014, RSS-Gen Issue 4, Nov. 2014.

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&IC standards.

Report No.:	DDT-R16Q1216-6E2		
Date of Test:	Dec. 16, 2016 ~ Jan. 14, 2017	Date of Report:	Jan. 16, 2017

Prepared By:


Damon Hu/Engineer

Approved by:


Kevin Peng/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

1. Summary of test results

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10 :2013 ANSI C63.4:2014 RSS-247 Issue 1 5.4.2	PASS
20dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013 ANSI C63.4:2014 RSS-247 Issue 1 5.1	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2013 ANSI C63.4:2014 RSS-247 Issue 1 5.1	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013 ANSI C63.4:2014 RSS-247 Issue 1 5.1	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2013 ANSI C63.4:2014 RSS-247 Issue 1 5.1	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2013 ANSI C63.4:2014 RSS-247 Issue 1 5.5 RSS-Gen Issue 4 8.9 8.10	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10 :2013 ANSI C63.4:2014 RSS-247 Issue 1 5.5 RSS-Gen Issue 4 8.9 8.10	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013 ANSI C63.4:2014 RSS-Gen Issue 4 8.8	PASS
Antenna requirement	FCC Part 15: 15.203 ANSI C63.4:2014 RSS-Gen Issue 4 8.3	PASS

2. General test information

2.1. Description of EUT

EUT* Name	: Speaker
Model Number	: JOB ROCKER MAX; OFFROAD
Difference of models	: All models are identical, except the model OFFROAD doesn't have the DC charge board and the appearances are different.
EUT function description	: Please reference user manual of this device
Power supply	: AC 100-240V, 50/60Hz or DC 12V from the DC charger or DC 12V from built-in battery
Radio Specification	: Bluetooth V4.1 without BLE mode
Operation frequency	: 2402MHz -2480MHz
Modulation	: GFSK, $\pi/4$ QPSK, 8-DPSK
Data rate	: 1Mbps, 2Mbps, 3Mbps
Antenna Type	: Built-in undetachable dipole antenna, maximum PK gain:2.0dBi
Date of Receipt	: Dec. 16, 2016
Sample Type	: Series production

Note 1: EUT is the ab. of equipment under test.

Note 2: EUT can powered from AC 120V/60Hz and built-in battery, according exploration test, when powered from AC 120V/60Hz will have worse EMC performance, so all the final tests were performed with AC 120V/60Hz.

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Parameter	Remark
Built-in AC Adapter	Shenzhen Green Power Electronic Technology Co., Ltd.	JFY40A-160250	Input:100-240Vac 50/60Hz, output: DC 16V, 2.5A	Alternative
Built-in AC Adapter	Dongguan Guanjin Electronics Technology Co., Ltd.	K40P160250	Input:100-240Vac 50/60Hz, output: DC 16V, 2.5A	
Built-in Battery	SHENZHEN LEOCH BATTERIES TECHNOLOGY CO., LTD	DJW 12-5.0	12V5.0Ah/20hr	Alternative
Built-in Battery	SHENZHEN RITAR POWER CO., LTD	RT1250	12V5.0Ah	

2.3. Assistant equipment used for test

Description of Assistant equipment	Manufacturer	Model number	EMC Compliance	Other
/	/	/	/	/

2.4. Block diagram of EUT configuration for test



The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode as blow table.

Test software: Airoha AB1500 Family LAB Test Tool, Version 1.3.0.0.

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
$\pi/4$ QPSK Hopping on TX mode	CH0 to CH78	2402 to 2480
8-DPSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
GFSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
$\pi/4$ QPSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
8-DPSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480

Note: For $\pi/4$ QPSK its same modulation type with 8-DPSK, and based exploratory test, there is no significant difference of that two types test result, so except output power, all other items final test were only performed with the worse case 8-DPSK and GFSK.

2.5. Deviations of test standard

No Deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808 Tel: +86-0769-89201699 <http://www.dgddt.com>

FCC Registration Number: 270092; Industry Canada site registration number: 10288A-1

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power(Conducted)(Spectrum analyzer)	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.38dB(3.6GHz ≤ f < 8GHz)
Peak Output Power(Conducted)(Power Sensor)	0.74dB
Dwell Time	0.6%
Conducted spurious emissions	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.40dB(3.6GHz ≤ f < 8GHz)
	1.66dB(8GHz ≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20KHz)	3×10-8
Temperature	0.4℃
Humidity	2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-18GHz)	4.10dB(1-6GHz)
	4.40dB (6GHz-18Gz)
Uncertainty for Power line conduction emission test	3.32dB (150KHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test					
Spectrum analyzer	R&S	FSU26	1166.1660.26	Oct. 16, 2016	1 Year
Vector Signal Generator	Agilent	E8267D	MY52098743	Oct. 20, 2016	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jul. 05, 2016	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Apr. 18, 2016	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Apr. 19, 2016	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Oct. 24, 2016	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2016	1 Year
RF Cable	Micable	C10-01-01-1	100309	Aug. 18, 2016	1 Year
Test Software	JS Tonscend	JS1120-2	Ver.2.5	N/A	N/A
USB Data acquisition	Agilent	U2531A	TW55043503	N/A	N/A
Auto control Unit	JS Tonscend	JS0806-2	158060010	N/A	N/A
Radiated Emission Test					
EMI Test Receiver	R&S	ESU8	100316	Oct. 16, 2016	1 Year
Spectrum analyzer	R&S	FSU26	1166.1660.26	Oct. 16, 2016	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Oct. 27, 2016	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 16, 2016	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Oct. 12, 2016	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Oct. 16, 2016	1 Year
RF Cable	HUBSER	CP-X2	W11.03	Oct. 16, 2016	1 Year
RF Cable	HUBSER	CP-X1	W12.02	Oct. 16, 2016	1 Year
MI Cable	HUBSER	C10-01-01-1M	1091629	Oct. 16, 2016	1 Year
Test software	Audix	E3	V 6.11111b	/	/
Power Line Conducted Emissions Test					
Test Receiver	R&S	ESU8	100316	Oct. 16, 2016	1 Year
LISN 1	R&S	ENV216	101109	Oct. 16, 2016	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 16, 2016	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 16, 2016	1 Year
CE Cable 1	HUBSER	ESU8/RF2	W10.01	Oct. 16, 2016	1 Year
Test software	Audix	E3	V 6.11111b	/	/

4. Maximum Peak Output Power

4.1. Block diagram of test setup



4.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

4.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Measure the maximum output power of EUT by spectrum analyzer with PK detector and RBW=2MHz(above 20dB bandwidth of measured signal), VBW=3MHz

Note: The attenuator loss was inputted into spectrum analyzer as amplitude offset.

4.4. Test Result

Mode	Freq (MHz)	Result (dBm)	Limit (dBm)	Conclusion
GFSK	2402	3.290	21	PASS
	2441	2.790	21	PASS
	2480	2.800	21	PASS
$\pi/4$ QPSK	2402	3.380	21	PASS
	2441	2.880	21	PASS
	2480	3.120	21	PASS
8-DPSK	2402	3.570	21	PASS
	2441	3.090	21	PASS
	2480	3.210	21	PASS
Test Date : Jan. 03, 2017			Test Engineer : Damon Hu	

5. 20dB Bandwidth and 99% Bandwidth

5.1. Block diagram of test setup

Same as section 4.1

5.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

5.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 kHz RBW and 100 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

5.4. Test Result

Mode	Freq (MHz)	20dB bandwidth Result (MHz)	99% bandwidth Result (MHz)	Limit (MHz)	Margin (MHz)	Conclusion
GFSK	2402	1.130	0.996	/	/	PASS
	2441	1.126	1.008	/	/	PASS
	2480	1.126	1.000	/	/	PASS
8-DPSK	2402	1.388	1.252	/	/	PASS
	2441	1.390	1.252	/	/	PASS
	2480	1.390	1.248	/	/	PASS
Test Date : Jan. 03, 2017				Test Engineer: Damon Hu		

GFSK Mode 2402MHz

Ref 20 dBm -Att 20 dB
-RBW 100 kHz -Masker 4 [T1]
-VBW 300 kHz -14.85 dBm
SWT 3 ms 2.40254000 GHz

20 Offset 9.6 dB
1 9.6 dB
2 1.18 dB
3 1.18 dB
4 1.18 dB
5 1.18 dB
6 1.18 dB
7 1.18 dB
8 1.18 dB
9 1.18 dB
10 1.18 dB
11 1.18 dB
12 1.18 dB
13 1.18 dB
14 1.18 dB
15 1.18 dB
16 1.18 dB
17 1.18 dB
18 1.18 dB
19 1.18 dB
20 1.18 dB

Center 2.402 GHz 200 kHz/ Span 2 MHz

Date: 3.JAN.2017 09:04:56

GFSK Mode 2480MHz

Ref 20 dBm -Att 20 dB
-RBW 100 kHz -Masker 4 [T1]
-VBW 300 kHz -15.19 dBm
SWT 3 ms 2.480334000 GHz

20 Offset 9.6 dB
1 9.6 dB
2 1.18 dB
3 1.18 dB
4 1.18 dB
5 1.18 dB
6 1.18 dB
7 1.18 dB
8 1.18 dB
9 1.18 dB
10 1.18 dB
11 1.18 dB
12 1.18 dB
13 1.18 dB
14 1.18 dB
15 1.18 dB
16 1.18 dB
17 1.18 dB
18 1.18 dB
19 1.18 dB
20 1.18 dB

Center 2.48 GHz 200 kHz/ Span 2 MHz

Date: 3.JAN.2017 09:07:52

8-DPSK Mode 2402MHz

Ref 20 dBm -Att 20 dB
-RBW 100 kHz -Masker 4 [T1]
-VBW 300 kHz -19.06 dBm
SWT 3 ms 2.402710000 GHz

20 Offset 9.6 dB
1 9.6 dB
2 1.18 dB
3 1.18 dB
4 1.18 dB
5 1.18 dB
6 1.18 dB
7 1.18 dB
8 1.18 dB
9 1.18 dB
10 1.18 dB
11 1.18 dB
12 1.18 dB
13 1.18 dB
14 1.18 dB
15 1.18 dB
16 1.18 dB
17 1.18 dB
18 1.18 dB
19 1.18 dB
20 1.18 dB

Center 2.402 GHz 200 kHz/ Span 2 MHz

Date: 3.JAN.2017 09:10:36

8-DPSK Mode 2441MHz

Ref 20 dBm -Att 20 dB
-RBW 100 kHz -Masker 4 [T1]
-VBW 300 kHz -19.49 dBm
SWT 3 ms 2.441704000 GHz

20 Offset 9.6 dB
1 9.6 dB
2 1.18 dB
3 1.18 dB
4 1.18 dB
5 1.18 dB
6 1.18 dB
7 1.18 dB
8 1.18 dB
9 1.18 dB
10 1.18 dB
11 1.18 dB
12 1.18 dB
13 1.18 dB
14 1.18 dB
15 1.18 dB
16 1.18 dB
17 1.18 dB
18 1.18 dB
19 1.18 dB
20 1.18 dB

Center 2.441 GHz 200 kHz/ Span 2 MHz

Date: 3.JAN.2017 09:11:45

8-DPSK Mode 2480MHz

Ref 20 dBm -Att 20 dB
-RBW 100 kHz -Masker 4 [T1]
-VBW 300 kHz -19.49 dBm
SWT 3 ms 2.480702000 GHz

20 Offset 9.6 dB
1 9.6 dB
2 1.18 dB
3 1.18 dB
4 1.18 dB
5 1.18 dB
6 1.18 dB
7 1.18 dB
8 1.18 dB
9 1.18 dB
10 1.18 dB
11 1.18 dB
12 1.18 dB
13 1.18 dB
14 1.18 dB
15 1.18 dB
16 1.18 dB
17 1.18 dB
18 1.18 dB
19 1.18 dB
20 1.18 dB

Center 2.48 GHz 200 kHz/ Span 2 MHz

Date: 3.JAN.2017 09:14:16

6. Carrier Frequency Separation

6.1. Block diagram of test setup

Same as section 4.1

6.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


6.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The carrier frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW.

6.4. Test Result

Mode	Channel separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz) 2/3 of 20dB bandwidth	Conclusion
GFSK	0.998	1.13	0.753	PASS
8-DPSK	1.000	1.39	0.927	PASS
Test Date : Jan. 03, 2017			Test Engineer: Damon Hu	

6.5. Original test data



8. Dwell Time

8.1. Block diagram of test setup

Same as section 4.1

8.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

8.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula Dwell time = total hops *pulse's on time.

DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot RX, 1 time slot TX). So, total hops is $10.12 \times 31.6 = 320$.

DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots RX, 1 time slot TX). So, total hops is $5.06 \times 31.6 = 160$.

DH5 Packet permit maximum $1600 / 79 / 6 = 3.376$ hops per second in each channel (5 time slots RX, 1 time slot TX). So, total hops is $3.376 \times 31.6 = 106.7$.

3DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot RX, 1 time slot TX). So, total hops is $10.12 \times 31.6 = 320$.

3DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots RX, 1 time slot TX). So, total hops is $5.06 \times 31.6 = 160$.

3DH5 Packet permit maximum $1600 / 79 / 6 = 3.376$ hops per second in each channel (5 time slots RX, 1 time slot TX). So, total hops is $3.376 \times 31.6 = 106.7$.

8.4. Test Result


Mode	Dwell time (s)	Pulse's on time (ms)	Total hops	Limit	Conclusion
DH1	0.128	0.4	320	<400ms	PASS
DH3	0.166	1.04	160	<400ms	PASS
DH5	0.244	2.29	106.7	<400ms	PASS
3-DH1	0.131	0.41	320	<400ms	PASS
3-DH3	0.166	1.04	160	<400ms	PASS
3-DH5	0.245	2.3	106.7	<400ms	PASS

Test Date : Jan. 03, 2017

Test Engineer: Damon Hu

Note: Dwell time = total hops *pulse's on time.


8.5. Original test data




9. Radiated emission

9.1. Block diagram of test setup

In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

9.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.3. Test Procedure

(1) EUT was placed on a non-metallic table, 150 cm above the ground plane inside a semi-anechoic chamber.

(2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used
9KHz-30MHz	Active Loop antenna
30MHz-1GHz	Trilog Broadband Antenna
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)
18GHz-40GHz	Horn Antenna(18GHz-40GHz)

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

- (c) Change modulation type of device if practicable.
- (d) Change power supply range from 85% to 115% of the rated supply voltage
- (e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9KHz to 18GHz.

- (4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.
- (5) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz, 110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.
- (6) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

- (7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RMS detector RBW 1MHz VBW 3MHz for Average measure(according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).
- (8) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

9.4. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9 KHz to 25GHz were comply with 15.209 limits.

Note1: According exploratory test no any obvious emission were detected from 9KHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in GFSK, Tx 2441MHz mode.

Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply


with AV limit.

Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q1216-4\RE.EM6
Test Date	: 2016-11-10	Tested By : Jerry
EUT	: Speaker	Model Number : JOB ROCKER MAX
Power Supply	: AC 120V/60Hz	Test Mode : TX mode
Condition	: Temp:24.5°C,Humi:55%, Press:100.1kPa	Antenna/Distance : 2016 VULB9163 1#/3m/HORIZONTAL
Memo	: Built-in AC adapter: JFY40A-160250	

Data: 70



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	72.14	13.85	7.06	4.08	24.99	40.00	-15.01	QP	HORIZONTAL
2	93.49	4.97	11.33	4.24	20.54	43.50	-22.96	QP	HORIZONTAL
3	155.91	13.69	7.86	4.64	26.19	43.50	-17.31	QP	HORIZONTAL
4	269.45	10.45	12.87	5.23	28.55	46.00	-17.45	QP	HORIZONTAL
5	289.20	14.46	13.40	5.33	33.19	46.00	-12.81	QP	HORIZONTAL
6	357.98	10.86	14.94	5.62	31.42	46.00	-14.58	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.


2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q1216-4\RE.EM6
Test Date	: 2016-11-10	Tested By : Jerry
EUT	: Speaker	Model Number : JOB ROCKER MAX
Power Supply	: AC 120V/60Hz	Test Mode : TX mode
Condition	: Temp:24.5°C,Humi:55%, Press:100.1kPa	Antenna/Distance : 2016 VULB9163 1#/3m/VERTICAL
Memo	: Built-in AC adapter: JFY40A-160250	

Data: 71



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	32.66	12.41	11.47	3.71	27.59	40.00	-12.41	QP	VERTICAL
2	44.45	9.75	12.35	3.83	25.93	40.00	-14.07	QP	VERTICAL
3	66.01	11.77	9.08	4.03	24.88	40.00	-15.12	QP	VERTICAL
4	72.03	17.95	7.09	4.08	29.12	40.00	-10.88	QP	VERTICAL
5	289.01	10.65	13.38	5.33	29.36	46.00	-16.64	QP	VERTICAL
6	351.75	10.46	14.75	5.60	30.81	46.00	-15.19	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.


2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q1216-4\RE.EM6
Test Date	: 2016-11-10	Tested By : Jerry
EUT	: Speaker	Model Number : JOB ROCKER MAX
Power Supply	: AC 120V/60Hz	Test Mode : TX mode
Condition	: Temp:24.5°C,Humi:55%, Press:100.1kPa	Antenna/Distance : 2016 VULB9163 1#/3m/HORIZONTAL
Memo	: Built-in AC adapter: K40P160250	

Data: 84



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	57.39	6.68	11.67	3.95	22.30	40.00	-17.70	QP	HORIZONTAL
2	72.08	13.78	7.07	4.08	24.93	40.00	-15.07	QP	HORIZONTAL
3	108.27	9.77	11.20	4.35	25.32	43.50	-18.18	QP	HORIZONTAL
4	167.82	15.04	8.31	4.71	28.06	43.50	-15.44	QP	HORIZONTAL
5	289.00	14.01	13.38	5.33	32.72	46.00	-13.28	QP	HORIZONTAL
6	357.93	9.83	14.94	5.62	30.39	46.00	-15.61	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.


2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\16Q1216-4\RE.EM6**
Test Date : 2016-11-10 **Tested By** : Jerry
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : AC 120V/60Hz **Test Mode** : TX mode
Condition : Temp:24.5°C,Humi:55%,
Press:100.1kPa **Antenna/Distance** : 2016 VULB9163 1#/3m/VERTICAL
Memo : Built-in AC adapter: K40P160250

Data: 85



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	52.21	15.56	11.70	3.91	31.17	40.00	-8.83	QP	VERTICAL
2	72.08	15.97	7.07	4.08	27.12	40.00	-12.88	QP	VERTICAL
3	108.27	9.21	11.20	4.35	24.76	43.50	-18.74	QP	VERTICAL
4	210.79	9.93	10.83	4.95	25.71	43.50	-17.79	QP	VERTICAL
5	289.00	13.64	13.38	5.33	32.35	46.00	-13.65	QP	VERTICAL
6	339.59	12.33	14.67	5.55	32.55	46.00	-13.45	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)


Freq. (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector type	Polarization
GFSK Tx mode 2402MHz									
2862.00	35.46	31.31	30.14	6.61	43.24	74.00	-30.76	Peak	VERTICAL
4010.00	33.87	33.41	29.04	7.61	45.85	74.00	-28.15	Peak	VERTICAL
4804.00	37.81	33.74	29.32	8.48	50.71	54.00	-3.29	Average	VERTICAL
4804.00	42.86	33.74	29.32	8.48	55.76	74.00	-18.24	Peak	VERTICAL
6054.00	32.28	35.09	29.23	9.71	47.85	74.00	-26.15	Peak	VERTICAL
7104.00	33.15	36.29	30.43	10.53	49.54	74.00	-24.46	Peak	VERTICAL
1868.00	36.82	27.51	29.01	5.34	40.66	74.00	-33.34	Peak	HORIZONTAL
3107.00	35.83	31.75	30.13	6.88	44.33	74.00	-29.67	Peak	HORIZONTAL
4804.00	37.67	33.74	29.32	8.48	50.57	54.00	-3.43	Average	HORIZONTAL
4804.00	42.34	33.74	29.32	8.48	55.24	74.00	-18.76	Peak	HORIZONTAL
6040.00	33.33	35.07	29.22	9.70	48.88	74.00	-25.12	Peak	HORIZONTAL
7468.00	32.43	36.58	30.75	10.83	49.09	74.00	-24.91	Peak	HORIZONTAL
GFSK Tx mode 2441MHz									
2897.00	35.25	31.41	30.15	6.66	43.17	74.00	-30.83	Peak	HORIZONTAL
3947.00	34.89	33.25	29.07	7.58	46.65	74.00	-27.35	Peak	HORIZONTAL
4882.00	37.27	33.72	29.33	8.56	50.22	74.00	-23.78	Peak	HORIZONTAL
6194.00	33.57	35.32	29.36	9.78	49.31	74.00	-24.69	Peak	HORIZONTAL
7328.00	32.84	36.47	30.59	10.71	49.43	74.00	-24.57	Peak	HORIZONTAL
3058.00	35.10	31.72	30.16	6.85	43.51	74.00	-30.49	Peak	VERTICAL
3772.00	34.57	32.74	29.18	7.47	45.60	74.00	-28.40	Peak	VERTICAL
4882.00	36.78	33.72	29.33	8.56	49.73	54.00	-4.27	Average	VERTICAL
4882.00	42.32	33.72	29.33	8.56	55.27	74.00	-18.73	Peak	VERTICAL
6033.00	32.50	35.05	29.22	9.70	48.03	74.00	-25.97	Peak	VERTICAL
7328.00	34.64	36.47	30.59	10.71	51.23	74.00	-22.77	Peak	VERTICAL
GFSK Tx mode 2480MHz									
2995.00	35.02	31.69	30.20	6.77	43.28	74.00	-30.72	Peak	HORIZONTAL
3947.00	34.59	33.25	29.07	7.58	46.35	74.00	-27.65	Peak	HORIZONTAL
4960.00	39.64	33.71	29.34	8.63	52.64	74.00	-21.36	Peak	HORIZONTAL
6054.00	33.00	35.09	29.23	9.71	48.57	74.00	-25.43	Peak	HORIZONTAL
7447.00	33.92	36.56	30.73	10.81	50.56	74.00	-23.44	Peak	HORIZONTAL
2988.00	34.91	31.67	30.20	6.77	43.15	74.00	-30.85	Peak	VERTICAL
3947.00	34.04	33.25	29.07	7.58	45.80	74.00	-28.20	Peak	VERTICAL
4960.00	37.46	33.71	29.34	8.63	50.46	54.00	-3.54	Average	VERTICAL
4960.00	42.91	33.71	29.34	8.63	55.91	74.00	-18.09	Peak	VERTICAL
6327.00	32.63	35.53	29.51	9.85	48.50	74.00	-25.50	Peak	VERTICAL
7447.00	33.75	36.56	30.73	10.81	50.39	74.00	-23.61	Peak	VERTICAL
Result: Pass									
Test Date : Jan. 12, 2017					Test Engineer: Damon Hu				

Note: 1.30MHz~18GHz: (Scan with GFSK, $\pi/4$ QPSK, 8-DPSK, the worst case is GFSK Mode)

2. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

10. Band Edge Compliance (radiated method)

10.1. Block diagram of test setup



10.2. Limit

All restriction bands should comply with 15.209, other emission should be at least 20dB below the fundamental.

10.3. Test Procedure

Same with clause 9.3 except change investigated frequency range from 2310MHz to 2410MHz and 2475MHz to 2510MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.

10.4. Test result


PASS. (See below detailed test result)

Remark: hopping on and hopping off mode all have been test, hopping off mode is worse and reported only.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\16Q1216-6\RF.EM6**
Test Date : 2017-01-05 **Tested By** : Jerry
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : DC 12V **Test Mode** : TX mode 2402MHz
Condition : Temp:24.5°C,Humi:55%,
Antenna/Distance : 2016 HF907/3m/HORIZONTAL
Press:100.1kPa
Memo : GFSK

Data: 12



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2342.00	41.99	29.59	29.32	5.96	48.22	74.00	-25.78	Peak	HORIZONTAL
2	2390.00	39.44	29.78	29.41	6.01	45.82	74.00	-28.18	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\16Q1216-6\RF.EM6**
Test Date : 2017-01-05 **Tested By** : Jerry
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : DC 12V **Test Mode** : TX mode 2402MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/VERTICAL
Memo : GFSK

Data: 13



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2344.50	42.20	29.60	29.33	5.96	48.43	74.00	-25.57	Peak	VERTICAL
2	2390.00	40.00	29.78	29.41	6.01	46.38	74.00	-27.62	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\16Q1216-6\RF.EM6**
Test Date : 2017-01-05 **Tested By** : Jerry
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : DC 12V **Test Mode** : TX mode 2480MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/HORIZONTAL
Memo : GFSK

Data: 18



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	43.04	30.14	29.71	6.15	49.62	74.00	-24.38	Peak	HORIZONTAL
2	2490.03	42.84	30.16	29.73	6.15	49.42	74.00	-24.58	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\16Q1216-6\RF.EM6**
Test Date : 2017-01-05 **Tested By** : Jerry
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : DC 12V **Test Mode** : TX mode 2480MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/VERTICAL
Memo : GFSK

Data: 19



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	43.12	30.14	29.71	6.15	49.70	74.00	-24.30	Peak	VERTICAL
2	2493.20	42.77	30.17	29.73	6.15	49.36	74.00	-24.64	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\16Q1216-6\RF.EM6**
Test Date : 2017-01-05 **Tested By** : Jerry
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : DC 12V **Test Mode** : TX mode 2402MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/VERTICAL
Memo : 8-DPSK

Data: 28



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2341.10	41.89	29.58	29.32	5.96	48.11	74.00	-25.89	Peak	VERTICAL
2	2390.00	38.97	29.78	29.41	6.01	45.35	74.00	-28.65	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\16Q1216-6\RF.EM6**
Test Date : 2017-01-05 **Tested By** : Jerry
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : DC 12V **Test Mode** : TX mode 2402MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/HORIZONTAL
Memo : 8-DPSK

Data: 29



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2343.30	42.75	29.59	29.33	5.96	48.97	74.00	-25.03	Peak	HORIZONTAL
2	2390.00	40.82	29.78	29.41	6.01	47.20	74.00	-26.80	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\16Q1216-6\RF.EM6**
Test Date : 2017-01-05 **Tested By** : Jerry
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : DC 12V **Test Mode** : TX mode 2480MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/VERTICAL
Memo : 8-DPSK

Data: 20



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	42.21	30.14	29.71	6.15	48.79	74.00	-25.21	Peak	VERTICAL
2	2494.10	43.01	30.18	29.73	6.15	49.61	74.00	-24.39	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\16Q1216-6\RF.EM6**
Test Date : 2017-01-05 **Tested By** : Jerry
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : DC 12V **Test Mode** : TX mode 2480MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/HORIZONTAL
Memo : 8-DPSK

Data: 21



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	43.58	30.14	29.71	6.15	50.16	74.00	-23.84	Peak	HORIZONTAL
2	2492.33	44.20	30.17	29.73	6.15	50.79	74.00	-23.21	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

11. Band Edge Compliance (conducted method)

11.1. Block diagram of test setup

Same as section 4.1


11.2. Limit

All restriction bands should comply with 15.209, other emission should be at least 20dB below the fundamental.


11.3. Test result

Mode	Freq. (MHz)	Conclusion
GFSK	Hopping off 2402	PASS
	Hopping off 2480	PASS
	Hopping on	PASS
8-DPSK	Hopping off 2402	PASS
	Hopping off 2480	PASS
	Hopping on	PASS
Test Date : Jan. 03, 2017		Test Engineer: Damon Hu

11.4. Original test data




GFSK/LCH/Hop




Date: 9.JAN.2017 02:16:33

GFSK/HCH/No Hop




Date: 9.JAN.2017 02:08:54

GFSK/HCH/Hop




Date: 9.JAN.2017 02:18:36


8DPSK/LCH/No Hop




8DPSK/LCH/Hop




8DPSK/HCH/No Hop





12. Power Line Conducted Emission

12.1. Block diagram of test setup



12.2. Power Line Conducted Emission Limits(Class B)

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

12.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 3 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 KHz.

12.4. Test Result

PASS. (See below detailed test result)


Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means Peak detection; “----” mans Average detection

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **E:\2016 report data\16Q1216-4\CE.EM6**
Test Date : 2016-11-10 **Tested By** : Sincere
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,
Press:100.1kPa **LISN** : 2016 ENV216/LINE
Memo : Built-in AC adapter: JFY40A-160250

Data: 66



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.155	25.06	9.61	0.02	9.86	44.55	55.74	-11.19	Average	LINE
2	0.155	32.04	9.61	0.02	9.86	51.53	65.74	-14.21	QP	LINE
3	0.206	20.96	9.61	0.02	9.86	40.45	53.36	-12.91	Average	LINE
4	0.206	28.12	9.61	0.02	9.86	47.61	63.36	-15.75	QP	LINE
5	0.406	19.66	9.61	0.02	9.86	39.15	47.73	-8.58	Average	LINE
6	0.406	26.02	9.61	0.02	9.86	45.51	57.73	-12.22	QP	LINE
7	0.771	16.26	9.61	0.03	9.86	35.76	46.00	-10.24	Average	LINE
8	0.771	20.67	9.61	0.03	9.86	40.17	56.00	-15.83	QP	LINE
9	10.125	19.07	9.74	0.11	9.90	38.82	50.00	-11.18	Average	LINE
10	10.125	22.79	9.74	0.11	9.90	42.54	60.00	-17.46	QP	LINE
11	25.727	12.69	10.04	0.17	9.98	32.88	50.00	-17.12	Average	LINE
12	25.727	18.32	10.04	0.17	9.98	38.51	60.00	-21.49	QP	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	E:\2016 report data\16Q1216-4\CE.EM6
Test Date	: 2016-11-10	Tested By : Sincere
EUT	: Speaker	Model Number : JOB ROCKER MAX
Power Supply	: AC 120V/60Hz	Test Mode : Tx mode
Condition	: Temp:24.5°C,Humi:55%, Press:100.1kPa	LISN : 2016 ENV216/NEUTRAL
Memo	: Built-in AC adapter: JFY40A-160250	

Data: 68



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.156	23.24	9.61	0.02	9.86	42.73	55.69	-12.96	Average	NEUTRAL
2	0.156	32.13	9.61	0.02	9.86	51.62	65.69	-14.07	QP	NEUTRAL
3	0.203	21.12	9.61	0.02	9.86	40.61	53.49	-12.88	Average	NEUTRAL
4	0.203	28.29	9.61	0.02	9.86	47.78	63.49	-15.71	QP	NEUTRAL
5	0.226	22.04	9.61	0.02	9.86	41.53	52.61	-11.08	Average	NEUTRAL
6	0.226	28.93	9.61	0.02	9.86	48.42	62.61	-14.19	QP	NEUTRAL
7	0.404	19.90	9.61	0.02	9.86	39.39	47.77	-8.38	Average	NEUTRAL
8	0.404	26.70	9.61	0.02	9.86	46.19	57.77	-11.58	QP	NEUTRAL
9	0.775	16.14	9.61	0.03	9.86	35.64	46.00	-10.36	Average	NEUTRAL
10	0.775	21.94	9.61	0.03	9.86	41.44	56.00	-14.56	QP	NEUTRAL
11	10.288	17.12	9.74	0.11	9.90	36.87	50.00	-13.13	Average	NEUTRAL
12	10.288	22.76	9.74	0.11	9.90	42.51	60.00	-17.49	QP	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **E:\2016 report data\16Q1216-4\CE.EM6**
Test Date : 2016-10-26 **Tested By** : Sincere
EUT : Speaker **Model Number** : JOB ROCKER MAX
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,
Press:100.1kPa **LISN** : 2016 ENV216/LINE
Memo : Built-in AC adapter: K40P160250

Data: 50



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.152	20.70	9.61	0.02	9.86	40.19	55.87	-15.68	Average	LINE
2	0.152	32.15	9.61	0.02	9.86	51.64	65.87	-14.23	QP	LINE
3	0.173	13.03	9.61	0.02	9.86	32.52	54.81	-22.29	Average	LINE
4	0.173	22.83	9.61	0.02	9.86	42.32	64.81	-22.49	QP	LINE
5	0.291	12.00	9.61	0.02	9.86	31.49	50.50	-19.01	Average	LINE
6	0.291	17.27	9.61	0.02	9.86	36.76	60.50	-23.74	QP	LINE
7	0.389	10.80	9.61	0.02	9.86	30.29	48.08	-17.79	Average	LINE
8	0.389	15.85	9.61	0.02	9.86	35.34	58.08	-22.74	QP	LINE
9	0.499	11.97	9.61	0.02	9.86	31.46	46.01	-14.55	Average	LINE
10	0.499	17.29	9.61	0.02	9.86	36.78	56.01	-19.23	QP	LINE
11	0.775	13.88	9.61	0.03	9.86	33.38	46.00	-12.62	Average	LINE
12	0.775	18.18	9.61	0.03	9.86	37.68	56.00	-18.32	QP	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	E:\2016 report data\16Q1216-4\CE.EM6
Test Date	: 2016-10-26	Tested By : Sincere
EUT	: Speaker	Model Number : JOB ROCKER MAX
Power Supply	: AC 120V/60Hz	Test Mode : Tx mode
Condition	: Temp:24.5°C,Humi:55%, Press:100.1kPa	LISN : 2016 ENV216/NEUTRAL
Memo	: Built-in AC adapter: K40P160250	

Data: 52



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.150	21.14	9.61	0.02	9.86	40.63	56.00	-15.37	Average	NEUTRAL
2	0.150	32.31	9.61	0.02	9.86	51.80	66.00	-14.20	QP	NEUTRAL
3	0.184	17.44	9.61	0.02	9.86	36.93	54.28	-17.35	Average	NEUTRAL
4	0.184	27.24	9.61	0.02	9.86	46.73	64.28	-17.55	QP	NEUTRAL
5	0.226	14.88	9.61	0.02	9.86	34.37	52.61	-18.24	Average	NEUTRAL
6	0.226	23.91	9.61	0.02	9.86	43.40	62.61	-19.21	QP	NEUTRAL
7	0.582	11.81	9.61	0.03	9.86	31.31	46.00	-14.69	Average	NEUTRAL
8	0.582	17.71	9.61	0.03	9.86	37.21	56.00	-18.79	QP	NEUTRAL
9	0.775	13.59	9.61	0.03	9.86	33.09	46.00	-12.91	Average	NEUTRAL
10	0.775	18.18	9.61	0.03	9.86	37.68	56.00	-18.32	QP	NEUTRAL
11	21.486	16.53	10.00	0.15	9.96	36.64	50.00	-13.36	Average	NEUTRAL
12	21.486	23.89	10.00	0.15	9.96	44.00	60.00	-16.00	QP	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

13. Antenna Requirements

13.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2. Result

The antennas used for this product are Built-in undetachable dipole antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 2.0dBi.

END OF REPORT