

BT

DUT: HA-A03T2

Communication System: BT ; Frequency: 2441 MHz;Duty Cycle: 1:1.30208
Medium: H2450 Medium parameters used: $f = 2441 \text{ MHz}$; $\sigma = 1.76 \text{ S/m}$; $\epsilon_r = 40.25$; $\rho = 1000 \text{ kg/m}^3$
Ambient Temperature : $22.4 \text{ }^\circ\text{C}$; Liquid Temperature : $22.2 \text{ }^\circ\text{C}$

DASY5 Configuration:
- Probe: EX3DV4 - SN3970; Calibrated: 2023/5/17;
- Electronics: DAE4 Sn1418; Calibrated: 2023/4/25
- Phantom: SAM; Type: QD000P40CD; Serial: TP:1794
- Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

Right-DH5/Area Scan (6x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (measured) = 0.114 W/kg

Right-DH5/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.187 V/m ; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.211 W/kg

SAR(1 g) = 0.086 W/kg ; SAR(10 g) = 0.037 W/kg

Maximum value of SAR (measured) = 0.140 W/kg



