

Emission Test Report

Standard: FCC Part 15 Subpart C / IC RSS-210

Document Number : FCC 19-0251-0

Model Number: WM3B2200BG

measured with **IBM ThinkPad X30 Series**
and **IBM ThinkPad X40 Series**

FCC ID: ANO20040501CX2
IC: 349E-WM3B22-U

February 6, 2004

Prepared :
EMC R&D Staff Engineer

Takeshi Asano


Signature: 

IBM Japan, Ltd.
EMC Engineering
LAB-S59

1623-14, Shimotsuruma,
Yamato-shi Kanagawa-ken 242, Japan
Phone: +81-46-215-4779
Fax: +81-46-273-7420
E-Mail: asano@jp.ibm.com

Reviewed and Checked :
EMC R&D Staff Engineer

Toshiya Murota

Signature: 

IBM Japan, Ltd.
EMC Engineering
LAB-S59

1623-14, Shimotsuruma,
Yamato-shi Kanagawa-ken 242, Japan
Phone: +81-46-215-6574
Fax: +81-46-273-7420
E-Mail: murota@jp.ibm.com

Approved :
Manager, EMC Engineering
/ NVLAP signatory

Akihisa Sakurai

Signature: 

IBM Japan, Ltd.
EMC Engineering
LAB-S59

1623-14, Shimotsuruma,
Yamato-shi Kanagawa-ken 242, Japan
Phone: +81-46-215-2613
Fax: +81-46-273-7420
E-Mail: akihisa@jp.ibm.com

MEASUREMENT / TECHNICAL REPORT – Part 15 Subpart C (Intentional Radiator)

Model: WM3B22-U (802.11b/g Wireless LAN Adapter)

with

IBM ThinkPad X30 Series

(Machine Type: 2672, 2673, 2890, 2891)

and

IBM ThinkPad X40 Series

(Machine Type: 2369, 2370, 2371, 2372, 2381)

FCC ID : ANO20040501CX2

February 6, 2004

This report concerns: (check one) Original Grant ☒ _____ Class I change ☐ _____ Class II change ☐ _____
Equipment type: <u>Wireless LAN device</u>
This report shall not be reproduced except in full, without the written permission of this test lab.
The measurement results contained in this report relate only to the item which was tested.
Measurement procedure used is ANSI C63.4-2000 unless otherwise specified.
Other test procedure: _____
The FCC has issued provisional acceptance of this test laboratory for Declaration of Conformity testing per letter dated 1997.
APPLICANT ANTI-DRUG ABUSE CERTIFICATION: By checking yes, the applicant certifies that, in the case of an individual applicant, he or she is not subject to a denial of federal benefits, that includes FCC benefits, pursuant to Section 5301 of the Anti-Drug Abuse of 1988, 21 U.S.C. 853(a), or, in the case of a non-individual applicant (e.g. corporation, partnership or other unincorporated association), no party to the application is subject to a denial of federal benefits, that includes FCC benefits, pursuant to that section. For the definition of a “party” for these purposes, see 47 CFR 1.2002(b). ☒ Yes or No
“Report shall not be reproduced except in full, without the written approval of the laboratory” “the report must not be used by the client to claim product endorsement by NVLAP or any agency of the US government”
Prepared by: Takeshi Asano IBM Japan Corporation, Yamato EMC Engineering LAB-S59, 1623-14, Shimotsuruma, Yamato-shi Kanagawa-ken 242-8502, Japan Tel: +81-46-215-4779 Fax: +81-46-273-7420

- Index -

A.	General Information.....	5
A.1	Test Methodology.....	5
A.2	Test Facility / NVLAP Accreditation.....	5
A.3	EUT details	5
B.	Summary of Test Results.....	6
C.	Operation Mode of EUT	7
D.	Justification	7
E.	Test Instruments	8
F.	Measurement Uncertainty.....	9
G.	Temperature and Humidity	9
H.	Related Submittal(s)/Grant(s)/Notes	9
1.	Bandwidth at 6 dB below.....	10
1.1	Test Procedure.....	10
1.2	Test Instruments and Measurement Setup.....	10
1.3	Measurement Results	10
1.4	Trace Data of 6dB bandwidth.....	12
2.	Occupied Bandwidth (20 dB Bandwidth)	18
2.1	Test Procedure.....	18
2.2	Test Instruments and Measurement Setup.....	18
2.3	Measurement Results	18
2.4	Trace Data of Occupied Bandwidth	20
3.	Conducted Peak Output Power.....	26
3.1	Test Procedure.....	26
3.2	Test Instruments and Measurement Setup.....	26
3.3	Measurement Results	26
3.4	Trace Data of Conducted Peak Output Power.....	27
4.	Out of Band Emissions (Conducted Spurious).....	33
4.1	Test Procedure.....	33
4.2	Test Instruments and Measurement Setup.....	33
4.3	Measurement Results	33
4.4	Trace Data of Out of Band Emissions	34
5.	Peak Power Spectral Density	40
5.1	Test Procedure.....	40
5.2	Test Instruments and Measurement Setup.....	40
5.3	Measurement Results	40
5.4	Trace Data of Peak Power Spectral Density	41
6.	AC Wireline Conducted Emissions (150KHz – 30MHz)	47
6.1	Test Procedure.....	47
6.2	Test Instruments and Measurement Setup.....	47
6.3	Powerline Voltage Calculation.....	48
6.4	Measurement Results	49

7. Restricted Bands Radiation (30MHz – 1GHz)	52
7.1 Test Procedure.....	52
7.2 Test Instruments and Measurement Setup.....	52
7.3 Field Strength Calculation	54
7.4 Measurement Results	55
8. Restricted Bands Radiatio (1GHz – 25GHz)	58
8.1 Test Procedure.....	58
8.2 Test Instruments and Measurement Setup.....	58
8.3 Field Strength Calculation	60
8.4 Measurement Results	61
8.5 Measurement plots of adjacent restricted band.....	64
8.5.1 List of Measurement Results	64
8.5.2 Bandedge Measurement Plots for ThinkPad X30 Series	65
8.5.3 Bandedge Measurement Plots for ThinkPad X40 Series	89

A. General Information

APPLICANT : IBM Japan, Ltd.
 TEST SITE : IBM Japan, Ltd., Yamato Semi-anechoic chamber #1
 TEST SITE ADDRESS : 1623 – 14 Shimotsuruma, Yamato-shi, Kanagawa 242-8502 Japan
 Tel: +81-46-215-4779, Fax: +81-46-273-7420
 REGULATION : FCC Part 15 Subpart C
 Industry Canada RSS-210 (Issue No.5)
 MODEL NUMBER : WM3B2200BG
 FCC ID : ANO20040501CX2
 IC Certification Number : 349E-MW3B22-U
 SERIAL NUMBER : 006FA0473
 PHYSICAL CONDITION : Preproduction
 KIND OF EQUIPMENT : DTS: IEEE802.11b/g Wireless LAN Mini-PCI card
 TESTED DATE : January 26, 27, 28, 29, 30, February 4 and 5, 2004

A.1 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4-2000. Radiated testing was performed at an antenna to EUT distance of 3 meters.

A.2 Test Facility / NVLAP Accreditation

The semi-anechoic chamber #1 used to correct the data are located in Yamato Laboratory, IBM Japan.

- This facility has been fully described in a report dated September 1998, submitted to the FCC office, and accepted in a letter, dated Nov. 2, 1998(31040/SIT).
- IBM Yamato EMC Engineering is recognized under the National Voluntary Laboratory Accreditation Program for satisfactory compliance with Criteria established in Title 15, Part 285 Code of Federal Regulations.(NVLAP Lab code: 200198-0)
- This facility is accepted by **Industry Canada** in a letter dated March 19, 2001 as number **IC 349E** for chamber #2, and January 25, 2002 as number **IC 4221** for chamber #1.

A.3 EUT details

Table A EUT details

Model and S/N	FCC ID IC Certification Number	Description
WM3B22-U (s/n 006FA0473)	FCC ID: ANO20040501CX2 IC: 349E-MW3B22-U	Applying modular transmitter Built_in type IEEE802.11b/g Wireless LAN Mini-PCI card without antenna
ThinkPad X30 Series M/T 2672-UPx (s/n zz-04049)	N/A	Host equipment IBM Notebook PC with built_in antenna CPU: Intel® Pentium® M Processor, 1.7GHz
ThinkPad X40 Series M/T : 2371-SD1 (s/n SIT#15023)		IBM Notebook PC with built-in antenna CPU: Intel® Pentium M Processor, 1.3 GHz
P/N 02K6810	N/A	Universal AC adapter 56W, Unshielded power cord

B. Summary of Test Results

Table-B presents the list of the measurement items for DTS (Digital Transmissions System) devices under FCC Part 15 Subpart C and Industry Canada RSS-210.

The section numbers of upper portion are showing FCC number, and the other (lower) ones are for IC.

Table-B List of the measurements

Section(s)	Test Items : Transmit mode (TX):		Condition	Result
15.247(a)(2) 6.2.2(o)(b)	Bandwidth at 6 dB below	FCC requirement	Conducted	Pass
– 5.9.1	Occupied BW (Bandwidth at 20 dB below)	IC requirement		Pass
15.247(c) 6.2.2(o)(e1)	Out of Band Emissions	The radiated emission in any 100kHz of outband shall be at least 20dB below the highest inband spectral density.		Pass
15.247(b)(3) 6.2.2(o)(b)	Transmitter peak output power	Shall not exceed 1.0 W.		Pass
15.247(d) 6.2.2(o)(b)	Transmitter power spectral Density	Shall not be greater than 8 dBm in any 3kHz band.		Pass
15.207 6.2.2(o)(e3) / 6.6	AC Wireline Conducted Emissions 150kHz – 30MHz	Class B: Freq.(MHz) QP(dBμV) Ave.(dBμV) 0.15 - 0.5 66 - 56 56 - 46 0.5 - 5 56 46 5 - 30 60 50	Radiated (30MHz-1GHz)	Pass
15.205 / 209 6.2.1 / 6.2.2(o)(e3) / 6.3	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Shall not exceed the limits specified in FCC 15.209 or RSS-210 Table3.	Radiated (1– 25GHz)	Pass

	Test Items : Receive mode (RX):			
15.207 6.2.2(o)(e3) / 7.4	AC Wireline Conducted Emissions 150kHz – 30MHz	Class B: Freq.(MHz) QP(dBμV) Ave.(dBμV) 0.15 - 0.5 66 - 56 56 - 46 0.5 - 5 56 46 5 - 30 60 50	Conducted	Pass
15.205 / 209 6.2.1 / 6.2.2(o)(e3) / 7.3	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Shall not exceed the limits specified in FCC 15.209 or RSS-210 Table3.	Radiated (30MHz -1GHz)	Pass
			Radiated (1– 25GHz)	Pass

	Other requirements		Result
15.247(b)(4)(i) –	Antenna gain	Peak gain of the device : 1.28 and 1.67 dBi	N/A
15.203 6.2.2(o)(e2)	Unique antenna connector	The device employs an unique electronic connector so called BIOS Lock . Refer to “Confidential_BIOS-Lock” exhibit.	complies

C. Operation Mode of EUT

- All tests were performed using the “CRTU II, version 2.2.9.3000” test program provided by Intel Corporation. This tool supports the continuous or burst transmission mode for the testing purpose. The parameter GAIN in the test software was set to 31.0 for IEEE 802.11b mode and was set to 26.0 for ch.1 and 11 and 27.0 for ch.2 through 10 of IEEE 802.11g mode.
- The following frequencies were chosen for the measurements.
Tx tests: 2412MHz (lowest), 2437MHz(middle), and 2462MHz (highest)
Rx tests: 2437MHz(middle)

Table-C Transmission mode of EUT

Operation Frequency [GHz]	Rated output power (conducted) [dBm]										
	IEEE802.11b (DSSS)			IEEE802.11g (OFDM)							
	1/2M bps	5.5M bps	11M bps	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
2.412 (Ch. 1)	+17	+17	+17	+12	+12	+12	+12	+12	+12	+12	+12
2.417 (Ch. 2)	+17	+17	+17	+13	+13	+13	+13	+13	+13	+13	+13
2.422 (Ch. 3)	+17	+17	+17	+13	+13	+13	+13	+13	+13	+13	+13
2.427 (Ch. 4)	+17	+17	+17	+13	+13	+13	+13	+13	+13	+13	+13
2.432 (Ch. 5)	+17	+17	+17	+13	+13	+13	+13	+13	+13	+13	+13
2.437 (Ch. 6)	+17	+17	+17	+13	+13	+13	+13	+13	+13	+13	+13
2.442 (Ch. 7)	+17	+17	+17	+13	+13	+13	+13	+13	+13	+13	+13
2.447 (Ch. 8)	+17	+17	+17	+13	+13	+13	+13	+13	+13	+13	+13
2.452 (Ch. 9)	+17	+17	+17	+13	+13	+13	+13	+13	+13	+13	+13
2.457 (Ch. 10)	+17	+17	+17	+13	+13	+13	+13	+13	+13	+13	+13
2.462 (Ch. 11)	+17	+17	+17	+12	+12	+12	+12	+12	+12	+12	+12

D. Justification

- The shading columns in the above Table C are measurement plots in this test report.
- The host PCs (IBM ThinkPad X30 Series and X40 Series) are designed with the same conceptual hardware configuration of compact size laptop PC. The antennas of host PCs marked in shading in Table-D below were used for EUT which have comparatively higher gains and worse measurement results in each host PC series (X30 or X40). Then, the worst case data were selected for this report among the two systems. The actual highest emissions taken in this report for the Chapter 6 through 8 were found at 1Mb/s for DSSS and 6Mb/s for OFDM on the auxiliary antenna of ThinkPad X40 Series. Refer to the Chapter 8.5 concerning the evaluation of the worst emission case.

Table-D Peak Antenna Gains of EUT

	Main Antenna gain	Auxiliary Antenna gain
ThinkPad X30 Series	0.62 dBi (peak)	1.28 dBi (peak)
ThinkPad X40 Series	0.39 dBi (peak)	1.67 dBi (peak)

E. Test Instruments

Table-E List of Measuring Instruments

Description	Model	Serial Number	Calibration Date	Calibration Interval
Computer	IBM 6868-30J	97-901X3	N/A	N/A
Computer	IBM 6589-13J	97-15613	N/A	N/A
Spectrum Analyzer (100Hz-1.5GHz)	HP 85680B	2601A02634	09/09/03	1 year
Spectrum Analyzer (100Hz-1.5GHz)	HP 85680B	3019A05156	08/14/03	1 year
Spectrum Analyzer (100Hz-1.5GHz)	HP 85680B	2841A04254	08/25/03	1 year
Spectrum Analyzer Display	HP 85662A	2542A12308	09/09/03	1 year
Spectrum Analyzer Display	HP 85662A	3026A19366	08/14/03	1 year
Spectrum Analyzer Display	HP 85662A	2816A16831	08/25/03	1 year
Quasi-Peak Adapter	HP 85650A	2043A00062	09/09/03	1 year
Quasi-Peak Adapter	HP 85650A	2811A01433	08/14/03	1 year
Quasi-Peak Adapter	HP 85650A	2811A01156	08/25/03	1 year
Amplifier (100KHz - 1.3GHz)				
- for 30-200MHz	HP 8447F	2805A02919	04/14/03	1 year
- for 200-1000MHz	HP 8447D	2727A05190	04/14/03	1 year
Amplifier (1GHz - 18GHz)	HP 8449B	3008A00582	06/11/03	1 year
Amplifier (18 – 25GHz)	Agilent 83051A	3950M00193	01/27/04	1 year
Spectrum Analyzer EMI Test Receiver	R&S ESI26	836119/003	05/01/03	1 year
Receiver (9kHz-30MHz)	R&S ESH3	891806/012	10/17/03	1 year
Receiver (20MHz-1.3GHz)	R&S ESVP	892111/030	03/17/03	1 year
Biconical Antenna (30-200MHz)	EMCO 3108	2536	04/23/03	1 year
Log-Periodic Antenna (200-1000MHz)	EMCO 3146	2849	04/23/03	1 year
Horn Antenna (1- 18GHz)	EMCO 3115	9903-5774	07/17/03	1 year
Horn Antenna (3.95- 5.85GHz)	EMCO 3160-5	1099	07/17/03	1 year
Horn Antenna (5.85- 8.20GHz)	EMCO 3160-6	9712-1044	07/17/03	1 year
Horn Antenna (18- 26.5GHz)	EMCO 3160-9	0004-1202	07/17/03	1 year
LISN	EMCO 3810/2NM	00022007	05/20/03	1 year
Switch/control unit	HP 3488A	2719A17226 2719A17228	N/A N/A	N/A N/A
Plotter	HP 7550A	2631A33619	N/A	N/A
Coaxial cables (1 – 18GHz):	Length:			
- Horn Ant <=> RF Amp.	6 m	- EM206SCO	03/27/03	1 year
- RF Amp. <=> Spectrum Analyzer	16m	- GEM0101	03/27/03	1 year
Coaxial cables (18 – 25GHz):				
- Horn Ant <=> RF Amp.	3m	- SF102-20167	03/27/03	1 year
- RF Amp. <=> Spectrum Analyzer	1m	- SF102-21105	03/27/03	1 year
N-Coax cables:				
- Bi-coni Ant <=> 10m Cable	9 m	- EM103L01	04/14/03	1 year
- 10m Cable <=> Shield Panel	10 m	- EM103L02	04/14/03	1 year
- Shield Panel <=> RF Amp	7 m	- EM103L03	04/14/03	1 year
- RF Amp <=> Power Splitter	0.5m	- EM103L04	04/14/03	1 year
- Log-peri Ant <=> 10m Cable	9 m	- EM103H01	04/14/03	1 year
- 10m Cable <=> Shield Panel	10 m	- EM103H02	04/14/03	1 year

- Shield Panel <=> RF Amp	7 m	- EM103H03	04/14/03	1 year
- RF Amp <=> Power Splitter	0.5m	- EM103H04	04/14/03	1 year
Coax cables:				
- Lism-L <=> SW/Con.unit (SW100)	4 m	- EMIC-L	04/14/03	1 year
- Lism-N <=> SW/Con.unit (SW101)	4 m	- EMIC-N	04/14/03	1 year
- SW/Con.unit <=> RCVR (Input)	1 m	- EMIC-R	04/14/03	1 year
- SW/Con.unit<=> Spe Ana.(Signal In)	1 m	- EMIC-S	04/14/03	1 year
- Power Splitter <=> SW/Con.unit (SW110)	1 m	- EM103L05	04/14/03	1 year
- Power Splitter <=> SW/Con.unit (SW300)	1 m	- EM103L06	04/14/03	1 year
- Power Splitter <=> SW/Con.unit (SW100)	1 m	- EM103H05	04/14/03	1 year
- Power Splitter <=> SW/Con.unit (SW301)	1 m	- EM103H06	04/14/03	1 year
- SW/Con.unit <=> Receiver (Input)	2 m	- EM1RCV	04/14/03	1 year
- SW/Con.unit <=> Spe Ana.(Signal In) for 30- 200MHz	2 m	- EM1SPL	04/14/03	1 year
- SW/Con.unit <=> Spe Ana.(Signal In) for 200-1000MHz	2 m	- EM1SPH	04/14/03	1 year

Notes.

- The above equipment calibration is traceable to National standards.
- HP: Hewlett Packard, R&S: Rohde & Schwarz

F. Measurement Uncertainty

Uncertainties of the both, the Yamato EMI radiated test facilities (EMI chambers, #1 and #2) and the Yamato EMI conducted test facility are derived with the NIS 81 "Treatment of uncertainty in EMC measurements" 1994.

Estimated site uncertainty values are as follows.

EMI chamber #1 : 4.39dB

EMI chamber #2 : 4.40dB

EMI conducted measurement system : 2.4dB

Detail should be referred to "Treatment of Uncertainty, Calculations and Policy" report, document number TCR 10-0015.

G. Temperature and Humidity

The temperature is controlled within range of 17° to 28°.

The relative humidity is controlled within range of 40% to 70%.

H. Related Submittal(s)/Grant(s)/Notes

The host unit with full peripheral devices including the applying modular as an unintentional radiator is classified as a Digital Device under the FCC Part 15 Subpart B or the Industry Canada Class B Emission Compliance (ICES-003), and subject to DoC.

1. Bandwidth at 6 dB below

[FCC 15.247(a)(2), RSS-210 6.2.2(o)(b)]

1.1 Test Procedure

The bandwidth at 6 dB down from the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT was operating in transmission mode at the appropriate center frequency.

The spectrum analyzer was set to :

RBW=100kHz, VBW=100kHz*1, Span=30MHz, Sweep = suitable duration based on the EUT specification

*1: To be adjusted accordingly based on the spectrum stability

1.2 Test Instruments and Measurement Setup

Table 1-1 : 6 dB Bandwidth Test Instruments

Description	Model	Serial Number
Spectrum Analyzer EMI Test Receiver	R&S ESI26	836119/003
Coax cables: - Spectrum Analyzer <=> EUT	Length : 110 cm Loss : 1.3 dB	

Notes: - R&S: Rohde & Schwarz




Figure 1: Measurement setup for 6dB bandwidth test

1.3 Measurement Results

Test Date: January 26 and 27, 2004

1.3.1 2.4GHz band DSSS mode

Table 1-2-1. 6dB bandwidth, 2.4GHz band DSSS mode, TX mode 1Mbps

Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 6 dB below (MHz)	Limit (MHz)
2412 (ch. 1)	omitted	2407.46	2416.66	9.20	> 0.5
2437 (ch. 6)	Plot 1-1	2432.46	2441.60	9.14	
2462 (ch. 11)	omitted	2457.46	2466.60	9.14	

Table 1-2-2. 6dB bandwidth, 2.4GHz band DSSS mode, TX mode 5.5Mbps

Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 6 dB below (MHz)	Limit (MHz)
2412 (ch. 1)	omitted	2407.46	2416.90	9.44	> 0.5
2437 (ch. 6)	Plot 1-2	2432.82	2441.30	8.48	
2462 (ch. 11)	omitted	2457.58	2466.36	8.78	

Table 1-2-3. 6dB bandwidth, 2.4GHz band DSSS mode, TX mode 11Mbps

Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 6 dB below (MHz)	Limit (MHz)
2412 (ch. 1)	omitted	2407.46	2416.60	9.14	> 0.5
2437 (ch. 6)	Plot 1-3	2432.40	2441.54	9.14	
2462 (ch. 11)	omitted	2457.04	2466.66	9.62	

1.3.2 2.4GHz band OFDM mode

Table 1-2-4. 6dB bandwidth, 2.4GHz band OFDM mode, TX mode 6Mbps

Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 6 dB below (MHz)	Limit (MHz)
2412 (ch. 1)	omitted	2403.79	2420.27	16.48	> 0.5
2437 (ch. 6)	Plot 1-4	2428.79	2445.27	16.48	
2462 (ch. 11)	omitted	2453.79	2470.27	16.48	

Table 1-2-5. 6dB bandwidth, 2.4GHz band OFDM mode, TX mode 18Mbps


Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 6 dB below (MHz)	Limit (MHz)
2412 (ch. 1)	omitted	2403.73	2420.33	16.60	> 0.5
2437 (ch. 6)	Plot 1-5	2428.73	2445.33	16.60	
2462 (ch. 11)	omitted	2453.73	2470.33	16.60	

Table 1-2-6. 6dB bandwidth, 2.4GHz band OFDM mode, TX mode 54Mbps


Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 6 dB below (MHz)	Limit (MHz)
2412 (ch. 1)	Plot 1-6	2403.73	2420.33	16.60	> 0.5
2437 (ch. 6)	omitted	2428.67	2445.33	16.66	
2462 (ch. 11)	omitted	2453.73	2470.33	16.60	

1.4 Trace Data of 6dB bandwidth

The plots are comparatively worse measurement cases in the previous [Table 1-2-1](#) through [Table 1-2-6](#).




Plot 1-1. 6dB BW at 2437MHz. (DSSS. 1Mbps)




Date: 27.JAN.2004 21:28:06

Plot 1-2. 6dB BW at 2437MHz. (DSSS. 5.5Mbps)




Date: 27.JAN.2004 21:30:56

Plot 1-3. 6dB BW at 2437MHz (DSSS, 11Mbps)




Date: 26.JAN.2004 20:20:25

Plot 1-4. 6dB BW at 2437MHz (OFDM. 6Mbps)



Date: 26.JAN.2004 20:22:02

Plot 1-5. 6dB BW at 2437MHz (OFDM, 18Mbps)



Date: 26.JAN.2004 20:18:28

Plot 1-6. 6dB BW at 2412MHz (OFDM, 54Mbps)

2. Occupied Bandwidth (20 dB Bandwidth) [RSS-210 5.9.1]

2.1 Test Procedure

The bandwidth at 20 dB down from the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT was operating in transmission mode at the appropriate center frequency.

The spectrum analyzer was set to:

RBW=100kHz, VBW=100kHz^{*1}, Span=50MHz, Sweep = suitable duration based on the EUT specification

^{*1}: To be adjusted accordingly based on the spectrum stability

2.2 Test Instruments and Measurement Setup

Same as the Chapter 1 (Table 1-1 & Figure 1).

2.3 Measurement Results

Test Date: January 26 and 27, 2004

2.3.1 2.4GHz band DSSS mode

Table 2-2-1. Occupied bandwidth, 2.4GHz band DSSS mode, TX 1Mbps

Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 20 dB below (MHz)
2412 (ch. 1)	Plot 2-1	2403.43	2420.67	17.24
2437 (ch. 6)	omitted	2428.63	2445.62	16.99
2462 (ch. 11)	omitted	2453.43	2470.17	16.74

Table 2-2-2. Occupied bandwidth, 2.4GHz band DSSS mode, TX 5.5Mbps

Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 20 dB below (MHz)
2412 (ch. 1)	Plot 2-2	2403.13	2420.67	17.54
2437 (ch. 6)	omitted	2428.43	2445.32	16.89
2462 (ch. 11)	omitted	2453.53	2470.57	17.04

Table 2-2-3. Occupied bandwidth, 2.4GHz band DSSS mode, TX 11Mbps

Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 20 dB below (MHz)
2412 (ch. 1)	Plot 2-3	2403.43	2420.67	17.24
2437 (ch. 6)	omitted	2428.43	2445.22	16.79
2462 (ch. 11)	omitted	2453.93	2470.47	16.54

2.3.2 2.4GHz band OFDM mode

Table 2-2-4. Occupied bandwidth, 2.4GHz band OFDM mode, TX 6Mbps

Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 20 dB below (MHz)
2412 (ch. 1)	omitted	2402.63	2421.17	18.54
2437 (ch. 6)	Plot 2-4	2427.63	2446.22	18.59
2462 (ch. 11)	omitted	2452.73	2471.17	18.44

Table 2-2-5. Occupied bandwidth, 2.4GHz band OFDM mode, TX 18Mbps


Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 20 dB below (MHz)
2412 (ch. 1)	Plot 2-5	2402.93	2421.17	18.24
2437 (ch. 6)	omitted	2427.93	2446.02	18.09
2462 (ch. 11)	omitted	2452.93	2471.07	18.14

Table 2-2-6. Occupied bandwidth, 2.4GHz band OFDM mode, TX 54Mbps


Center Frequency (MHz)	Trace number	Lower frequency (MHz)	Upper frequency (MHz)	Bandwidth at 20 dB below (MHz)
2412 (ch. 1)	omitted	2402.93	2421.17	18.24
2437 (ch. 6)	Plot 2-6	2427.63	2446.42	18.79
2462 (ch. 11)	omitted	2452.93	2471.17	18.24

2.4 Trace Data of Occupied Bandwidth

The plots are comparatively worse measurement cases in the previous [Table 2-2-1](#) through [Table 2-2-6](#).




Plot 2-1. 20dB BW at 2412MHz (DSSS, 1Mbps)




Date: 27.JAN.2004 22:05:08

Plot 2-2. 20dB BW at 2412MHz (DSSS, 5.5Mbps)



Date: 27.JAN.2004 22:06:36

Plot 2-3. 20dB BW at 2412MHz (DSSS, 11Mbps)




Date: 26.JAN.2004 21:11:51

Plot 2-4. 20dB BW at 2437MHz (OFDM, 6Mbps)




Marker 1 [T1] RBW 100 kHz RF Att 40 dB
Ref Lvl -0.74 dBm VBW 100 kHz
30 dBm 2.41335271 GHz SWT 12.5 ms Unit dBm



Date: 26.JAN.2004 21:08:10

Plot 2-5. 20dB BW at 2412MHz (OFDM, 18Mbps)



Date: 26.JAN.2004 21:15:03

Plot 2-6. 20dB BW at 2437MHz (OFDM, 54Mbps)

3. Conducted Peak Output Power

[FCC 15.247(b)(3), RSS-210 6.2.2(o)(b)]

3.1 Test Procedure

The test was performed with 6dB bandwidth measurement method in accordance with Appendix C of FCC R&O 97114.

The spectrum analyzer was connected to the antenna terminal, while EUT was operating in continuous burst transmission mode (shown in the Chapter C) at the appropriate center frequencies.

The spectrum analyzer was set to :

VBW= 30kHz, RBW=1MHz,

Span=30-40MHz encompassing the entire 6 dB emission bandwidth of the transmission signal,

Mode= sample detector, Trigger= free run

The band power measurement function was used to measure the peak power of each transmission mode. The analyzer computed the peak power by integrating the spectrum across the 6 dB emission bandwidth given by the previous chapter.

3.2 Test Instruments and Measurement Setup

The test instruments and setup configuration are the same as the Table 1-1 and Figure 1.


3.3 Measurement Results

Test Date: January 26 and 27, 2004

Table 3-2-1. Conducted peak output power measurement results


Measured Frequency (MHz)	Tx mode (Mb/s)	Analyzer reading (dBm)	Trace number	Cable Loss (dB)	Results (dBm)	Limit		Margin to limit (dBm)
						FCC (dBm)	IC (dBm)	
2412 (DSSS)	1	14.97	omitted	1.3	16.27 (42.4mW)	30	30	13.73
	5.5	15.81	Plot 3-1		17.11 (51.4mW)			12.89
	11	15.74	omitted		17.04 (50.6mW)			12.96
2437 (DSSS)	1	14.68	omitted	1.3	15.98 (39.6mW)			14.02
	5.5	15.46	Plot 3-2		16.76 (47.4mW)			13.24
	11	15.43	omitted		16.73 (47.1mW)			13.27
2462 (DSSS)	1	14.41	omitted	1.3	15.71 (37.2mW)			14.29
	5.5	15.16	Plot 3-3		16.46 (44.3mW)			13.54
	11	15.09	omitted		16.39 (43.6mW)			13.61
2412 (OFDM)	6	11.05	Plot 3-4	1.3	12.35 (17.2mW)			17.65
	18	10.88	omitted		12.18 (16.5mW)			17.82
	54	11.00	omitted		12.30 (17.0mW)			17.70
2437 (OFDM)	6	12.00	Plot 3-5	1.3	13.30 (21.4mW)			16.70
	18	11.71	omitted		13.01 (20.0mW)			16.99
	54	11.94	omitted		13.24 (21.1mW)			16.76
2462 (OFDM)	6	10.82	Plot 3-6	1.3	12.12 (16.3mW)			17.88
	18	10.56	omitted		11.86 (15.3mW)			18.14
	54	10.77	omitted		12.07 (16.1mW)			17.93

3.4 Trace Data of Conducted Peak Output Power




Date: 27.JAN.2004 21:44:02

Plot 3-1. Conducted Peak Output Power of 2412MHz (DSSS, 5.5Mbps)




Date: 27.JAN.2004 21:51:20

Plot 3-2. Conducted Peak Output Power of 2437MHz (DSSS, 5.5Mbps)




Date: 27.JAN.2004 21:58:16

Plot 3-3. Conducted Peak Output Power of 2462MHz (DSSS, 5.5Mbps)




Date: 26.JAN.2004 20:35:39

Plot 3-4. Conducted Peak Output Power of 2412MHz (OFDM, 6Mbps)



Date: 26.JAN.2004 20:45:48

Plot 3-5. Conducted Peak Output Power of 2437MHz (OFDM, 6Mbps)



Date: 26.JAN.2004 20:55:38

Plot 3-6. Conducted Peak Output Power of 2462MHz (OFDM, 6Mbps)

4. Out of Band Emissions (Conducted Spurious)

[FCC 15.247(c), RSS-210 6.2.2(o)(e1)]

4.1 Test Procedure

The outband emissions in any 100kHz bandwidth was measured with a spectrum analyzer connected to the antenna terminal, while EUT was operating in transmission mode at the appropriate center frequency.

The spectrum analyzer was set to:

RBW = 100kHz, VBW = 100kHz*1, Scanning frequency range = 30MHz~2GHz, 2GHz~3GHz, and 3GHz~25GHz, Sweep = suitable duration based on the EUT specification

*1: To be adjusted accordingly based on the spectrum stability

4.2 Test Instruments and Measurement Setup

Same as the Chapter 1 (Table 1-1 & Figure 1).

4.3 Measurement Results

All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 20dB lower than the highest inband spectral density.


The measurement was performed with the worse cases of each transmission mode, that tend to have higher conducted peak power, based on the results of previous Chapter 3, “Conducted Peak Output Power” measurement.

Test Date: January 26 and 27, 2004 : See the following plots.


Center Frequency (MHz)		Tx Rate (worst case)	Trace number *1
2412 (ch. 1)	DSSS	5.5Mb/s	Plot 4-1
2437 (ch. 6)		5.5Mb/s	Plot 4-2
2462 (ch. 11)		5.5Mb/s	Plot 4-3
2412 (ch. 1)	OFDM	6Mb/s	Plot 4-4
2437 (ch. 6)		6Mb/s	Plot 4-5
2462 (ch. 11)		6Mb/s	Plot 4-6

*1 : Each submittal plot includes the highest conducted spurious in the 10th harmonics frequency range of each worst case in measured Tx modes.


4.4 Trace Data of Out of Band Emissions




Date: 27.JAN.2004 22:24:41




Plot 4-1. Out of band emissions around 2412MHz (DSSS, 5.5Mbps)




Date: 27.JAN.2004 22:33:44




Plot 4-2. Out of band emissions around 2437MHz (DSSS, 5.5Mbps)




Date: 27. JAN. 2004 22:42:45


Plot 4-3. Out of band emissions around 2462MHz (DSSS, 5.5Mbps)




Date: 26.JAN.2004 21:27:12




Plot 4-4. Out of band emissions around 2412MHz (OFDM, 6Mbps)




Date: 26.JAN.2004 21:35:34




Plot 4-5. Out of band emissions around 2437MHz (OFDM, 6Mbps)



Date: 26.JAN.2004 21:48:49



Date: 26.JAN.2004 21:49:19



Date: 26.JAN.2004 21:49:55

Plot 4-6. Out of band emissions around 2462MHz (OFDM, 6Mbps)

5. Peak Power Spectral Density

[FCC 15.247(d), RSS-210 6.2.2(o)(b)]

5.1 Test Procedure

The power spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT was operating in transmission mode at the appropriate center frequency.

The pre-scanning was performed with the spectrum analyzer to search and locate the center frequency at the peak emission of each transmission mode.

Then, the spectral analyzer was set to the emission peak found in the pre-scan and the peak power spectral density was measured with:

RBW = 3 kHz, VBW = 3 kHz, Span = 300 kHz, Sweep = 100 seconds

5.2 Test Instruments and Measurement Setup

Same as the Chapter 1 (Table 1-1 & Figure 1).

5.3 Measurement Results


The measurement was performed with the worse cases of each transmission mode, that tend to have higher conducted peak power, based on the results of previous Chapter 3, “Conducted Peak Output Power” measurement.

Test Date: January 26 and 27, 2004

Table 5-1. Peak Power Spectrum Density, TX mode


Ch No.			Frequency (MHz)	Analyzer Reading (dBm)	Trace number	Cable loss (dB)	Result (dBm)	Limit (dBm)	Margin (dB)
DSSS	2.4GHz 5.5Mbps	1	2411.88	-8.92	Plot 5-1	1.3	- 7.6	8.0	15.6
		6	2438.02	-8.91	Plot 5-2	1.3	- 7.6	8.0	15.6
		11	2462.41	-9.48	Plot 5-3	1.3	- 8.2	8.0	16.2
OFDM	2.4GHz 6Mbps	1	2411.09	-13.21	Plot 5-4	1.3	-11.9	8.0	19.9
		6	2437.62	-11.47	Plot 5-5	1.3	-10.2	8.0	18.2
		11	2461.62	-14.20	Plot 5-6	1.3	-12.9	8.0	20.9

5.4 Trace Data of Peak Power Spectral Density




Date: 27. JAN. 2004 22:55:23

Plot 5-1. Peak Power Spectral Density of 2412MHz (DSSS, 5.5Mbps)



Date: 27.JAN.2004 23:04:09

Plot 5-2. Peak Power Spectral Density of 2437MHz (DSSS, 5.5Mbps)




Date: 27.JAN.2004 23:16:16

Plot 5-3. Peak Power Spectral Density of 2462MHz (DSSS, 5.5Mbps)



Marker 1 [T1] RBW 3 kHz RF Att 40 dB
Ref Lvl -13.21 dBm VBW 3 kHz
30 dBm 2.41108647 GHz SWT 100 s Unit dBm




Date: 26.JAN.2004 21:59:18

Plot 5-4. Peak Power Spectral Density of 2412MHz (OFDM, 6Mbps)




Ref Lvl	Marker 1 [T1]	RBW	3 kHz	RF Att	40 dB
30 dBm	-11.47 dBm	VBW	3 kHz		
	2.43762435 GHz	SWT	100 s	Unit	dBm



Date: 26.JAN.2004 22:09:30

Plot 5-5. Peak Power Spectral Density of 2437MHz (OFDM, 6Mbps)



Date: 26.JAN.2004 22:19:33

Plot 5-6. Peak Power Spectral Density of 2462MHz (OFDM, 6Mbps)

6. AC Wireline Conducted Emissions (150KHz – 30MHz)

[FCC 15.207, RSS-210 6.6 / 7.4]

6.1 Test Procedure

The conducted emissions are measured in the IBM shielded room with a spectrum analyzer in peak hold. Emissions closest to the limit are measured in the quasi-peak mode (QP) with the tuned receiver using a bandwidth of 9kHz. The emissions are maximized further by cable manipulation. The highest emissions relative to the limit are listed.

6.2 Test Instruments and Measurement Setup

Table 6-1. Conducted Emission Test Instrumentation

Description	Model	Serial Number
Computer	IBM 6589-13J	97-15613
Spectrum Analyzer (100Hz-1.5GHz)	HP 85680B	2841A04254
Spectrum Analyzer Display	HP 85662A	2816A16831
Quasi-Peak Adapter	HP 85650A	2811A01156
Receiver (9kHz-30MHz)	R&S ESH3	891806/012
LISN	EMCO 3810/2NM	00022007
Switch/control unit	HP 3488A	2719A17228
Plotter	HP 7550A	2631A33619
Coax cables: - Lisen-L <=> SW/Con.unit (SW100) - Lisen-N <=> SW/Con.unit (SW101) - SW/Con.unit <=> RCVR (Input) - SW/Con.unit<=> Spe Ana.(Signal In)	Length: 4 m 4 m 1 m 1 m	- EMIC-L - EMIC-N - EMIC-R - EMIC-S

Notes: - HP: Hewlett Packard, R&S: Rohde & Schwarz




Figure 6. Cables for Conducted Emission Test

6.3 Powerline Voltage Calculation

The powerline voltage is calculated by adding insertion losses of LISN, Cable, Switch control unit and Pulse limiter to the measured reading. All factors are included in the reported data.

$$PV = R + CORR$$

where:

PV = Powerline Voltage (dBμV)

R = Measured Receiver Input Amplitude (dBμV)

CORR = Correction Factor (dB) = LL+CL+SWL+PLL

LL = Insertion loss of LISN (dB)

CL = Insertion loss of Cable (dB)

SWL = Insertion loss of Switch control unit (dB)

PLL = Insertion loss of Pulse Limiter (dB)

Given a Receiver input reading of 50.0 dBμV, LISN loss of 0.6 dB, Cable loss of 0.1dB, Switch control unit loss of 0.1dB and Pulse limiter loss of 0.2dB. The Powerline Voltage of the measured emission is:

$$CORR = 0.6 + 0.1 + 0.1 + 0.2 = 1.0 \text{ (dB)}$$

$$PV = 50.0 + 1.0 = 51.0 \text{ (dBμV)}$$

6.4 Measurement Results

The EUT was found to comply to the limits of FCC Part 15 Subpart C and RSS-210 with a margin of 14.4dB. The 6 highest emissions relative to the limits are reported.

Test Date: January 30, 2004

6.3.1 EUT in 2.4GHz DSSS transmission mode

Table 6-2-1. Ch.1 (2412MHz) **TX** mode 1Mbps

Frequency (MHz)	QP			AV			CISPR22 QP Limit (dBμV)	CISPR22 AV Limit (dBμV)	Phase
	Measured Reading (dBμV)	Corr. Factor (dB)	Powerline Voltage (dBμV)	Measured Reading (dBμV)	Corr. Factor (dB)	Powerline Voltage (dBμV)			
0.3798	34.6	0.6	35.2	33.3	0.6	33.9	58.3	48.3	Neutral
0.4838	29.5	0.6	30.1	23.9	0.6	24.5	56.3	46.3	Neutral
0.5888	28.4	0.6	29.0	26.8	0.6	27.4	56.0	46.0	Neutral
0.8591	29.0	0.6	29.6	23.8	0.6	24.4	56.0	46.0	Neutral
1.2473	28.3	0.6	28.9	24.6	0.6	25.2	56.0	46.0	Line
2.1048	28.1	0.7	28.8	23.3	0.7	24.0	56.0	46.0	Neutral

Table 6-2-2. Ch.6 (2437MHz) **TX** mode 1Mbps

Frequency (MHz)	QP			AV			CISPR22 QP Limit (dBμV)	CISPR22 AV Limit (dBμV)	Phase
	Measured Reading (dBμV)	Corr. Factor (dB)	Powerline Voltage (dBμV)	Measured Reading (dBμV)	Corr. Factor (dB)	Powerline Voltage (dBμV)			
0.1598	45.7	0.5	46.2	25.5	0.5	26.0	65.5	55.5	Neutral
0.3752	34.1	0.6	34.7	29.2	0.6	29.8	58.4	48.4	Neutral
0.5865	28.7	0.6	29.3	27.4	0.6	28.0	56.0	46.0	Neutral
0.8653	29.7	0.6	30.3	27.3	0.6	27.9	56.0	46.0	Neutral
1.2445	28.0	0.6	28.6	24.6	0.6	25.2	56.0	46.0	Neutral
1.6228	27.6	0.6	28.2	22.9	0.6	23.5	56.0	46.0	Line

Table 6-2-3. Ch.11 (2462MHz) **TX** mode 1Mbps

Frequency (MHz)	QP			AV			CISPR22 QP Limit (dBμV)	CISPR22 AV Limit (dBμV)	Phase
	Measured Reading (dBμV)	Corr. Factor (dB)	Powerline Voltage (dBμV)	Measured Reading (dBμV)	Corr. Factor (dB)	Powerline Voltage (dBμV)			
0.1602	47.6	0.5	48.1	25.5	0.5	26.0	65.5	55.5	Neutral
0.3742	33.1	0.6	33.7	29.1	0.6	29.7	58.4	48.4	Neutral
0.5835	28.7	0.6	29.3	25.4	0.6	26.0	56.0	46.0	Neutral
0.8630	30.0	0.6	30.6	28.7	0.6	29.3	56.0	46.0	Neutral
1.2433	27.9	0.6	28.5	24.8	0.6	25.4	56.0	46.0	Line
1.8289	27.9	0.7	28.6	24.9	0.7	25.6	56.0	46.0	Neutral

Table 6-2-4. Ch. 6 (2437MHz) **RX** mode

Frequency (MHz)	QP			AV			CISPR22 QP Limit (dB μ V)	CISPR22 AV Limit (dB μ V)	Phase
	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)			
0.1724	43.3	0.5	43.8	26.3	0.5	26.8	64.8	54.8	Neutral
0.3856	34.0	0.6	34.6	29.1	0.6	29.7	58.2	48.2	Neutral
0.4838	28.4	0.6	29.0	23.3	0.6	23.9	56.3	46.3	Neutral
0.5815	30.2	0.6	30.8	27.6	0.6	28.2	56.0	46.0	Neutral
0.8664	29.7	0.6	30.3	25.1	0.6	25.7	56.0	46.0	Neutral
1.2593	28.9	0.6	29.5	22.1	0.6	22.7	56.0	46.0	Neutral

6.3.2 EUT in 2.4GHz OFDM transmission modeTable 6-2-5. Ch.1 (2412MHz) **TX** mode 6Mbps

Frequency (MHz)	QP			AV			CISPR22 QP Limit (dB μ V)	CISPR22 AV Limit (dB μ V)	Phase
	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)			
0.3794	34.8	0.6	35.4	31.7	0.6	32.3	58.3	48.3	Neutral
0.4848	27.7	0.6	28.3	22.0	0.6	22.6	56.3	46.3	Neutral
0.5892	28.4	0.6	29.0	26.9	0.6	27.5	56.0	46.0	Neutral
0.8634	29.4	0.6	30.0	25.5	0.6	26.1	56.0	46.0	Neutral
1.1259	27.0	0.6	27.6	20.0	0.6	20.6	56.0	46.0	Neutral
2.4742	26.2	0.7	26.9	20.4	0.7	21.1	56.0	46.0	Neutral

Table 6-2-6. Ch.6 (2437MHz) **TX** mode 6Mbps

Frequency (MHz)	QP			AV			CISPR22 QP Limit (dB μ V)	CISPR22 AV Limit (dB μ V)	Phase
	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)			
0.1599	46.2	0.5	46.7	29.5	0.5	30.0	65.5	55.5	Neutral
0.3709	30.5	0.6	31.1	27.3	0.6	27.9	58.5	48.5	Line
0.5903	28.3	0.6	28.9	26.4	0.6	27.0	56.0	46.0	Line
0.8651	28.8	0.6	29.4	22.6	0.6	23.2	56.0	46.0	Neutral
1.2373	27.2	0.6	27.8	23.2	0.6	23.8	56.0	46.0	Line
1.8234	27.0	0.7	27.7	22.7	0.7	23.4	56.0	46.0	Neutral

Table 6-2-7. Ch.11 (2462MHz) **TX** mode 6Mbps

Frequency (MHz)	QP			AV			CISPR22 QP Limit (dB μ V)	CISPR22 AV Limit (dB μ V)	Phase
	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)			
0.2044	40.7	0.5	41.2	25.1	0.5	25.6	63.4	53.4	Neutral
0.3771	34.3	0.6	34.9	32.8	0.6	33.4	58.3	48.3	Neutral
0.5878	28.4	0.6	29.0	27.2	0.6	27.8	56.0	46.0	Line
0.8569	30.1	0.6	30.7	25.7	0.6	26.3	56.0	46.0	Neutral
1.1286	27.6	0.6	28.2	21.3	0.6	21.9	56.0	46.0	Neutral
1.8316	27.1	0.7	27.8	21.5	0.7	22.2	56.0	46.0	Neutral

Table 6-2-8. Ch.6 (2437MHz) **RX** mode

Frequency (MHz)	QP			AV			CISPR22 QP Limit (dB μ V)	CISPR22 AV Limit (dB μ V)	Phase
	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)	Measured Reading (dB μ V)	Corr. Factor (dB)	Powerline Voltage (dB μ V)			
0.3837	34.6	0.6	35.2	33.0	0.6	33.6	58.2	48.2	Neutral
0.4854	29.3	0.6	29.9	25.2	0.6	25.8	56.2	46.2	Neutral
0.5813	28.8	0.6	29.4	25.9	0.6	26.5	56.0	46.0	Neutral
0.8646	29.5	0.6	30.1	26.4	0.6	27.0	56.0	46.0	Neutral
1.2457	28.5	0.6	29.1	22.1	0.6	22.7	56.0	46.0	Neutral
1.3465	25.4	0.6	26.0	20.5	0.6	21.1	56.0	46.0	Line

7. Restricted Bands Radiation (30MHz – 1GHz)

[FCC 15.205 / 209, RSS-210 6.3 / 7.3]

7.1 Test Procedure

Preliminary radiated emissions are measured in the semi-anechoic chamber at a 3 meter distance on every azimuth in both horizontal and vertical polarity. The antennas are also scanned in height. The emissions are recorded with a spectrum analyzer in peak hold mode. The identified emissions are further maximized by a cable manipulation. Emissions closest to the limits are measured in the quasi-peak mode with the tuned receiver using a bandwidth of 120kHz. The highest emissions relative to the limit are listed.

7.2 Test Instruments and Measurement Setup

Table 7-1 Radiated Emission Test Instrumentation

Description	Model	Serial Number
Computer	IBM 6868-30J	97-901X3
Spectrum Analyzer (100Hz-1.5GHz) for 30-200MHz	HP 85680B	2601A02634
Spectrum Analyzer Display for 30-200MHz	HP 85662A	2542A12308
Quasi-Peak Adapter for 30-200MHz	HP 85650A	2043A00062
Spectrum Analyzer (100Hz-1.5GHz) for 200-1000MHz	HP 85680B	3019A05156
Spectrum Analyzer Display for 200-1000MHz	HP 85662A	3026A19366
Quasi-Peak Adapter for 200-1000MHz	HP 85650A	2811A01433
Amplifier (100KHz-1.3GHz)		
- for 30-200MHz	HP 8447F	2805A02919
- for 200-1000MHz	HP 8447D	2727A05190
Biconical Antenna (30-200MHz)	EMCO 3108	2536
Log-Periodic Antenna (200-1000MHz)	EMCO 3146	2849
Receiver (20MHz-1.3GHz)	R&S ESVP	892111/030
Switch/control unit	HP 3488A	2719A17226
N-Coax cables:	Length:	
- Bi-coni Ant <=> 10m Cable	9 m	- EM103L01
- 10m Cable <=> Shield Panel	10 m	- EM103L02
- Shield Panel <=> RF Amp	7 m	- EM103L03
- RF Amp <=> Power Splitter	0.5m	- EM103L04
- Log-peri Ant <=> 10m Cable	9 m	- EM103H01
- 10m Cable <=> Shield Panel	10 m	- EM103H02
- Shield Panel <=> RF Amp	7 m	- EM103H03
- RF Amp <=> Power Splitter	0.5m	- EM103H04
Coax cables:		
- Power Splitter <=> SW/Con.unit (SW110)	1 m	- EM103L05
- Power Splitter <=> SW/Con.unit (SW300)	1 m	- EM103L06
- Power Splitter <=> SW/Con.unit (SW100)	1 m	- EM103H05
- Power Splitter <=> SW/Con.unit (SW301)	1 m	- EM103H06
- SW/Con.unit <=> Receiver (Input)	2 m	- EM1RCV
- SW/Con.unit <=> Spe Ana.(Signal In) for 30- 200MHz	2 m	- EM1SPL
- SW/Con.unit <=> Spe Ana.(Signal In) for 200-1000MHz	2 m	- EM1SPH

Notes:

- HP: Hewlett Packard, R&S: Rohde & Schwarz




Figure 7 Cables for Radiated Emission Test

7.3 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. In this test facility, the Antenna Factor, Cable Loss, and Amplifier Gains are loaded into the Rohde & Schwarz Receiver and the corrected field strength can be read directly on the receiver. All factors are included in the reported data.

$$FS = R + AF + CORR$$

where:

FS	=	Field Strength
R	=	Measured Receiver Input Amplitude
AF	=	Antenna Factor
CORR	=	Correction Factor = CL - AG
CL	=	Cable Loss
AG	=	Amplifier Gain

For example :

Given a Receiver input reading of 51.5dB μ V; Antenna Factor of 8.5dB/m; Cable Loss of 1.3dB; and an Amplifier Gain of 26dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 = 35.3\text{dB}\mu\text{V/m}$$

Conversion between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as:

$$\text{Level}(\text{dB}\mu\text{V/m}) = 20 \times \text{Log}(\text{Level}(\mu\text{V/m}))$$

$$40\text{dB}\mu\text{V/m} = 100\mu\text{V/m}$$

$$48\text{dB}\mu\text{V/m} = 250\mu\text{V/m}$$

7.4 Measurement Results

The EUT was found to comply to the limits of FCC Part 15 Subpart C and RSS-210 with a margin of 3.2 dB at 30MHz - 1000MHz band.

The 6 highest emissions relative to the limits are reported.

Test Date: January 29, 2004

7.4.1 EUT in 2.4GHz DSSS transmission mode

Table 7-2-1. Ch.1 (2412MHz) **TX** mode 1Mbps

Frequency (MHz)	Polarity (H/V)	Measured (dB μ V)	Antenna Factor (dB/m)	Corr. Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Field Strength (μ V/m)	Limit (μ V/m)
360.877	V	28.5	14.4	-13.5	29.4	46.0	29.5	200
453.475	V	24.0	16.5	-13.8	26.7	46.0	21.6	200
496.209	V	23.7	17.7	-13.4	28.0	46.0	25.1	200
663.537	V	21.1	20.4	-12.1	29.4	46.0	29.5	200
831.896	V	22.9	21.8	-9.7	35.0	46.0	56.2	200
902.201	V	28.2	22.7	-9.1	41.8	46.0	123.0	200

Table 7-2-2. Ch.6 (2437MHz) **TX** mode 1Mbps

Frequency (MHz)	Polarity (H/V)	Measured (dB μ V)	Antenna Factor (dB/m)	Corr. Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Field Strength (μ V/m)	Limit (μ V/m)
52.047	V	27.8	10.4	-18.3	19.9	40.0	9.9	100
360.886	V	28.4	14.4	-13.5	29.3	46.0	29.2	200
453.028	V	24.8	16.5	-13.8	27.5	46.0	23.7	200
499.721	V	23.5	17.8	-13.3	28.0	46.0	25.1	200
831.716	H	24.4	21.8	-9.7	36.5	46.0	66.8	200
902.255	V	29.2	22.7	-9.1	42.8	46.0	138.0	200

Table 7-2-3. Ch.11 (2462MHz) **TX** mode 1Mbps

Frequency (MHz)	Polarity (H/V)	Measured (dB μ V)	Antenna Factor (dB/m)	Corr. Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Field Strength (μ V/m)	Limit (μ V/m)
360.896	V	28.4	14.4	-13.5	29.3	46.0	29.2	200
453.267	V	24.5	16.5	-13.8	27.2	46.0	22.9	200
496.227	V	23.9	17.7	-13.4	28.2	46.0	25.7	200
665.302	V	20.3	20.5	-12.2	28.6	46.0	26.9	200
829.695	H	24.3	21.7	-9.7	36.3	46.0	65.3	200
902.230	V	28.6	22.7	-9.1	42.2	46.0	128.8	200

Table 7-2-4. Ch.6 (2437MHz) **RX** mode

Frequency (MHz)	Polarity (H/V)	Measured (dB μ V)	Antenna Factor (dB/m)	Corr. Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Field Strength (μ V/m)	Limit (μ V/m)
52.104	V	24.2	10.3	-18.2	16.3	40.0	6.5	100
194.096	H	25.3	13.5	-15.9	22.9	43.5	14.0	150
360.894	V	27.9	14.4	-13.5	28.8	46.0	27.5	200
498.130	V	23.3	17.7	-13.4	27.6	46.0	24.0	200
857.119	H	26.9	22.1	-10.1	38.9	46.0	88.1	200
902.231	V	28.6	22.7	-9.1	42.2	46.0	128.8	200

7.4.2 EUT in 2.4GHz OFDM transmission mode

Table 7-2-5. Ch.1 (2412MHz) **TX** mode 6Mbps

Frequency (MHz)	Polarity (H/V)	Measured (dB μ V)	Antenna Factor (dB/m)	Corr. Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Field Strength (μ V/m)	Limit (μ V/m)
225.559	H	30.6	10.5	-15.0	26.1	46.0	20.2	200
360.894	V	28.1	14.4	-13.5	29.0	46.0	28.2	200
452.537	V	24.5	16.5	-13.7	27.3	46.0	23.2	200
664.633	V	19.2	20.4	-12.1	27.5	46.0	23.7	200
829.955	H	25.2	21.7	-9.7	37.2	46.0	72.4	200
902.234	V	28.2	22.7	-9.1	41.8	46.0	123.0	200

Table 7-2-6. Ch.6 (2437MHz) **TX** mode 6Mbps

Frequency (MHz)	Polarity (H/V)	Measured (dB μ V)	Antenna Factor (dB/m)	Corr. Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Field Strength (μ V/m)	Limit (μ V/m)
225.560	H	31.7	10.5	-15.0	27.2	46.0	22.9	200
360.896	H	25.6	14.4	-13.5	26.5	46.0	21.1	200
541.347	H	22.8	17.9	-13.2	27.5	46.0	23.7	200
666.130	H	18.5	20.5	-12.1	26.9	46.0	22.1	200
830.542	H	23.6	21.7	-9.7	35.6	46.0	60.3	200
902.237	V	28.9	22.7	-9.1	42.5	46.0	133.4	200

Table 7-2-7. Ch.11 (2462MHz) **TX** mode 6Mbps

Frequency (MHz)	Polarity (H/V)	Measured (dB μ V)	Antenna Factor (dB/m)	Corr. Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Field Strength (μ V/m)	Limit (μ V/m)
225.561	H	31.3	10.5	-15.0	26.8	46.0	21.9	200
360.895	V	28.1	14.4	-13.5	29.0	46.0	28.2	200
452.093	V	24.8	16.5	-13.7	27.6	46.0	24.0	200
497.364	V	24.7	17.7	-13.4	29.0	46.0	28.2	200
828.498	H	23.6	21.6	-9.7	35.5	46.0	59.6	200
902.237	V	28.8	22.7	-9.1	42.4	46.0	131.8	200

Table 7-2-8. Ch.6 (2437MHz) **RX** mode

Frequency (MHz)	Polarity (H/V)	Measured (dB μ V)	Antenna Factor (dB/m)	Corr. Factor (dB)	Field Strength (dB μ V/m)	Limit (dB μ V/m)	Field Strength (μ V/m)	Limit (μ V/m)
360.895	V	28.3	14.4	-13.5	29.2	46.0	28.8	200
496.230	V	23.6	17.7	-13.4	27.9	46.0	24.8	200
541.342	V	24.7	17.9	-13.2	29.4	46.0	29.5	200
731.812	V	20.7	21.0	-11.1	30.6	46.0	33.9	200
830.054	H	25.0	21.7	-9.7	37.0	46.0	70.8	200
902.237	V	28.4	22.7	-9.1	42.0	46.0	125.9	200

8. Restricted Bands Radiatio (1GHz – 25GHz)

[FCC 15.205 / 209, RSS-210 6.3 / 7.3]

8.1 Test Procedure

Radiated emissions were measured in the frequency range with 1 GHz to 25GHz in transmitting mode and 1 GHz to 12.5GHz in receiving mode. All tests were performed in the semi-anechoic chamber at a 3-meter distance (except for the frequency range with 18 GHz to 25 GHz where test distance was reduced to 1 meter) on both horizontal and vertical polarities. The antenna was also scanned in height. The emissions are recorded with a spectrum analyzer in peak hold mode. The identified emissions are further maximized as a function of cable manipulation, azimuth, and antenna height. The emissions closest to the limits are measured in the peak mode with the tuned spectrum analyzer using resolution bandwidth of 1MHz / video bandwidth of 1MHz, and the average setting mode with the tuned spectrum analyzer using resolution bandwidth of 1MHz / video bandwidth of 100Hz or 10Hz. The highest emissions relative to the limit are listed.

8.2 Test Instruments and Measurement Setup

Table 8 Radiated Emission Test Instrumentation (1GHz – 25GHz)

Description	Model	Serial Number
Spectrum Analyzer EMI Test Receiver	R&S ESI26	836119/003
Amplifier (1 – 18GHz)	HP 8449B	3008A00582
Amplifier (18 – 25GHz)	Agilent 83051A	3950M00193
Horn Antenna (1 - 18GHz)	EMCO 3115	9903-5774
Horn Antenna (3.95 – 5.85GHz)	EMCO 3160-5	1099
Horn Antenna (5.85 – 8.2GHz)	EMCO 3160-6	9712-1044
Horn Antenna (18 - 25GHz)	EMCO 3160-9	0004-1202
Coaxial cables: - Horn Ant <=> RF Amp. (1-18GHz) - RF Amp. <=> Spectrum Analyzer (1-18GHz) - Horn Ant <=> RF Amp. (18-25GHz) - RF Amp. <=> Spectrum Analyzer (18-25GHz)	Length: 6 m 16 m 3m 1m	- EM206SCO - GEM0101 - SF102-20167 - SF102-21105

Notes: - HP: Hewlett Packard, R&S: Rohde & Schwarz




Figure 8-1. Cables for Radiated Emission Test (1 – 18 GHz)




Figure 8-2. Cables for Radiated Emission Test (18 - 25GHz)

8.3 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$FS = R + AF + CORR - FO$$

where:

FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor

CORR = Correction Factor = CL-AG

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

For example:

Given a Spectrum Analyzer input reading of 51.5 dB μ V; Antenna Factor of 8.5 dB/m; Cable Loss of 1.3 dB; Falloff Factor of 0 dB; and an Amplifier Gain of 26 dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26 - 0.0 = 35.6 \text{ dB}\mu\text{V/m}$$

Conversions between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as :

$$\text{Level(dB}\mu\text{V/m)} = 20 \times \text{Log}(\text{Level}(\mu\text{V/m}))$$

$$40 \text{ dB}\mu\text{V/m} = 100 \mu\text{V/m}$$

$$48 \text{ dB}\mu\text{V/m} = 250 \mu\text{V/m}$$

8.4 Measurement Results

The EUT was found to comply to the limits of FCC Part 15 Subpart C and RSS-210 with a margin of 0.8 dB. The measurement was done for the frequency range of 1 GHz to 25 GHz in TX mode and 1 GHz to 12.5GHz in RX mode.

Test Date: January 27, 28 and February 5, 2004

8.4.1 EUT in 2.4GHz DSSS transmission mode

*Note: OB means “operation band” (2400-2483.5MHz); in this case limit is 1W (measured conducted with power meter)

Table 8-2-1. Ch.1 (2412MHz) **TX** mode 1Mbps

Frequency (GHz)	Polarity (H/V)	Measured (dBμ V) (peak)	Measured (dBμ V) (average)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dBμ V/m) (peak)	FCC Limit (dBμ V/m) (peak)	Field Strength (dBμ V/m) (average)	FCC Limit (dBμ V/m) (average)
Inband 2.413	H	112.4	105.8	28.3	-29.6	0.0	111.1	OB*	104.5	OB*
Adjacent RB 2.387	H	63.2	50.4	28.2	-29.6	0.0	61.8	74.0	49.0	54.0
2.390	H	58.4	46.2	28.2	-29.6	0.0	57.0	74.0	44.8	54.0
1.028	V	48.6	-	24.3	-32.2	0.0	40.7	74.0	-	54.0
1.129	V	50.4	-	24.5	-31.8	0.0	43.1	74.0	-	54.0
1.163	V	53.6	-	24.6	-31.7	0.0	46.5	74.0	-	54.0
1.328	V	51.9	-	25.6	-31.3	0.0	46.2	74.0	-	54.0
2.313	H	56.1	43.2	28.0	-29.7	0.0	54.4	74.0	41.5	54.0
2.332	H	55.4	-	28.1	-29.6	0.0	53.9	74.0	-	54.0
2.373	H	58.0	47.7	28.2	-29.6	0.0	56.6	74.0	46.3	54.0
4.826	V	42.3	-	27.1	-27.2	0.0	42.2	74.0	-	54.0

Table 8-2-2. Ch.6 (2437MHz) **TX** mode 1Mbps

Frequency (GHz)	Polarity (H/V)	Measured (dBμ V) (peak)	Measured (dBμ V) (average)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dBμ V/m) (peak)	FCC Limit (dBμ V/m) (peak)	Field Strength (dBμ V/m) (average)	FCC Limit (dBμ V/m) (average)
Inband 2.438	H	112.2	105.7	28.4	-29.6	0.0	111.0	OB*	104.5	OB*
Adjacent RB 2.385	H	56.8	44.8	28.2	-29.6	0.0	55.4	74.0	43.4	54.0
2.484	H	55.9	44.9	28.4	-29.6	0.0	54.7	74.0	43.7	54.0
1.066	V	51.3	-	24.6	-32.0	0.0	43.9	74.0	-	54.0
1.100	V	51.2	-	24.4	-31.9	0.0	43.7	74.0	-	54.0
1.129	V	50.1	-	24.5	-31.8	0.0	42.8	74.0	-	54.0
1.161	V	50.9	-	24.6	-31.7	0.0	43.8	74.0	-	54.0
2.315	H	54.4	-	28.0	-29.7	0.0	52.7	74.0	-	54.0
2.337	H	57.6	44.6	28.1	-29.6	0.0	56.1	74.0	43.1	54.0
2.360	H	55.6	44.5	28.1	-29.6	0.0	54.1	74.0	43.0	54.0
4.876	V	40.8	-	27.0	-27.0	0.0	40.8	74.0	-	54.0

Table 8-2-3. Ch.11 (2462MHz) **TX** mode 1Mbps

Frequency (GHz)	Polarity (H/V)	Measured (dB μ V) (<i>peak</i>)	Measured (dB μ V) (<i>average</i>)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dB μ V/m) (<i>peak</i>)	FCC Limit (dB μ V/m) (<i>peak</i>)	Field Strength (dB μ V/m) (<i>average</i>)	FCC Limit (dB μ V/m) (<i>average</i>)
Inband 2.463	H	112.2	105.5	28.4	-29.6	0.0	111.0	OB*	104.3	OB*
Adjacent RB 2.484	H	60.5	50.3	28.4	-29.6	0.0	59.3	74.0	49.1	54.0
2.488	H	63.1	54.3	28.4	-29.6	0.0	61.9	74.0	53.1	54.0
1.100	V	49.7	-	24.4	-31.9	0.0	42.2	74.0	-	54.0
1.129	V	48.8	-	24.5	-31.8	0.0	41.5	74.0	-	54.0
1.161	V	52.7	-	24.6	-31.7	0.0	45.6	74.0	-	54.0
1.325	V	51.4	-	25.6	-31.3	0.0	45.7	74.0	-	54.0
2.344	H	53.9	-	28.1	-29.6	0.0	52.4	74.0	-	54.0
2.360	H	55.6	43.8	28.1	-29.6	0.0	54.1	74.0	42.3	54.0
2.383	H	56.8	44.9	28.2	-29.6	0.0	55.4	74.0	43.5	54.0
4.926	V	40.3	-	27.0	-27.0	0.0	40.3	74.0	-	54.0

Table 8-2-4. Ch.6 (2437MHz) **RX** mode

Frequency (GHz)	Polarity (H/V)	Measured (dB μ V) (<i>peak</i>)	Measured (dB μ V) (<i>average</i>)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dB μ V/m) (<i>peak</i>)	FCC Limit (dB μ V/m) (<i>peak</i>)	Field Strength (dB μ V/m) (<i>average</i>)	FCC Limit (dB μ V/m) (<i>average</i>)
1.129	V	50.8	-	24.5	-31.8	0.0	43.5	74.0	-	54.0
1.161	V	52.5	-	24.6	-31.7	0.0	45.4	74.0	-	54.0
1.327	V	52.6	-	25.6	-31.3	0.0	46.9	74.0	-	54.0
1.494	V	50.8	-	25.5	-30.9	0.0	45.4	74.0	-	54.0

8.4.2 EUT in 2.4GHz OFDM transmission mode

*Note: OB means “operation band” (2400-2483.5MHz); in this case limit is 1W (measured conducted with power meter)

Table 8-2-5. Ch.1 (2412MHz) **TX** mode 6Mbps

Frequency (GHz)	Polarity (H/V)	Measured (dB μ V) (<i>peak</i>)	Measured (dB μ V) (<i>average</i>)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dB μ V/m) (<i>peak</i>)	FCC Limit (dB μ V/m) (<i>peak</i>)	Field Strength (dB μ V/m) (<i>average</i>)	FCC Limit (dB μ V/m) (<i>average</i>)
Inband 2.415	H	109.5	95.1	28.3	-29.6	0.0	108.2	OB*	93.8	OB*
Adjacent RB 2.380	H	62.8	46.3	28.2	-29.6	0.0	61.4	74.0	44.9	54.0
2.390	H	67.7	52.3	28.2	-29.6	0.0	66.3	74.0	50.9	54.0
1.065	V	51.6	-	24.6	-32.0	0.0	44.2	74.0	-	54.0
1.129	V	51.9	-	24.5	-31.8	0.0	44.6	74.0	-	54.0
1.160	V	53.6	-	24.6	-31.7	0.0	46.5	74.0	-	54.0
1.330	V	47.5	-	25.6	-31.3	0.0	41.8	74.0	-	54.0
2.313	H	58.8	45.9	28.0	-29.7	0.0	57.1	74.0	44.2	54.0
2.335	H	53.9	-	28.1	-29.6	0.0	52.4	74.0	-	54.0

Table 8-2-6. Ch.6 (2437MHz) **TX** mode 6Mbps

Frequency (GHz)	Polarity (H/V)	Measured (dB μ V) (<i>peak</i>)	Measured (dB μ V) (<i>average</i>)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dB μ V/m) (<i>peak</i>)	FCC Limit (dB μ V/m) (<i>peak</i>)	Field Strength (dB μ V/m) (<i>average</i>)	FCC Limit (dB μ V/m) (<i>average</i>)
Inband 2.435	H	109.8	96.0	28.4	-29.6	0.0	108.6	OB*	94.8	OB*
Adjacent RB 2.387	H	58.4	43.5	28.2	-29.6	0.0	57.0	74.0	42.1	54.0
2.484	H	57.8	43.3	28.4	-29.6	0.0	56.6	74.0	42.1	54.0
2.486	H	59.7	42.9	28.4	-29.6	0.0	58.5	74.0	41.7	54.0
1.132	V	51.0	-	24.6	-31.8	0.0	43.8	74.0	-	54.0
1.163	V	55.9	-	24.6	-31.7	0.0	48.8	74.0	-	54.0
1.330	V	51.3	-	25.6	-31.3	0.0	45.6	74.0	-	54.0
1.362	V	49.9	-	25.2	-31.3	0.0	43.8	74.0	-	54.0
2.281	H	51.9	-	27.8	-29.8	0.0	49.9	74.0	-	54.0
2.318	H	52.4	-	28.0	-29.7	0.0	50.7	74.0	-	54.0
2.336	H	59.0	45.6	28.1	-29.6	0.0	57.5	74.0	44.1	54.0
2.361	H	56.1	42.3	28.1	-29.6	0.0	54.6	74.0	40.8	54.0

Table 8-2-7. Ch.11 (2462MHz) **TX** mode 6Mbps

Frequency (GHz)	Polarity (H/V)	Measured (dB μ V) (<i>peak</i>)	Measured (dB μ V) (<i>average</i>)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dB μ V/m) (<i>peak</i>)	FCC Limit (dB μ V/m) (<i>peak</i>)	Field Strength (dB μ V/m) (<i>average</i>)	FCC Limit (dB μ V/m) (<i>average</i>)
Inband 2.459	H	108.8	94.6	28.4	-29.6	0.0	107.6	OB*	93.4	OB*
Adjacent RB 2.484	H	71.8	54.4	28.4	-29.6	0.0	70.6	74.0	53.2	54.0
2.487	H	68.0	52.1	28.4	-29.6	0.0	66.8	74.0	50.9	54.0
1.132	V	51.6	-	24.6	-31.8	0.0	44.4	74.0	-	54.0
1.164	V	54.5	-	24.6	-31.7	0.0	47.4	74.0	-	54.0
1.331	V	48.7	-	25.2	-31.3	0.0	42.6	74.0	-	54.0
1.495	V	49.6	-	25.5	-30.9	0.0	44.2	74.0	-	54.0
2.257	H	54.8	-	27.7	-29.8	0.0	52.7	74.0	-	54.0
2.289	H	56.5	44.2	27.8	-29.8	0.0	54.5	74.0	42.2	54.0
2.360	H	57.3	44.3	28.1	-29.6	0.0	55.8	74.0	42.8	54.0
2.387	H	56.9	43.4	28.2	-29.6	0.0	55.5	74.0	42.0	54.0

Table 8-2-8. Ch.6 (2437MHz) **RX** mode

Frequency (GHz)	Polarity (H/V)	Measured (dB μ V) (<i>peak</i>)	Measured (dB μ V) (<i>average</i>)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dB μ V/m) (<i>peak</i>)	FCC Limit (dB μ V/m) (<i>peak</i>)	Field Strength (dB μ V/m) (<i>average</i>)	FCC Limit (dB μ V/m) (<i>average</i>)
1.128	V	52.1	-	24.5	-31.8	0.0	44.8	74.0	-	54.0
1.163	V	53.0	-	24.6	-31.7	0.0	45.9	74.0	-	54.0
1.331	V	50.3	-	25.2	-31.3	0.0	44.2	74.0	-	54.0
1.495	V	52.7	-	25.5	-30.9	0.0	47.3	74.0	-	54.0

8.5 Measurement plots of adjacent restricted band

8.5.1 List of Measurement Results

a) EUT in 2.4GHz DSSS transmission mode

Measured with IBM ThinkPad X30 series

Tx Rate (Mb/s)	Frequency (GHz)	Polarity (H/V)	Reading (dBμV) (peak)	Rading (dBμV) (average)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dBμV/m) (peak)	Margin to Limit (dBμV/m) (peak)	Field Strength (dBμV/m) (average)	Margin to Limit (dBμV/m) (average)
1	2.374	H	57.0	48.1	28.2	-29.6	0.0	55.6	18.4	46.7	7.3
	2.488	H	57.2	48.1	28.4	-29.6	0.0	56.0	18.0	46.9	7.1
5.5	2.390	H	56.3	43.4	28.2	-29.6	0.0	54.9	19.1	42.0	12.0
	2.486	H	56.5	43.4	28.4	-29.6	0.0	55.3	18.7	42.2	11.8
11	2.390	H	57.4	42.5	28.2	-29.6	0.0	56.0	18.0	41.1	12.9
	2.486	H	56.3	43.0	28.4	-29.6	0.0	55.1	18.9	41.8	12.2

Measured with IBM ThinkPad X40 series

Tx Rate (Mb/s)	Frequency (GHz)	Polarity (H/V)	Reading (dBμV) (peak)	Rading (dBμV) (average)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dBμV/m) (peak)	Margin to Limit (dBμV/m) (peak)	Field Strength (dBμV/m) (average)	Margin to Limit (dBμV/m) (average)
1	2.387	H	63.2	50.4	28.2	-29.6	0.0	61.8	12.2	49.0	5.0
	2.488	H	63.1	54.3	28.4	-29.6	0.0	61.9	12.1	53.1	0.9
5.5	2.386	H	62.8	47.1	28.2	-29.6	0.0	61.4	12.6	45.7	8.3
	2.488	H	63.1	48.5	28.4	-29.6	0.0	61.9	12.1	47.3	6.7
11	2.386	H	64.1	45.6	28.2	-29.6	0.0	62.7	11.3	44.2	9.8
	2.488	H	63.1	47.8	28.4	-29.6	0.0	61.9	12.1	46.6	7.4

b) EUT in 2.4GHz OFDM transmission mode


Measured with IBM ThinkPad X30 series

Tx Rate (Mb/s)	Frequency (GHz)	Polarity (H/V)	Reading (dBμV) (peak)	Rading (dBμV) (average)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dBμV/m) (peak)	Margin to Limit (dBμV/m) (peak)	Field Strength (dBμV/m) (average)	Margin to Limit (dBμV/m) (average)
6	2.390	H	63.7	49.0	28.2	-29.6	0.0	62.3	11.7	47.6	6.4
	2.484	H	68.1	50.3	28.4	-29.6	0.0	66.9	7.1	49.1	4.9
18	2.390	H	61.7	47.3	28.2	-29.6	0.0	60.3	13.7	45.9	8.1
	2.484	H	64.3	48.7	28.4	-29.6	0.0	63.1	10.9	47.5	6.5
54	2.390	H	62.4	44.2	28.2	-29.6	0.0	61.0	13.0	42.8	11.2
	2.484	H	65.9	45.5	28.4	-29.6	0.0	64.7	9.3	44.3	9.7

Measured with IBM ThinkPad X40 series

Tx Rate (Mb/s)	Frequency (GHz)	Polarity (H/V)	Reading (dBμV) (peak)	Rading (dBμV) (average)	Antenna Factor (dB/m)	Corr. Factor (dB)	Falloff Factor (dB)	Field Strength (dBμV/m) (peak)	Margin to Limit (dBμV/m) (peak)	Field Strength (dBμV/m) (average)	Margin to Limit (dBμV/m) (average)
6	2.390	H	67.7	52.3	28.2	-29.6	0.0	66.3	7.7	50.9	3.1
	2.484	H	71.8	54.4	28.4	-29.6	0.0	70.6	3.4	53.2	0.8
18	2.390	H	67.4	50.4	28.2	-29.6	0.0	66.0	8.0	49.0	5.0
	2.484	H	71.3	52.4	28.4	-29.6	0.0	70.1	3.9	51.2	2.8
54	2.390	H	65.0	46.9	28.2	-29.6	0.0	63.6	10.4	45.5	8.5
	2.484	H	69.3	48.7	28.4	-29.6	0.0	68.1	5.9	47.5	6.5

8.5.2 Bandedge Measurement Plots for ThinkPad X30 Series




Date: 4.FEB.2004 10:39:43

Plot 8-1-1 Ch.1 2412MHz TX. DSSS 1Mbps (Peak). X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 102.83 dBμV VBW 10 Hz
117 dBμV 2.41129860 GHz SWT 25 s Unit dBμV




Date: 4.FEB.2004 10:38:57

Plot 8-1-2 Ch.1 2412MHz TX, DSSS 1Mbps (Average), X30 Series




Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 107.77 dBμV VBW 1 MHz
117 dBμV 2.46310220 GHz SWT 5 ms Unit dBμV



Date: 4.FEB.2004 10:42:56

Plot 8-1-3 Ch.11 2462MHz TX, DSSS 1Mbps (Peak), X30 Series




Date: 4.FEB.2004 10:42:12

Plot 8-1-4 Ch.11 2462MHz TX, DSSS 1Mbps (Average), X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 111.05 dBμV VBW 1 MHz
117 dBμV 2.41189980 GHz SWT 5 ms Unit dBμV




Date: 4.FEB.2004 10:35:36

Plot 8-2-1 Ch.1 2412MHz TX. DSSS 5.5Mbps (Peak). X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 92.92 dBμV VBW 10 Hz
117 dBμV 2.41310220 GHz SWT 25 s Unit dBμV




Date: 4.FEB.2004 10:36:45

Plot 8-2-2 Ch.1 2412MHz TX, DSSS 5.5Mbps (Average), X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 109.57 dBμV VBW 1 MHz
117 dBμV 2.46189980 GHz SWT 5 ms Unit dBμV




Date: 4.FEB.2004 10:46:01

Plot 8-2-3 Ch.11 2462MHz TX, DSSS 5.5Mbps (Peak), X30 Series



Ref Lvl 117 dBμV
Marker 1 [T1] 91.65 dBμV
2.46109820 GHz
RBW 1 MHz
VBW 10 Hz
SWT 25 s
RF Att 20 dB
Unit dBμV




Date: 4.FEB.2004 10:44:57

Plot 8-2-4 Ch.11 2462MHz TX, DSSS 5.5Mbps (Average), X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 112.24 dBμV VBW 1 MHz
117 dBμV 2.41230060 GHz SWT 5 ms Unit dBμV




Date: 4.FEB.2004 10:32:51

Plot 8-3-1 Ch.1 2412MHz TX, DSSS 11Mbps (Peak), X30 Series



Ref Lvl 117 dBμV
Marker 1 [T1] 85.51 dBμV
2.41129860 GHz
RBW 1 MHz
VBW 10 Hz
SWT 25 s
RF Att 20 dB
Unit dBμV




Date: 4.FEB.2004 10:34:33

Plot 8-3-2 Ch.1 2412MHz TX. DSSS 11Mbps (Average). X30 Series




Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 110.86 dBμV VBW 1 MHz
117 dBμV 2.46189980 GHz SWT 5 ms Unit dBμV



Date: 4.FEB.2004 10:47:57

Plot 8-3-3 Ch.11 2462MHz TX, DSSS 11Mbps (Peak), X30 Series




Date: 4.FEB.2004 10:47:34

Plot 8-3-4 Ch.11 2462MHz TX, DSSS 11Mbps (Average), X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 106.50 dBμV VBW 1 MHz
117 dBμV 2.41590782 GHz SWT 5 ms Unit dBμV




Date: 4.FEB.2004 11:16:00

Plot 8-4-1 Ch.1 2412MHz TX, OFDM 6Mbps (Peak), X30 Series



Ref Lvl 117 dBμV
Marker 1 [T1] 92.01 dBμV
2.41350301 GHz
RBW 1 MHz
RF Att 20 dB
VBW 10 Hz
SWT 25 s
Unit dBμV




Date: 4.FEB.2004 11:16:53

Plot 8-4-2 Ch.1 2412MHz TX, OFDM 6Mbps (Average), X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 104.93 dBμV VBW 1 MHz
117 dBμV 2.45909419 GHz SWT 5 ms Unit dBμV




Date: 4.FEB.2004 11:13:25

Plot 8-4-3 Ch.11 2462MHz TX. OFDM 6Mbps (Peak). X30 Series



Ref Lvl 117 dBμV
Marker 1 [T1] 91.24 dBμV
2.46049699 GHz
RBW 1 MHz
VBW 10 Hz
SWT 25 s
RF Att 20 dB
Unit dBμV




Date: 4.FEB.2004 11:14:35

Plot 8-4-4 Ch.11 2462MHz TX. OFDM 6Mbps (Average). X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 106.59 dBμV VBW 1 MHz
117 dBμV 2.40869339 GHz SWT 5 ms Unit dBμV




Date: 4.FEB.2004 11:17:52

Plot 8-5-1 Ch.1 2412MHz TX. OFDM 18Mbps (Peak). X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 85.66 dBμV VBW 10 Hz
117 dBμV 2.41350301 GHz SWT 25 s Unit dBμV




Date: 4.FEB.2004 11:18:42

Plot 8-5-2 Ch.1 2412MHz TX. OFDM 18Mbps (Average). X30 Series




Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 105.45 dBμV VBW 1 MHz
117 dBμV 2.46149900 GHz SWT 5 ms Unit dBμV



Date: 4.FEB.2004 11:10:26

Plot 8-5-3 Ch.11 2462MHz TX, OFDM 18Mbps (Peak), X30 Series




Date: 4.FEB.2004 11:11:36

Plot 8-5-4 Ch.11 2462MHz TX, OFDM 18Mbps (Average), X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 106.63 dBμV VBW 1 MHz
117 dBμV 2.40749098 GHz SWT 5 ms Unit dBμV




Date: 4.FEB.2004 11:20:05

Plot 8-6-1 Ch.1 2412MHz TX. OFDM 54Mbps (Peak). X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 117 dBμV 73.97 dBμV VBW 10 Hz
2.41350301 GHz SWT 25 s Unit dBμV




Date: 4.FEB.2004 11:21:01

Plot 8-6-2 Ch.1 2412MHz TX. OFDM 54Mbps (Average). X30 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 105.80 dBμV VBW 1 MHz
117 dBμV 2.46109820 GHz SWT 5 ms Unit dBμV




Date: 4.FEB.2004 11:08:29

Plot 8-6-3 Ch.11 2462MHz TX, OFDM 54Mbps (Peak), X30 Series




Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 73.37 dBμV VBW 10 Hz
117 dBμV 2.46069739 GHz SWT 25 s Unit dBμV



Date: 4.FEB.2004 11:09:36

Plot 8-6-4 Ch.11 2462MHz TX, OFDM 54Mbps (Average). X30 Series

8.5.3 Bandedge Measurement Plots for ThinkPad X40 Series




Date: 28. JAN. 2004 09:01:35

Plot 8-7-1 Ch.1 2412MHz TX, DSSS 1Mbps (Peak), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 105.83 dBμV VBW 10 Hz
117 dBμV 2.41290180 GHz SWT 25 s Unit dBμV




Date: 28.JAN.2004 09:02:53

Plot 8-7-2 Ch.1 2412MHz TX, DSSS 1Mbps (Average), X40 Series




Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 112.16 dBμV VBW 1 MHz
117 dBμV 2.46310220 GHz SWT 5 ms Unit dBμV



Date: 28.JAN.2004 08:50:05

Plot 8-7-3 Ch.11 2462MHz TX, DSSS 1Mbps (Peak), X40 Series




Date: 28. JAN. 2004 09:47:44

Plot 8-7-4 Ch.11 2462MHz TX, DSSS 1Mbps (Average), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 114.07 dBμV VBW 1 MHz
117 dBμV 2.41270140 GHz SWT 5 ms Unit dBμV




Date: 28.JAN.2004 09:00:18

Plot 8-8-1 Ch.1 2412MHz TX. DSSS 5.5Mbps (Peak). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 95.85 dBμV VBW 10 Hz
117 dBμV 2.41109820 GHz SWT 25 s Unit dBμV




Date: 28.JAN.2004 08:59:47

Plot 8-8-2 Ch.1 2412MHz TX, DSSS 5.5Mbps (Average), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 114.07 dBμV VBW 1 MHz
117 dBμV 2.46189980 GHz SWT 5 ms Unit dBμV




Date: 28.JAN.2004 08:51:09

Plot 8-8-3 Ch.11 2462MHz TX, DSSS 5.5Mbps (Peak), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 95.57 dBμV VBW 10 Hz
117 dBμV 2.46109820 GHz SWT 25 s Unit dBμV




Date: 28.JAN.2004 08:52:24

Plot 8-8-4 Ch.11 2462MHz TX, DSSS 5.5Mbps (Average), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 115.37 dBμV VBW 1 MHz
117 dBμV 2.41169940 GHz SWT 5 ms Unit dBμV




Date: 28.JAN.2004 08:57:33

Plot 8-9-1 Ch.1 2412MHz TX, DSSS 11Mbps (Peak), X40 Series



Ref Lvl 117 dBμV
Marker 1 [T1] 88.21 dBμV
2.41149900 GHz
RBW 1 MHz
VBW 10 Hz
SWT 25 s
RF Att 20 dB
Unit dBμV




Date: 28.JAN.2004 08:58:33

Plot 8-9-2 Ch.1 2412MHz TX. DSSS 11Mbps (Average). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 114.87 dBμV VBW 1 MHz
117 dBμV 2.46350301 GHz SWT 5 ms Unit dBμV




Date: 28.JAN.2004 08:54:52

Plot 8-9-3 Ch.11 2462MHz TX. DSSS 11Mbps (Peak). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 88.09 dBμV VBW 10 Hz
117 dBμV 2.46149900 GHz SWT 25 s Unit dBμV




Date: 28.JAN.2004 08:54:14

Plot 8-9-4 Ch.11 2462MHz TX, DSSS 11Mbps (Average), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 109.45 dBμV VBW 1 MHz
117 dBμV 2.41510621 GHz SWT 5 ms Unit dBμV




Date: 27.JAN.2004 19:16:29

Plot 8-10-1 Ch.1 2412MHz TX. OFDM 6Mbps (Peak). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 95.09 dBμV VBW 10 Hz
117 dBμV 2.41330261 GHz SWT 25 s Unit dBμV




Date: 27.JAN.2004 19:15:18

Plot 8-10-2 Ch.1 2412MHz TX. OFDM 6Mbps (Average). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 108.75 dBμV VBW 1 MHz
117 dBμV 2.45929459 GHz SWT 5 ms Unit dBμV




Date: 27.JAN.2004 19:08:58

Plot 8-10-3 Ch.11 2462MHz TX, OFDM 6Mbps (Peak), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 94.63 dBμV VBW 10 Hz
117 dBμV 2.46350301 GHz SWT 25 s Unit dBμV




Date: 27.JAN.2004 19:06:57

Plot 8-10-4 Ch.11 2462MHz TX, OFDM 6Mbps (Average). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 109.53 dBμV VBW 1 MHz
117 dBμV 2.41129860 GHz SWT 5 ms Unit dBμV




Date: 27.JAN.2004 19:18:00

Plot 8-11-1 Ch.1 2412MHz TX, OFDM 18Mbps (Peak), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 117 dBμV 88.52 dBμV VBW 10 Hz
2.41330261 GHz SWT 25 s Unit dBμV




Date: 27.JAN.2004 19:18:50

Plot 8-11-2 Ch.1 2412MHz TX, OFDM 18Mbps (Average), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 110.89 dBμV VBW 1 MHz
117 dBμV 2.46450501 GHz SWT 5 ms Unit dBμV




Date: 27.JAN.2004 19:10:25

Plot 8-11-3 Ch.11 2462MHz TX. OFDM 18Mbps (Peak). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 88.14 dBμV VBW 10 Hz
117 dBμV 2.46330261 GHz SWT 25 s Unit dBμV




Date: 27.JAN.2004 19:11:19

Plot 8-11-4 Ch.11 2462MHz TX. OFDM 18Mbps (Average). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 109.62 dBμV VBW 1 MHz
117 dBμV 2.41350301 GHz SWT 5 ms Unit dBμV




Date: 27.JAN.2004 19:21:09

Plot 8-12-1 Ch.1 2412MHz TX, OFDM 54Mbps (Peak), X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 117 dBμV 76.55 dBμV VBW 10 Hz
2.41330261 GHz SWT 25 s Unit dBμV




Date: 27.JAN.2004 19:20:40

Plot 8-12-2 Ch.1 2412MHz TX. OFDM 54Mbps (Average). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 110.96 dBμV VBW 1 MHz
117 dBμV 2.46370341 GHz SWT 5 ms Unit dBμV




Date: 27.JAN.2004 19:13:25

Plot 8-12-3 Ch.11 2462MHz TX. OFDM 54Mbps (Peak). X40 Series



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 76.23 dBμV VBW 10 Hz
117 dBμV 2.46350301 GHz SWT 25 s Unit dBμV



Date: 27.JAN.2004 19:12:33

Plot 8-12-4 Ch.11 2462MHz TX. OFDM 54Mbps (Average). X40 Series