



12. Radio Frequency Exposure

12.1.Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

12.2.EUT Specification

Frequency band (Operating)	☐ WLAN: 2412MHz ~ 2462MHz ☒ WLAN: 5150MHz ~ 5250MHz ☒ WLAN: 5250MHz ~ 5350MHz ☒ WLAN: 5470MHz ~ 5725MHz ☒ WLAN: 5725MHz ~ 5850MHz ☐ Bluetooth: 2402MHz ~ 2480MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Evaluation applied	☐ Blanket 1 mW Blanket Exemption ☒ MPE-based Exemption ☐ SAR-based Exemption
Remark: The maximum conducted output power is <u>24.97dBm (313.765mW)</u> at <u>5745MHz</u> (with <u>5.00dBi</u> antenna gain.)	

**12.3.Result**

Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Max.Tune up e.r.p. Power (dBm)	Max. Tune up e.r.p power (mW)	Limit (mW)
5230	21.88	22.38	5	25.23	333.43	3060
5270	23.16	23.66	5	26.51	447.71	3060
5690	23.84	24.34	5	27.19	523.60	3060
5745	24.97	25.47	5	28.32	679.20	3060

No non-compliance noted.

Maximum Permissible Exposure (Co-location)

Modulation Type	Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Antenna Gain(dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	MPE Ratio
11g	2437	27.20	27.70	3.50	20.00	804.00	3060.00	0.2627
GFSK(1Mbps)	2480	9.33	9.83	-1.00	20.00	4.66	3060.00	0.0015
11a	5745	24.97	25.47	5.00	20.00	679.20	3060.00	0.2220
Co-location Total								0.4862
Σ MPE ratios Limit								1.00

-----THE END OF REPORT-----