

Lucent Technologies Inc.
101 Crawfords Corner Rd.
P. O. Box 3030
Holmdel, NJ 07733-3030

November 20, 2000

Federal Communications Commission
Office of Engineering and Technology
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, Maryland 21046

Dear Examiner:

In accordance with Parts 2 and 22 of the Commission's Rules and Regulations, we are submitting herewith, statements and supporting data to show compliance with the requirements of the Commission for Certification of the Lucent Technologies Individual Carrier Linear Amplifier (ICLA) FCC ID: **AS5CMP-44**. The ICLA shall be used in Lucent Technologies, Inc. **FLEXENT**® Land Station Cellular system using Code Division Multiple Access (CDMA) technology, for use in Domestic Public Cellular Telecommunication Service. The ICLA is designed to provide 24 watts (43.8 dBm) to antenna port connection (J4).

The data summarized below is in the form presently used by the Commission's Radio Equipment List.

Manufacturer	Lucent Technologies Inc.
Equipment Identification	AS5CMP-44
Rules Part Number	22 (H)
Frequency Range	870.48 – 878.49 MHz and 881.52 – 888.51 MHz
Output Power	0.00008 to 24 Watts (-11 dBm to 43.8 dBm) Varied By Software
Frequency Tolerance	+/- 1.5 ppm
Emission Designator	1M23G9W

The FLEXENT Cellular Radio Frequency Unit (RFU) Cabinet uses ICLA. It is designed to the limitations specified in Part 22 (H). Whenever possible, the test procedures defined in CFR 47 Parts 2 and 22 were followed. Because some of the characteristics cannot be tested using the requirements in CFR 47, for those characteristics, IS 95 and IS 97 were used as evaluation criteria in this application. The ICLA has a maximum RF power output of 43.8 dBm and the power level for this application is 43.8 dBm. The ICLA gets input RF signal from a Predistortion CDMA Baseband Radio (PCBR) (FCC ID: **AS5CMP-43**) and the ICLA RF output is filtered by a transmit filter for specific cellular bands. The PCBR (**FCC ID: AS5CMP-43**) is being co-filed with the ICLA. The typical output level necessary for the PCBR for maximum output from the ICLA is 8.4 dBm. The actual power level delivered from the PCBR to ICLA is under software control.

Filed herewith is FCC Form 731 (Application for Equipment Certification – Radio Frequency Devices) and the required attachments. These exhibits contain the technical data, and the required statements and documents for equipment certification. The Global Product Compliance Laboratory, of Lucent Technologies Inc. will comply with request for additional information should the need arise.

Sincerely,

Dheena Moongilan
Distinguished Member of Technical Staff
Global Product Compliance Laboratory
phone: (732) 332-6003
email: moongilan@lucent.com

November 20, 2000

TABLE OF CONTENTS

	COVER LETTER
	Cover Letter
	Table of Content
	Letter for Confidential Treatment of Exhibits
	ATTESTATION STATEMENT
	Qualifications and Certifications
Section 2.911 (d)	Manufacturers, Identification
Section 2.1033 (c) (1,2)	Emissions, Frequency Range, Power Level
Section 2.1033 (c) (4-7)	
	USERS MANUAL
Section 2.1033 (c) (3)	Users Manual
	PARTS LIST/TUNE-UP PROCEDURE
Section 2.1033 (c) (9)	Tune-Up Procedure
	OPERATIONAL DESCRIPTION
Section 2.1033 (c) (13)	Description of Modulation System
	SCHEMATICS
Section 2.1033 (c) (10)	Schematic
	Block Diagrams
Section 2.1043 (b) (2)	
	ID LABEL/LOCATION INFORMATION
Section 2.1033 (c) (11) and 2.925 (a) (1)	Drawing of FCC ID
	EXTERNAL PHOTOS
Section 2.1033 (c) (12)	External Photos
	INTERNAL PHOTOS
Section 2.1033 (c) (12)	Internal Photos
	TEST REPORT
Section 2.1033 (c) (8)	Measurement of DC Power
Section 2.1033 (c) (14)	Listing of Required Measurements
Section 2.1046	Measurement of Radio Frequency Power Output
Section 2.1047	Measurement of Modulation Characteristics
Section 2.1049 and Section 22.900(d)(2)	Measurement of Occupied Bandwidth
Section 2.1051	Measurement of Spurious Emissions at Antenna
Section 2.1053	Field Strength of Spurious Radiation
Section 2.1055	Measurement of Frequency Stability
Section 2.1057	Frequency Spectrum to be Investigated
	Test Instruments Used for Test

Global Product Compliance Laboratory
101 Crawfords Corner Road
Holmdel, NJ 07733-3030

November 20, 2000

**Subject: Confidential Treatment for Internal Photos and Schematic -
FCC ID: AS5CMP-44.**

Dear Examiner:

The 'Flexent Cellular Radio Frequency Unit (RFU) Cabinet containing FCC ID AS5CMP-43, and FCC ID AS5CMP-44 will not be sold to the general public, but restricted to network operators. The Lucent Technologies holds the proprietary rights of equipment construction. The general public does not have access to Internal Construction of Flexent RFU. The schematics and block diagrams contain Lucent Technologies Proprietary information. Therefore I would like to request you to treat the following as confidential.

- (1) Internal photos
- (2) Schematics, Circuit descriptions and Block Diagrams

Thanks.

Sincerely,

Dheena Moongilan
Distinguished Member of Technical Staff
Bldg. 11B, Room 184

