





2.5. Conducted Spurious Emissions


2.5.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

Additional requirement for LTE Band 7:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 55 + 10 log(P) dB. This calculated to be -25dBm.

2.5.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 500hm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.5.3. Test procedure

KDB 971168 D01v03 Section 6.0 and ANSI/TIA-603-E-2016.

2.5.4. Test Result





LTE Band 2 CSE 1.4MHz/QPSK/Low CH 1.4MHz/16QAM/Low CH OR RL RF SO Q AC Center Freq 10.015000000 GHz PNO: Fast | Free Run | Free R enter Freq 10.015000000 GHz PN0: Fast (ECalind now #Atten: 20 dB Avg Type: RMS Avg|Hold: 58/100 Avg Type: RMS Avg|Hold: 60/100 Ref Offset 26.5 dB Ref 20.00 dBm Ref Offset 26.5 dB Ref 20.00 dBm Center Free 10.015000000 GH Center Free 10.015000000 GH Stop Fre CF Step 1.997000000 GHz <u>tuto</u> Man CF Ste 1.997000000 GH uto Ma Freq Offse Freq Offse 1.4MHz/QPSK/Mid CH 1.4MHz/16QAM/Mid CH Avg Type: RMS Avg|Hold: 56/100 Avg Type: RMS Avg|Hold: 58/100 r Freg 10.015000000 GHz r Freg 10.015000000 GHz Ref Offset 26.5 dB Ref 20.00 dBm Ref Offset 26.5 dB Ref 20.00 dBm Center Fre Center Free Stop Fre 1.879 2 GHz 16.935 6 GHz 22.022 dBn -26.539 dBn Freq Offse Freq Offse 1.4MHz/QPSK/High CH 1.4MHz/16QAM/High CH FF | S0 Q AC | r Freq 10.015000000 GHz PNO: Fast | Trig: Free Run | ##tten: 20 dB | Special Continuous | Special Avg Type: RMS Avg|Hold: 51/100 Avg Type: RMS Avg|Hold: 57/100 Ref Offset 26.5 dB Ref 20.00 dBm Ref Offset 26.5 dB Ref 20.00 dBm Center Fre Center Fre Stop Fre Freq Offse Freq Offse





