




# TEST REPORT

Report No.....: CHTEW19050130 Report Verification: 

Project No.....: SHT1904069805EW

FCC ID.....: 2AK4CPP20US

Applicant's name.....: Petcube, Inc.

Address.....: 2711 Centerville Road, Suite 400, Wilmington Delaware United States 19808

Manufacturer.....: Petcube, Inc.

Address.....: 2711 Centerville Road, Suite 400, Wilmington Delaware United States 19808

Test item description.....: Petcube Play 2

Trade Mark.....: Petcube

Model/Type reference.....: PP20US

Listed Model(s).....: -

Standard.....: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample.....: May 13, 2019

Date of testing.....: May 13, 2019- May 29, 2019

Date of issue.....: May 30, 2019

Result.....: PASS

Compiled by  
(position+printedname+signature)....: File administrators Echo Wei

*Echo Wei*

Supervised by  
(position+printedname+signature)....: Project Engineer Jerry Zhao

*Jerry Zhao*

Approved by  
(position+printedname+signature)....: RF Manager Hans Hu

*Hans Hu*

Testing Laboratory Name.....: Shenzhen Huatongwei International Inspection Co., Ltd.

Address.....: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

*The test report merely correspond to the test sample.*

## Contents

<b><u>1.</u></b>	<b><u>TEST STANDARDS AND REPORT VERSION</u></b>	<b><u>3</u></b>
1.1.	Test Standards	3
1.2.	Report version	3
<b><u>2.</u></b>	<b><u>TEST DESCRIPTION</u></b>	<b><u>4</u></b>
<b><u>3.</u></b>	<b><u>SUMMARY</u></b>	<b><u>5</u></b>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<b><u>4.</u></b>	<b><u>TEST ENVIRONMENT</u></b>	<b><u>7</u></b>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<b><u>5.</u></b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b><u>11</u></b>
5.1.	Antenna requirement	11
5.2.	Conducted Emissions (AC Main)	12
5.3.	Conducted Peak Output Power	15
5.4.	Power Spectral Density	16
5.5.	6dB bandwidth	20
5.6.	Restricted band	24
5.7.	Band edge and Spurious Emissions (conducted)	28
5.8.	Spurious Emissions (radiated)	41
<b><u>6.</u></b>	<b><u>TEST SETUP PHOTOS</u></b>	<b><u>47</u></b>
<b><u>7.</u></b>	<b><u>EXTERANAL AND INTERNAL PHOTOS</u></b>	<b><u>48</u></b>

## 1. TEST STANDARDS AND REPORT VERSION

### 1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 15.247 Meas Guidance v05](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

### 1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-05-30	Original

## 2. TEST DESCRIPTION

Test Item	FCC Rule	Result	Test Engineer
Antenna requirement	15.203/15.247(c)	PASS	JiongSheng.Feng
Line Conducted Emissions (AC Main)	15.207	PASS	Zhiwei Liu
Conducted Peak Output Power	15.247(b)(3)	PASS	JiongSheng.Feng
Power Spectral Density	15.247(e)	PASS	JiongSheng.Feng
6dB Bandwidth	15.247(a)(2)	PASS	JiongSheng.Feng
Restricted band	15.247(d)/15.205	PASS	JiongSheng.Feng
Spurious Emissions	15.247(d)/15.209	PASS	Tony Duan

Note: The measurement uncertainty is not included in the test result.

### 3. SUMMARY

#### 3.1. Client Information

Applicant:	Petcube, Inc.
Address:	2711 Centerville Road,Suite 400,Wilmington Delaware United States 19808
Manufacturer:	Petcube, Inc.
Address:	2711 Centerville Road,Suite 400,Wilmington Delaware United States 19808

#### 3.2. Product Description

Name of EUT:	Petcube Play 2
Trade Mark:	Petcube
Model No.:	PP20US
Listed Model(s):	-
Power supply:	DC 5V, 2A
Adapter information:	-
Hardware version:	v2.1.x.1.5
Software version:	v2.8.0.3560
<b>WIFI</b>	
Supported type:	802.11b/802.11g/802.11n(HT20)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)
Operation frequency:	2412MHz~2462MHz
Channel number:	11
Channel separation:	5MHz
Antenna type:	PCB antenna
Antenna gain:	0.5dB

### 3.3. Operation state

#### ➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

802.11b/g/n(HT20)	
Channel	Frequency (MHz)
01	2412
02	2417
...	...
06	2437
...	...
10	2457
11	2462

#### ➤ Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit (duty cycle>98%).
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit(duty cycle>98%). The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data Recorded in the report.

### 3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○	/	Manufacturer:	/
		Model No.:	/
○	/	Manufacturer:	/
		Model No.:	/

### 3.5. Modifications

No modifications were implemented to meet testing criteria.

## **4. TEST ENVIRONMENT**

### **4.1. Address of the test laboratory**

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

### **4.2. Test Facility**

#### **CNAS-Lab Code: L1225**

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### **A2LA-Lab Cert. No.: 3902.01**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### **FCC-Registration No.: 762235**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

#### **IC-Registration No.:5377B-1**

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B-1.

#### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

### 4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

### 4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.51 dB	(1)
Conducted spurious emissions 9kHz~40GHz	0.63 dB	(1)
Conducted Disturbance 150kHz~30MHz	3.02 dB	(1)
Radiated Emissions below 1GHz	4.90 dB	(1)
Radiated Emissions above 1GHz	4.96 dB	(1)
Occupied Bandwidth	70 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .



#### 4.5. Equipments Used during the Test

● Conducted Emission						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	ESCI	101247	2018/10/27	2019/10/26
●	Artificial Mains	SCHWARZBECK	NNLK 8121	573	2018/10/27	2019/10/26
●	Pulse Limiter	R&S	ESH3-Z2	100499	2018/10/27	2019/10/26
●	RF Connection Cable	HUBER+SUHNER	EF400	N/A	2018/11/15	2019/11/14
●	Test Software	R&S	ES-K1	N/A	N/A	N/A
○	Single Balanced Telecom Pair ISN	FCC	FCC-TLISN-T2-02	20371	2018/10/28	2019/10/27
○	Two Balanced Telecom Pairs ISN	FCC	FCC-TLISN-T4-02	20373	2018/10/28	2019/10/27
○	Four Balanced Telecom Pairs ISN	FCC	FCC-TLISN-T8-02	20375	2018/10/28	2019/10/27
○	V-Network	R&S	ESH3-Z6	100211	2018/10/27	2019/10/26
○	V-Network	R&S	ESH3-Z6	100210	2018/10/27	2019/10/26
○	2-Line V-Network	R&S	ESH3-Z5	100049	2018/10/27	2019/10/26
● Radiated Emission-6th test site						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	SAC-3m-02	N/A	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	ESCI	100900	2018/10/28	2019/10/27
●	Loop Antenna	R&S	HFH2-Z2	100020	2017/11/20	2020/11/19
●	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	546	2017/04/05	2020/04/04
●	Pre-Amplifier	SCHWARZBECK	BBV 9742	N/A	2018/11/15	2019/11/14
●	RF Connection Cable	HUBER+SUHNER	N/A	N/A	2018/09/28	2019/09/27
●	RF Connection Cable	HUBER+SUHNER	SUCOFLEX104	501184/4	2018/09/28	2019/09/27
●	Test Software	R&S	ES-K1	N/A	N/A	N/A
●	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
●	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A
● Radiated emission-7th test site						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	SAC-3m-01	N/A	2018/09/30	2021/09/29
●	Spectrum Analyzer	R&S	FSP40	100597	2018/10/27	2019/10/26
●	Horn Antenna	SCHWARZBECK	9120D	1011	2017/03/27	2020/03/26
●	Pre-amplifier	BONN	BLWA0160-2M	1811887	2018/11/14	2019/11/13
●	Pre-amplifier	CD	PAP-0102	12004	2018/11/14	2019/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	BBV 9718	9718-248	2019/04/28	2020/04/27
●	RF Connection Cable	HUBER+SUHNER	RE-7-FH	N/A	2018/11/15	2019/11/14
●	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	2018/11/15	2019/11/14
●	Test Software	Audix	E3	N/A	N/A	N/A
●	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
●	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A

● RF Conducted Method						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2018/10/28	2019/10/27
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2018/09/29	2019/09/28
●	OSP	R&S	OSP120	101317	N/A	N/A
○	Radio communication tester	R&S	CMW500	137688-Lv	2018/09/29	2019/09/28
○	Test software	Tonscend	JS1120-1(LTE)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-2(WIFI)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-3(WCDMA)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-4(GSM)	N/A	N/A	N/A

## 5. TEST CONDITIONS AND RESULTS

### 5.1. Antenna requirement

#### REQUIREMENT:

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

#### TEST RESULTS

☒ Passed      ☐ Not Applicable

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



## 5.2. Conducted Emissions (AC Main)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

### TEST MODE:

Please refer to the clause 3.3

### TEST RESULTS


☒ Passed ☐ Not Applicable

Note:

- 1) Transd=Cable lose+ Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit -Level

Test Line:

L

**MEASUREMENT RESULT: "GM1905155016\_fin"**

5/15/2019 1:32PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.159000	43.30	9.9	66	22.2	QP	L1	GND
1.167000	41.70	9.9	56	14.3	QP	L1	GND
1.945500	43.10	9.9	56	12.9	QP	L1	GND
2.724000	44.80	9.9	56	11.2	QP	L1	GND
3.502500	46.50	9.9	56	9.5	QP	L1	GND
4.281000	46.70	9.9	56	9.3	QP	L1	GND


**MEASUREMENT RESULT: "GM1905155016\_fin2"**

5/15/2019 1:32PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
1.167000	37.40	9.9	46	8.6	AV	L1	GND
1.945500	38.70	9.9	46	7.3	AV	L1	GND
2.724000	40.30	9.9	46	5.7	AV	L1	GND
3.502500	42.20	9.9	46	3.8	AV	L1	GND
4.281000	42.40	9.9	46	3.6	AV	L1	GND
5.059500	37.80	10.0	50	12.2	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM1905155015\_fin"**

5/15/2019 1:29PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.231000	33.80	9.9	62	28.6	QP	N	GND
0.348000	34.80	9.9	59	24.2	QP	N	GND
1.941000	36.10	9.9	56	19.9	QP	N	GND
2.719500	38.90	9.9	56	17.1	QP	N	GND
3.498000	41.50	9.9	56	14.5	QP	N	GND
4.272000	32.90	9.9	56	23.1	QP	N	GND

**MEASUREMENT RESULT: "GM1905155015\_fin2"**

5/15/2019 1:29PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.388500	33.50	9.9	48	14.6	AV	N	GND
1.167000	34.70	9.9	46	11.3	AV	N	GND
1.945500	36.10	9.9	46	9.9	AV	N	GND
2.719500	34.90	9.9	46	11.1	AV	N	GND
3.498000	37.90	9.9	46	8.1	AV	N	GND
4.276500	39.00	9.9	46	7.0	AV	N	GND

### 5.3. Conducted Peak Output Power

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47 CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

#### TEST MODE:

Please refer to the clause 3.3

#### TEST RESULTS

☒ Passed ☐ Not Applicable

Type	Channel	Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
802.11b	01	14.85	12.74	≤30.00	Pass
	06	15.20	12.91		
	11	15.30	12.72		
802.11g	01	15.53	14.36	≤30.00	Pass
	06	15.93	14.77		
	11	16.11	14.87		
802.11n(HT20)	01	15.88	14.36	≤30.00	Pass
	06	15.92	14.46		
	11	15.88	14.53		


## 5.4. Power Spectral Density

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:  
Center frequency=DTS channel center frequency  
Span =1.5 times the DTS bandwidth  
RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW  
Sweep time = auto couple  
Detector = peak  
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST MODE:

Please refer to the clause 3.3


### TEST RESULTS


☒ Passed      ☐ Not Applicable


Type	Channel	Power Spectral Density (dBm/30KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-4.69	≤8.00	Pass
	06	-4.43		
	11	-3.40		
802.11g	01	-8.67	≤8.00	Pass
	06	-8.41		
	11	-8.10		
802.11n(HT20)	01	-8.01	≤8.00	Pass
	06	-8.25		
	11	-8.15		

Test plot as follows:










## 5.5. 6dB bandwidth

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):**

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).  
 Center Frequency = DTS channel center frequency  
 Span = 2 x DTS bandwidth  
 RBW = 100 kHz, VBW  $\geq$  3 x RBW  
 Sweep time = auto couple  
 Detector = Peak  
 Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

### TEST MODE:


Please refer to the clause 3.3


### TEST RESULTS

☒ Passed      ☐ Not Applicable

Type	Channel	6dB Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	8.58	$\geq 500$	Pass
	06	8.49		
	11	8.43		
802.11g	01	15.81	$\geq 500$	Pass
	06	15.78		
	11	15.75		
802.11n(HT20)	01	17.70	$\geq 500$	Pass
	06	17.73		
	11	17.76		

Test plot as follows:





Type:

802.11n(HT20)

CH01

**Spectrum**

Ref Level 20.50 dBm Offset 1.00 dB RBW 100 kHz  
Att 30 dB SWI 1.04 ms VBW 300 kHz Mode Auto Sweep

Count 500/500

1 Frequency Sweep

2 Marker Table

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		2.40318 GHz	-9.85 dBm		
M2	1		2.41449 GHz	-3.65 dBm		
D3	M1	1	17.7 MHz	-1.50 dB		

Date: 23 MAY 2019 11:55:23

CH06

**Spectrum**

Ref Level 20.50 dBm Offset 1.00 dB RBW 100 kHz  
Att 30 dB SWI 1.04 ms VBW 300 kHz Mode Auto Sweep

Count 500/500

1 Frequency Sweep

2 Marker Table

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		2.42812 GHz	-10.55 dBm		
M2	1		2.43949 GHz	-3.58 dBm		
D3	M1	1	17.73 MHz	0.71 dB		

Date: 23 MAY 2019 11:54:26

CH11

**Spectrum**

Ref Level 20.50 dBm Offset 1.00 dB RBW 100 kHz  
Att 30 dB SWI 1.04 ms VBW 300 kHz Mode Auto Sweep

Count 500/500

1 Frequency Sweep

2 Marker Table

Type	Ref	Trc	X-Value	Y-Value	Function	Function Result
M1	1		2.45312 GHz	-10.72 dBm		
M2	1		2.4623 GHz	-3.45 dBm		
D3	M1	1	17.76 MHz	-0.03 dB		

Date: 23 MAY 2019 11:26:21


## 5.6. Restricted band

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

### TEST CONFIGURATION



### TEST PROCEDURE

- 1) The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2) The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3) The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- 4) The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- 5) The receiver set as follow:  
RBW=1MHz, VBW=3MHz PEAK detector for Peak value.  
RBW=1MHz, VBW=3MHz RMS detector for Average value.

### TEST MODE:

Please refer to the clause 3.3

### TEST RESULTS

☒ Passed ☐ Not Applicable

Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor



802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	14.00	28.05	7.73	0.00	49.78	74.00	-24.22	Vertical	Peak
2390.01	13.81	27.65	7.84	0.00	49.30	74.00	-24.70	Vertical	Peak
2310.00	14.55	28.05	7.73	0.00	50.33	74.00	-23.67	Horizontal	Peak
2390.01	14.80	27.65	7.84	0.00	50.29	74.00	-23.71	Horizontal	Peak
2310.00	10.76	28.05	7.73	0.00	46.54	54.00	-7.46	Vertical	Average
2390.01	10.45	27.65	7.84	0.00	45.94	54.00	-8.06	Vertical	Average
2310.00	10.75	28.05	7.73	0.00	46.53	54.00	-7.47	Horizontal	Average
2390.01	10.46	27.65	7.84	0.00	45.95	54.00	-8.05	Horizontal	Average

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	13.58	27.26	8.04	0.00	48.88	74.00	-25.12	Vertical	Peak
2500.00	13.54	27.20	8.08	0.00	48.82	74.00	-25.18	Vertical	Peak
2483.49	13.25	27.26	8.04	0.00	48.55	74.00	-25.45	Horizontal	Peak
2500.00	14.52	27.20	8.08	0.00	49.80	74.00	-24.20	Horizontal	Peak
2483.49	10.43	27.26	8.04	0.00	45.73	54.00	-8.27	Vertical	Average
2500.00	10.34	27.20	8.08	0.00	45.62	54.00	-8.38	Vertical	Average
2483.49	10.54	27.26	8.04	0.00	45.84	54.00	-8.16	Horizontal	Average
2500.00	10.42	27.20	8.08	0.00	45.70	54.00	-8.30	Horizontal	Average

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	14.30	28.05	7.73	0.00	50.08	74.00	-23.92	Vertical	Peak
2390.01	16.63	27.65	7.84	0.00	52.12	74.00	-21.88	Vertical	Peak
2310.00	13.41	28.05	7.73	0.00	49.19	74.00	-24.81	Horizontal	Peak
2390.01	15.53	27.65	7.84	0.00	51.02	74.00	-22.98	Horizontal	Peak
2310.00	10.76	28.05	7.73	0.00	46.54	54.00	-7.46	Vertical	Average
2390.01	12.40	27.65	7.84	0.00	47.89	54.00	-6.11	Vertical	Average
2310.00	10.76	28.05	7.73	0.00	46.54	54.00	-7.46	Horizontal	Average
2390.01	12.21	27.65	7.84	0.00	47.70	54.00	-6.30	Horizontal	Average

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	15.96	27.26	8.04	0.00	51.26	74.00	-22.74	Vertical	Peak
2500.00	13.18	27.20	8.08	0.00	48.46	74.00	-25.54	Vertical	Peak
2483.49	16.30	27.26	8.04	0.00	51.60	74.00	-22.40	Horizontal	Peak
2500.00	14.03	27.20	8.08	0.00	49.31	74.00	-24.69	Horizontal	Peak
2483.49	12.33	27.26	8.04	0.00	47.63	54.00	-6.37	Vertical	Average
2500.00	10.67	27.20	8.08	0.00	45.95	54.00	-8.05	Vertical	Average
2483.49	13.29	27.26	8.04	0.00	48.59	54.00	-5.41	Horizontal	Average
2500.00	10.91	27.20	8.08	0.00	46.19	54.00	-7.81	Horizontal	Average

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	14.80	28.05	7.73	0.00	50.58	74.00	-23.42	Vertical	Peak
2390.01	15.15	27.65	7.84	0.00	50.64	74.00	-23.36	Vertical	Peak
2310.00	13.28	28.05	7.73	0.00	49.06	74.00	-24.94	Horizontal	Peak
2390.01	15.00	27.65	7.84	0.00	50.49	74.00	-23.51	Horizontal	Peak
2310.00	10.80	28.05	7.73	0.00	46.58	54.00	-7.42	Vertical	Average
2390.01	11.72	27.65	7.84	0.00	47.21	54.00	-6.79	Vertical	Average
2310.00	10.75	28.05	7.73	0.00	46.53	54.00	-7.47	Horizontal	Average
2390.01	11.54	27.65	7.84	0.00	47.03	54.00	-6.97	Horizontal	Average

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	14.12	27.26	8.04	0.00	49.42	74.00	-24.58	Vertical	Peak
2500.00	13.82	27.20	8.08	0.00	49.10	74.00	-24.90	Vertical	Peak
2483.49	15.52	27.26	8.04	0.00	50.82	74.00	-23.18	Horizontal	Peak
2500.00	13.97	27.20	8.08	0.00	49.25	74.00	-24.75	Horizontal	Peak
2483.49	11.67	27.26	8.04	0.00	46.97	54.00	-7.03	Vertical	Average
2500.00	10.52	27.20	8.08	0.00	45.80	54.00	-8.20	Vertical	Average
2483.49	12.11	27.26	8.04	0.00	47.41	54.00	-6.59	Horizontal	Average
2500.00	10.70	27.20	8.08	0.00	45.98	54.00	-8.02	Horizontal	Average


## 5.7. Band edge and Spurious Emissions (conducted)

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure  
Center frequency=DTS channel center frequency  
The span = 1.5 times the DTS bandwidth.  
RBW = 100 kHz, VBW  $\geq 3 \times$  RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum PSD level  
  
Note: the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement  
Set the center frequency and span to encompass frequency range to be measured  
RBW = 100 kHz, VBW  $\geq 3 \times$  RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.



### TEST MODE:



Please refer to the clause 3.3




### TEST RESULTS

☒ Passed      ☐ Not Applicable

Test Item:	Bandedge	Type:	802.11 b																																										
CH01	<div><div><div><div>MultiView</div><div>Spectrum</div></div><div><div>Ref Level 20.00 dBm</div><div>Offset 1.00 dB</div><div>RBW 100 kHz</div><div>Att 30 dB</div><div>SWT 1.12 ms</div><div>VBW 300 kHz</div><div>Mode Auto Sweep</div><div>Count 300/300</div></div><div><div>Frequency Sweep</div><div><div><div>30 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>M1</div><div>-20.400 dBm</div></div></div><div><div>2.31 GHz</div><div>1001 pts</div><div>11.2 MHz/</div><div>2.422 GHz</div></div><div><div>2 Marker Table</div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.41288 GHz</td><td>-0.46 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-49.21 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-62.58 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-62.92 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.399376 GHz</td><td>-49.36 dBm</td><td></td><td></td></tr></table></div></div></div></div> <div>Date: 23 MAY 2019 11:08:38</div>			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.41288 GHz	-0.46 dBm			M2	1		2.4 GHz	-49.21 dBm			M3	1		2.39 GHz	-62.58 dBm			M4	1		2.31 GHz	-62.92 dBm			M5	1		2.399376 GHz	-49.36 dBm		
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.41288 GHz	-0.46 dBm																																									
M2	1		2.4 GHz	-49.21 dBm																																									
M3	1		2.39 GHz	-62.58 dBm																																									
M4	1		2.31 GHz	-62.92 dBm																																									
M5	1		2.399376 GHz	-49.36 dBm																																									
CH11	<div><div><div><div>MultiView</div><div>Spectrum</div></div><div><div>Ref Level 20.00 dBm</div><div>Offset 1.00 dB</div><div>RBW 100 kHz</div><div>Att 30 dB</div><div>SWT 1.03 ms</div><div>VBW 300 kHz</div><div>Mode Auto Sweep</div><div>Count 300/300</div></div><div><div>Frequency Sweep</div><div><div><div>30 dBm</div><div>0 dBm</div><div>-10 dBm</div><div>-20 dBm</div><div>-30 dBm</div><div>-40 dBm</div><div>-50 dBm</div><div>-60 dBm</div><div>-70 dBm</div></div><div><div>M1</div><div>-19.410 dBm</div></div></div><div><div>2.452 GHz</div><div>1001 pts</div><div>4.8 MHz/</div><div>2.5 GHz</div></div><div><div>2 Marker Table</div><table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.462573 GHz</td><td>0.59 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-61.65 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-62.20 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.4856 GHz</td><td>-59.87 dBm</td><td></td><td></td></tr></table></div></div></div></div> <div>Date: 23 MAY 2019 11:09:57</div>			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.462573 GHz	0.59 dBm			M2	1		2.4835 GHz	-61.65 dBm			M3	1		2.5 GHz	-62.20 dBm			M4	1		2.4856 GHz	-59.87 dBm									
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.462573 GHz	0.59 dBm																																									
M2	1		2.4835 GHz	-61.65 dBm																																									
M3	1		2.5 GHz	-62.20 dBm																																									
M4	1		2.4856 GHz	-59.87 dBm																																									


Test Item:	Bandedge	Type:	802.11 g																																										
CH01	<div><div>MultiViewSpectrum</div><div>Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SW 1.12 ms VBW 300 kHz Mode Auto Sweep Count 300/300</div><div>Frequency Sweep</div><div><p>2 Marker Table</p><table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.41221 GHz</td><td>-3.37 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-46.57 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-57.95 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-64.26 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.399936 GHz</td><td>-47.91 dBm</td><td></td><td></td></tr></tbody></table><p>Date: 23 MAY 2019 11:41:02</p></div></div>			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.41221 GHz	-3.37 dBm			M2	1		2.4 GHz	-46.57 dBm			M3	1		2.39 GHz	-57.95 dBm			M4	1		2.31 GHz	-64.26 dBm			M5	1		2.399936 GHz	-47.91 dBm		
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.41221 GHz	-3.37 dBm																																									
M2	1		2.4 GHz	-46.57 dBm																																									
M3	1		2.39 GHz	-57.95 dBm																																									
M4	1		2.31 GHz	-64.26 dBm																																									
M5	1		2.399936 GHz	-47.91 dBm																																									
CH11	<div><div>MultiViewSpectrum</div><div>Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SW 1.03 ms VBW 300 kHz Mode Auto Sweep Count 300/300</div><div>Frequency Sweep</div><div><p>2 Marker Table</p><table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.462286 GHz</td><td>-2.65 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-55.58 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-58.07 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.486992 GHz</td><td>-54.22 dBm</td><td></td><td></td></tr></tbody></table><p>Date: 23 MAY 2019 11:41:53</p></div></div>			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.462286 GHz	-2.65 dBm			M2	1		2.4835 GHz	-55.58 dBm			M3	1		2.5 GHz	-58.07 dBm			M4	1		2.486992 GHz	-54.22 dBm									
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.462286 GHz	-2.65 dBm																																									
M2	1		2.4835 GHz	-55.58 dBm																																									
M3	1		2.5 GHz	-58.07 dBm																																									
M4	1		2.486992 GHz	-54.22 dBm																																									

Test Item:	Bandedge	Type:	802.11 n(HT20)																																										
CH01	<div><div>MultiViewSpectrum</div><div>Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SW 1.12 ms VBW 300 kHz Mode Auto Sweep Count 300/300</div><div>Frequency Sweep</div><div></div><div>2 Marker Table</div><table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.41221 GHz</td><td>-2.84 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-43.42 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-54.78 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-62.94 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.39816 GHz</td><td>-42.22 dBm</td><td></td><td></td></tr></tbody></table><div>Date: 23 MAY 2019 11:08:14</div></div>			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.41221 GHz	-2.84 dBm			M2	1		2.4 GHz	-43.42 dBm			M3	1		2.39 GHz	-54.78 dBm			M4	1		2.31 GHz	-62.94 dBm			M5	1		2.39816 GHz	-42.22 dBm		
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.41221 GHz	-2.84 dBm																																									
M2	1		2.4 GHz	-43.42 dBm																																									
M3	1		2.39 GHz	-54.78 dBm																																									
M4	1		2.31 GHz	-62.94 dBm																																									
M5	1		2.39816 GHz	-42.22 dBm																																									
CH11	<div><div>MultiViewSpectrum</div><div>Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SW 1.03 ms VBW 300 kHz Mode Auto Sweep Count 300/300</div><div>Frequency Sweep</div><div></div><div>2 Marker Table</div><table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-Value</th><th>Y-Value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.461614 GHz</td><td>-3.35 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-55.73 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-58.11 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.486944 GHz</td><td>-53.76 dBm</td><td></td><td></td></tr></tbody></table><div>Date: 23 MAY 2019 11:06:57</div></div>			Type	Ref	Trc	X-Value	Y-Value	Function	Function Result	M1	1		2.461614 GHz	-3.35 dBm			M2	1		2.4835 GHz	-55.73 dBm			M3	1		2.5 GHz	-58.11 dBm			M4	1		2.486944 GHz	-53.76 dBm									
Type	Ref	Trc	X-Value	Y-Value	Function	Function Result																																							
M1	1		2.461614 GHz	-3.35 dBm																																									
M2	1		2.4835 GHz	-55.73 dBm																																									
M3	1		2.5 GHz	-58.11 dBm																																									
M4	1		2.486944 GHz	-53.76 dBm																																									


Test Item:	SE	Type:	802.11 b
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			




CH06  
Reference level




CH06  
30MHz~1000MHz




CH06  
1GHz~26GHz




CH11  
Reference level






CH11  
30MHz~1000MHz




CH11  
1GHz~26GHz




Test Item:	SE	Type:	802.11 g
CH01 Reference level	 <p>Ref Level 30.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWF 1.04 ms VBW 300 kHz Mode Auto Sweep Count 100/100 M1[1] -3.30 dBm 2.412700 GHz CF 2.412 GHz 1001 pts 3.0 MHz/ Span 30.0 MHz Date: 23 MAY 2019 10:53:41</p>		
CH01 30MHz~1000MHz	 <p>Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWF 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M1[1] -60.64 dBm 552.0530 MHz H1 -23.300 dBm 30.0 MHz 30001 pts 97.0 MHz/ 1.0 GHz Date: 23 MAY 2019 10:53:58</p>		
CH01 1GHz~26GHz	 <p>Ref Level 20.00 dBm Offset 1.00 dB BW 100 kHz Att 30 dB SWF 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 M1[1] -52.21 dBm 25.802500 GHz H1 -23.300 dBm 1.0 GHz 30001 pts 2.5 GHz/ 26.0 GHz Date: 23 MAY 2019 10:54:19</p>		


CH06  
Reference level




CH06  
30MHz~1000MHz




CH06  
1GHz~26GHz




CH11  
Reference level



CH11  
30MHz~1000MHz




CH11  
1GHz~26GHz







CH06  
Reference level




CH06  
30MHz~1000MHz




CH06  
1GHz~26GHz




CH11  
Reference level



CH11  
30MHz~1000MHz



CH11  
1GHz~26GHz





## 5.8. Spurious Emissions (radiated)


### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

### TEST CONFIGURATION


#### ➤ 9kHz ~30MHz



#### ➤ 30MHz ~ 1GHz



#### ➤ Above 1GHz



**TEST PROCEDURE**

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Below 1 GHz:  
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;  
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - (3) From 1 GHz to 10<sup>th</sup> harmonic:  
RBW=1MHz, VBW=3MHz Peak detector for Peak value.  
RBW=1MHz, VBW=3MHz RMS detector for Average value.

**TEST MODE:**

Please refer to the clause 3.3

**TEST RESULTS**

☒ **Passed**      ☐ **Not Applicable**

Note:

- 1) Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.

➤ **9kHz ~ 30MHz**

The EUT was pre-scanned the frequency band (9kHz~30MHz), found the radiated level lower than the limit, so don't show on the report.


➤ **30MHz ~1000MHz**

Have pre-scan all modulation mode, found the 802.11b mode CH01 which it was worst case, so only the worst case's data on the test report.

## ➤ 30MHz ~ 1GHz

Polarization:

Vertical


**MEASUREMENT RESULT: "GM1905176034\_red"**

5/17/2019 1:23PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
43.580000	29.70	-9.2	40.0	10.3	QP	100.0	0.00	VERTICAL
95.960000	26.20	-11.3	43.5	17.3	QP	100.0	22.00	VERTICAL
103.720000	32.40	-10.6	43.5	11.1	QP	100.0	113.00	VERTICAL
582.900000	33.20	0.1	46.0	12.8	QP	100.0	88.00	VERTICAL
594.540000	38.20	0.7	46.0	7.8	QP	100.0	77.00	VERTICAL
918.520000	34.70	6.7	46.0	11.3	QP	100.0	88.00	VERTICAL

Polarization:

Horizontal

**MEASUREMENT RESULT: "GM1905176035\_red"**

5/17/2019 1:27PM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
51.340000	20.20	-8.9	40.0	19.8	QP	100.0	286.00	HORIZONTAL
57.160000	18.90	-9.5	40.0	21.1	QP	100.0	39.00	HORIZONTAL
103.720000	21.60	-10.6	43.5	21.9	QP	100.0	0.00	HORIZONTAL
239.520000	26.10	-9.0	46.0	19.9	QP	100.0	261.00	HORIZONTAL
357.860000	27.30	-5.8	46.0	18.7	QP	100.0	169.00	HORIZONTAL
924.340000	35.50	6.7	46.0	10.5	QP	300.0	251.00	HORIZONTAL

## ➤ 1 GHz ~ 25 GHz

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2987.92	45.05	28.59	8.92	37.58	44.98	74.00	-29.02	Vertical	Peak
3993.90	38.03	29.70	10.51	36.76	41.48	74.00	-32.52	Vertical	Peak
5434.56	33.51	31.64	12.51	34.54	43.12	74.00	-30.88	Vertical	Peak
8042.90	31.67	37.06	15.67	33.06	51.34	74.00	-22.66	Vertical	Peak
2987.92	43.26	28.59	8.92	37.58	43.19	74.00	-30.81	Horizontal	Peak
4821.76	34.48	31.56	11.73	35.69	42.08	74.00	-31.92	Horizontal	Peak
6645.07	32.67	34.20	14.12	33.70	47.29	74.00	-26.71	Horizontal	Peak
7245.81	32.35	36.25	14.53	33.45	49.68	74.00	-24.32	Horizontal	Peak

802.11b					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2987.92	46.78	28.59	8.92	37.58	46.71	74.00	-27.29	Vertical	Peak
3983.75	36.66	29.70	10.50	36.77	40.09	74.00	-33.91	Vertical	Peak
5603.13	32.72	31.79	12.71	34.36	42.86	74.00	-31.14	Vertical	Peak
7319.96	32.69	36.30	14.58	33.32	50.25	74.00	-23.75	Vertical	Peak
2995.54	43.71	28.60	8.94	37.58	43.67	74.00	-30.33	Horizontal	Peak
3653.46	38.39	29.30	9.99	37.02	40.66	74.00	-33.34	Horizontal	Peak
4871.10	34.98	31.46	11.69	35.61	42.52	74.00	-31.48	Horizontal	Peak
7319.96	33.20	36.30	14.58	33.32	50.76	74.00	-23.24	Horizontal	Peak

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2995.54	46.11	28.60	8.94	37.58	46.07	74.00	-27.93	Vertical	Peak
4004.08	36.52	29.71	10.53	36.76	40.00	74.00	-34.00	Vertical	Peak
5311.47	34.48	31.32	12.36	34.77	43.39	74.00	-30.61	Vertical	Peak
7394.88	32.47	36.30	14.73	33.20	50.30	74.00	-23.70	Vertical	Peak
2995.54	45.42	28.60	8.94	37.58	45.38	74.00	-28.62	Horizontal	Peak
5125.52	33.51	31.80	12.04	35.13	42.22	74.00	-31.78	Horizontal	Peak
6696.01	32.07	34.20	14.19	33.72	46.74	74.00	-27.26	Horizontal	Peak
8002.06	31.72	37.10	15.52	33.07	51.27	74.00	-22.73	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3168.08	38.36	28.80	9.35	37.42	39.09	74.00	-34.91	Vertical	Peak
3616.45	36.73	29.30	10.00	37.05	38.98	74.00	-35.02	Vertical	Peak
5703.86	31.86	31.62	12.81	34.31	41.98	74.00	-32.02	Vertical	Peak
7245.81	31.74	36.25	14.53	33.45	49.07	74.00	-24.93	Vertical	Peak
3616.45	37.64	29.30	10.00	37.05	39.89	74.00	-34.11	Horizontal	Peak
4821.76	33.51	31.56	11.73	35.69	41.11	74.00	-32.89	Horizontal	Peak
6628.18	31.49	34.20	14.10	33.69	46.10	74.00	-27.90	Horizontal	Peak
7357.33	32.89	36.30	14.66	33.26	50.59	74.00	-23.41	Horizontal	Peak

802.11g					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2987.92	43.66	28.59	8.92	37.58	43.59	74.00	-30.41	Vertical	Peak
3653.46	36.61	29.30	9.99	37.02	38.88	74.00	-35.12	Vertical	Peak
5311.47	34.16	31.32	12.36	34.77	43.07	74.00	-30.93	Vertical	Peak
7319.96	32.79	36.30	14.58	33.32	50.35	74.00	-23.65	Vertical	Peak
2987.92	47.10	28.59	8.92	37.58	47.03	74.00	-26.97	Horizontal	Peak
3993.90	36.55	29.70	10.51	36.76	40.00	74.00	-34.00	Horizontal	Peak
4871.10	33.93	31.46	11.69	35.61	41.47	74.00	-32.53	Horizontal	Peak
7319.96	32.36	36.30	14.58	33.32	49.92	74.00	-24.08	Horizontal	Peak

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2995.54	46.20	28.60	8.94	37.58	46.16	74.00	-27.84	Vertical	Peak
3728.63	35.90	29.39	10.05	36.96	38.38	74.00	-35.62	Vertical	Peak
5271.06	32.89	31.36	12.25	34.85	41.65	74.00	-32.35	Vertical	Peak
8063.40	31.17	37.04	15.69	33.05	50.85	74.00	-23.15	Vertical	Peak
3983.75	36.93	29.70	10.50	36.77	40.36	74.00	-33.64	Horizontal	Peak
5338.58	33.71	31.38	12.43	34.72	42.80	74.00	-31.20	Horizontal	Peak
6662.01	31.50	34.20	14.14	33.71	46.13	74.00	-27.87	Horizontal	Peak
8022.46	31.35	37.08	15.60	33.06	50.97	74.00	-23.03	Horizontal	Peak

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2972.75	38.19	28.57	8.89	37.58	38.07	74.00	-35.93	Vertical	Peak
3616.45	36.82	29.30	10.00	37.05	39.07	74.00	-34.93	Vertical	Peak
4821.76	33.10	31.56	11.73	35.69	40.70	74.00	-33.30	Vertical	Peak
7245.81	32.43	36.25	14.53	33.45	49.76	74.00	-24.24	Vertical	Peak
2995.54	44.98	28.60	8.94	37.58	44.94	74.00	-29.06	Horizontal	Peak
3616.45	36.31	29.30	10.00	37.05	38.56	74.00	-35.44	Horizontal	Peak
5718.40	32.18	31.69	12.81	34.30	42.38	74.00	-31.62	Horizontal	Peak
8083.96	31.48	37.02	15.68	33.04	51.14	74.00	-22.86	Horizontal	Peak

802.11n(HT20)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
3049.39	37.30	28.70	9.05	37.53	37.52	74.00	-36.48	Vertical	Peak
3983.75	35.92	29.70	10.50	36.77	39.35	74.00	-34.65	Vertical	Peak
5865.83	32.27	32.23	12.94	34.22	43.22	74.00	-30.78	Vertical	Peak
7319.96	32.55	36.30	14.58	33.32	50.11	74.00	-23.89	Vertical	Peak
2995.54	42.82	28.60	8.94	37.58	42.78	74.00	-31.22	Horizontal	Peak
3653.46	36.87	29.30	9.99	37.02	39.14	74.00	-34.86	Horizontal	Peak
4871.10	33.69	31.46	11.69	35.61	41.23	74.00	-32.77	Horizontal	Peak
7319.96	32.25	36.30	14.58	33.32	49.81	74.00	-24.19	Horizontal	Peak

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2987.92	38.62	28.59	8.92	37.58	38.55	74.00	-35.45	Vertical	Peak
3913.39	35.23	29.70	10.39	36.82	38.50	74.00	-35.50	Vertical	Peak
4920.96	34.16	31.42	11.72	35.52	41.78	74.00	-32.22	Vertical	Peak
7860.74	31.77	36.47	15.24	33.06	50.42	74.00	-23.58	Vertical	Peak
2995.54	46.20	28.60	8.94	37.58	46.16	74.00	-27.84	Horizontal	Peak
3489.84	38.01	28.92	9.86	37.15	39.64	74.00	-34.36	Horizontal	Peak
4652.95	34.17	31.06	11.51	36.00	40.74	74.00	-33.26	Horizontal	Peak
7394.88	32.80	36.30	14.73	33.20	50.63	74.00	-23.37	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.




## 6. TEST SETUP PHOTOS

### Conducted Emissions (AC Mains)



### Radiated Emissions





## **7. EXTERANAL AND INTERNAL PHOTOS**

Reference to the test report No.: CHTEW19050128

-----End of Report-----