

Dec. 20, 2018

FCC ID: 2ABWOMCR418NX

Model Number: MCR41808, MCR41808A, MCR41808B, MCR41808C, MCR41808D, MCR41808E, MCR41808F, MCR41808G

To:

Federal Communication Commission
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD 21046

To Whom It May Concern,

We, **Everex Electronics Ltd** hereby declare that our product (0.9 inch Alarm Clock Digital PLL FM Radio with Wireless) Model Number: **MCR41808, MCR41808A, MCR41808B, MCR41808C, MCR41808D, MCR41808E, MCR41808F, MCR41808G** will conduct FCC compliance testing, the sDOC part in recognized test lab. (**Shenzhen HUAK Testing Technology Co., Ltd.**).

The product above support BT function and WPC function, we will apply BT function by certification procedure and WPC function by sDoC procedure.

The product conforms KDB 680106 D01 V03 Clause 5 b) as follows;


Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operate in the frequency range 115.0 KHz - 205.0 KHz
Output power from each primary coil is less than 15 watts	Yes	The maximum output power of the primary coil is 5W.
The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.	Yes	The transfer system includes single coil that is able to detect receiver device.
Client device is placed directly in contact with the transmitter.	Yes	Client device is placed directly in contact with the transmitter.
Mobile exposure conditions only (portable exposure conditions are not	Yes	Mobile exposure conditions only

Everex Electronics Ltd
Unit01, 19/F.,Block A, Kailey Industrial Centre, 12 Fung Yip Street, Chai Wan, Hong Kong
Tel: +86-13424355423 Email: liubin198459@126.com

covered by this exclusion).		
The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Please contact me if you have any question.

Sincerely,



Name: Fanhua woo

Company: Everex Electronics Ltd

Address: Unit01, 19/F.,Block A, Kailey Industrial Centre, 12 Fung Yip Street, Chai Wan, Hong Kong

Tel: +86-13424355423

Email: liubin198459@126.com