

TEST REPORT

FCC MPE Test for IT109B005-UA Certification

APPLICANT innertron

REPORT NO. HCT-RF-2309-FC010

DATE OF ISSUE September 22, 2023

> Tested by Sang Su Lee

Technical Manager Jong Seok Lee

HCT CO., LTD. Bongjai Huh Bongjai Huh / CEO

HCT CO., LTD. 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA Tel. +82 31 634 6300 Fax. +82 31 645 6401 The report shall not be reproduced except in full(only partly) without approval of the laboratory.

F-TP22-03(Rev.04)



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA Tel. +82 31 634 6300 Fax. +82 31 645 6401



Applicant	innertron 301, Harmony-ro, Yeonsu-gu, Incheon City 22014 Korea	
Eut Type Model Name	0.5W Public Safety Signal Booster IT109B005-UA	
FCC ID	2BCYP-IT7080BDA27DA	
	The result shown in this test report refer only to the sample(s) tested unless otherwise stated. This test results were applied only to the test methods required by the standard.	



REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	September 22, 2023	Initial Release

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

Test Report Statement:

The above Test Report is not related to the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS(Korea Laboratory Accreditation Scheme) / A2LA(American Association for Laboratory Accreditation), which signed the ILAC-MRA.

If this report is required to confirmation of authenticity, please contact to www.hct.co.kr





RF Exposure Statement

1. Limit

According to §1.1310, §2.1091 RF exposure is calculated.

(B) Limits for General Population/Oncontrolled Exposures				
Frequency range (MHz)	Electric field Strength (V/m)	Magneticfield Strength (A/m)	Powerdensity (mW/cm²)	Averagingtime (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f²)	30
30 - 300	27.5	0.073	0.2	30
300 - 1500			f/1500	30
1500 - 100.000	•••••		1.0	30

(B) Limits for General Population/Uncontrolled Exposures

F = frequency in MHz

* = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$S = PG/4\pi R^2$

- S = Power density
- P = power input to antenna
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna



HCT

3. RESULTS

25.50	dBm
354.81	mW
70.00	cm
799.00	MHz
12.00	dBi
15.85	-
0.0913	mW/cm ²
0.5327	mW/cm ²
	25.50 354.81 70.00 799.00 12.00 15.85 0.0913 0.5327

- 800 MHz (806 ~ 816) – Uplink, 1 Carrier

Max Peak output Power at antenna input terminal	25.50	dBm
Max Peak output Power at antenna input terminal	354.81	mW
Prediction distance	70.00	cm
Prediction frequency	806.00	MHz
Antenna Gain(typical)	12.00	dBi
Antenna Gain(numeric)	15.85	-
Power density at prediction frequency(S)	0.0913	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5373	mW/cm ²





- 800 MHz (817 ~ 824) -	– Uplink, 1 Carrier
-------------------------	---------------------

Max Peak output Power at antenna input terminal	25.50	dBm
Max Peak output Power at antenna input terminal	354.81	mW
Prediction distance	70.00	cm
Prediction frequency	817.00	MHz
Antenna Gain(typical)	12.00	dBi
Antenna Gain(numeric)	15.85	-
Power density at prediction frequency(S)	0.0913	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5447	mW/cm ²





Report No. HCT-RF-2309-FC010

- 700 MHz (769 ~ 775) – Downlink	1 Carrier
1001012	100 110		, + 0000000

Max Peak output Power at antenna input terminal	28.50	dBm
Max Peak output Power at antenna input terminal	707.95	mW
Prediction distance	70.00	cm
Prediction frequency	769.00	MHz
Antenna Gain(typical)	7.00	dBi
Antenna Gain(numeric)	5.01	-
Power density at prediction frequency(S)	0.0576	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5127	mW/cm ²

- 800 MHz (85)	L ~ 861) – Dov	wnlink, 1 Carrier
----------------	----------------	-------------------

Max Peak output Power at antenna input terminal	28.50	dBm
Max Peak output Power at antenna input terminal	707.95	mW
Prediction distance	70.00	cm
Prediction frequency	851.00	MHz
Antenna Gain(typical)	7.00	dBi
Antenna Gain(numeric)	5.01	-
Power density at prediction frequency(S)	0.0576	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5673	mW/cm ²



Report No. HCT-RF-2309-FC010

- 800 MHz (86	2 ~ 869) -	Downlink, 1	Carrier
---------------	------------	-------------	---------

Max Peak output Power at antenna input terminal	28.50	dBm
Max Peak output Power at antenna input terminal	707.95	mW
Prediction distance	70.00	cm
Prediction frequency	862.00	MHz
Antenna Gain(typical)	7.00	dBi
Antenna Gain(numeric)	5.01	-
Power density at prediction frequency(S)	0.0576	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.5747	mW/cm ²



Simultaneous band emission conditions

[Uplink]

Band	MPE Ratio (Power density / Limit)	Sum of MPE Ratio	
799 ~ 805	0.1714		
806~816	0.1699	0.5089	≤ 1
817~824	0.1676		

[Downlink]

Band	MPE Ratio (Power density / Limit)	Sum of MPE Ratio	
769 ~ 775	0.1124		
851~861	0.1015	0.3141	≤ 1
862 ~ 869	0.1002		

*Note

- The result of each band was applied to the worst value.
 MPE ratios are calculated as
- [(Power density1 / MPE Limit) + [(Power density2 / MPE Limit) + \ldots] \leq 1