

**FCC §1.1310 & §2.1091**

**For**

**Jiangsu Yuyue Medical Equipment & Supply Co., Ltd.**

No.1 Baisheng Road Development Zone, Danyang, Jiangsu province, 212300 China

**FCC ID: 2A2JJYE650ARS**

<b>Report Type:</b> Original Report	<b>Product Name:</b> Electronic Blood Pressure Monitor
<b>Report Number:</b>	<u>RKSA240319002-00C</u>
<b>Report Date:</b>	<u>2024-04-24</u>
<b>Reviewed By:</b>	<u>Jenny Yang</u> Jenny Yang
<b>Approved By:</b>	<u>Kyle Xu</u> Kyle Xu
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.

**TABLE OF CONTENTS**

**REPORT REVISION HISTORY.....3**

**GENERAL INFORMATION.....4**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....4

**FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....5**

**EUT PHOTOGRAPHS .....7**

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSA240319002-00C	R1V1	2024-04-24	Initial Release

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant:	Jiangsu Yuyue Medical Equipment & Supply Co., Ltd.
Tested Model:	YE650ARS
Product Name:	Electronic Blood Pressure Monitor
Power Supply:	DC 3.7V from battery or DC 5V charging by adapter
RF Function:	BLE (1Mbps)
Maximum Output Power:	6.17 dBm
Operating Band/Frequency:	2402-2480MHz
Channel Number:	40
Channel Separation:	2 MHz
Modulation Type	GFSK
Antenna Type:	PCB Antenna
★Maximum Antenna Gain:	3.09 dBi

*Adapter Information:*

*Model: HT-C38B-0510WW*

*Input: 100-240V-50/60Hz, 0.35A Max*

*Output: 5V, 1000mA*

*Note: The maximum antenna gain was declared by the manufacturer.*

*All measurement and test data in this report was gathered from production sample serial number: RKSA240319002-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2024-03-19.)*

## **FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

### **Applicable Standard**

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### **Calculated Formulary**

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:**

Mode	Frequency Range (MHz)	Antenna Gain		★Tune-up Output Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
BLE	2402~2480	3.09	2.04	6.5	4.47	20	0.002	1.0

**Note:**

1. For the above tune up power were declared by the manufacturer.

**Result:** The device meet FCC MPE at 20 cm distance.

## **EUT PHOTOGRAPHS**

---

Please refer to the attachment EXHIBIT A-EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B-EUT INTERNAL PHOTOGRAPHS.

### **Declarations**

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor  $k=2$  with the 95.45% confidence interval.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***