

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042

Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2004-0092

2. Customer

- Name (FCC) : LG Electronics USA / Name (IC) : LG ELECTRONICS INC.
- Address (FCC) : 1000 Sylvan Avenue, Englewood Cliffs, New Jersey, United States, 07632
Address (IC) : 222, LG-ro, Jinwi-myeon Pyeongtaek-si, Gyeonggi-do 451-713 Korea (Republic Of)

3. Use of Report : FCC & IC Original Grant

4. Product Name / Model Name : Telematics / TLVHE4IU-N

FCC ID : BEJTLVHE4IU-N / IC : 2703H-TLVHE4IUN

5. Test Method Used : KDB971168 D01v03r01, ANSI/TIA-603-E-2016, ANSI C63.26-2015

Test Specification : §2, §22(H), §24(E), §27

RSS-132 Issue 3 , RSS-133 Issue 6, RSS-139 Issue3

6. Date of Test : 2020.04.01 ~ 2020.04.10

7. Testing Environment : Refer to appended test report.

8. Test Result : Refer to attached test result.

Affirmation	Tested by Name : JungWoo Kim 	Reviewed by Name : JaeJin Lee 
-------------	--	---

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2020 . 04 . 23 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description	Tested by	Revised by
DRTFCC2004-0092	Apr. 23, 2020	Initial issue	JungWoo Kim	JaeJin Lee

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
2.1. EUT DESCRIPTION.....	5
2.2. EUT CAPABILITIES.....	5
2.3. TESTING ENVIRONMENT	5
2.4. MEASURING INSTRUMENT CALIBRATION	5
2.5. MEASUREMENT UNCERTAINTY.....	5
2.6. TEST FACILITY	5
3. DESCRIPTION OF TESTS.....	6
3.1 ERP & EIRP (Effective Radiated Power & Equivalent Isotropic Radiated Power)	6
3.2 PEAK TO AVERAGE RATIO	8
3.3 OCCUPIED BANDWIDTH (99 % Bandwidth)	10
3.4 SPURIOUS EMISSIONS AT ANTENNA TERMINAL	11
3.5 BAND EDGE EMISSIONS AT ANTENNA TERMINAL	12
3.6 RADIATED SPURIOUS EMISSIONS	13
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE.....	14
4. LIST OF TEST EQUIPMENT	15
5. SUMMARY OF TEST RESULTS.....	16
6. EMISSION DESIGNATOR AND SAMPLE CALCULATION....	17
7. TEST DATA	19
7.1 Conducted OUTPUT POWER	19
7.2 PEAK TO AVERAGE RATIO	21
7.3 OCCUPIED BANDWIDTH (99 % Bandwidth)	21
7.4 SPURIOUS MISSIONS AT ANTENNA TERMINAL.....	22
7.5 BAND EDGE EMISSIONS AT ANTENNA TERMINAL	22
7.6 EFFECTIVE RADIATED POWER.....	23
7.7 EQUIVALENT ISOTROPIC RADIATED POWER.....	24
7.8 RADIATED SPURIOUS EMISSIONS	26
7.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE.....	31
7.9.1 FREQUENCY STABILITY (GPRS850)	31
7.9.2 FREQUENCY STABILITY (WCDMA850)	32
7.9.3 FREQUENCY STABILITY (WCDMA1700)	33
7.9.4 FREQUENCY STABILITY (GPRS1900)	34
7.9.5 FREQUENCY STABILITY (WCDMA1900)	35
8. TEST PLOTS	36
8.1 PEAK TO AVERAGE RATIO	36
8.2 OCCUPIED BANDWIDTH (99 % Bandwidth)	43
8.3 SPURIOUS EMISSIONS AT ANTENNA TERMINAL	63
8.4 BAND EDGE EMISSIONS AT ANTENNA TERMINAL.....	84

1. GENERAL INFORMATION

Applicant Name(FCC) : LG Electronics USA, Inc.
Applicant Name(IC) : LG ELECTRONICS INC.
Address(FCC) : 1000 Sylvan Ave. Englewood Cliffs, New Jersey, United States 07632
Address(IC) : 222, LG-ro, Jinwi-myeon Pyeongtaek-si, Gyeonggi-do 451-713 Korea (Republic Of)
FCC ID : BEJTLVHE4IU-N
IC : 2703H-TLVHE4IUN
FCC Classification : PCS Licensed Transmitter (PCB)
EUT : Telematics
Model Name(FCC, IC) : TLVHE4IU-N
Add Model Name(FCC, IC) : NA
Hardware Version : H14
Software Version : X244
Serial Number : Conducted : 912VIPA677824 / Radiated : 912vike677813
Supplying power : DC 12 V
Antenna Type : External Antenna

Mode	Tx Frequency (MHz)	Emission Designator	ERP (Max. Power)		EIRP (Max. Power)	
			dBm	W	dBm	W
GPRS850	824.2 ~ 848.8	248KGXW	26.96	0.497	29.11	0.815
EDGE850	824.2 ~ 848.8	246KG7W	20.37	0.109	22.52	0.179
WCDMA850	826.4 ~ 846.6	4M14F9W	17.52	0.056	19.67	0.093
HSUPA850	826.4 ~ 846.6	4M17F9W	16.36	0.043	18.51	0.071
WCDMA1700	1712.4 ~ 1752.6	4M15F9W	-	-	17.30	0.054
HSUPA1700	1712.4 ~ 1752.6	4M14F9W	-	-	16.02	0.040
GPRS1900	1850.2 ~ 1909.8	246KGXW	-	-	24.32	0.270
EDGE1900	1850.2 ~ 1909.8	251KG7W	-	-	18.69	0.074
WCDMA1900	1852.4 ~ 1907.6	4M16F9W	-	-	18.32	0.068
HSUPA1900	1852.4 ~ 1907.6	4M16F9W	-	-	16.99	0.050

2. INTRODUCTION

2.1. EUT DESCRIPTION

The Equipment Under Test (EUT) supports GPRS/WCDMA/LTE.

2.2. EUT CAPABILITIES

This EUT contains the following capabilities:

850/1900 GPRS/EGPRS, 850/1700/1900 WCDMA/HSUPA, Multi-band LTE.

2.3. TESTING ENVIRONMENT

Ambient Condition	
▪ Temperature	+20 °C ~ +25 °C
▪ Relative Humidity	37 % ~ 45 %

2.4. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
Radiated Disturbance (Below 1 GHz)	5.1 dB (The confidence level is about 95 %, $k = 2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.4 dB (The confidence level is about 95 %, $k = 2$)
Radiated Disturbance (Above 18 GHz)	5.3 dB (The confidence level is about 95 %, $k = 2$)

2.6. TEST FACILITY

DT&C Co., Ltd.

The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042.

The test site complies with the requirements of § 2.948 according to ANSI C63.4-2014.

- FCC & IC MRA Accredited Test Firm No. : KR0034
- ISED #: 5740A


www.dtnc.net

Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

3. DESCRIPTION OF TESTS

3.1 ERP & EIRP (Effective Radiated Power & Equivalent Isotropic Radiated Power)

Test Set-up



These measurements were performed at 3 m test site. The equipment under test is placed on a non-conductive table 1.5 meters above a turntable which is flush with the ground plane and 3 meters from the receive antenna. For measurements above 1 GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.

Test Procedure

- ANSI/TIA-603-E-2016 - Section 2.2.17
- KDB971168 D01v03 - Section 5.2.2
- ANSI 63.26-2015 – Section 5.2.4.4.1

Test setting

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW = 1% to 5% of the OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
 - 1) Set = auto-couple, or
 - 2) Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. Transmission period is the on and off time of the transmitter.
6. Detector = power averaging (rms).
7. If the EUT can be configured to transmit continuously, then set the trigger to free run.
8. If the EUT cannot be configured to transmit continuously, then use a sweep trigger with the level set to enable triggering only on full power bursts and configure the EUT to transmit at full power for the entire duration of each sweep. Verify that the sweep time is less than or equal to the transmission burst duration. Time gating can also be used under similar constraints (i.e., configured such that measurement data is collected only during active full-power transmissions).
9. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. To accurately determine the average power over multiple symbols, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.

10. Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band or channel power measurement function, with the band/channel limits set equal to the OBW band edges. If the instrument does not have a band or channel power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

The receiver antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer.

A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminal of the substitute antenna is measured.


The ERP/EIRP is calculated using the following formula:

$$\text{ERP/EIRP} = \text{The conducted power at the substitute antenna's terminal [dBm]} + \text{Substitute Antenna gain [dBd for ERP, dBi for EIRP]}$$

For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn antenna and an isotropic antenna are taken into consideration.

3.2 PEAK TO AVERAGE RATIO

Test set-up



Test Procedure

- KDB971168 D01v03 - Section 5.7.2
- ANSI C63.26-2015 – Section 5.2.3.4

A peak to average ratio measurement is performed at the conducted port of the EUT.

The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The present of time the signal spends at or above the level defines the probability for that particular power level.

Test setting

The spectrum Analyzer's CCDF measurement function is enabled.

1. Set resolution/measurement bandwidth \geq OBW or specified reference bandwidth.
2. Set the number of counts to a value that stabilizes the measured CCDF curve.
3. Set the measurement interval as follows:
 - 1) For continuous transmissions, set to the greater of $[10 \times (\text{number of points in sweep}) \times (\text{transmission symbol period})]$ or 1 ms.
 - 2) For burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize. Set the measurement interval to a time that is less than or equal to the burst duration.
 - 3) If there are several carriers in a single antenna port, the peak power shall be determined for each individual carrier (by disabling the other carriers while measuring the required carrier) and the total peak power calculated from the sum of the individual carrier peak powers.
4. Record the maximum PAPR level associated with a probability of 0.1%.
5. The peak power level is calculated from the sum of the PAPR value from step d) to the measured average power.

□ Alternate Procedure

- KDB971168 D01v03 - Section 5.7.3
- ANSI C63.26-2015 – Section 5.2.6

Use one of the measurement procedures of the peak power and record as P_{Pk} .

Use one of the measurement procedures of the average power and record as P_{Avg} .

Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = P_{Pk} (\text{dBm or dBW}) - P_{Avg} (\text{dBm or dBW}).$$

Where,

PAPR peak-to-average power ratio, in dB

P_{Pk} measured peak power or peak PSD level, in dBm or dBW

P_{Avg} measured average power or average PSD level, in dBm or dBW

- Peak Power Measurement


1. Set the RBW \geq OBW
2. Set VBW $\geq 3 \times$ RBW
3. Set span $\geq 2 \times$ RBW
4. Sweep time $\geq 10 \times$ (number of points in sweep) \times (transmission symbol period).
5. Detector = peak
6. Trace mode = max hold
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the peak amplitude level.

- Average Power Measurement

1. Set span to 2 x to 3 x the OBW.
2. Set RBW = 1% to 5% of the OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW..
5. Sweep time = 1) auto-couple, or
 - 2) set $\geq [10 \times$ (number of points in sweep) \times (transmission period)] for single sweep (automation-compatible (measurement. Transmission period is the on and off time of the transmitter.
6. Detector = power averaging (RMS).
7. If the EUT can be configured to transmit continuously, then set the trigger to free run.
8. If the EUT cannot be configured to transmit continuously, then use a sweep trigger with the level set to enable triggering only on full power bursts and configure the EUT to transmit at full power for the entire duration of each Sweep. Verify that the sweep time is less than or equal to the transmission burst duration. Time gating can also be used under similar constraints (i.e., configured such that measurement data is collected only during active full-Power transmissions)
9. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. To accurately determine the average power over multiple symbols, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.
10. Compute the power by integrating the spectrum across the OBW of the signal using the instrument's band or channel power measurement function, with the band/channel limits set equal to the OBW band edges. If the instrument does not have a band or channel power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

3.3 OCCUPIED BANDWIDTH (99 % Bandwidth)

Test set-up



Offset value information

Frequency (MHz)	Offset Value (dB)	Frequency (MHz)	Offset Value (dB)
824.2	7.11	1850.2	8.06
826.4	7.11	1852.4	8.06
836.6	7.14	1880.0	8.07
846.6	7.16	1907.6	8.08
848.8	7.17	1909.8	8.08
1712.4	8.01	-	-
1732.4	8.02	-	-
1752.6	8.04	-	-

Note. 1: The offset values from EUT to Spectrum analyzer were measured and used for test.

Test Procedure

- **KDB971168 D01v03 - Section 4.3**
- **ANSI C63.26-2015 – Section 5.4.4**


The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power of a given emission.

Test setting

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 ~ 5 % of the expected OBW & VBW $\geq 3 \times$ RBW
3. Detector = Peak
4. Trace mode = Max hold
5. Sweep = Auto couple
6. The trace was allowed to stabilize
7. If necessary, step 2 ~ 6 were repeated after changing the RBW such that it would be within 1 ~ 5 % of the 99 % occupied bandwidth observed in step 6.

3.4 SPURIOUS EMISSIONS AT ANTENNA TERMINAL

Test set-up



Offset value information

Frequency (MHz)	Offset Value (dB)	Frequency (MHz)	Offset Value (dB)
10000	11.92	20000	15.25
-	-	-	-

Note. 1: The offset value from EUT to Spectrum analyzer was measured and used for test.

Test Procedure

- **KDB971168 D01v03 - Section 6**
- **ANSI C63.26-2015 - Section 5.7**

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The EUT was setup to maximum output power at its low, middle, high channel with all bandwidths. The spectrum is scanned from 9 kHz up to a frequency including its 10th harmonic.

The power of any spurious emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, where P is the transmitter power in Watts.


Test setting

1. RBW = 100 kHz(Below 1 GHz) or 1 MHz(Above 1 GHz) & VBW $\geq 3 \times$ RBW (Refer to Note 1)
2. Detector = RMS & Trace mode = Max hold
3. Sweep time = Auto couple
4. Number of sweep point $\geq 2 \times$ span / RBW
5. The trace was allowed to stabilize

Note 1: Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22 and 1 MHz or greater for Part 24, 27

3.5 BAND EDGE EMISSIONS AT ANTENNA TERMINAL

Test set-up



Offset value information

Frequency Range(MHz)	Offset Value (dB)	Frequency Range(MHz)	Offset Value (dB)	Frequency Range(MHz)	Offset Value (dB)
819-823	7.11	1701-1709	8.01	1845-1855	8.06
823-825	7.11	1705-1715	8.01	1909-1911	8.08
819-829	7.12	1750-1760	8.04	1905-1915	8.08
848-850	7.17	1756-1764	8.04	1911-1915	8.08
844-854	7.17	1845-1849	8.06	-	-
850-854	7.17	1849-1851	8.06	-	-
-	-	-	-	-	-

Note. 1: The offset value from EUT to Spectrum analyzer was measured and used for test.

Test Procedure

- KDB971168 D01v03 - Section 6
- ANSI C63.26-2015 - Section 5.7

All out of band emissions are measured by means of a calibrated spectrum analyzer. The EUT was setup to maximum output power at its lowest and highest channel with all modulations.

The power of any spurious emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, where P is the transmitter power in Watts.

Test setting


1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW $\geq 1\%$ of the emission
4. VBW $\geq 3 \times$ RBW
5. Detector = RMS & Trace mode = Max hold
6. Sweep time = Auto couple or 1 s for band edge
7. Number of sweep point $\geq 2 \times$ span / RBW
8. The trace was allowed to stabilize

Note 1: In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of **at least one percent** of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

3.6 RADIATED SPURIOUS EMISSIONS

Test Set-up



These measurements were performed at 3 m test site. The equipment under test is placed on a non-conductive table 0.8-meters above a turntable which is flush with the ground plane and 3 meters from the receive antenna. For measurements above 1 GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.

Test Procedure

- ANSI/TIA-603-E-2016 - Section 2.2.12
- KDB971168 D01v03 - Section 5.8
- ANSI C63.26-2015 - Section 5.5

Test setting

1. RBW = 100 kHz for below 1 GHz and 1 MHz for above 1 GHz / VBW $\geq 3 \times$ RBW
2. Detector = RMS & Trace mode = Max hold
3. Sweep time = Auto couple
4. Number of sweep point $\geq 2 \times$ span / RBW
5. The trace was allowed to stabilize

The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer.


For radiated spurious emission measurements below 1 GHz, a half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading.

For radiated spurious emission measurements above 1 GHz, a Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. The difference between the gain of the horn and an isotropic antenna are taken into consideration.

3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up

Constant Temp & Humidity Chamber



Test Procedure

- ANSI/TIA-603-E-2016
- KDB971168 D01v03 - Section 9

The frequency stability of the transmitter is measured by:

a.) **Temperature:**

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

b.) **Primary Supply Voltage:**

The primary supply voltage is varied from 85 % to 115 % of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification:

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block for Part 24, 27. The frequency stability of the transmitter shall be maintained within ± 0.000 25 % (± 2.5 ppm) of the center frequency for Part 22.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature.
(20 °C to provide a reference)
2. The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C.
A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

4. LIST OF TEST EQUIPMENT

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal. Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	19/12/16	20/12/16	MY48010133
Spectrum Analyzer	Agilent Technologies	N9020A	19/06/26	20/06/26	US47360812
DC power supply	Agilent Technologies	66332A	19/06/25	20/06/25	MY43001172
Multimeter	FLUKE	17B+	19/12/16	20/12/16	36390701WS
Power Divider	Weinschel	1515-1	19/12/16	20/12/16	TW493
Temp & Humi	SJ Science	SJ-TH-S50	19/06/25	20/06/25	U5542113
Radio Communication Analyzer	Agilent Technologies	E5515C	19/12/16	20/12/16	GB43461134
Thermohygrometer	BODYCOM	BJ5478	19/12/18	20/12/18	120612-2
Thermohygrometer	BODYCOM	BJ5478	19/12/18	20/12/18	120612-1
Signal Generator	Rohde Schwarz	SMBV100A	19/12/16	20/12/16	255571
Signal Generator	ANRITSU	MG3695C	19/12/16	20/12/16	173501
Loop Antenna	ETS-Lindgren	6502	19/09/18	21/09/18	00226186
Bilog Antenna	Schwarzbeck	VULB 9160	19/04/23	21/04/23	9160-3362
Dipole Antenna	Schwarzbeck	UHA9105	19/02/28	21/02/28	2261
Dipole Antenna	Schwarzbeck	UHA9105	18/04/13	20/04/13	2262
HORN ANT	ETS	3117	18/05/10	20/05/10	00140394
HORN ANT	ETS	3117	20/03/26	22/03/26	00152145
HORN ANT	A.H.Systems	SAS-574	19/04/23	21/04/23	154
HORN ANT	A.H.Systems	SAS-574	19/07/03	21/07/03	155
Amplifier	EMPOWER	BBS3Q7ELU	19/06/24	20/06/24	1020
PreAmplifier	H.P	8447D	19/12/16	20/12/16	2944A07774
PreAmplifier	Agilent	8449B	19/06/27	20/06/27	3008A02108
High-pass filter	Wainwright	WHKX12-935-1000-15000-40SS	19/06/24	20/06/24	7
High-pass filter	Wainwright	WHKX12-2580-3000-18000-80SS	19/06/24	20/06/24	3
Cable	DTNC	Cable	20/01/16	21/01/16	M-01
Cable	DTNC	Cable	20/01/16	21/01/16	M-02
Cable	Junkosha	MWX315	20/01/16	21/01/16	M-05
Cable	Junkosha	MWX221	20/01/16	21/01/16	M-06
Cable	DTNC	Cable	20/01/16	21/01/16	RF-09

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017.

Note2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself.

5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	RSS Section(s)	Parameter	Status Note 1
2.1046	RSS-132 [5.4] RSS-133 [6.4] RSS-139 [6.5]	Conducted Output Power	C
22.913(a) 24.232(c) 27.50(d.4)	RSS-132 [5.4] [SRSP-503(5.1.3)] RSS-133 [6.4] [SRSP-510(5.1.2)] RSS-139[6.5] SRSP-513(5.1.2)]	Effective Radiated Power Equivalent Isotropic Radiated Power	C
2.1049	RSS-Gen [6.7]	Occupied Bandwidth	C
2.1051 22.917(a) 24.238(a) 27.53(h)	RSS-132 [5.5] RSS-133 [6.5] RSS-139 [6.6]	Band Edge Emissions at Antenna Terminal Spurious Emissions at Antenna Terminal	C
24.232(d) 27.50(d.5)	RSS-132 [5.4] RSS-133 [6.4] RSS-139 [6.5]	Peak to Average Ratio	C
2.1053 22.917(a) 24.238(a) 27.53(h)	RSS-132 [5.5] RSS-133 [6.5] RSS-139 [6.6]	Radiated Spurious and Harmonic Emissions	C
2.1055 22.355 24.235 27.54	RSS-132 [5.3] RSS-133 [6.3] RSS-139 [6.4]	Frequency Stability	C

Note 1: C=Comply NC=Not Comply NT=Not Tested NA=Not Applicable

6. EMISSION DESIGNATOR AND SAMPLE CALCULATION

A. Emission Designator

GPRS850 Emission Designator

Emission Designator = **248KGXW**

GSM OBW = 247.52 kHz

(Measured at the 99.75 % power bandwidth)

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

GPRS1900 Emission Designator

Emission Designator = **246KGXW**

GSM OBW = 245.87 kHz

(Measured at the 99.75 % power bandwidth)

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

WCDMA850 Emission Designator

Emission Designator = **4M14F9W**

WCDMA OBW = 4.1350 MHz

(Measured at the 99.75 % power bandwidth)

F = Frequency Modulation

9 = Composite Digital Information

W = Combination (Audio/Data)

WCDMA1700 Emission Designator

Emission Designator = **4M15F9W**

WCDMA OBW = 4.1475 MHz

(Measured at the 99.75 % power bandwidth)

F = Frequency Modulation

9 = Composite Digital Information

W = Combination (Audio/Data)

WCDMA1900 Emission Designator

Emission Designator = **4M16F9W**

WCDMA OBW = 4.1589 MHz

(Measured at the 99.75 % power bandwidth)

F = Frequency Modulation

9 = Composite Digital Information

W = Combination (Audio/Data)

EDGE850 Emission Designator

Emission Designator = **246KG7W**

EDGE OBW = 245.86 kHz

(Measured at the 99.75 % power bandwidth)

G = Phase Modulation

7 = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE1900 Emission Designator

Emission Designator = **251KG7W**

EDGE OBW = 251.11 kHz

(Measured at the 99.75 % power bandwidth)

G = Phase Modulation

7 = Cases not otherwise covered

W = Combination (Audio/Data)

HSUPA850 Emission Designator

Emission Designator = **4M17F9W**

HSUPA OBW = 4.1655 MHz

(Measured at the 99.75 % power bandwidth)

F = Frequency Modulation

9 = Composite Digital Information

W = Combination (Audio/Data)

HSUPA1700 Emission Designator

Emission Designator = **4M14F9W**

HSUPA OBW = 4.1374 MHz

(Measured at the 99.75 % power bandwidth)

F = Frequency Modulation

9 = Composite Digital Information

W = Combination (Audio/Data)

HSUPA1900 Emission Designator

Emission Designator = **4M16F9W**

HSUPA OBW = 4.1593 MHz

(Measured at the 99.75 % power bandwidth)

F = Frequency Modulation

9 = Composite Digital Information

W = Combination (Audio/Data)

B. For substitution method

- 1) The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1 GHz respectively above ground.
- 2) The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
- 3) During the test, the turn table is rotated until the maximum signal is found.
- 4) Record the field strength meter's level. (ex. Spectrum reading level is -8.5 dBm)
- 5) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 6) Increase the signal generator output till the field strength meter's level is equal to the item (4).
(ex. Signal generator level is -18.04 dBm)
- 7) The gain of the cable and amplifier between the signal generator and terminals of substituted antenna is 46.92 dB at test frequency.
- 8) Record the level at substituted antenna terminal. (ex. 28.88dBm)
- 9) The result is calculated as below;

EIRP(dBm) = LEVLE@ANTENNA TERMINAL + TX Antenna Gain (dBi)


ERP(dBm) = LEVLE@ANTENNA TERMINAL + TX Antenna Gain (dBd)

Where, TX Antenna Gain (dBd) = TX Antenna Gain (dBi) - 2.15 dB

7. TEST DATA

7.1 Conducted OUTPUT POWER

A base station simulator was used to establish communication with the EUT. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



The output power was measured using the Agilent E5515C

▪ GPRS/EDGE

Band	Channel	Maximum Burst-Averaged Output Power(dBm)								
		GSM Voice	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot	EDGE 1 TX Slot	EDGE 2 TX Slot	EDGE 3 TX Slot	EDGE 4 TX Slot
Cellular	128	-	32.08	30.21	28.27	26.84	26.04	25.24	25.11	25.03
	190	-	32.04	29.71	27.74	26.73	25.84	24.87	24.61	24.64
	251	-	32.14	29.81	27.65	26.62	25.71	24.89	24.73	24.69
PCS	512	-	29.48	27.53	25.49	24.34	24.52	24.40	24.44	24.18
	661	-	29.06	27.93	25.31	24.12	24.81	24.64	24.54	24.71
	810	-	28.92	27.72	25.14	23.93	24.91	24.71	24.63	24.38

▪ GPRS/EDGE

Band	Channel	Calculated Maximum Frame-Averaged Output Power(dBm)								
		GSM Voice	GPRS 1 TX Slot	GPRS 2 TX Slot	GPRS 3 TX Slot	GPRS 4 TX Slot	EDGE 1 TX Slot	EDGE 2 TX Slot	EDGE 3 TX Slot	EDGE 4 TX Slot
Cellular	128	-	23.05	24.19	24.01	23.83	17.01	19.22	20.85	22.02
	190	-	23.01	23.69	23.48	23.72	16.81	18.85	20.35	21.63
	251	-	23.11	23.79	23.39	23.61	16.68	18.87	20.47	21.68
PCS	512	-	20.45	21.51	21.23	21.33	15.49	18.38	20.18	21.17
	661	-	20.03	21.91	21.05	21.11	15.78	18.62	20.28	21.70
	810	-	19.89	21.70	20.88	20.92	15.88	18.69	20.37	21.37

Note: Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots

• WCDMA

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band (dBm)			AWS Band (dBm)			3GPP MPR (dB)
			4132	4183	4233	1312	1412	1513	
99	WCDMA	12.2 kbps RMC	22.27	22.46	22.30	21.92	22.02	22.08	-
99		12.2 kbps AMR	-	-	-	-	-	-	-
5	HSDPA	Subtest 1	21.22	21.40	21.26	20.86	20.97	21.03	0
5		Subtest 2	21.23	21.39	21.25	20.85	20.97	21.02	0
5		Subtest 3	20.75	20.92	20.79	20.37	20.50	20.56	0.5
5		Subtest 4	20.74	20.92	20.77	20.37	20.49	20.54	0.5
6	HSUPA	Subtest 1	21.20	21.39	21.25	20.80	20.96	21.03	0
6		Subtest 2	19.23	19.71	19.25	19.81	19.96	19.99	2
6		Subtest 3	20.17	20.72	20.25	20.24	20.34	20.37	1
6		Subtest 4	19.22	19.37	19.24	19.74	19.86	19.97	2
6		Subtest 5	21.17	21.35	21.33	20.74	20.89	20.97	0

3GPP Release Version	Mode	3GPP 34.121 Subtest	PCS Band (dBm)			3GPP MPR (dB)
			9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.28	22.05	21.95	-
99		12.2 kbps AMR	-	-	-	-
5	HSDPA	Subtest 1	21.23	20.98	20.90	0
5		Subtest 2	21.24	20.97	20.90	0
5		Subtest 3	20.73	20.49	20.41	0.5
5		Subtest 4	20.74	20.51	20.41	0.5
6	HSUPA	Subtest 1	21.23	20.96	20.88	0
6		Subtest 2	19.22	18.97	18.87	2
6		Subtest 3	20.18	19.94	19.84	1
6		Subtest 4	19.19	18.96	18.87	2
6		Subtest 5	21.21	20.97	20.88	0

*This device was not supported the voice call.

7.2 PEAK TO AVERAGE RATIO

- Plots of the EUT's Peak- to- Average Ratio are shown in Clause 8.1

7.3 OCCUPIED BANDWIDTH (99 % Bandwidth)

Mode	Channel	Frequency(MHz)	Test Result (kHz)
GPRS850	128	824.2	243.63
	190	836.6	245.64
	251	848.8	247.52
EDGE850	128	824.2	243.38
	190	836.6	245.86
	251	848.8	240.47
GPRS1900	512	1850.2	240.48
	661	1880.0	244.37
	810	1909.8	245.87
EDGE1900	512	1850.2	245.24
	661	1880.0	251.11
	810	1909.8	245.73
WCDMA850	4132	826.4	4127.20
	4183	836.6	4135.00
	4233	846.6	4109.00
HSUPA850	4132	826.4	4123.70
	4183	836.6	4165.50
	4233	846.6	4117.50
WCDMA1700	1312	1712.4	4128.90
	1412	1732.4	4147.50
	1513	1752.6	4126.00
HSUPA1700	1312	1712.4	4132.00
	1412	1732.4	4137.40
	1513	1752.6	4102.30
WCDMA1900	9262	1852.4	4151.60
	9400	1880.0	4158.90
	9538	1907.6	4146.80
HSUPA1900	9262	1852.4	4159.30
	9400	1880.0	4135.70
	9538	1907.6	4153.20

7.4 SPURIOUS MISSIONS AT ANTENNA TERMINAL

- Plots of the EUT's Conducted Spurious Emissions are shown in Clause 8.3

7.5 BAND EDGE EMISSIONS AT ANTENNA TERMINAL

- Plots of the EUT's Band Edge are shown in Clause 8.4

7.6 EFFECTIVE RADIATED POWER

- GPRS850 data

Mode	CH	Frequency (MHz)	Ant. Pol. (H/V)	LEVEL@ TX ANTENNA TERMINAL (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (W)	Note.
GPRS850	128	824.2	H	27.59	-0.63	26.96	0.497	1TX
GPRS850	190	836.6	H	27.53	-0.74	26.79	0.478	1TX
GPRS850	251	848.8	H	25.19	-0.85	24.34	0.272	1TX
GPRS850	128	824.2	H	25.91	-0.63	25.28	0.337	2TX
EDGE850	128	824.2	H	21.00	-0.63	20.37	0.109	1TX
EDGE850	190	836.6	H	20.79	-0.74	20.05	0.101	1TX
EDGE850	251	848.8	H	18.53	-0.85	17.68	0.059	1TX

GPRS850 data

Mode	CH	Frequency (MHz)	Calculated frame ERP ^{Note1} (dBm)	Note.
GPRS850	128	824.2	17.93	1TX
GPRS850	190	836.6	17.76	1TX
GPRS850	251	848.8	15.31	1TX
GPRS850	128	824.2	19.26	2TX
EDGE850	128	824.2	11.34	1TX
EDGE850	190	836.6	11.02	1TX
EDGE850	251	848.8	8.65	1TX

Note1: The Frame-ERP was calculated from the measured burst-ERP power by converting the slot powers into linear units and calculating the energy over 8 timeslots

- WCDMA850 data

Mode	CH	Frequency (MHz)	Ant. Pol. (H/V)	LEVEL@ TX ANTENNA TERMINAL (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (W)	Note.
WCDMA850	4132	826.4	H	18.16	-0.65	17.51	0.056	-
WCDMA850	4183	836.6	H	18.26	-0.74	17.52	0.056	-
WCDMA850	4233	846.6	H	15.92	-0.83	15.09	0.032	-

- HSUPA850 data

Mode	CH	Frequency (MHz)	Ant. Pol. (H/V)	LEVEL@ TX ANTENNA TERMINAL (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (W)	Note.
HSUPA850	4132	826.4	H	17.01	-0.65	16.36	0.043	-
HSUPA850	4183	836.6	H	17.07	-0.74	16.33	0.043	-
HSUPA850	4233	846.6	H	14.85	-0.83	14.02	0.025	-

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.

The worst case data is reported.

7.7 EQUIVALENT ISOTROPIC RADIATED POWER

- WCDMA1700 data

Mode	CH	Frequency (MHz)	Ant. Pol. (H/V)	LEVEL@ TX ANTENNA TERMINAL (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Note.
WCDMA1700	1312	1712.4	V	7.60	6.02	13.62	0.023	-
WCDMA1700	1412	1732.4	V	7.76	5.84	13.60	0.023	-
WCDMA1700	1513	1752.6	V	11.65	5.65	17.30	0.054	-

- HSUPA1700 data

Mode	CH	Frequency (MHz)	Ant. Pol. (H/V)	LEVEL@ TX ANTENNA TERMINAL (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Note.
HSUPA1700	1312	1712.4	V	6.29	6.02	12.31	0.017	-
HSUPA1700	1412	1732.4	V	6.39	5.84	12.23	0.017	-
HSUPA1700	1513	1752.6	V	10.37	5.65	16.02	0.040	-

- GPRS1900 data

Mode	CH	Frequency (MHz)	Ant. Pol. (H/V)	LEVEL@ TX ANTENNA TERMINAL (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Note.
GPRS1900	512	1850.2	V	17.68	4.96	22.64	0.184	1TX
GPRS1900	661	1880.0	V	18.94	4.80	23.74	0.237	1TX
GPRS1900	810	1909.8	V	19.68	4.64	24.32	0.270	1TX
GPRS1900	810	1909.8	V	17.98	4.64	22.62	0.183	2TX
EDGE1900	512	1850.2	V	12.36	4.96	17.32	0.054	1TX
EDGE1900	661	1880.0	V	12.93	4.80	17.73	0.059	1TX
EDGE1900	810	1909.8	V	14.05	4.64	18.69	0.074	1TX

- GPRS1900 data

Mode	CH	Frequency (MHz)	Calculated frame EIRP ^{Note1} (dBm)	Note.
GPRS1900	512	1850.2	13.61	1TX
GPRS1900	661	1880.0	14.71	1TX
GPRS1900	810	1909.8	15.29	1TX
GPRS1900	810	1909.8	16.60	2TX
EDGE1900	512	1850.2	8.29	1TX
EDGE1900	661	1880.0	8.70	1TX
EDGE1900	810	1909.8	9.66	1TX

Note1: The Frame-EIRP was calculated from the measured burst-EIRP power by converting the slot powers into linear units and calculating the energy over 8 timeslots

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.

The worst case data is reported.

- WCDMA1900 data

Mode	CH	Frequency (MHz)	Ant. Pol. (H/V)	LEVEL@ TX ANTENNA TERMINAL (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Note.
WCDMA1900	9262	1852.4	V	10.74	4.95	15.69	0.037	-
WCDMA1900	9400	1880.0	V	11.27	4.80	16.07	0.040	-
WCDMA1900	9538	1907.6	V	13.67	4.65	18.32	0.068	-

- HSUPA1900 data

Mode	CH	Frequency (MHz)	Ant. Pol. (H/V)	LEVEL@ TX ANTENNA TERMINAL (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Note.
HSUPA1900	9262	1852.4	V	9.66	4.95	14.61	0.029	-
HSUPA1900	9400	1880.0	V	10.01	4.80	14.81	0.030	-
HSUPA1900	9538	1907.6	V	12.34	4.65	16.99	0.050	-

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.

The worst case data is reported.

7.8 RADIATED SPURIOUS EMISSIONS

- GPRS850 data

Channel (ERP)	Tx Freq. (MHz)	Freq. (MHz)	POL (H/V)	LEVEL@ ANTENNA TERMINAL (dBm)	Substitute Antenna Gain (dBd)	Correct Generator Level (dBm)	Limit (dBm)	Margin (dB)
128 (0.497 W)	824.2	1648.49	V	-43.16	3.82	-39.34	-13.00	26.34
		2472.79	H	-46.49	3.79	-42.70	-13.00	29.70
		3296.91	H	-45.96	5.53	-40.43	-13.00	27.43
		4121.03	H	-46.91	6.93	-39.98	-13.00	26.98
190 (0.478 W)	836.6	1673.46	V	-42.59	3.90	-38.69	-13.00	25.69
		2509.60	H	-41.87	3.81	-38.06	-13.00	25.06
		3346.64	H	-44.68	5.66	-39.02	-13.00	26.02
		4182.74	H	-47.08	6.93	-40.15	-13.00	27.15
251 (0.272 W)	848.8	1697.70	V	-41.14	3.97	-37.17	-13.00	24.17
		2546.64	H	-44.60	3.71	-40.89	-13.00	27.89
		3395.05	H	-43.35	5.79	-37.56	-13.00	24.56
		4244.03	H	-47.84	6.85	-40.99	-13.00	27.99

- No other spurious and harmonic emissions were reported greater than listed emissions above table.

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.

The worst case data is reported.

- WCDMA850 data

Channel (ERP)	Tx Freq. (MHz)	Freq. (MHz)	POL (H/V)	LEVEL@ ANTENNA TERMINAL (dBm)	Substitute Antenna Gain (dBr)	Correct Generator Level (dBm)	Limit (dBm)	Margin (dB)
4132 (0.056 W)	826.4	1650.71	V	-52.60	3.82	-48.78	-13.00	35.78
		2482.05	V	-49.80	3.80	-46.00	-13.00	33.00
4183 (0.056 W)	836.6	1671.06	V	-52.47	3.89	-48.58	-13.00	35.58
		2513.20	V	-47.06	3.80	-43.26	-13.00	30.26
4233 (0.032 W)	846.6	1695.24	V	-52.19	3.96	-48.23	-13.00	35.23
		2540.63	V	-45.54	3.72	-41.82	-13.00	28.82

- No other spurious and harmonic emissions were reported greater than listed emissions above table.

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.

The worst case data is reported.

- HSUPA850 data

Channel (ERP)	Tx Freq. (MHz)	Freq. (MHz)	POL (H/V)	LEVEL@ ANTENNA TERMINAL (dBm)	Substitute Antenna Gain (dBr)	Correct Generator Level (dBm)	Limit (dBm)	Margin (dB)
4132 (0.043 W)	826.4	1650.84	V	-53.12	3.82	-49.30	-13.00	36.30
		2482.39	V	-49.48	3.80	-45.68	-13.00	32.68
4183 (0.043 W)	836.6	1670.79	V	-52.95	3.89	-49.06	-13.00	36.06
		2510.46	V	-47.06	3.80	-43.26	-13.00	30.26
4233 (0.025 W)	846.6	1695.22	V	-51.71	3.96	-47.75	-13.00	34.75
		2540.27	V	-45.47	3.73	-41.74	-13.00	28.74

- No other spurious and harmonic emissions were reported greater than listed emissions above table.

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.

The worst case data is reported.

- WCDMA1700 data

Channel (EIRP)	Tx Freq. (MHz)	Freq. (MHz)	POL (H/V)	LEVEL@ ANTENNA TERMINAL (dBm)	Substitute Antenna Gain (dBi)	Correct Generator Level (dBm)	Limit (dBm)	Margin (dB)
1312 (0.023 W)	1712.4	3425.46	H	-55.04	8.02	-47.02	-13.00	34.02
1412 (0.023 W)	1732.4	3467.20	H	-55.08	8.12	-46.96	-13.00	33.96
1513 (0.054 W)	1752.6	3507.58	H	-55.69	8.22	-47.47	-13.00	34.47

- No other spurious and harmonic emissions were reported greater than listed emissions above table.

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.

The worst case data is reported.

- HSUPA1700 data

Channel (EIRP)	Tx Freq. (MHz)	Freq. (MHz)	POL (H/V)	LEVEL@ ANTENNA TERMINAL (dBm)	Substitute Antenna Gain (dBi)	Correct Generator Level (dBm)	Limit (dBm)	Margin (dB)
1312 (0.017 W)	1712.4	3425.46	H	-55.21	8.01	-47.20	-13.00	34.20
1412 (0.023 W)	1732.4	3467.20	H	-54.78	8.12	-46.66	-13.00	33.66
1513 (0.040 W)	1752.6	3507.58	H	-55.58	8.22	-47.36	-13.00	34.36

- No other spurious and harmonic emissions were reported greater than listed emissions above table.

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.

The worst case data is reported.

- GPRS1900 data

Channel (EIRP)	Tx Freq. (MHz)	Freq. (MHz)	POL (H/V)	LEVEL@ ANTENNA TERMINAL (dBm)	Substitute Antenna Gain (dBi)	Correct Generator Level (dBm)	Limit (dBm)	Margin (dB)
512 (0.184 W)	1850.2	3700.34	H	-37.12	8.38	-28.74	-13.00	15.74
		5550.44	V	-35.81	10.41	-25.40	-13.00	12.40
		7401.03	V	-46.46	11.70	-34.76	-13.00	21.76
		9250.66	V	-42.23	13.24	-28.99	-13.00	15.99
		11103.12	V	-43.86	13.33	-30.53	-13.00	17.53
661 (0.237 W)	1880.0	3759.91	H	-36.05	8.36	-27.69	-13.00	14.69
		5639.90	V	-29.20	10.64	-18.56	-13.00	5.56
		7519.59	V	-45.11	11.94	-33.17	-13.00	20.17
		9400.29	V	-40.86	13.28	-27.58	-13.00	14.58
		11280.47	V	-39.92	13.26	-26.66	-13.00	13.66
810 (0.270 W)	1909.8	3819.64	H	-36.33	8.22	-28.11	-13.00	15.11
		5729.21	V	-31.83	10.72	-21.11	-13.00	8.11
		7639.19	V	-47.21	12.18	-35.03	-13.00	22.03
		9548.88	V	-37.68	13.12	-24.56	-13.00	11.56
		11456.90	V	-44.16	13.20	-30.96	-13.00	17.96

- No other spurious and harmonic emissions were reported greater than listed emissions above table.

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.
The worst case data is reported.

- WCDMA1900 data

Channel (EIRP)	Tx Freq. (MHz)	Freq. (MHz)	POL (H/V)	LEVEL@ ANTENNA TERMINAL (dBm)	Substitute Antenna Gain (dBi)	Correct Generator Level (dBm)	Limit (dBm)	Margin (dB)
9262 (0.037 W)	1852.4	3702.51	V	-52.72	8.38	-44.34	-13.00	31.34
		5557.61	V	-49.39	10.44	-38.95	-13.00	25.95
9400 (0.040 W)	1880.0	3758.18	V	-50.44	8.37	-42.07	-13.00	29.07
		5643.01	V	-38.42	10.65	-27.77	-13.00	14.77
9538 (0.068 W)	1907.6	3813.19	V	-48.62	8.22	-40.40	-13.00	27.40
		5719.77	V	-47.02	10.73	-36.29	-13.00	23.29

- No other spurious and harmonic emissions were reported greater than listed emissions above table.

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.

The worst case data is reported.

- HSUPA1900 data

Channel (EIRP)	Tx Freq. (MHz)	Freq. (MHz)	POL (H/V)	LEVEL@ ANTENNA TERMINAL (dBm)	Substitute Antenna Gain (dBi)	Correct Generator Level (dBm)	Limit (dBm)	Margin (dB)
9262 (0.029 W)	1852.4	3702.92	V	-52.61	8.38	-44.23	-13.00	31.23
		5560.18	V	-49.59	10.44	-39.15	-13.00	26.15
9400 (0.030 W)	1880.0	3758.04	V	-50.57	8.37	-42.20	-13.00	29.20
		5643.01	V	-37.95	10.65	-27.30	-13.00	14.30
9538 (0.050 W)	1907.6	3812.86	V	-48.75	8.22	-40.53	-13.00	27.53
		5719.83	V	-46.69	10.73	-35.96	-13.00	22.96

- No other spurious and harmonic emissions were reported greater than listed emissions above table.

NOTES:

This EUT was tested under all configurations and the highest power is reported in GSM mode and WCDMA mode with HSDPA inactive at 12.2 kbps RMC and TPC bits set to "1" and in GSM mode using a Power Control Level of "0" in PCS Band and "5" in the Cellular Band. This EUT was tested with the fully charged battery. Also, we have done x, y, z planes in EUT and horizontal and vertical polarization of detecting antenna.


The worst case data is reported.

7.9 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

7.9.1 FREQUENCY STABILITY (GPRS850)

OPERATING FREQUENCY : 836,600,000 Hz
 CHANNEL : 190(Mid)
 REFERENCE VOLTAGE : 12.00 V DC
 LIMIT(FCC&IC) : ± 0.00025 % or 2.5 ppm


VOLTAGE (%)	POWER (V DC)	TEMP (°C)	FREQ (Hz)	Deviation	
				(ppm)	(%)
100%	12.00	+20(Ref)	836,600,004	0.005	0.00000048
100%		-30	836,600,001	0.001	0.00000012
100%		-20	836,600,009	0.011	0.00000108
100%		-10	836,599,987	-0.016	-0.00000155
100%		0	836,600,005	0.006	0.00000060
100%		+10	836,600,007	0.008	0.00000084
100%		+20	836,600,004	0.005	0.00000048
100%		+30	836,599,989	-0.013	-0.00000131
100%		+40	836,600,004	0.005	0.00000048
100%		+50	836,600,009	0.011	0.00000108
115%	13.80	+20	836,600,004	0.005	0.00000048
85%	10.20	+20	836,599,993	-0.008	-0.00000084



7.9.2 FREQUENCY STABILITY (WCDMA850)

OPERATING FREQUENCY : 836,600,000 Hz
 CHANNEL : 4183(Mid)
 REFERENCE VOLTAGE : 12.00 V DC
 LIMIT(FCC&IC) : ± 0.00025 % or 2.5 ppm


VOLTAGE (%)	POWER (V DC)	TEMP (°C)	FREQ (Hz)	Deviation	
				(ppm)	(%)
100%	12.00	+20(Ref)	836,599,980	-0.024	-0.00000239
100%		-30	836,599,982	-0.022	-0.00000215
100%		-20	836,600,004	0.005	0.00000048
100%		-10	836,599,987	-0.016	-0.00000155
100%		0	836,599,999	-0.001	-0.00000012
100%		+10	836,600,007	0.008	0.00000084
100%		+20	836,599,980	-0.024	-0.00000239
100%		+30	836,600,009	0.011	0.00000108
100%		+40	836,600,004	0.005	0.00000048
100%		+50	836,600,003	0.004	0.00000036
115%	13.80	+20	836,599,986	-0.017	-0.00000167
85%	10.20	+20	836,599,993	-0.008	-0.00000084



7.9.3 FREQUENCY STABILITY (WCDMA1700)

OPERATING FREQUENCY : 1,732,400,000 Hz
 CHANNEL : 1412(Mid)
 REFERENCE VOLTAGE : 12.00 V DC
 LIMIT(FCC&IC) : The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

VOLTAGE (%)	POWER (V DC)	TEMP (°C)	FREQ (Hz)	Deviation	
				(ppm)	(%)
100%	12.00	+20(Ref)	1,732,400,011	0.006	0.00000063
100%		-30	1,732,400,008	0.005	0.00000046
100%		-20	1,732,399,996	-0.002	-0.00000023
100%		-10	1,732,400,015	0.009	0.00000087
100%		0	1,732,400,003	0.002	0.00000017
100%		+10	1,732,399,993	-0.004	-0.00000040
100%		+20	1,732,400,011	0.006	0.00000063
100%		+30	1,732,400,001	0.001	0.00000006
100%		+40	1,732,399,987	-0.008	-0.00000075
100%		+50	1,732,399,993	-0.004	-0.00000040
115%	13.80	+20	1,732,400,005	0.003	0.00000029
85%	10.20	+20	1,732,400,007	0.004	0.00000040




Note. Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain inband when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

7.9.4 FREQUENCY STABILITY (GPRS1900)

OPERATING FREQUENCY : 1,880,000,000 Hz
 CHANNEL : 661(Mid)
 REFERENCE VOLTAGE : 12 V DC
 LIMIT(FCC) : The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.
 LIMIT(IC) : ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (V DC)	TEMP (°C)	FREQ (Hz)	Deviation	
				(ppm)	(%)
100%	12.00	+20(Ref)	1,880,000,008	0.004	0.00000043
100%		-30	1,880,000,003	0.002	0.00000016
100%		-20	1,880,000,001	0.001	0.00000005
100%		-10	1,879,999,982	-0.010	-0.00000096
100%		0	1,880,000,004	0.002	0.00000021
100%		+10	1,880,000,003	0.002	0.00000016
100%		+20	1,880,000,008	0.004	0.00000043
100%		+30	1,880,000,007	0.004	0.00000037
100%		+40	1,879,999,996	-0.002	-0.00000021
100%		+50	1,879,999,997	-0.002	-0.00000016
115%	13.80	+20	1,879,999,987	-0.007	-0.00000069
85%	10.20	+20	1,880,000,007	0.004	0.00000037




Note. Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain inband when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

7.9.5 FREQUENCY STABILITY (WCDMA1900)

OPERATING FREQUENCY : 1,880,000,000 Hz
 CHANNEL : 9400(Mid)
 REFERENCE VOLTAGE : 12 V DC
 LIMIT(FCC) : The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.
 LIMIT(IC) : ± 0.00025 % or 2.5 ppm


VOLTAGE (%)	POWER (V DC)	TEMP (°C)	FREQ (Hz)	Deviation	
				(ppm)	(%)
100%	12.00	+20(Ref)	1,880,000,007	0.004	0.00000037
100%		-30	1,880,000,009	0.005	0.00000048
100%		-20	1,880,000,001	0.001	0.00000005
100%		-10	1,880,000,008	0.004	0.00000043
100%		0	1,880,000,004	0.002	0.00000021
100%		+10	1,879,999,987	-0.007	-0.00000069
100%		+20	1,880,000,007	0.004	0.00000037
100%		+30	1,880,000,004	0.002	0.00000021
100%		+40	1,879,999,982	-0.010	-0.00000096
100%		+50	1,879,999,999	-0.001	-0.00000005
115%	13.80	+20	1,880,000,007	0.004	0.00000037
85%	10.20	+20	1,880,000,002	0.001	0.00000011



Note. Based on the results of the frequency stability test at the center channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain inband when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

8. TEST PLOTS


8.1 PEAK TO AVERAGE RATIO




$$\text{PAPR (dB)} = \text{P}_{\text{Pk}} (\text{dBm}) - \text{P}_{\text{Avg}} (\text{dBm}) = 33.07 \text{ dBm} - 32.84 \text{ dBm} = 0.23 \text{ dB}$$

-P_{Pk} (dBm)

EDGE850 & Channel: 190


-P_{Avg} (dBm)


EDGE850 & Channel: 190



$$\text{PAPR (dB)} = \text{P}_{\text{Pk}} (\text{dBm}) - \text{P}_{\text{Avg}} (\text{dBm}) = 29.28 \text{ dBm} - 25.83 \text{ dBm} = 3.45 \text{ dB}$$

-P_{Pk} (dBm)

GPRS1900 & Channel: 661


-P_{Avg} (dBm)


GPRS1900 & Channel: 661



$$\text{PAPR (dB)} = \text{P}_{\text{Pk}} (\text{dBm}) - \text{P}_{\text{Avg}} (\text{dBm}) = 30.31 \text{ dBm} - 30.17 \text{ dBm} = 0.14 \text{ dB}$$

-P_{Pk} (dBm)

EDGE1900 & Channel: 661



-P_{Avg} (dBm)

EDGE1900 & Channel: 661




$$\text{PAPR (dB)} = \text{P}_{\text{Pk}} (\text{dBm}) - \text{P}_{\text{Avg}} (\text{dBm}) = 29.32 \text{ dBm} - 25.92 \text{ dBm} = 3.40 \text{ dB}$$

WCDMA850 & Channel: 4183




HSUPA850 & Channel: 4183



WCDMA1700 & Channel: 1412




HSUPA1700 & Channel: 1412



WCDMA1900 & Channel: 9400




HSUPA1900 & Channel: 9400




8.2 OCCUPIED BANDWIDTH (99 % Bandwidth)


GPRS850 & Channel: 128




GPRS850 & Channel: 190




GPRS850 & Channel: 251




EDGE850 & Channel: 128




EDGE850 & Channel: 190




EDGE850 & Channel: 251



GPRS1900 & Channel: 512




GPRS1900 & Channel: 661




GSM1900 & Channel: 810




EDGE1900 & Channel: 512




EDGE1900 & Channel: 661




EDGE1900 & Channel: 810




WCDMA850 & Channel: 4132




WCDMA850 & Channel: 4183



WCDMA850 & Channel: 4233



HSUPA850 & Channel: 4132



HSUPA850 & Channel: 4183

