

RF EXPOSURE REPORT

CERTIFICATE OF CONFORMITY

FCC Rule Part: FCC Part 2 (Section 2.1091 and 2.1093)

Report No.: MFBBQJ-WTW-P24040202

FCC ID: ACJ9TGWW23C

Product: Radio Module

Brand: Panasonic

Model No.: WW23C

Received Date: 2024/4/10

Test Date: 2024/5/3

Issued Date: 2024/7/31

Applicant: Panasonic Corporation of North America

Address: Two Riverfront Plaza, Newark, NJ 07102-5490, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:

Approved by:

Jeremy Lin

, **Date:**

2024/7/31

Jeremy Lin / Project Engineer

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Gina Liu / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate.....	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula.....	5
2.3 Classification	5
3 Test Results	6

Release Control Record

Issue No.	Description	Date Issued
MFBBQJ-WTW-P24040202	Original release.	2024/7/31

1 Certificate

Product: Radio Module

Brand: Panasonic

Test Model: WW23C

Sample Status: Engineering sample

Applicant: Panasonic Corporation of North America

Test Date: 2024/5/3

FCC Rule Part: FCC Part 2 (Section 2.1091 and 2.1093)

Standard: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Test Results

Environmental Conditions:	25°C, 60% RH	Tested By:	Jisyoung Wang
---------------------------	--------------	------------	---------------

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA II	1850-1910	24	0.1	20	0.051	1.00
WCDMA IV	1710-1755	24	1.16	20	0.065	1.00
WCDMA V	824-849	24	-0.65	20	0.043	0.55
LTE 2	1850-1910	24	0.1	20	0.051	1.00
LTE 4	1710-1755	24	1.16	20	0.065	1.00
LTE 5	824-849	24	-0.65	20	0.043	0.55
LTE 7	2500-2570	24	-0.24	20	0.047	1.00
LTE 12	699-716	24	0.36	20	0.054	0.47
LTE 13	777-787	24	-0.26	20	0.047	0.52
LTE 14	788-798	24	-0.26	20	0.047	0.53
LTE 25	1850-1915	24	0.1	20	0.051	1.00
LTE 26	814-849	24	-0.65	20	0.043	0.54
LTE 42	3452-3597.5	19	2.82	20	0.030	1.00
LTE 48	3552.5-3697.5	19	3.65	20	0.037	1.00
LTE 66	1710.7-1779.3	24	1.16	20	0.065	1.00
WLAN	2412-2462	23.87	2.99	20	0.097	1.00
	5180-5240	22.61	2.33	20	0.062	1.00
	5260-5320	22.87	2.33	20	0.066	1.00
	5500-5720	23.96	1.8	20	0.075	1.00
	5745-5825	24.1	1.78	20	0.077	1.00
	5925-7125	13.15	3.15	20	0.008	1.00
BT	2402-2480	10.5	2.66	20	0.004	1.00
BLE	2402-2480	8.72	2.66	20	0.003	1.00

Note:

1. The EUT is authorized for use in specific End-product. Please refer to below for more details.

Product	Brand	Model
Personal Computer	Panasonic	FZ-55

2. The EUT contains certified WLAN module (Model: WL23A, FCC ID: ACJ9TGWL23A), Refer to WLAN module report: 200611-01.TR01, 200611-01.TR02, 200611-01.TR03, 200611-01.TR04, 200611-01.TR05 and 200611-01.TR38. for WLAN power.
3. The WWAN Max Power is Tune-up Power.
4. The above Antenna information refers to the manufacturer's antenna specifications, the laboratory shall not be held responsible.
5. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

<SAR Exemption Analysis>

A single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

Mode	Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Ant. to Surface (mm)	Power Threshold (mW)	Require SAR Testing?
RFID-RI18A	0.01356	-26.83	0.00207	5	1	NO
RFID-RI23B	0.01356	-35.93	0.00026	5	1	NO

<Estimated SAR Calculation>

For instance, a given antenna may qualify for a SAR-based exemption according to **<SAR Exemption Analysis>**, with $P_{ant} < P_{th}$, where P_{ant} is maximum time-averaged power or effective radiated power (ERP), whichever is greater, and P_{th} is SAR exemption threshold.

The estimate SAR value is calculated based the following equation:

$$SAR_{est} = 1.6 \cdot P_{ant} / P_{th} \text{ [W/kg]}$$

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
RFID-RI18A	0.01356	-26.83	0.00207	Body	0	0.003312
RFID-RI23B	0.01356	-35.93	0.00026	Body	0	0.000416

Note:

1. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

Conclusion:

Both of the WWAN and WLAN and NFC can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WWAN + WLAN 2.4GHz + BT + MAX. RFID = $0.054/0.47 + 0.097/1 + 0.004/1 + 0.003312/1.6 = 0.2179$

WWAN + WLAN 5GHz + BT + MAX. RFID = $0.054/0.47 + 0.062/1 + 0.004/1 + 0.003312/1.6 = 0.1829$

WWAN + WLAN 6GHz + BT + MAX. RFID = $0.054/0.47 + 0.008/1 + 0.004/1 + 0.003312/1.6 = 0.1289$

Therefore, the maximum calculations of above situations are less than the “1” limit.

--- END ---